

Internet Engineering Task Force (IETF)  
Request for Comments: 6779  
Category: Standards Track  
ISSN: 2070-1721

U. Herberg  
LIX, Ecole Polytechnique  
R. Cole  
US Army CERDEC  
I. Chakeres  
DRS CenGen  
October 2012

## Definition of Managed Objects for the Neighborhood Discovery Protocol

### Abstract

This document defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular, it describes objects for configuring parameters of the Neighborhood Discovery Protocol (NHDP) process on a router. The MIB module defined in this document, denoted NHDP-MIB, also reports state, performance information, and notifications about NHDP. This additional state and performance information is useful to troubleshoot problems and performance issues during neighbor discovery.

### Status of This Memo

This is an Internet Standards Track document.

This document is a product of the Internet Engineering Task Force (IETF). It represents the consensus of the IETF community. It has received public review and has been approved for publication by the Internet Engineering Steering Group (IESG). Further information on Internet Standards is available in Section 2 of RFC 5741.

Information about the current status of this document, any errata, and how to provide feedback on it may be obtained at <http://www.rfc-editor.org/info/rfc6779>.

## Copyright Notice

Copyright (c) 2012 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

1. Introduction . . . . .	3
2. The Internet-Standard Management Framework . . . . .	3
3. Conventions . . . . .	3
4. Overview . . . . .	3
4.1. Terms . . . . .	4
4.2. Notation . . . . .	4
5. Structure of the MIB Module . . . . .	4
5.1. Notifications . . . . .	5
5.1.1. Introduction . . . . .	5
5.1.2. Notification Generation . . . . .	5
5.1.3. Limiting Frequency of Notifications . . . . .	5
5.2. The Configuration Group . . . . .	6
5.3. The State Group . . . . .	7
5.4. The Performance Group . . . . .	7
5.5. Tables and Indexing . . . . .	7
6. Relationship to Other MIB Modules . . . . .	9
6.1. Relationship to the SNMPv2-MIB . . . . .	9
6.2. Relationship to Routing Protocol MIB Modules Relying on the NHDP-MIB Module . . . . .	10
6.3. MIB Modules Required for IMPORTS . . . . .	10
7. Definitions . . . . .	10
8. Security Considerations . . . . .	62
9. Applicability Statement . . . . .	64
10. IANA Considerations . . . . .	65
11. Acknowledgements . . . . .	65
12. References . . . . .	65
12.1. Normative References . . . . .	65
12.2. Informative References . . . . .	66

## 1. Introduction

This document defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular, it describes objects for configuring parameters of the Neighborhood Discovery Protocol (NHDP) [RFC6130] process on a router. The MIB module defined in this document, denoted NHDP-MIB, also reports state, performance information, and notifications about NHDP. This additional state and performance information is useful to troubleshoot problems and performance issues during neighbor discovery.

## 2. The Internet-Standard Management Framework

For a detailed overview of the documents that describe the current Internet-Standard Management Framework, please refer to section 7 of RFC 3410 [RFC3410].

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. MIB objects are generally accessed through the Simple Network Management Protocol (SNMP). Objects in the MIB are defined using the mechanisms defined in the Structure of Management Information (SMI). This memo specifies a MIB module that is compliant to the SMIV2, which is described in STD 58, RFC 2578 [RFC2578], STD 58, RFC 2579 [RFC2579] and STD 58, RFC 2580 [RFC2580].

## 3. Conventions

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC2119].

## 4. Overview

[RFC6130] allows a router to discover and track topological information of routers up to two hops away by virtue of exchanging HELLO messages. This information is useful for routers running various routing and multicast flooding protocols developed within the IETF MANET Working Group.

#### 4.1. Terms

The following definitions apply throughout this document:

- o Notification Objects - triggers and associated notification messages allowing for asynchronous tracking of pre-defined events on the managed router.
- o Configuration Objects - switches, tables, and objects that are initialized to default settings or set through the management interface defined by this MIB module.
- o State Objects - automatically generated values that define the current operating state of the NHDP instance in the router.
- o Performance Objects - automatically generated values that help an administrator or automated tool to assess the performance of the NHDP instance on the router and the overall discovery performance within the Mobile Ad Hoc Network (MANET).

#### 4.2. Notation

The same notations as defined in [RFC6130] are used throughout this document.

#### 5. Structure of the MIB Module

This section presents the structure of the NHDP-MIB module. The MIB module is arranged into the following structure:

- o nhdpNotifications - objects defining NHDP-MIB notifications.
- o nhdpObjects - defining objects within this MIB module. The objects are arranged into the following groups:
  - \* Configuration Group - defining objects related to the configuration of the NHDP instance on the router.
  - \* State Group - defining objects that reflect the current state of the NHDP instance running on the router.
  - \* Performance Group - defining objects that are useful to a management station when characterizing the performance of NHDP on the router and in the MANET.
- o nhdpConformance - defining the minimal and maximal conformance requirements for implementations of this MIB module.

## 5.1. Notifications

This section describes the use of notifications and mechanisms to enhance the ability to manage NHDP routing domains.

### 5.1.1. Introduction

Notifications can be emitted by a router running an instance of this specification as a reaction to a specific event. This allows a network manager to efficiently determine the source of problems or significant changes of configuration or topology, instead of polling a possibly large number of routers.

### 5.1.2. Notification Generation

When an exception event occurs, the application notifies the local agent, which sends a notification to the appropriate SNMP management stations. The message includes the notification type and may include a list of notification-specific variables. Section 7 contains the notification definitions, which includes the variable lists. At least one IP address of the router that originates the notification is included in the variable list so that the network manager may determine the source of the notification.

### 5.1.3. Limiting Frequency of Notifications

To limit the frequency of notifications, the following additional mechanisms are suggested, similar to those in [RFC4750].

#### 5.1.3.1. Ignoring Initial Activity

The majority of critical events occur when NHDP is first enabled on a router, at which time the symmetric neighbors and two-hop neighbors of the router are discovered. During this initial period, a potential flood of notifications is unnecessary since the events are expected. To avoid unnecessary notifications, a router SHOULD NOT originate expected notifications until a certain time interval has elapsed, which is to be predefined by the network manager. It is RECOMMENDED that this time interval is at least 3 x `nhdpNextHelloInterval`, so that symmetric neighbors are discovered. The suppression window for notifications is started when the `nhdpNextIfStatus` transitions from its default value of 'false(2)' to 'true(1)'.

#### 5.1.3.2. Throttling Notifications

The mechanism for throttling the notifications is the same as in [RFC4750] (i.e., the number of transmitted notifications per time is bounded).

Appropriate values for the window time and upper bound are to be selected by the network manager and depend on the deployment of the MANET. If NHDP is deployed on a lossy, wireless medium, sending too many notifications in a short time interval may lead to collisions and dropped packets. In particular, in dense deployments of routers running NHDP (i.e., where each router has many neighbors), a change of the local topology may trigger many notifications at the same time. [RFC4750] recommends "7 traps with a window time of 10 seconds" as the upper bound. As NHDP is expected to be deployed in more lossy channels than OSPF, it is RECOMMENDED to choose a lower threshold for the number of notifications per time than that. Specifically, it is RECOMMENDED that the threshold value for the objects reflecting the change be set to a value of '10' and the DEFAULT values for these objects within the Notifications Group be set to this value. Further, a time window for the change objects is defined within this MIB module. It is RECOMMENDED that if the number of occurrences exceeds the change threshold within the previous change window, then the notification is to be sent. Furthermore, it is RECOMMENDED that the value for this window be set to at least 5 times the `nhdpHelloInterval`.

The following objects are used to define the thresholds and time windows for specific notifications defined in the NHDP-MIB module: `nhdpNbrStateChangeThreshold`, `nhdpNbrStateChangeWindow`, `nhdp2HopNbrStateChangeThreshold`, and `nhdp2HopNbrStateChangeWindow`.

#### 5.1.3.3. One Notification per Event

Similar to the mechanism in [RFC4750], only one notification is sent per event.

#### 5.2. The Configuration Group

The router running NHDP is configured with a set of controls. The authoritative list of configuration controls within the NHDP-MIB module are found within the MIB module itself. Generally, an attempt was made in developing the NHDP-MIB module to support all configuration objects defined in [RFC6130]. For all of the configuration parameters, the same constraints and default values of these parameters as defined in [RFC6130] are followed. Refer to [RFC5148] for guidance on setting jitter-related parameters, e.g., `nhdpMaxJitter`.

### 5.3. The State Group

The State Group reports current state information of a router running NHDP. The NHDP-MIB State Group tables were designed to contain the complete set of state information defined within the information bases specified in Sections 6, 7, and 8 of [RFC6130].

Two constructs, i.e., TEXTUAL-CONVENTIONS, are defined to support the tables in the State Group. NHDP stores and indexes information through sets of (dynamically defined) addresses, i.e., address sets. Within SMIV2, it is not possible to index tables with variably defined address sets. Hence, these TEXTUAL-CONVENTIONS are defined to provide a local mapping between NHDP-managed address sets and SMIV2 table indexing. These constructs are the NeighborIfIndex and NeighborRouterIndex. These are locally (to the router) defined, unique identifiers of virtual neighbors and neighbor interfaces. Due to the nature of NHDP, the local router may have identified distinct address sets but is not able to associate these as a single interface. Hence, two or more NeighborIfIndexes pointing to multiple distinct address sets may, in fact, be related to a common neighbor interface. This ambiguity may also hold with respect to the assignment of the NeighborRouterIndex. The local MIB agent is responsible for managing, aggregating, and retiring the defined indexes and for updating MIB tables using these indexes as the local router learns more about its neighbors' topologies. These constructs are used to define indexes to the appropriate State Group tables and to correlate table entries to address sets, virtual neighbor interfaces, and virtual neighbors within the MANET.

### 5.4. The Performance Group

The Performance Group reports values relevant to system performance. Unstable neighbors or 2-hop neighbors and frequent changes of sets can have a negative influence on the performance of NHDP. This MIB module defines several objects that can be polled in order to, e.g., calculate histories or monitor frequencies of changes. This may help the network administrator to determine unusual topology changes or other changes that affect stability and reliability of the MANET. One such framework is specified in [REPORT-MIB].

### 5.5. Tables and Indexing

The NHDP-MIB module contains a number of tables that record data related to:

- o the local router,
- o a local MANET interface on the router,

- o other routers that are 1 hop removed from the local router,
- o interfaces on other routers that are 1 hop removed from the local router, and
- o other routers that are 2 hops removed from the local router.

The NHDP-MIB module's tables are indexed via the following constructs:

- o `nhdpIfIndex` - the `IfIndex` of the local router on which NHDP is configured.
- o `nhdpDiscIfIndex` - a locally managed index representing a known interface on a neighboring router.
- o `nhdpDiscRouterIndex` - a locally managed index representing an ID of a known neighboring router.

These tables and their indexing are:

- o `nhdpInterfaceTable` - describes the configuration of the interfaces of this router. This table has INDEX { `nhdpIfIndex` }.
- o `nhdpLibLocalIfSetTable` - records all network addresses that are defined as local interface network addresses on this router. This table has INDEX { `nhdpLibLocalIfSetIndex` }.
- o `nhdpLibRemovedIfAddrSetTable` - records network addresses that were recently used as local interface network addresses on this router but have been removed. This table has INDEX { `nhdpLibRemovedIfAddrSetIndex` }.
- o `nhdpInterfaceStateTable` - records state information related to specific interfaces of this router. This table has INDEX { `nhdpIfIndex` }.
- o `nhdpDiscIfSetTable` - includes the `nhdpDiscRouterIndex` of the discovered router, the `nhdpDiscIfIndex` of the discovered interface, and the current set of addresses associated with this neighbor interface. This table has INDEX { `nhdpDiscIfSetIndex` }.
- o `nhdpLibLinkSetTable` - for each local interface, records all links belonging to other routers that are, or recently were, 1-hop neighbors to this router. This table has INDEX { `nhdpIfIndex`, `nhdpDiscIfIndex` }.



- o nhdpIib2HopSetTable - for each local interface, records network addresses (one at a time) of symmetric 2-hop neighbors and the symmetric links to symmetric 1-hop neighbors of this router through which these symmetric 2-hop neighbors can be reached. This table has INDEX { nhdpIfIndex, nhdpDiscIfIndex, nhdpIib2HopSetIpAddressType, nhdpIib2HopSetIpAddress }.
- o nhdpNibNeighborSetTable - records all network addresses of each 1-hop neighbor to this router. This table has INDEX { nhdpDiscRouterIndex }.
- o nhdpNibLostNeighborSetTable - records network addresses of other routers that were recently symmetric 1-hop neighbors to this router but are now advertised as lost. This table has INDEX { nhdpDiscRouterIndex }.
- o nhdpInterfacePerfTable - records performance objects that are measured for each local NHDP interface on this router. This table has INDEX { nhdpIfIndex }.
- o nhdpDiscIfSetPerfTable - records performance objects that are measured for each discovered interface of a neighbor of this router. This table has INDEX { nhdpDiscIfIndex }.
- o nhdpDiscNeighborSetPerfTable - records performance objects that are measured for discovered neighbors of this router. This table has INDEX { nhdpDiscRouterIndex }.
- o nhdpIib2HopSetPerfTable - records performance objects that are measured for discovered 2-hop neighbors of this router. This table has INDEX { nhdpDiscRouterIndex }.

## 6. Relationship to Other MIB Modules

This section specifies the relationship of the MIB module contained in this document to other standards, particularly to standards containing other MIB modules. MIB modules and specific definitions imported from MIB modules that SHOULD be implemented in conjunction with the MIB module contained within this document are identified in this section.

### 6.1. Relationship to the SNMPv2-MIB

The System group in the SNMPv2-MIB module [RFC3418] is defined as being mandatory for all systems, and the objects apply to the entity as a whole. The System group provides identification of the management entity and certain other system-wide data. The NHDP-MIB module does not duplicate those objects.

## 6.2. Relationship to Routing Protocol MIB Modules Relying on the NHDP-MIB Module

[RFC6130] allows routing protocols to rely on the neighborhood information that is discovered by means of HELLO message exchange. In order to allow for troubleshooting, fault isolation, and management of such routing protocols through a routing protocol MIB module, it may be desired to align the State Group tables of the NHDP-MIB module and the routing protocol MIB module. This is accomplished through the definition of two TEXTUAL-CONVENTIONS in the NHDP-MIB module: the NeighborIfIndex and the NeighborRouterIndex. These object types are used to develop indexes into common NHDP-MIB module and routing protocol State Group tables. These objects are locally significant but should be locally common to the NHDP-MIB module and the routing protocol MIB module implemented on a common networked router. This will allow for improved cross-referencing of information across the two MIB modules.

## 6.3. MIB Modules Required for IMPORTS

The following NHDP-MIB module IMPORTS objects from SNMPv2-SMI [RFC2578], SNMPv2-TC [RFC2579], SNMPv2-CONF [RFC2580], IF-MIB [RFC2863], INET-ADDRESS-MIB [RFC4001], and FLOAT-TC-MIB [RFC6340].

## 7. Definitions

This section contains the MIB module defined by the specification.

```
NHDP-MIB DEFINITIONS ::= BEGIN
```

```
-- This MIB module defines objects for the management of
-- NHDP (RFC 6130) - The Neighborhood Discovery Protocol,
-- Clausen, T., Dearlove, C., and J. Dean, January 2011.
```

```
IMPORTS
```

```
MODULE-IDENTITY, OBJECT-TYPE, NOTIFICATION-TYPE,
Counter32, Counter64, Integer32, Unsigned32, mib-2,
TimeTicks
FROM SNMPv2-SMI -- RFC 2578
```

```
TEXTUAL-CONVENTION, TruthValue, TimeStamp,
RowStatus
FROM SNMPv2-TC -- RFC 2579
```

```
MODULE-COMPLIANCE, OBJECT-GROUP, NOTIFICATION-GROUP
FROM SNMPv2-CONF -- STD 58
```

SnmpAdminString  
FROM SNMP-FRAMEWORK-MIB -- RFC 3411

InetAddressType, InetAddress,  
InetAddressPrefixLength  
FROM INET-ADDRESS-MIB -- RFC 4001

InterfaceIndex  
FROM IF-MIB -- RFC 2863

Float32TC  
FROM FLOAT-TC-MIB -- RFC 6340

;

nhdpMIB MODULE-IDENTITY

LAST-UPDATED "201210221000Z" -- 22 October 2012

ORGANIZATION "IETF MANET Working Group"

CONTACT-INFO

"WG E-Mail: manet@ietf.org"

WG Chairs: sratliff@cisco.com  
jmacker@nrl.navy.mil

Editors: Ulrich Herberg  
LIX, Ecole Polytechnique  
91128 Palaiseau Cedex  
France

ulrich@herberg.name  
<http://www.herberg.name/>

Robert G. Cole  
US Army CERDEC  
Space and Terrestrial Communications  
6010 Frankford Street  
Bldg 6010, Room 453H  
Aberdeen Proving Ground, Maryland 21005  
USA  
+1 443 395-8744

robert.g.cole@us.army.mil  
<http://www.cs.jhu.edu/~rgcole/>

Ian D Chakeres  
DRS CenGen  
9250 Bendix Road North  
Columbia, Maryland 21045  
USA

ian.chakeres@gmail.com  
<http://www.ianchak.com/>

## DESCRIPTION

"This NHDP-MIB module is applicable to routers implementing the Neighborhood Discovery Protocol defined in RFC 6130.

Copyright (c) 2012 IETF Trust and the persons identified as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject to the license terms contained in, the Simplified BSD License set forth in Section 4.c of the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>).

This version of this MIB module is part of RFC 6779; see the RFC itself for full legal notices."

```
-- revision
REVISION "201210221000Z" -- 22 October 2012
DESCRIPTION
    "Initial version of this MIB module,
     published as RFC 6779."
 ::= { mib-2 213 }
```

```
--
-- Top-Level Components of this MIB Module
--
nhdpNotifications OBJECT IDENTIFIER ::= { nhdpMIB 0 }
nhdpObjects        OBJECT IDENTIFIER ::= { nhdpMIB 1 }
nhdpConformance   OBJECT IDENTIFIER ::= { nhdpMIB 2 }
```

```
--
-- TEXTUAL-CONVENTIONS
--
-- Two new TEXTUAL-CONVENTIONS have been defined in
-- this MIB module for indexing into the following
-- tables and indexing into other tables in other MIB modules.
-- This was necessary because NHDP manages and
```

```
-- indexes based upon dynamic address tuples, i.e.,
-- address sets, while SMI requires statically
-- defined indexes for accessing its table rows.
-- The NeighborIfIndex defines a unique (to the local router)
-- index referencing a discovered virtual interface on another
-- neighbor within the MANET. The NeighborRouterIndex defines a
-- unique (to the local router) index referencing a discovered
-- virtual neighbor within the MANET.
--
-- Due to the nature of NHDP,
-- different indexes may be related to common neighbor
-- interfaces or common neighbor routers, but the information
-- obtained through NHDP has not allowed the local router
-- to relate these virtual objects (i.e., interfaces or routers)
-- at this point in time. As more topology information
-- is gathered by the local router, it may associate
-- virtual interfaces or routers and collapse these
-- indexes appropriately.
--
-- Multiple addresses can be associated with a
-- given NeighborIfIndex. Each NeighborIfIndex is
-- associated with a NeighborRouterIndex. Throughout
-- the nhdpStateObjGroup, the
-- NeighborIfIndex and the NeighborRouterIndex are used
-- to define the set of IpAddrs related to a virtual
-- neighbor interface or virtual neighbor under discussion.
```

NeighborIfIndex ::= TEXTUAL-CONVENTION

DISPLAY-HINT "d"

STATUS current

DESCRIPTION

"An arbitrary, locally unique identifier associated with a virtual interface of a discovered NHDP neighbor. Due to the nature of NHDP, the local router may not know if two distinct addresses belong to the same interface of a neighbor or to two different interfaces. As the local router gains more knowledge of its neighbors, its local view may change, and this table will be updated to reflect the local router's current understanding, associating address sets to neighbor interfaces. The local router identifies a virtual neighbor interface through the receipt of address lists advertised through an NHDP HELLO message.

All objects of type NeighborIfIndex are assigned by the agent out of a common number space.

The value for each discovered virtual neighbor interface may not remain constant from one re-initialization of the entity's network management agent to the next re-initialization. If the local router gains information associating two virtual interfaces on a neighbor as a common interface, then the agent MUST aggregate the two address sets to a single index chosen from the set of aggregated indexes, and it MUST update all tables in this MIB module that are indexed by indexes of type NeighborIfIndex. It MAY then reuse freed index values following the next agent restart.

The specific value is meaningful only within a given SNMP entity."

SYNTAX           Unsigned32 (1..2147483647)

NeighborRouterIndex ::= TEXTUAL-CONVENTION

DISPLAY-HINT "d"

STATUS           current

DESCRIPTION

"An arbitrary, locally unique identifier associated with a virtual discovered neighbor (one or two hop). Due to the nature of NHDP, the local router may identify multiple virtual neighbors that, in fact, are one and the same. Neighbors that are two hops away with more than one advertised address will exhibit this behavior. As the local router's knowledge of its neighbors' topology increases, the local router will be able to associate multiple virtual neighbor indexes into a single virtual neighbor index chosen from the set of aggregated indexes; it MUST update all tables in this MIB module indexed by these indexes, and it MAY reuse the freed indexes following the next agent re-initialization.

All objects of type NeighborRouterIndex are assigned by the agent out of a common number space.

The NeighborRouterIndex defines a discovered NHDP peer virtual neighbor of the local router. The value for each discovered virtual neighbor index MUST remain constant at least from one re-initialization of the entity's network management agent to the next re-initialization, except if an application is deleted and re-created.

The specific value is meaningful only within a given SNMP entity. A NeighborRouterIndex value MUST not be reused

```
        until the next agent restart."
SYNTAX      Unsigned32 (1..2147483647)

--
-- nhdpObjects
--
--      1) Configuration Objects Group
--      2) State Objects Group
--      3) Performance Objects Group
--
-- nhdpConfigurationObjGrp
--
-- Contains the NHDP objects that configure specific options
-- that determine the overall performance and operation of
-- NHDP.

nhdpConfigurationObjGrp OBJECT IDENTIFIER ::= { nhdpObjects 1 }

nhdpInterfaceTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF NhdpInterfaceEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The nhdpInterfaceTable describes the
        configuration of the interfaces of this router
        that are intended to use MANET control protocols.
        As such, this table 'sparse augments' the ifTable
        specifically when NHDP is to be configured to
        operate over this interface.  The interface is
        identified by the ifIndex from the interfaces
        group defined in the Interfaces Group MIB module.

        A conceptual row in this table exists if and only
        if either a manager has explicitly created the row
        or there is an interface on the managed device
        that supports and runs NHDP.

        The manager can create a row by setting
        rowStatus to 'createAndGo' or 'createAndWait'.
        Row objects having associated DEFVAL clauses are
        automatically defined by the agent with these
        values during row creation, unless the manager
        explicitly defines these object values during the
        row creation."
```

If the corresponding entry with ifIndex value is deleted from the Interface Table, then the entry in this table is automatically deleted, NHDP is disabled on this interface, and all configuration and state information related to this interface is to be removed from memory."

## REFERENCE

"RFC 2863 - The Interfaces Group MIB, McCloghrie, K., and F. Kastenholz, June 2000"

```
::= { nhdpConfigurationObjGrp 1 }
```

```
nhdpInterfaceEntry OBJECT-TYPE
```

```
SYNTAX      NhdpInterfaceEntry
```

```
MAX-ACCESS  not-accessible
```

```
STATUS      current
```

```
DESCRIPTION
```

"The nhdpInterfaceEntry describes one NHDP local interface configuration as indexed by its ifIndex as defined in the Standard MIB II Interface Table (RFC 2863).

The objects in this table are persistent, and when written, the device SHOULD save the change to non-volatile storage. For further information on the storage behavior for these objects, refer to the description for the nhdpIfRowStatus object."

```
INDEX { nhdpIfIndex }
```

```
::= { nhdpInterfaceTable 1 }
```

```
NhdpInterfaceEntry ::=
```

```
SEQUENCE {
```

```
  nhdpIfIndex
```

```
    InterfaceIndex,
```

```
  nhdpIfName
```

```
    SnmpAdminString,
```

```
  nhdpIfStatus
```

```
    TruthValue,
```

```
  nhdpHelloInterval
```

```
    Unsigned32,
```

```
  nhdpHelloMinInterval
```

```
    Unsigned32,
```

```
  nhdpRefreshInterval
```

```
    Unsigned32,
```

```
  nhdpLHoldTime
```

```
    Unsigned32,
```

```
  nhdpPHoldTime
```



```

        Unsigned32,
        nhdpHystAcceptQuality
        Float32TC,
        nhdpHystRejectQuality
        Float32TC,
        nhdpInitialQuality
        Float32TC,
        nhdpInitialPending
        TruthValue,
        nhdpHpMaxJitter
        Unsigned32,
        nhdpHtMaxJitter
        Unsigned32,
        nhdpIfRowStatus
        RowStatus
    }

nhdpIfIndex OBJECT-TYPE
    SYNTAX      InterfaceIndex
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "This value MUST correspond to an ifIndex referring
         to a valid entry in the Interfaces Table."
    REFERENCE
        "RFC 2863 - The Interfaces Group MIB, McCloghrie, K.,
         and F. Kastenholz, June 2000"
    ::= { nhdpInterfaceEntry 1 }

nhdpIfName OBJECT-TYPE
    SYNTAX      SnmpAdminString
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The textual name of the interface.  The value of this
         object SHOULD be the name of the interface as assigned by
         the local device.  This can be a text-name, such as 'le0'
         or a simple port number, such as '1',
         depending on the interface-naming syntax of the device.

         If there is no local name or this object is otherwise not
         applicable, then this object contains a zero-length string."
    ::= { nhdpInterfaceEntry 2 }

nhdpIfStatus OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-create
    STATUS      current

```

```
DESCRIPTION
  "nhdpIfStatus indicates whether this interface is
  currently running NHDP. A value of 'true(1)' indicates
  that NHDP is running on this interface.
  A value of 'false(2)' indicates that NHDP is not
  currently running on this interface. This corresponds
  to the I_manet parameter in the Local Interface Set
  of NHDP."
  DEFVAL { false }
 ::= { nhdpInterfaceEntry 3 }

--
-- Interface Parameters - Message Intervals
--

nhdpHelloInterval OBJECT-TYPE
  SYNTAX      Unsigned32
  UNITS       "milliseconds"
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
    "nhdpHelloInterval corresponds to
    HELLO_INTERVAL of NHDP and represents the
    maximum time between the transmission of two
    successive HELLO messages on this MANET interface.

    Guidance for setting this object may be found
    in Section 5 of the NHDP specification (RFC 6130),
    which indicates that:
      o nhdpHelloInterval > 0
      o nhdpHelloInterval >= nhdpHelloMinInterval"
  REFERENCE
    "Section 5 on Protocol Parameters and
    Constraints of RFC 6130 - Mobile Ad Hoc
    Network (MANET) Neighborhood Discovery
    Protocol (NHDP), Clausen, T., Dearlove,
    C., and J. Dean, April 2011"
  DEFVAL { 2000 }
 ::= { nhdpInterfaceEntry 4 }

nhdpHelloMinInterval OBJECT-TYPE
  SYNTAX      Unsigned32
  UNITS       "milliseconds"
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
    "nhdpHelloMinInterval corresponds to
    HELLO_MIN_INTERVAL of NHDP and represents
```

the minimum interval between transmission of two successive HELLO messages on this MANET interface.

Guidance for setting this object may be found in Section 5 of the NHDP specification (RFC 6130), which indicates that:

o nhdpHelloMinInterval <= nhdpHelloInterval"

REFERENCE

"Section 5 on Protocol Parameters and Constraints of RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood Discovery Protocol (NHDP), Clausen, T., Dearlove, C., and J. Dean, April 2011"

DEFVAL { 500 }

::= { nhdpInterfaceEntry 5 }

nhdpRefreshInterval OBJECT-TYPE

SYNTAX Unsigned32  
UNITS "milliseconds"  
MAX-ACCESS read-create  
STATUS current

DESCRIPTION

"nhdpRefreshInterval corresponds to REFRESH\_INTERVAL of NHDP and represents the maximum interval between advertisements of each 1-hop neighbor network address and its status. Each advertisement is in a HELLO message on this MANET interface.

Guidance for setting this object may be found in Section 5 of the NHDP specification (RFC 6130), which indicates that:

o nhdpRefreshInterval >= nhdpHelloInterval"

REFERENCE

"Section 5 on Protocol Parameters and Constraints of RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood Discovery Protocol (NHDP), Clausen, T., Dearlove, C., and J. Dean, April 2011"

DEFVAL { 2000 }

::= { nhdpInterfaceEntry 6 }

--

-- Interface Parameters - Information Validity times

--

nhdpLHoldTime OBJECT-TYPE

SYNTAX Unsigned32  
UNITS "milliseconds"

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"nhdpLHoldTime corresponds to L\_HOLD\_TIME of NHDP and represents the period of advertisement, on this MANET interface, of former 1-hop neighbor network addresses as lost in HELLO messages, allowing recipients of these HELLO messages to accelerate removal of this information from their Link Sets.

Guidance for setting this object may be found in Section 5 of the NHDP specification (RFC 6130), which indicates that it should be assigned a value significantly greater than the refresh interval held by nhdpRefreshInterval."

REFERENCE

"Section 5 on Protocol Parameters and Constraints of RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood Discovery Protocol (NHDP), Clausen, T., Dearlove, C., and J. Dean, April 2011"

DEFVAL { 6000 }

::= { nhdpInterfaceEntry 7 }

nhdpPHoldTime OBJECT-TYPE

SYNTAX Unsigned32

UNITS "milliseconds"

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"nhdpPHoldTime corresponds to H\_HOLD\_TIME of NHDP and is used as the value in the VALIDITY\_TIME Message TLV included in all HELLO messages on this MANET interface. It is then used by each router receiving such a HELLO message to indicate the validity of the information taken from that HELLO message and recorded in the receiving router's Information Bases.

Guidance for setting this object may be found in Section 5 of the NHDP specification (RFC 6130), which indicates that it should be assigned a value significantly greater than the refresh interval held by nhdpRefreshInterval and must be representable as described in RFC 5497."

REFERENCE

"Section 5 on Protocol Parameters and Constraints of RFC 6130 - Mobile Ad Hoc Network

```

        (MANET) Neighborhood Discovery Protocol (NHDP),
        Clausen, T., Dearlove, C., and J. Dean, April 2011"
    DEFVAL { 6000 }
 ::= { nhdpInterfaceEntry 8 }

--
-- Interface Parameters - Link Quality
--

nhdpHystAcceptQuality OBJECT-TYPE
    SYNTAX      Float32TC
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "nhdpHystAcceptQuality corresponds to
        HYST_ACCEPT of NHDP and represents the link
        quality threshold at or above which a link becomes
        usable, if it was not already so.

        Guidance for setting this object may be found
        in Section 5 of the NHDP specification (RFC 6130),
        which indicates that:
            o 0 <= nhdpHystRejectQuality
              <= nhdpHystAcceptQuality <= 1.0

        The default value for this object is 1.0. According to
        RFC 6340:
            Since these textual conventions are defined in terms
            of the OCTET STRING type, the SMI's mechanisms for
            formally setting range constraints are not available.
            MIB designers using these textual conventions will need
            to use DESCRIPTION clauses to spell out any applicable
            range constraints beyond those implied by the underlying
            IEEE types.

        Therefore, this object does not have a DEFVAL clause."
    REFERENCE
        "Section 5 on Protocol Parameters and
        Constraints of RFC 6130 - Mobile Ad Hoc Network
        (MANET) Neighborhood Discovery Protocol (NHDP),
        Clausen, T., Dearlove, C., and J. Dean, April 2011"
--    DEFVAL { 1.0 }    see DESCRIPTION
 ::= { nhdpInterfaceEntry 9 }

nhdpHystRejectQuality OBJECT-TYPE
    SYNTAX      Float32TC
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION

```

"nhdpHystRejectQuality corresponds to HYST\_REJECT of NHDP and represents the link quality threshold below which a link becomes unusable, if it was not already so.

Guidance for setting this object may be found in Section 5 of the NHDP specification (RFC 6130), which indicates that:

- o 0 <= nhdpHystRejectQuality <= nhdpHystAcceptQuality <= 1.0

The default value for this object is 0.0. According to RFC 6340:

Since these textual conventions are defined in terms of the OCTET STRING type, the SMI's mechanisms for formally setting range constraints are not available. MIB designers using these textual conventions will need to use DESCRIPTION clauses to spell out any applicable range constraints beyond those implied by the underlying IEEE types.

Therefore, this object does not have a DEFVAL clause."

#### REFERENCE

"Section 5 on Protocol Parameters and Constraints of RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood Discovery Protocol (NHDP), Clausen, T., Dearlove, C., and J. Dean, April 2011"

```
-- DEFVAL { 0.0 } see DESCRIPTION
 ::= { nhdpInterfaceEntry 10 }
```

```
nhdpInitialQuality OBJECT-TYPE
SYNTAX      Float32TC
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
```

"nhdpInitialQuality corresponds to INITIAL\_QUALITY of NHDP and represents the initial quality of a newly identified link.

Guidance for setting this object may be found in Section 5 of the NHDP specification (RFC 6130), which indicates that:

- o 0 <= nhdpInitialQuality <= 1.0

The default value for this object is 1.0. According to RFC 6340:

Since these textual conventions are defined in terms of the OCTET STRING type, the SMI's mechanisms for

formally setting range constraints are not available. MIB designers using these textual conventions will need to use DESCRIPTION clauses to spell out any applicable range constraints beyond those implied by the underlying IEEE types.

Therefore, this object does not have a DEFVAL clause."

REFERENCE

"Section 5 on Protocol Parameters and Constraints of RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood Discovery Protocol (NHDP), Clausen, T., Dearlove, C., and J. Dean, April 2011"

```
-- DEFVAL { 1.0 } see DESCRIPTION
 ::= { nhdpInterfaceEntry 11 }
```

nhdpInitialPending OBJECT-TYPE

SYNTAX TruthValue  
 MAX-ACCESS read-create  
 STATUS current  
 DESCRIPTION

"nhdpInitialPending corresponds to INITIAL\_PENDING of NHDP. If the value of this object is 'true(1)', then a newly identified link is considered pending and is not usable until the link quality has reached or exceeded the nhdpHystAcceptQuality threshold.

Guidance for setting this object may be found in Section 5 of the NHDP specification (RFC 6130), which indicates that:

- o If nhdpInitialQuality >= nhdpHystAcceptQuality, then nhdpInitialPending := false(2).
- o If nhdpInitialQuality < nhdpHystRejectQuality, then nhdpInitialPending := true(1)."

REFERENCE

"Section 5 on Protocol Parameters and Constraints of RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood Discovery Protocol (NHDP), Clausen, T., Dearlove, C., and J. Dean, April 2011"

```
DEFVAL { false }
 ::= { nhdpInterfaceEntry 12 }
```

```
--
-- Interface Parameters - Jitter
--
```

nhdpHpMaxJitter OBJECT-TYPE

SYNTAX Unsigned32  
 UNITS "milliseconds"  
 MAX-ACCESS read-create

```

STATUS      current
DESCRIPTION
  "nhdpHpMaxJitter corresponds to
  HP_MAXJITTER of NHDP and represents the
  value of MAXJITTER used in RFC 5148 for
  periodically generated HELLO messages on
  this MANET interface.

  Guidance for setting this object may be found
  in Section 5 of RFC 5148, which indicates that:
    o nhdpHpMaxJitter <= nhdpHelloInterval / 2
    o nhdpHpMaxJitter should not be greater
      than nhdpHelloInterval / 4
    o If nhdpMinHelloInterval > 0, then
      nhdpHpMaxJitter <= nhdpHelloMinInterval; and
      nhdpHpMaxJitter should not be greater than
      nhdpHelloMinInterval / 2"

REFERENCE
  "Section 5 of RFC 5148 - Jitter Considerations in
  Mobile Ad Hoc Networks (MANETs),
  Clausen, T., Dearlove, C., and B. Adamson, February 2008"
DEFVAL { 500 }
 ::= { nhdpInterfaceEntry 13 }

nhdpHtMaxJitter OBJECT-TYPE
SYNTAX      Unsigned32
UNITS       "milliseconds"
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
  "nhdpHtMaxJitter corresponds to
  HT_MAXJITTER of NHDP and represents the
  value of MAXJITTER used in RFC 5148 for
  externally triggered HELLO messages on this
  MANET interface.

  Guidance for setting this object may be found
  in Section 5 of RFC 5148, which indicates that:
    o nhdpHtMaxJitter <= nhdpHelloInterval / 2
    o nhdpHtMaxJitter should not be greater
      than nhdpHelloInterval / 4
    o If nhdpMinHelloInterval > 0, then
      nhdpHtMaxJitter <= nhdpHelloMinInterval; and
      nhdpHtMaxJitter should not be greater than
      nhdpHelloMinInterval / 2"

REFERENCE
  "Section 5 of RFC 5148 - Jitter Considerations in
  Mobile Ad Hoc Networks (MANETs),

```



```

    Clausen, T., Dearlove, C., and B. Adamson, February 2008"
    DEFVAL { 500 }
 ::= { nhdPInterfaceEntry 14 }

nhdPIfRowStatus OBJECT-TYPE
    SYNTAX      RowStatus
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "This object permits management of the table
        by facilitating actions such as row creation,
        construction, and destruction.  The value of
        this object has no effect on whether other
        objects in this conceptual row can be
        modified.

        An entry may not exist in the 'active(1)' state unless all
        objects in the entry have a defined appropriate value.  For
        objects with DEFVAL clauses, the management station
        does not need to specify the value of this object in order
        for the row to transit to the 'active(1)' state; the default
        value for this object is used.  For objects that do not
        have DEFVAL clauses, then the network manager MUST
        specify the value of this object prior to this row
        transitioning to the 'active(1)' state.

        When this object transitions to 'active(1)', all objects
        in this row SHOULD be written to non-volatile (stable)
        storage.  Read-create objects in this row MAY be modified.
        When an object in a row with nhdPIfRowStatus of 'active(1)'
        is changed, then the updated value MUST be reflected in NHDP,
        and this new object value MUST be written to non-volatile
        storage.

        If the value of this object is not equal to 'active(1)',
        all associated entries in the nhdPLibLocalIfSetTable,
        nhdPInterfaceStateTable, nhdPIibLinkSetTable, and
        nhdPInterfacePerfTable MUST be deleted."
    REFERENCE
        "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
        Discovery Protocol (NHDP), Clausen, T., Dearlove,
        C., and J. Dean, April 2011"
    DEFVAL { active }
 ::= { nhdPInterfaceEntry 15 }

--
-- Router Parameters - Information Validity Time
--
```

```
nhdnHoldTime OBJECT-TYPE
  SYNTAX      Unsigned32
  UNITS       "milliseconds"
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
    "nhdnHoldTime corresponds to
     N_HOLD_TIME of NHDP and is used as the period
     during which former 1-hop neighbor network
     addresses are advertised as lost in HELLO
     messages, allowing recipients of these HELLO
     messages to accelerate removal of this information
     from their 2-Hop Sets.

     This object is persistent, and when written,
     the entity SHOULD save the change to
     non-volatile storage."
  REFERENCE
    "Section 5 on Protocol Parameters and
     Constraints of RFC 6130 - Mobile Ad Hoc Network
     (MANET) Neighborhood Discovery Protocol (NHDP),
     Clausen, T., Dearlove, C., and J. Dean, April 2011"
  DEFVAL { 6000 }
 ::= { nhdnConfigurationObjGrp 2 }
```

```
nhdnHoldTime OBJECT-TYPE
  SYNTAX      Unsigned32
  UNITS       "milliseconds"
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
    "nhdnHoldTime corresponds to
     I_HOLD_TIME of NHDP and represents the period
     for which a recently used local interface network
     address is recorded.

     This object is persistent, and when written,
     the entity SHOULD save the change to
     non-volatile storage."
  REFERENCE
    "Section 5 on Protocol Parameters and
     Constraints of RFC 6130 - Mobile Ad Hoc Network
     (MANET) Neighborhood Discovery Protocol (NHDP),
     Clausen, T., Dearlove, C., and J. Dean, April 2011"
  DEFVAL { 6000 }
 ::= { nhdnConfigurationObjGrp 3 }
```

```
-- A router's Local Information Base (LIB)
--
-- Local Interface Set Table
--
```

**nhdpLibLocalIfSetTable** OBJECT-TYPE  
SYNTAX SEQUENCE OF NhdplibLocalIfSetEntry  
MAX-ACCESS not-accessible  
STATUS current  
DESCRIPTION  
"A router's Local Interface Set records all network addresses that are defined as local MANET interface network addresses. As such, this table 'sparse augments' the nhdpInterfaceTable when network addresses are being defined for the interfaces existing within the nhdpInterfaceTable. The local interface is defined by the nhdpIfIndex.

The Local Interface Set consists of Local Interface Address Tuples per MANET interface and their prefix lengths (in order to determine the network addresses related to the interface).

A conceptual row in this table exists if and only if a manager has explicitly created the row. The manager can create a row by setting rowStatus to 'createAndGo' or 'createAndWait'.

Further guidance on the addition or removal of local addresses and network addresses is found in Section 9 of RFC 6130."

REFERENCE  
"RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood Discovery Protocol (NHDP), Clausen, T., Dearlove, C., and J. Dean, April 2011"

```
::= { nhdpConfigurationObjGrp 4 }
```

**nhdpLibLocalIfSetEntry** OBJECT-TYPE  
SYNTAX NhdplibLocalIfSetEntry  
MAX-ACCESS not-accessible  
STATUS current  
DESCRIPTION  
"A router's Local Interface Set consists of Configured Interface Address Tuples for each network interface.

The objects in this table are persistent, and when written, the device SHOULD save the change to non-volatile storage. For further information on the storage behavior for these objects, refer to the description for the nhdpLibLocalIfSetRowStatus object."

## REFERENCE

"RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood Discovery Protocol (NHDP), Clausen, T., Dearlove, C., and J. Dean, April 2011"

INDEX { nhdpLibLocalIfSetIndex }

::= { nhdpLibLocalIfSetTable 1 }

NhdpLibLocalIfSetEntry ::=

```
SEQUENCE {
    nhdpLibLocalIfSetIndex
        Integer32,
    nhdpLibLocalIfSetIfIndex
        InterfaceIndex,
    nhdpLibLocalIfSetIpAddrType
        InetAddressType,
    nhdpLibLocalIfSetIpAddr
        InetAddress,
    nhdpLibLocalIfSetIpAddrPrefixLen
        InetAddressPrefixLength,
    nhdpLibLocalIfSetRowStatus
        RowStatus
}
```

nhdpLibLocalIfSetIndex OBJECT-TYPE

SYNTAX Integer32 (0..65535)

MAX-ACCESS not-accessible

STATUS current

## DESCRIPTION

"The index for this table. Necessary because multiple addresses may be associated with a given nhdpIfIndex."

## REFERENCE

"RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood Discovery Protocol (NHDP), Clausen, T., Dearlove, C., and J. Dean, April 2011"

::= { nhdpLibLocalIfSetEntry 1 }

nhdpLibLocalIfSetIfIndex OBJECT-TYPE

SYNTAX InterfaceIndex

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"Specifies the local nhdpIfIndex for which this IP address was added."

## REFERENCE

"RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood Discovery Protocol (NHDP), Clausen, T., Dearlove, C., and J. Dean, April 2011"

::= { nhdpLibLocalIfSetEntry 2 }

nhdpLibLocalIfSetIpAddressType OBJECT-TYPE

SYNTAX InetAddressType

MAX-ACCESS read-create

STATUS current

## DESCRIPTION

"The type of the nhdpLibLocalIfSetIpAddress in the InetAddress MIB (RFC 4001).

Only the values 'ipv4(1)' and 'ipv6(2)' are supported."

## REFERENCE

"RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood Discovery Protocol (NHDP), Clausen, T., Dearlove, C., and J. Dean, April 2011"

::= { nhdpLibLocalIfSetEntry 3 }

nhdpLibLocalIfSetIpAddress OBJECT-TYPE

SYNTAX InetAddress (SIZE(4|16))

MAX-ACCESS read-create

STATUS current

## DESCRIPTION

"nhdpLibLocalIfSetIpAddress is an address of an interface of this router.

This object is interpreted according to the setting of nhdpLibLocalIfSetIpAddressType."

## REFERENCE

"RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood Discovery Protocol (NHDP), Clausen, T., Dearlove, C., and J. Dean, April 2011"

::= { nhdpLibLocalIfSetEntry 4 }

nhdpLibLocalIfSetIpAddressPrefixLen OBJECT-TYPE

SYNTAX InetAddressPrefixLength

MAX-ACCESS read-create

STATUS current

## DESCRIPTION

"Indicates the number of leading one bits that form the mask. The mask is logically ANDed

to the nhdplibLocalIfSetIpAddress to determine the address prefix. A row match is true if the address used as an index falls within the network address range defined by the address prefix."

## REFERENCE

"RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood Discovery Protocol (NHDP), Clausen, T., Dearlove, C., and J. Dean, April 2011"

```
::= { nhdplibLocalIfSetEntry 5 }
```

```
nhdplibLocalIfSetRowStatus OBJECT-TYPE
```

```
SYNTAX      RowStatus
MAX-ACCESS  read-create
STATUS      current
```

## DESCRIPTION

"This object permits management of the table by facilitating actions such as row creation, construction, and destruction. The value of this object has no effect on whether other objects in this conceptual row can be modified.

An entry may not exist in the 'active(1)' state unless all read-create objects in the entry have a defined appropriate value. As no objects in this table have DEFVAL clauses, the management station MUST specify the values of all read-create objects prior to this row transitioning to the 'active(1)' state.

When this object transitions to 'active(1)', all objects in this row SHOULD be written to non-volatile (stable) storage. Read-create objects in this row MAY be modified. When an object in a row with nhdplibRowStatus of 'active(1)' is changed, then the updated value MUST be reflected in NHDP, and this new object value MUST be written to non-volatile storage."

## REFERENCE

"RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood Discovery Protocol (NHDP), Clausen, T., Dearlove, C., and J. Dean, April 2011"

```
DEFVAL { notReady }
::= { nhdplibLocalIfSetEntry 6 }
```

```
--
-- Removed Interface Addr Set Table
--
```

```

nhdpLibRemovedIfAddrSetTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF NhdplibRemovedIfAddrSetEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A router's Removed Interface Address Set records
        network addresses that were recently used as local
        interface network addresses.  If a router's interface
        network addresses are immutable, then the Removed
        Interface Address Set is always empty and may be omitted.
        It consists of Removed Interface Address Tuples, one
        per network address."
    REFERENCE
        "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
        Discovery Protocol (NHDP), Clausen, T., Dearlove,
        C., and J. Dean, April 2011"
 ::= { nhdpConfigurationObjGrp 5 }

nhdpLibRemovedIfAddrSetEntry OBJECT-TYPE
    SYNTAX      NhdplibRemovedIfAddrSetEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A router's Removed Interface Address Set consists
        of Removed Interface Address Tuples, one per network
        address:

        (IR_local_iface_addr, IR_time)

        The association between these addresses and the
        router's Interface is found in the Standard MIB II's
        IP address table (RFC 1213)."
    REFERENCE
        "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
        Discovery Protocol (NHDP), Clausen, T., Dearlove,
        C., and J. Dean, April 2011"
    INDEX { nhdpLibRemovedIfAddrSetIndex }
 ::= { nhdpLibRemovedIfAddrSetTable 1 }

NhdplibRemovedIfAddrSetEntry ::=
    SEQUENCE {
        nhdpLibRemovedIfAddrSetIndex
            Integer32,
        nhdpLibRemovedIfAddrSetIpAddrType
            InetAddressType,
        nhdpLibRemovedIfAddrSetIpAddr
            InetAddress,
        nhdpLibRemovedIfAddrSetIpAddrPrefixLen
    }

```

```

        InetAddressPrefixLength,
nhdplibRemovedIfAddrSetIfIndex
        InterfaceIndex,
nhdplibRemovedIfAddrSetIRTime
        TimeStamp
    }

nhdplibRemovedIfAddrSetIndex OBJECT-TYPE
SYNTAX      Integer32 (0..65535)
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
    "The index for this table. Necessary
    because multiple addresses may be associated
    with a given nhdplibIfIndex."
REFERENCE
    "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
    Discovery Protocol (NHDP), Clausen, T., Dearlove,
    C., and J. Dean, April 2011"
 ::= { nhdplibRemovedIfAddrSetEntry 1 }

nhdplibRemovedIfAddrSetIpAddressType OBJECT-TYPE
SYNTAX      InetAddressType
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The type of the nhdplibRemovedIfAddrSetIpAddress
    in the InetAddress MIB (RFC 4001).

    Only the values 'ipv4(1)' and
    'ipv6(2)' are supported."
REFERENCE
    "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
    Discovery Protocol (NHDP), Clausen, T., Dearlove,
    C., and J. Dean, April 2011"
 ::= { nhdplibRemovedIfAddrSetEntry 2 }

nhdplibRemovedIfAddrSetIpAddress OBJECT-TYPE
SYNTAX      InetAddress (SIZE(4|16))
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "nhdplibRemovedIfAddrSetIpAddress is a
    recently used address of an interface of
    this router."
REFERENCE
    "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
    Discovery Protocol (NHDP), Clausen, T., Dearlove,
```



```
    C., and J. Dean, April 2011"
 ::= { nhdpLibRemovedIfAddrSetEntry 3 }

nhdpLibRemovedIfAddrSetIpAddrPrefixLen OBJECT-TYPE
    SYNTAX      InetAddressPrefixLength
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Indicates the number of leading one bits that
         form the mask.  The mask is logically ANDed
         to the nhdpLibRemovedIfAddrSetIpAddr to determine
         the address prefix.  A row match is true
         if the address used as an index falls within
         the network address range defined by the
         address prefix."
    REFERENCE
        "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
         Discovery Protocol (NHDP), Clausen, T., Dearlove,
         C., and J. Dean, April 2011"
 ::= { nhdpLibRemovedIfAddrSetEntry 4 }

nhdpLibRemovedIfAddrSetIfIndex OBJECT-TYPE
    SYNTAX      InterfaceIndex
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Specifies the local IfIndex from which this
         IP address was recently removed."
    REFERENCE
        "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
         Discovery Protocol (NHDP), Clausen, T., Dearlove,
         C., and J. Dean, April 2011"
 ::= { nhdpLibRemovedIfAddrSetEntry 5 }

nhdpLibRemovedIfAddrSetIRTime OBJECT-TYPE
    SYNTAX      TimeStamp
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "nhdpLibRemovedIfAddrSetIRTime specifies the value
         of sysUptime when this entry should expire and be
         removed from the nhdpLibRemovedIfAddrSetTable."
    REFERENCE
        "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
         Discovery Protocol (NHDP), Clausen, T., Dearlove,
         C., and J. Dean, April 2011"
 ::= { nhdpLibRemovedIfAddrSetEntry 6 }
```

```
--
-- nhdpStateObjGrp
--

-- Contains information describing the current state of the NHDP
-- process on this router.

nhdpStateObjGrp OBJECT IDENTIFIER ::= { nhdpObjects 2 }

nhdpUpTime OBJECT-TYPE
    SYNTAX      TimeStamp
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The value of sysUpTime at the time the current NHDP
        process was initialized."
 ::= { nhdpStateObjGrp 1 }

nhdpInterfaceStateTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF NhdInterfaceStateEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "nhdpInterfaceStateTable lists state information
        related to specific interfaces of this router.
        The value of nhdpIfIndex is an ifIndex from the
        interfaces group defined in the Interfaces Group
        MIB.

        The objects in this table are persistent, and when
        written, the entity SHOULD save the change to
        non-volatile storage."
    REFERENCE
        "RFC 2863 - The Interfaces Group MIB, McCloghrie,
        K., and F. Kastenholz, June 2000."
 ::= { nhdpStateObjGrp 2 }

nhdpInterfaceStateEntry OBJECT-TYPE
    SYNTAX      NhdInterfaceStateEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "nhdpInterfaceStateEntry describes one NHDP
        local interface state as indexed by
        its nhdpIfIndex."
    INDEX { nhdpIfIndex }
 ::= { nhdpInterfaceStateTable 1 }
```

```
NhdpInterfaceStateEntry ::=
    SEQUENCE {
        nhdpIfStateUpTime
            TimeStamp
    }

nhdpIfStateUpTime OBJECT-TYPE
    SYNTAX      TimeStamp
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The value of the sysUpTime when
         NHDP was last initialized on this
         MANET interface."
 ::= { nhdpInterfaceStateEntry 1 }

--
-- This table allows for the mapping between discovered
-- remote interfaces and routers and their addresses.
--

nhdpDiscIfSetTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF NhdpDiscIfSetEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A router's set of discovered interfaces on
         neighboring routers."
    REFERENCE
        "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
         Discovery Protocol (NHDP), Clausen, T., Dearlove,
         C., and J. Dean, April 2011"
 ::= { nhdpStateObjGrp 3 }

nhdpDiscIfSetEntry OBJECT-TYPE
    SYNTAX      NhdpDiscIfSetEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The entries include the nhdpDiscRouterIndex of
         the discovered router, the nhdpDiscIfIndex
         of the discovered interface, and the
         current set of addresses associated
         with this neighbor interface. The
         nhdpDiscIfIndex uniquely identifies
         the remote interface address sets
         through this table. It does not need
         to be unique across the MANET but MUST
```

```

        be locally unique within this router."
REFERENCE
    "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
    Discovery Protocol (NHDP), Clausen, T., Dearlove,
    C., and J. Dean, April 2011"
INDEX { nhdpDiscIfSetIndex }
 ::= { nhdpDiscIfSetTable 1 }

NhdpDiscIfSetEntry ::=
SEQUENCE {
    nhdpDiscIfSetIndex
        Integer32,
    nhdpDiscIfIndex
        NeighborIfIndex,
    nhdpDiscRouterIndex
        NeighborRouterIndex,
    nhdpDiscIfSetIpAddrType
        InetAddressType,
    nhdpDiscIfSetIpAddr
        InetAddress,
    nhdpDiscIfSetIpAddrPrefixLen
        InetAddressPrefixLength
}

nhdpDiscIfSetIndex OBJECT-TYPE
SYNTAX      Integer32 (0..65535)
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
    "The index for this table. Necessary
    because multiple addresses may be associated
    with a given nhdpDiscIfIndex."
REFERENCE
    "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
    Discovery Protocol (NHDP), Clausen, T., Dearlove,
    C., and J. Dean, April 2011"
 ::= { nhdpDiscIfSetEntry 1 }

nhdpDiscIfIndex OBJECT-TYPE
SYNTAX      NeighborIfIndex
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The NHDP interface index (locally created)
    of a neighbor's interface. Used for cross-
    indexing into other NHDP tables and other
    MIB modules."
REFERENCE

```

```
"RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
Discovery Protocol (NHDP), Clausen, T., Dearlove,
C., and J. Dean, April 2011"
 ::= { nhdpDiscIfSetEntry 2 }

nhdpDiscRouterIndex OBJECT-TYPE
    SYNTAX      NeighborRouterIndex
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The NHDP neighbor index (locally created)
        of a neighboring router. Used for cross-
        indexing into other NHDP tables and other
        MIB modules."
    REFERENCE
        "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
        Discovery Protocol (NHDP), Clausen, T., Dearlove,
        C., and J. Dean, April 2011"
 ::= { nhdpDiscIfSetEntry 3 }

nhdpDiscIfSetIpAddrType OBJECT-TYPE
    SYNTAX      InetAddressType
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The type of the nhdpDiscIfSetIpAddr
        in the InetAddress MIB (RFC 4001).

        Only the values 'ipv4(1)' and
        'ipv6(2)' are supported."
    REFERENCE
        "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
        Discovery Protocol (NHDP), Clausen, T., Dearlove,
        C., and J. Dean, April 2011"
 ::= { nhdpDiscIfSetEntry 4 }

nhdpDiscIfSetIpAddr OBJECT-TYPE
    SYNTAX      InetAddress (SIZE(4|16))
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The nhdpDiscIfSetIpAddr is a
        recently used address of a neighbor
        of this router."
    REFERENCE
        "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
        Discovery Protocol (NHDP), Clausen, T., Dearlove,
        C., and J. Dean, April 2011"
```

```
::= { nhdpDiscIfSetEntry 5 }

nhdpDiscIfSetIpAddrPrefixLen OBJECT-TYPE
    SYNTAX      InetAddressPrefixLength
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Indicates the number of leading one bits that
         form the mask. The mask is logically ANDED
         to the nhdpDiscIfSetIpAddr to determine
         the address prefix. A row match is true
         if the address used as an index falls within
         the network address range defined by the
         address prefix."
    REFERENCE
        "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
         Discovery Protocol (NHDP), Clausen, T., Dearlove,
         C., and J. Dean, April 2011"
 ::= { nhdpDiscIfSetEntry 6 }

-- Interface Information Base (IIB)
--
-- Link Set
--

nhdpIibLinkSetTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF NhdpiibLinkSetEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A Link Set of an interface records all links
         from other routers that are, or recently
         were, 1-hop neighbors."
    REFERENCE
        "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
         Discovery Protocol (NHDP), Clausen, T., Dearlove,
         C., and J. Dean, April 2011"
 ::= { nhdpStateObjGrp 4 }

nhdpIibLinkSetEntry OBJECT-TYPE
    SYNTAX      NhdpiibLinkSetEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A Link Set consists of Link Tuples, each
         representing a single link indexed by the
         local and remote interface pair:"
```

```
(L_neighbor_iface_addr_list, L_HEARD_time,
  L_SYM_time, L_quality, L_pending,
  L_lost, L_time).
```

The local interface is indexed via the `nhdpIfIndex`. The 1-hop interface is indexed via the `nhdpDiscIfIndex`. There SHOULD be an entry in this table for each local interface and associated 1-hop neighbor reachable on this local interface.

Note that `L_quality` is not included in the entries below, because updates may be required too frequently."

REFERENCE

"RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood Discovery Protocol (NHDP), Clausen, T., Dearlove, C., and J. Dean, April 2011"

```
INDEX { nhdpIfIndex,
        nhdpDiscIfIndex }
 ::= { nhdpIibLinkSetTable 1 }
```

`NhdpIibLinkSetEntry` ::=

```
SEQUENCE {
  nhdpIibLinkSetLHeardTime
    TimeStamp,
  nhdpIibLinkSetLSymTime
    TimeStamp,
  nhdpIibLinkSetLPending
    TruthValue,
  nhdpIibLinkSetLLost
    TruthValue,
  nhdpIibLinkSetLTime
    TimeStamp
}
```

`nhdpIibLinkSetLHeardTime` OBJECT-TYPE

SYNTAX TimeStamp

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"`nhdpIibLinkSetLHeardTime` corresponds to `L_HEARD_time` of NHDP and represents the time up to which the MANET interface of the 1-hop neighbor would be considered heard if not considering link quality."

REFERENCE

"RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood

```
Discovery Protocol (NHDP), Clausen, T., Dearlove,
C., and J. Dean, April 2011"
 ::= { nhdpIibLinkSetEntry 1 }

nhdpIibLinkSetLSymTime OBJECT-TYPE
    SYNTAX      TimeStamp
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "nhdpIibLinkSetLSymTime corresponds
         to L_SYM_time of NHDP and represents the time
         up to which the link to the 1-hop neighbor
         would be considered symmetric if not considering
         link quality."
    REFERENCE
        "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
         Discovery Protocol (NHDP), Clausen, T., Dearlove,
         C., and J. Dean, April 2011"
 ::= { nhdpIibLinkSetEntry 2 }

nhdpIibLinkSetLPending OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "nhdpIibLinkSetLPending corresponds
         to L_pending of NHDP and is a boolean flag,
         describing if a link is considered pending
         (i.e., a candidate, but not yet established,
         link)."
    REFERENCE
        "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
         Discovery Protocol (NHDP), Clausen, T., Dearlove,
         C., and J. Dean, April 2011"
 ::= { nhdpIibLinkSetEntry 3 }

nhdpIibLinkSetLLOst OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "nhdpIibLinkSetLLOst corresponds
         to L_lost of NHDP and is a boolean flag,
         describing if a link is considered lost due
         to low link quality."
    REFERENCE
        "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
         Discovery Protocol (NHDP), Clausen, T., Dearlove,
```



```

    C., and J. Dean, April 2011"
 ::= { nhdplibLinkSetEntry 4 }

nhdplibLinkSetLTime OBJECT-TYPE
    SYNTAX      TimeStamp
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "nhdplibLinkSetLTime specifies the value
         of sysUptime when this entry should expire and be
         removed from the nhdplibLinkSetTable."
    REFERENCE
        "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
         Discovery Protocol (NHDP), Clausen, T., Dearlove,
         C., and J. Dean, April 2011"
 ::= { nhdplibLinkSetEntry 5 }

--
-- 2-Hop Set
--

nhdplib2HopSetTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF Nhdplib2HopSetEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A 2-Hop Set of an interface records network
         addresses of symmetric 2-hop neighbors and
         the symmetric links to symmetric 1-hop neighbors
         through which these symmetric 2-hop neighbors
         can be reached. It consists of 2-Hop Tuples."
    REFERENCE
        "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
         Discovery Protocol (NHDP), Clausen, T., Dearlove,
         C., and J. Dean, April 2011"
 ::= { nhdplib2HopSetEntry 5 }

nhdplib2HopSetEntry OBJECT-TYPE
    SYNTAX      Nhdplib2HopSetEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "nhdplib2HopSetTable consists of 2-Hop Tuples,
         each representing a single network address of
         a symmetric 2-hop neighbor and a single MANET
         interface of a symmetric 1-hop neighbor.

         (N2_neighbor_iface_addr_list,
          N2_2hop_addr, N2_time)."

```

The entries include the 2-hop neighbor addresses, which act as the table index, and associated 1-hop symmetric link address set, designated through `nhdpDiscIfIndex`, and an expiration time. The `nhdpIfIndex` in the INDEX is the interface index of the local interface through which these 2-hop addresses are accessible. The `nhdpDiscIfIndex` in the INDEX represents the 1-hop neighbor interface through which these 2-hop addresses are reachable."

## REFERENCE

"RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood Discovery Protocol (NHDP), Clausen, T., Dearlove, C., and J. Dean, April 2011"

```
INDEX { nhdpIfIndex,
        nhdpDiscIfIndex,
        nhdpIib2HopSetIpAddressType,
        nhdpIib2HopSetIpAddress
      }
```

```
::= { nhdpIib2HopSetTable 1 }
```

```
NhdpIib2HopSetEntry ::=
```

```
SEQUENCE {
  nhdpIib2HopSetIpAddressType
    InetAddressType,
  nhdpIib2HopSetIpAddress
    InetAddress,
  nhdpIib2HopSetIpAddrPrefixLen
    InetAddressPrefixLength,
  nhdpIib2HopSet1HopIfIndex
    NeighborIfIndex,
  nhdpIib2HopSetN2Time
    TimeStamp
}
```

```
nhdpIib2HopSetIpAddressType OBJECT-TYPE
```

```
SYNTAX      InetAddressType
```

```
MAX-ACCESS  not-accessible
```

```
STATUS      current
```

```
DESCRIPTION
```

"The type of the `nhdpIib2HopSetIpAddress` in the `InetAddress` MIB module (RFC 4001).

Only the values 'ipv4(1)' and 'ipv6(2)' are supported."

## REFERENCE

"RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood

```
Discovery Protocol (NHDP), Clausen, T., Dearlove,
C., and J. Dean, April 2011"
 ::= { nhdpIib2HopSetEntry 1 }

nhdpIib2HopSetIpAddress OBJECT-TYPE
    SYNTAX      InetAddress (SIZE(4|16))
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "nhdpIib2HopSetIpAddr corresponds
        to N2_2hop_addr of NHDP and is a network
        address of a symmetric 2-hop neighbor that
        has a symmetric link (using any MANET
        interface) to the indicated symmetric
        1-hop neighbor."
    REFERENCE
        "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
        Discovery Protocol (NHDP), Clausen, T., Dearlove,
        C., and J. Dean, April 2011"
 ::= { nhdpIib2HopSetEntry 2 }

nhdpIib2HopSetIpAddressPrefixLen OBJECT-TYPE
    SYNTAX      InetAddressPrefixLength
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Indicates the number of leading one bits that
        form the mask. The mask is logically ANDed
        to the nhdpIib2HopSetIpAddress to determine
        the address prefix. A row match is true
        if the address used as an index falls within
        the network address range defined by the
        address prefix."
    REFERENCE
        "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
        Discovery Protocol (NHDP), Clausen, T., Dearlove,
        C., and J. Dean, April 2011"
 ::= { nhdpIib2HopSetEntry 3 }

nhdpIib2HopSet1HopIfIndex OBJECT-TYPE
    SYNTAX      NeighborIfIndex
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "nhdpIib2HopSet1HopIfIndex is
        nhdpDiscIfIndex of the 1-hop
        neighbor that communicated the ipAddress
        of the 2-hop neighbor in this row entry."
```

```

REFERENCE
    "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
    Discovery Protocol (NHDP), Clausen, T., Dearlove,
    C., and J. Dean, April 2011"
 ::= { nhdplib2HopSetEntry 4 }

nhdplib2HopSetN2Time OBJECT-TYPE
    SYNTAX      TimeStamp
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "nhdplib2HopSetN2Time specifies the value
        of sysUptime when this entry should expire and be
        removed from the nhdplib2HopSetTable."
    REFERENCE
        "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
        Discovery Protocol (NHDP), Clausen, T., Dearlove,
        C., and J. Dean, April 2011"
 ::= { nhdplib2HopSetEntry 5 }

--
-- Neighbor Information Base (NIB)
--
-- Each router maintains a Neighbor Information Base
-- that records information about addresses of
-- current and recently symmetric 1-hop neighbors.

--
-- Neighbor Set
--
-- The Neighbor Set Table is small because
-- most of the corresponding information is found
-- in the nhdpDiscoveredIfTable above.
--

nhdpNibNeighborSetTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF NhdpNibNeighborSetEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A router's Neighbor Set records all
        network addresses of each 1-hop
        neighbor."
    REFERENCE
        "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
        Discovery Protocol (NHDP), Clausen, T., Dearlove,
        C., and J. Dean, April 2011"
 ::= { nhdpStateObjGrp 6 }

```

```

nhdpNibNeighborSetEntry OBJECT-TYPE
    SYNTAX      NhdpNextNeighborSetEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A router's Neighbor Set consists
        of Neighbor Tuples, each representing
        a single 1-hop neighbor:

        (N_neighbor_addr_list, N_symmetric)"
    REFERENCE
        "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
        Discovery Protocol (NHDP), Clausen, T., Dearlove,
        C., and J. Dean, April 2011"
    INDEX { nhdpDiscRouterIndex }
 ::= { nhdpNibNeighborSetTable 1 }

NhdpNextNeighborSetEntry ::=
    SEQUENCE {
        nhdpNibNeighborSetNSymmetric
        TruthValue
    }

nhdpNibNeighborSetNSymmetric OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "nhdpNibNeighborNSymmetric corresponds
        to N_symmetric of NHDP and is a boolean flag,
        describing if this is a symmetric 1-hop neighbor."
    REFERENCE
        "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
        Discovery Protocol (NHDP), Clausen, T., Dearlove,
        C., and J. Dean, April 2011"
 ::= { nhdpNibNeighborSetEntry 1 }

--
-- Lost Neighbor Set
--
nhdpNibLostNeighborSetTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF NhdpNextLostNeighborSetEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A router's Lost Neighbor Set records network
        addresses of routers that were recently
        symmetric 1-hop neighbors but are now

```

```

        advertised as lost."
REFERENCE
    "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
    Discovery Protocol (NHDP), Clausen, T., Dearlove,
    C., and J. Dean, April 2011"
 ::= { nhdpStateObjGrp 7 }

nhdpNibLostNeighborSetEntry OBJECT-TYPE
SYNTAX      NhdpNextLostNeighborSetEntry
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
    "A router's Lost Neighbor Set consists of
    Lost Neighbor Tuples, each representing a
    single such network address:

    (NL_neighbor_addr, NL_time)"
REFERENCE
    "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
    Discovery Protocol (NHDP), Clausen, T., Dearlove,
    C., and J. Dean, April 2011"
INDEX { nhdpDiscRouterIndex }
 ::= { nhdpNibLostNeighborSetTable 1 }

NhdpNextLostNeighborSetEntry ::=
SEQUENCE {
    nhdpNibLostNeighborSetNLTime
        TimeStamp
}

nhdpNibLostNeighborSetNLTime OBJECT-TYPE
SYNTAX      TimeStamp
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "nhdpNibLostNeighborSetNLTime
    specifies the value of sysUptime when this entry
    should expire and be removed from the
    nhdpNibLostNeighborSetTable."
REFERENCE
    "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
    Discovery Protocol (NHDP), Clausen, T., Dearlove,
    C., and J. Dean, April 2011"
 ::= { nhdpNibLostNeighborSetEntry 1 }

--
-- nhdpPerformanceObjGrp
--

```

```
-- Contains objects that help to characterize the performance of
-- the NHDP process, typically counters.
--
nhdpPerformanceObjGrp OBJECT IDENTIFIER ::= { nhdpObjects 3 }

--
-- Objects per local interface
--

nhdpInterfacePerfTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF NhdpInterfacePerfEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "This table summarizes performance objects that are
        measured per local NHDP interface."
    REFERENCE
        "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
        Discovery Protocol (NHDP), Clausen, T., Dearlove,
        C., and J. Dean, April 2011"
    ::= { nhdpPerformanceObjGrp 1 }

nhdpInterfacePerfEntry OBJECT-TYPE
    SYNTAX      NhdpInterfacePerfEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A single entry contains performance counters for
        a local NHDP interface."
    INDEX { nhdpIfIndex }

    ::= { nhdpInterfacePerfTable 1 }

NhdpInterfacePerfEntry ::=
    SEQUENCE {
        nhdpIfHelloMessageXmits
            Counter32,
        nhdpIfHelloMessageRecvd
            Counter32,
        nhdpIfHelloMessageXmitAccumulatedSize
            Counter64,
        nhdpIfHelloMessageRecvdAccumulatedSize
            Counter64,
        nhdpIfHelloMessageTriggeredXmits
            Counter32,
        nhdpIfHelloMessagePeriodicXmits
            Counter32,
        nhdpIfHelloMessageXmitAccumulatedSymmetricNeighborCount
```

```
        Counter32,
nhdpIfHelloMessageXmitAccumulatedHeardNeighborCount
        Counter32,
nhdpIfHelloMessageXmitAccumulatedLostNeighborCount
        Counter32
    }

nhdpIfHelloMessageXmits OBJECT-TYPE
    SYNTAX      Counter32
    UNITS       "messages"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "A counter is incremented each time a HELLO
        message has been transmitted on that interface."
 ::= { nhdpInterfacePerfEntry 1 }

nhdpIfHelloMessageRecvd OBJECT-TYPE
    SYNTAX      Counter32
    UNITS       "messages"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "A counter is incremented each time a
        HELLO message has been received on that interface."
 ::= { nhdpInterfacePerfEntry 2 }

nhdpIfHelloMessageXmitAccumulatedSize OBJECT-TYPE
    SYNTAX      Counter64
    UNITS       "octets"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "A counter is incremented by the number of octets in
        a HELLO message each time a
        HELLO message has been sent."
 ::= { nhdpInterfacePerfEntry 3 }

nhdpIfHelloMessageRecvdAccumulatedSize OBJECT-TYPE
    SYNTAX      Counter64
    UNITS       "octets"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "A counter is incremented by the number of octets in
        a HELLO message each time a
        HELLO message has been received."
 ::= { nhdpInterfacePerfEntry 4 }
```



```
nhdpIfHelloMessageTriggeredXmits OBJECT-TYPE
    SYNTAX      Counter32
    UNITS       "messages"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "A counter is incremented each time a triggered
        HELLO message has been sent."
 ::= { nhdpInterfacePerfEntry 5 }

nhdpIfHelloMessagePeriodicXmits OBJECT-TYPE
    SYNTAX      Counter32
    UNITS       "messages"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "A counter is incremented each time a periodic
        HELLO message has been sent."
 ::= { nhdpInterfacePerfEntry 6 }

nhdpIfHelloMessageXmitAccumulatedSymmetricNeighborCount OBJECT-TYPE
    SYNTAX      Counter32
    UNITS       "neighbors"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "A counter is incremented by the number of advertised
        symmetric neighbors in a HELLO each time a HELLO
        message has been sent."
 ::= { nhdpInterfacePerfEntry 7 }

nhdpIfHelloMessageXmitAccumulatedHeardNeighborCount OBJECT-TYPE
    SYNTAX      Counter32
    UNITS       "neighbors"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "A counter is incremented by the number of advertised
        heard neighbors in a HELLO each time a HELLO
        message has been sent."
 ::= { nhdpInterfacePerfEntry 8 }

nhdpIfHelloMessageXmitAccumulatedLostNeighborCount OBJECT-TYPE
    SYNTAX      Counter32
    UNITS       "neighbors"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
```

```

        "A counter is incremented by the number of advertised
        lost neighbors in a HELLO each time a HELLO
        message has been sent."
 ::= { nhdpInterfacePerfEntry 9 }

--
-- Objects per discovered neighbor interface
--
nhdpDiscIfSetPerfTable OBJECT-TYPE
    SYNTAX          SEQUENCE OF NhdpcDiscIfSetPerfEntry
    MAX-ACCESS      not-accessible
    STATUS          current
    DESCRIPTION
        "A router's set of performance properties for
        each discovered interface of a neighbor."
    REFERENCE
        "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
        Discovery Protocol (NHDP), Clausen, T., Dearlove,
        C., and J. Dean, April 2011"
 ::= { nhdpPerformanceObjGrp 2 }

nhdpDiscIfSetPerfEntry OBJECT-TYPE
    SYNTAX          NhdpcDiscIfSetPerfEntry
    MAX-ACCESS      not-accessible
    STATUS          current
    DESCRIPTION
        "There is an entry for each discovered
        interface of a neighbor."
    REFERENCE
        "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
        Discovery Protocol (NHDP), Clausen, T., Dearlove,
        C., and J. Dean, April 2011"
    INDEX { nhdpDiscIfIndex }
 ::= { nhdpDiscIfSetPerfTable 1 }

NhdpcDiscIfSetPerfEntry ::=
    SEQUENCE {
        nhdpDiscIfRecvdPackets
            Counter32,
        nhdpDiscIfExpectedPackets
            Counter32
    }

nhdpDiscIfRecvdPackets OBJECT-TYPE
    SYNTAX          Counter32
    UNITS           "packets"
    MAX-ACCESS      read-only
    STATUS          current

```

```
DESCRIPTION
  "This counter increments each
  time this router receives a packet from that interface
  of the neighbor."
REFERENCE
  "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
  Discovery Protocol (NHDP), Clausen, T., Dearlove,
  C., and J. Dean, April 2011"
 ::= { nhdDiscIfSetPerfEntry 1 }

nhdDiscIfExpectedPackets OBJECT-TYPE
  SYNTAX      Counter32
  UNITS       "packets"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "This counter increments by the number
    of missed packets from this neighbor based
    on the packet sequence number each time this
    router receives a packet from that interface
    of the neighbor."
  REFERENCE
    "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
    Discovery Protocol (NHDP), Clausen, T., Dearlove,
    C., and J. Dean, April 2011"
 ::= { nhdDiscIfSetPerfEntry 2 }

--
-- Objects concerning the Neighbor Set
--

nhdpNibNeighborSetChanges OBJECT-TYPE
  SYNTAX      Counter32
  UNITS       "changes"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "This counter increments each time the Neighbor Set changes.
    A change occurs whenever a new Neighbor Tuple has been
    added, a Neighbor Tuple has been removed, or any entry of
    a Neighbor Tuple has been modified."
 ::= { nhdpPerformanceObjGrp 3 }

--
-- Objects per discovered neighbor
--

nhdDiscNeighborSetPerfTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF NhdDiscNeighborSetPerfEntry
```

```

MAX-ACCESS    not-accessible
STATUS        current
DESCRIPTION   "A router's set of discovered neighbors and
               their properties."
REFERENCE     "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
               Discovery Protocol (NHDP), Clausen, T., Dearlove,
               C., and J. Dean, April 2011"
 ::= { nhdPerformanceObjGrp 4 }

nhdDiscNeighborSetPerfEntry OBJECT-TYPE
SYNTAX        NhdDiscNeighborSetPerfEntry
MAX-ACCESS    not-accessible
STATUS        current
DESCRIPTION   "The entries include the nhdDiscRouterIndex of
               the discovered router as well as performance
               objects related to changes of the Neighbor
               Set."
REFERENCE     "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
               Discovery Protocol (NHDP), Clausen, T., Dearlove,
               C., and J. Dean, April 2011"
INDEX { nhdDiscRouterIndex }
 ::= { nhdDiscNeighborSetPerfTable 1 }

NhdDiscNeighborSetPerfEntry ::=
SEQUENCE {
    nhdDiscNeighborNibNeighborSetChanges
        Counter32,
    nhdDiscNeighborNibNeighborSetUpTime
        TimeStamp,
    nhdDiscNeighborNibNeighborSetReachableLinkChanges
        Counter32
}

nhdDiscNeighborNibNeighborSetChanges OBJECT-TYPE
SYNTAX        Counter32
UNITS         "changes"
MAX-ACCESS    read-only
STATUS        current
DESCRIPTION   "This object returns the number of changes
               to the given Neighbor Tuple."
REFERENCE     "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
               Discovery Protocol (NHDP), Clausen, T., Dearlove,

```

```

    C., and J. Dean, April 2011"
 ::= { nhdDiscNeighborSetPerfEntry 1 }

nhdDiscNeighborNibNeighborSetUpTime OBJECT-TYPE
    SYNTAX      TimeStamp
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "This object returns the sysUpTime when
         the neighbor becomes 'nbrup'. A neighbor is
         said to become 'nbrup' if a new nhdNibNeighborSetEntry
         is created for a particular nhdNibNeighborSetRouterIndex.
         It becomes 'nbrdown' if the entry for that neighbor
         has been deleted."
    REFERENCE
        "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
         Discovery Protocol (NHDP), Clausen, T., Dearlove,
         C., and J. Dean, April 2011"
 ::= { nhdDiscNeighborSetPerfEntry 2 }

nhdDiscNeighborNibNeighborSetReachableLinkChanges OBJECT-TYPE
    SYNTAX      Counter32
    UNITS       "changes"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "This object counts each time the neighbor changes
         the interface(s) over which it is reachable.
         A change in the set of Link Tuples corresponding
         to the appropriate Neighbor Tuple is registered,
         i.e., a corresponding Link Tuple is added or removed
         from the set of all corresponding Link Tuples."
    REFERENCE
        "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
         Discovery Protocol (NHDP), Clausen, T., Dearlove,
         C., and J. Dean, April 2011"
 ::= { nhdDiscNeighborSetPerfEntry 3 }

--
-- Objects per discovered 2-hop neighbor
--
nhdPIib2HopSetPerfTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF NhdPIib2HopSetPerfEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "This table contains performance objects per
         discovered 2-hop neighbor."

```

```
REFERENCE
    "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
    Discovery Protocol (NHDP), Clausen, T., Dearlove,
    C., and J. Dean, April 2011"
 ::= { nhdpPerformanceObjGrp 5 }

nhdpIib2HopSetPerfEntry OBJECT-TYPE
SYNTAX      Nhdpiib2HopSetPerfEntry
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
    "The entries contain performance objects per
    discovered 2-hop neighbor."
REFERENCE
    "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
    Discovery Protocol (NHDP), Clausen, T., Dearlove,
    C., and J. Dean, April 2011"
INDEX { nhdpDiscRouterIndex }
 ::= { nhdpIib2HopSetPerfTable 1 }

Nhdpiib2HopSetPerfEntry ::=
SEQUENCE {
    nhdpIib2HopSetPerfChanges
        Counter32,
    nhdpIib2HopSetPerfUpTime
        TimeStamp
}

nhdpIib2HopSetPerfChanges OBJECT-TYPE
SYNTAX      Counter32
UNITS       "changes"
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "This object counts the changes of the union of all
    N2_neighbor_iface_addr_list of 2-Hop Tuples with an
    N2_2hop_addr equal to one of the given 2-hop
    neighbor's addresses."
REFERENCE
    "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
    Discovery Protocol (NHDP), Clausen, T., Dearlove,
    C., and J. Dean, April 2011"
 ::= { nhdpIib2HopSetPerfEntry 1 }

nhdpIib2HopSetPerfUpTime OBJECT-TYPE
SYNTAX      TimeStamp
MAX-ACCESS  read-only
STATUS      current
```

```

DESCRIPTION
  "This object returns the sysUpTime
  when the 2-Hop Tuple
  corresponding to the given 2-hop neighbor IP address
  was registered in the nhdpIib2HopSetTable."
REFERENCE
  "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
  Discovery Protocol (NHDP), Clausen, T., Dearlove,
  C., and J. Dean, April 2011"
 ::= { nhdpIib2HopSetPerfEntry 2 }

--
-- nhdpNotifications
--

nhdpNotificationsObjects OBJECT IDENTIFIER ::= { nhdpNotifications 0 }
nhdpNotificationsControl OBJECT IDENTIFIER ::= { nhdpNotifications 1 }
nhdpNotificationsStates OBJECT IDENTIFIER ::= { nhdpNotifications 2 }

-- nhdpNotificationsObjects

nhdpNbrStateChange NOTIFICATION-TYPE
  OBJECTS { nhdpIfName, -- The originator of
            -- the notification.
            nhdpNbrState -- The new state
          }
  STATUS current
  DESCRIPTION
    "nhdpNbrStateChange is a notification sent when
    more than nhdpNbrStateChangeThreshold neighbors change
    their status (i.e., 'down(0)', 'asymmetric(1)', or
    'symmetric(2)') within a time window of
    nhdpNbrStateChangeWindow."
 ::= { nhdpNotificationsObjects 1 }

nhdp2HopNbrStateChange NOTIFICATION-TYPE
  OBJECTS { nhdpIfName, -- The originator
            -- of the notification
            nhdp2HopNbrState -- The new state
          }
  STATUS current
  DESCRIPTION
    "nhdp2HopNbrStateChange is a notification sent
    when more than nhdp2HopNbrStateChangeThreshold 2-hop
    neighbors change their status (i.e., 'down(0)' or
    'up(1)') within a time window of
    nhdp2HopNbrStateChangeWindow."
 ::= { nhdpNotificationsObjects 2 }

```

```
nhdPIfStateChange NOTIFICATION-TYPE
  OBJECTS { nhdPIfName, -- The local interface
            nhdPIfStatus -- The new status
          }
  STATUS      current
  DESCRIPTION
    "nhdPIfStateChange is a notification sent when
     nhdPIfStatus has changed on this interface."
 ::= { nhdPNotificationsObjects 3 }

-- nhdPNotificationsControl

nhdPNbrStateChangeThreshold OBJECT-TYPE
  SYNTAX      Integer32 (0..255)
  UNITS       "changes"
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
    "A threshold value for the
     nhdPNbrStateChange object.  If the
     number of occurrences exceeds this threshold
     within the previous nhdPNbrStateChangeWindow,
     then the nhdPNbrStateChange notification
     is to be sent.

     It is recommended that the value of this
     threshold be set to at least 10 and higher
     in dense topologies with frequent expected
     topology changes."
  DEFVAL { 10 }
 ::= { nhdPNotificationsControl 1 }

nhdPNbrStateChangeWindow OBJECT-TYPE
  SYNTAX      TimeTicks
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
    "A time window for the
     nhdPNbrStateChange object.  If the
     number of occurrences exceeds the
     nhdPNbrStateChangeThreshold
     within the previous nhdPNbrStateChangeWindow,
     then the nhdPNbrStateChange notification
     is to be sent.

     It is recommended that the value for this
     window be set to at least 5 times the
     nhdPHelloInterval."
```



```

        This object represents the time in hundredths
        of a second."
    DEFVAL { 1000 }
 ::= { nhdpNotificationsControl 2 }

nhdp2HopNbrStateChangeThreshold OBJECT-TYPE
    SYNTAX      Integer32 (0..255)
    UNITS       "changes"
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "A threshold value for the
        nhdp2HopNbrStateChange object.  If the
        number of occurrences exceeds this threshold
        within the previous nhdp2HopNbrStateChangeWindow,
        then the nhdp2HopNbrStateChange notification
        is to be sent.

        It is recommended that the value of this
        threshold be set to at least 10 and higher
        when topologies are expected to be highly dynamic."
    DEFVAL { 10 }
 ::= { nhdpNotificationsControl 3 }

nhdp2HopNbrStateChangeWindow OBJECT-TYPE
    SYNTAX      TimeTicks
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "A time window for the
        nhdp2HopNbrStateChange object.  If the
        number of occurrences exceeds the
        nhdp2HopNbrStateChangeThreshold
        within the previous nhdp2HopNbrStateChangeWindow,
        then the nhdp2HopNbrStateChange notification
        is to be sent.

        It is recommended that the value for this
        window be set to at least 5 times
        nhdpHelloInterval.

        This object represents the time in hundredths
        of a second."
    DEFVAL { 1000 }
 ::= { nhdpNotificationsControl 4 }

-- nhdpNotificationStates
```

```

nhdpNbrState OBJECT-TYPE
    SYNTAX      INTEGER {
                down(0),
                asymmetric(1),
                symmetric(2)
                }
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "NHDP neighbor states.  In NHDP, it is not
        necessary to remove Protocol Tuples from Protocol Sets
        at the exact time indicated, only to behave as if the
        Protocol Tuples were removed at that time.  This case is
        indicated here as 'down(0)', all other cases being
        indicated as 'asymmetric(1)' or 'symmetric(2)'.  If 'down(0)',
        the direct neighbor is also added to the
        nhdpNibLostNeighborSetTable."
 ::= { nhdpNotificationsStates 1 }

nhdp2HopNbrState OBJECT-TYPE
    SYNTAX      INTEGER {
                down(0),
                up(1)
                }
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "NHDP 2-hop neighbor states.  In NHDP, it is not
        necessary to remove Protocol Tuples from Protocol Sets
        at the exact time indicated, only to behave as if the
        Protocol Tuples were removed at that time.  This case is
        indicated here as 'down(0)'; otherwise, it is 'up(1)'."
 ::= { nhdpNotificationsStates 2 }

--
-- nhdpConformance information
--

nhdpCompliances      OBJECT IDENTIFIER ::= { nhdpConformance 1 }
nhdpMIBGroups        OBJECT IDENTIFIER ::= { nhdpConformance 2 }

-- Compliance Statements
nhdpBasicCompliance MODULE-COMPLIANCE
    STATUS      current
    DESCRIPTION
        "The basic implementation requirements for
        managed network entities that implement
        NHDP."

```

```
MODULE -- this module
MANDATORY-GROUPS { nhdpConfigurationGroup }
 ::= { nhdpCompliances 1 }

nhdpFullCompliance MODULE-COMPLIANCE
STATUS current
DESCRIPTION
  "The full implementation requirements for
  managed network entities that implement
  NHDP."
MODULE -- this module
MANDATORY-GROUPS { nhdpConfigurationGroup,
                   nhdpStateGroup,
                   nhdpNotificationObjectGroup,
                   nhdpNotificationGroup,
                   nhdpPerformanceGroup
                   }
 ::= { nhdpCompliances 2 }

--
-- Units of Conformance
--

nhdpConfigurationGroup OBJECT-GROUP
OBJECTS {
  nhdpIfName,
  nhdpIfStatus,
  nhdpHelloInterval,
  nhdpHelloMinInterval,
  nhdpRefreshInterval,
  nhdpLHoldTime,
  nhdpPHoldTime,
  nhdpHystAcceptQuality,
  nhdpHystRejectQuality,
  nhdpInitialQuality,
  nhdpInitialPending,
  nhdpHpMaxJitter,
  nhdpHtMaxJitter,
  nhdpNHoldTime,
  nhdpIHoldTime,
  nhdpIfRowStatus,
  nhdpLibLocalIfSetIfIndex,
  nhdpLibLocalIfSetIpAddrType,
  nhdpLibLocalIfSetIpAddr,
  nhdpLibLocalIfSetIpAddrPrefixLen,
  nhdpLibLocalIfSetRowStatus,
  nhdpLibRemovedIfAddrSetIpAddrType,
  nhdpLibRemovedIfAddrSetIpAddr,
```

```
    nhdpLibRemovedIfAddrSetIpAddrPrefixLen,
    nhdpLibRemovedIfAddrSetIfIndex,
    nhdpLibRemovedIfAddrSetIRTime
  }
  STATUS          current
  DESCRIPTION
    "Set of NHDP configuration objects implemented
    in this module."
 ::= { nhdpMIBGroups 2 }

nhdpStateGroup OBJECT-GROUP
  OBJECTS {
    nhdpUpTime,
    nhdpIfStateUpTime,
    nhdpDiscRouterIndex,
    nhdpDiscIfIndex,
    nhdpDiscIfSetIpAddrType,
    nhdpDiscIfSetIpAddr,
    nhdpDiscIfSetIpAddrPrefixLen,
    nhdpIibLinkSetLHeardTime,
    nhdpIibLinkSetLSymTime,
    nhdpIibLinkSetLPending,
    nhdpIibLinkSetLLOst,
    nhdpIibLinkSetLTime,
    nhdpIib2HopSetIpAddrPrefixLen,
    nhdpIib2HopSet1HopIfIndex,
    nhdpIib2HopSetN2Time,
    nhdpNibNeighborSetNSymmetric,
    nhdpNibLostNeighborSetNLTime
  }
  STATUS          current
  DESCRIPTION
    "Set of NHDP state objects implemented
    in this module."
 ::= { nhdpMIBGroups 3 }

nhdpPerformanceGroup OBJECT-GROUP
  OBJECTS {
    nhdpIfHelloMessageXmits,
    nhdpIfHelloMessageRecvd,
    nhdpIfHelloMessageXmitAccumulatedSize,
    nhdpIfHelloMessageRecvdAccumulatedSize,
    nhdpIfHelloMessageTriggeredXmits,
    nhdpIfHelloMessagePeriodicXmits,
    nhdpIfHelloMessageXmitAccumulatedSymmetricNeighborCount,
    nhdpIfHelloMessageXmitAccumulatedHeardNeighborCount,
    nhdpIfHelloMessageXmitAccumulatedLostNeighborCount,
    nhdpDiscIfRecvdPackets,
```

```
    nhdpDiscIfExpectedPackets,
    nhdpNibNeighborSetChanges,
    nhdpDiscNeighborNibNeighborSetChanges,
    nhdpDiscNeighborNibNeighborSetUpTime,
    nhdpDiscNeighborNibNeighborSetReachableLinkChanges,
    nhdpIib2HopSetPerfChanges,
    nhdpIib2HopSetPerfUpTime
  }
  STATUS      current
  DESCRIPTION
    "Set of NHDP performance objects implemented
    in this module."
 ::= { nhdpMIBGroups 4 }

nhdpNotificationObjectGroup OBJECT-GROUP
  OBJECTS {
    nhdpNbrStateChangeThreshold,
    nhdpNbrStateChangeWindow,
    nhdp2HopNbrStateChangeThreshold,
    nhdp2HopNbrStateChangeWindow,
    nhdpNbrState,
    nhdp2HopNbrState
  }
  STATUS      current
  DESCRIPTION
    "Set of NHDP notification objects implemented
    in this module."
 ::= { nhdpMIBGroups 5 }

nhdpNotificationGroup NOTIFICATION-GROUP
  NOTIFICATIONS {
    nhdpNbrStateChange,
    nhdp2HopNbrStateChange,
    nhdpIfStateChange
  }
  STATUS      current
  DESCRIPTION
    "Set of NHDP notifications implemented
    in this module."
 ::= { nhdpMIBGroups 6 }
```

END

## 8. Security Considerations

This MIB module defines objects for the configuration, monitoring, and notification of the Neighborhood Discovery Protocol [RFC6130]. NHDP allows routers to acquire topological information up to two hops away by virtue of exchanging HELLO messages. The information acquired by NHDP may be used by routing protocols. The neighborhood information, exchanged between routers using NHDP, serves these routing protocols as a baseline for calculating paths to all destinations in the MANET, relay set selection for network-wide transmissions, etc.

There are a number of management objects defined in this MIB module with a MAX-ACCESS clause of read-write and/or read-create. Such objects may be considered sensitive or vulnerable in some network environments. The support for SET operations in a non-secure environment without proper protection can have a negative effect on network operations. These are the tables and objects and their sensitivity/vulnerability:

- o nhdpIfStatus - This writable object turns on or off the NHDP process for the specified interface. If disabled, higher-level protocol functions, e.g., routing, would fail, causing network-wide disruptions.
- o nhdpHelloInterval, nhdpHelloMinInterval, and nhdpRefreshInterval - These writable objects control the rate at which HELLO messages are sent on an interface. If set at too high a rate, this could represent a form of denial-of-service (DoS) attack by overloading interface resources.
- o nhdpHystAcceptQuality, nhdpHystRejectQuality, nhdpInitialQuality, and nhdpInitialPending - These writable objects affect the perceived quality of the NHDP links and hence the overall stability of the network. If improperly set, these settings could result in network-wide disruptions.
- o nhdpInterfaceTable - This table contains writable objects that affect the overall performance and stability of the NHDP process. Failure of the NHDP process would result in network-wide failure. Particularly sensitive objects from this table are discussed in the previous list items. This is the only table in the NHDP-MIB module with writable objects.

Some of the readable objects in this MIB module (i.e., objects with a MAX-ACCESS other than not-accessible) may be considered sensitive or vulnerable in some network environments. It is thus important to control even GET and/or NOTIFY access to these objects and possibly

to even encrypt the values of these objects when sending them over the network via SNMP. These are the tables and objects and their sensitivity/vulnerability:

- o `nhdDiscIfSetTable` - The object contains information on discovered neighbors, specifically their IP address in the `nhdDiscIfSetIpAddress` object. This information provides an adversary broad information on the members of the MANET, located within this single table. This information can be used to expedite attacks on the other members of the MANET without having to go through a laborious discovery process on their own. This object is the index into the table and has a MAX-ACCESS of 'not-accessible'. However, this information can be exposed using SNMP operations.

MANET technology is often deployed to support communications of emergency services or military tactical applications. In these applications, it is imperative to maintain the proper operation of the communications network and to protect sensitive information related to its operation. Therefore, it is RECOMMENDED to provide support for the Transport Security Model (TSM) [RFC5591] in combination with TLS/DTLS [RFC6353].

SNMP versions prior to SNMPv3 did not include adequate security. Even if the network itself is secure (for example by using IPsec), there is no control as to who on the secure network is allowed to access and GET/SET (read/change/create/delete) the objects in this MIB module.

Implementations MUST provide the security features described by the SNMPv3 framework (see [RFC3410]), including full support for authentication and privacy via the User-based Security Model (USM) [RFC3414] with the AES cipher algorithm [RFC3826]. Implementations MAY also provide support for the Transport Security Model (TSM) [RFC5591] in combination with a secure transport such as SSH [RFC5592] or TLS/DTLS [RFC6353].

Further, deployment of SNMP versions prior to SNMPv3 is NOT RECOMMENDED. Instead, it is RECOMMENDED to deploy SNMPv3 and to enable cryptographic security. It is then a customer/operator responsibility to ensure that the SNMP entity giving access to an instance of this MIB module is properly configured to give access to the objects only to those principals (users) that have legitimate rights to indeed GET or SET (change/create/delete) them.

## 9. Applicability Statement

This document describes objects for configuring parameters of the Neighborhood Discovery Protocol [RFC6130] process on a router. This MIB module, denoted NHDP-MIB, also reports state, performance information, and notifications. This section provides some examples of how this MIB module can be used in MANET network deployments. A fuller discussion of MANET network management use cases and challenges will be provided elsewhere.

NHDP is designed to allow routers to automatically discover and track routers one hop remote (denoted "neighbors") and routers two hops remote (denoted "two-hop neighbors"). This information is used by other MANET protocols in operation on the router to perform routing, multicast forwarding, and other functions with ad hoc and mobile networks. In the following, three example scenarios are listed where this MIB module is useful:

- o For a Parking Lot Initial Configuration Situation - It is common for the vehicles comprising the MANET being forward deployed at a remote location, e.g., the site of a natural disaster, to be off-loaded in a parking lot where an initial configuration of the networking devices is performed. The configuration is loaded into the devices from a fixed location Network Operation Center (NOC) at the parking lot, and the vehicles are stationary at the parking lot while the configuration changes are made. Standards-based methods for configuration management from the co-located NOC are necessary for this deployment option.
- o For Mobile Vehicles with Low-Bandwidth Satellite Link to a Fixed NOC - Here, the vehicles carrying the MANET routers carry multiple wireless interfaces, one of which is a relatively low-bandwidth, on-the-move satellite connection that interconnects a fix NOC to the nodes of the MANET. Standards-based methods for monitoring and fault management from the fixed NOC are necessary for this deployment option.
- o For Fixed NOC and Mobile Local Manager in Larger Vehicles - for larger vehicles, a hierarchical network management arrangement is useful. Centralized network management is performed from a fixed NOC while local management is performed locally from within the vehicles. Standards-based methods for configuration, monitoring, and fault management are necessary for this deployment option.



## 10. IANA Considerations

The MIB module in this document uses the following IANA-assigned OBJECT IDENTIFIER value recorded in the SMI Numbers registry:

Descriptor -----	OBJECT IDENTIFIER value -----
NHDP-MIB	{ mib-2 213 }

## 11. Acknowledgements

The authors wish to thank Benoit Claise, Thomas Clausen, Justin Dean, Adrian Farrel, Joel Halpern, Al Morton, and Thomas Nadeau for their detailed reviews and insightful comments regarding this document.

This MIB document uses the template authored by D. Harrington, which is based on contributions from the MIB Doctors, especially Juergen Schoenwaelder, Dave Perkins, C.M. Heard, and Randy Presuhn.

## 12. References

## 12.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997.
- [RFC2578] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Structure of Management Information Version 2 (SMIv2)", STD 58, RFC 2578, April 1999.
- [RFC2579] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Textual Conventions for SMIv2", STD 58, RFC 2579, April 1999.
- [RFC2580] McCloghrie, K., Perkins, D., and J. Schoenwaelder, "Conformance Statements for SMIv2", STD 58, RFC 2580, April 1999.
- [RFC2863] McCloghrie, K. and F. Kastenholz, "The Interfaces Group MIB", RFC 2863, June 2000.
- [RFC3418] Presuhn, R., "Management Information Base (MIB) for the Simple Network Management Protocol (SNMP)", STD 62, RFC 3418, December 2002.

- [RFC4001] Daniele, M., Haberman, B., Routhier, S., and J. Schoenwaelder, "Textual Conventions for Internet Network Addresses", RFC 4001, February 2005.
- [RFC6130] Clausen, T., Dearlove, C., and J. Dean, "Mobile Ad Hoc Network (MANET) Neighborhood Discovery Protocol (NHDP)", RFC 6130, April 2011.
- [RFC6340] Presuhn, R., "Textual Conventions for the Representation of Floating-Point Numbers", RFC 6340, August 2011.

## 12.2. Informative References

- [REPORT-MIB] Cole, R., Macker, J., and A. Bierman, "Definition of Managed Objects for Performance Reporting", Work in Progress, January 2012.
- [RFC3410] Case, J., Mundy, R., Partain, D., and B. Stewart, "Introduction and Applicability Statements for Internet-Standard Management Framework", RFC 3410, December 2002.
- [RFC3414] Blumenthal, U. and B. Wijnen, "User-based Security Model (USM) for version 3 of the Simple Network Management Protocol (SNMPv3)", STD 62, RFC 3414, December 2002.
- [RFC3826] Blumenthal, U., Maino, F., and K. McCloghrie, "The Advanced Encryption Standard (AES) Cipher Algorithm in the SNMP User-based Security Model", RFC 3826, June 2004.
- [RFC4750] Joyal, D., Galecki, P., Giacalone, S., Coltun, R., and F. Baker, "OSPF Version 2 Management Information Base", RFC 4750, December 2006.
- [RFC5148] Clausen, T., Dearlove, C., and B. Adamson, "Jitter Considerations in Mobile Ad Hoc Networks (MANETs)", RFC 5148, February 2008.
- [RFC5591] Harrington, D. and W. Hardaker, "Transport Security Model for the Simple Network Management Protocol (SNMP)", RFC 5591, June 2009.
- [RFC5592] Harrington, D., Salowey, J., and W. Hardaker, "Secure Shell Transport Model for the Simple Network Management Protocol (SNMP)", RFC 5592, June 2009.

[RFC6353] Hardaker, W., "Transport Layer Security (TLS) Transport Model for the Simple Network Management Protocol (SNMP)", RFC 6353, July 2011.

#### Authors' Addresses

Ulrich Herberg  
LIX, Ecole Polytechnique  
91128 Palaiseau Cedex  
France

EEmail: [ulrich@herberg.name](mailto:ulrich@herberg.name)  
URI: <http://www.herberg.name/>

Robert G. Cole  
US Army CERDEC  
Space and Terrestrial Communications  
6010 Frankford Road, Bldg 6010, Room 453H  
Aberdeen Proving Ground, Maryland 21005  
United States

Phone: +1 443 395-8744  
EEmail: [robert.g.cole@us.army.mil](mailto:robert.g.cole@us.army.mil)  
URI: <http://www.cs.jhu.edu/~rgcole/>

Ian D Chakeres  
DRS CenGen  
9250 Bendix Road North  
Columbia, Maryland 21045  
United States

EEmail: [ian.chakeres@gmail.com](mailto:ian.chakeres@gmail.com)  
URI: <http://www.ianchak.com/>