

Package ‘WaveletKNN’

May 7, 2026

Type Package

Title Wavelet Based K-Nearest Neighbor Model

Version 0.1.0

Author Dr. Ranjit Kumar Paul [aut],
Dr. Md Yeasin [aut, cre]

Maintainer Dr. Md Yeasin <yeasin.iasri@gmail.com>

Description The employment of the Wavelet decomposition technique proves to be highly advantageous in the modelling of noisy time series data. Wavelet decomposition technique using the ``haar" algorithm has been incorporated to formulate a hybrid Wavelet KNN (K-Nearest Neighbour) model for time series forecasting, as proposed by An-joy and Paul (2017) <[DOI:10.1007/s00521-017-3289-9](https://doi.org/10.1007/s00521-017-3289-9)>.

License GPL-3

Encoding UTF-8

Imports caret, dplyr, caretForecast, Metrics, tseries, stats, wavelets

RoxygenNote 7.2.1

NeedsCompilation no

Repository CRAN

Date/Publication 2023-04-05 18:23:19 UTC

Contents

WaveletKNN	2
Index	3

WaveletKNN

Wavelet Based K-Nearest Neighbor Model

Description

Wavelet Based K-Nearest Neighbor Model

Usage

```
WaveletKNN(ts, MLag = 12, split_ratio = 0.8, wlevels = 3)
```

Arguments

ts	Time Series Data
MLag	Maximum Lags
split_ratio	Training and Testing Split
wlevels	Number of Wavelet Levels

Value

- Lag: Lags used in model
- Parameters: Parameters of the model
- Train_actual: Actual train series
- Test_actual: Actual test series
- Train_fitted: Fitted train series
- Test_predicted: Predicted test series
- Accuracy: RMSE and MAPE of the model

References

- Aminghafari, M. and Poggi, J.M. 2012. Nonstationary time series forecasting using wavelets and kernel smoothing. *Communications in Statistics-Theory and Methods*, 41(3),485-499.
- Paul, R.K. A and Anjoy, P. 2018. Modeling fractionally integrated maximum temperature series in India in presence of structural break. *Theory and Applied Climatology* 134, 241–249.

Examples

```
library("WaveletKNN")
data<- rnorm(100,100, 10)
WG<-WaveletKNN(ts=data)
```

Index

WaveletKNN, 2