

Package ‘covBM’

May 8, 2026

Title Brownian Motion Processes for 'nlme'-Models

Version 0.1.0

Description Allows Brownian motion, fractional Brownian motion, and integrated Ornstein-Uhlenbeck process components to be added to linear and non-linear mixed effects models using the structures and methods of the 'nlme' package.

Depends nlme (>= 3.0)

Imports stats

License GPL-3

NeedsCompilation yes

LazyData true

Author Oliver Stirrup [aut, cre]

Maintainer Oliver Stirrup <oliverstirrup@googlemail.com>

Repository CRAN

Date/Publication 2015-10-14 18:13:24

Contents

cd4	2
coef.covBM	3
coef.covFracBM	3
coef.covIOU	4
corMatrix.covBM	4
corMatrix.covFracBM	5
corMatrix.covIOU	5
covBM	6
covFracBM	6
covIOU	7
lmeBM	8
nlmeBM	9
print.summary.corStructBM	10
summary.covBM	10

summary.covFracBM	11
summary.covIOU	11

Index	12
--------------	-----------

cd4	<i>Serial CD4 counts in children with HIV.</i>
-----	--

Description

Dataset used in *Data Analysis Using Regression and Multilevel/Hierarchical Models* by Andrew Gelman and Jennifer Hill (Cambridge University Press, 2006). Rows with missing values of 'CD4CNT', 'visage' or 'baseage' have been removed.

Usage

cd4

Format

A data frame with 976 rows and 11 variables:

newpid Patient ID code.

t Time, in years from first visit.

sqrtcd4 Square root of CD4 count.

treatmnt Indicator variable for treatment, 1 represents control group and 2 indicates zinc treatment group.

CD4CNT CD4 count on original (untransformed) scale.

baseage Age of child in years at initial visit.

visage Age of child in years at given visit.

Source

<http://www.stat.columbia.edu/~gelman/arm/examples/cd4/>

coef.covBM	<i>coef.covBM</i>
------------	-------------------

Description

This is a method function that extracts the scale coefficient associated with a Brownian motion correlation structure object.

Usage

```
## S3 method for class 'covBM'
coef(object, unconstrained = TRUE, ...)
```

Arguments

object	An object of class <code>covBM</code> , inheriting from <code>corStruct</code> .
unconstrained	A logical value. If TRUE the coefficients are returned in unconstrained form (as used in the optimization algorithm). If FALSE the coefficients are returned in "natural" form.
...	Additional arguments (not used by this method).

Examples

```
cov1<-covBM(form=~time|group)
coef(cov1)
```

coef.covFracBM	<i>coef.covFracBM</i>
----------------	-----------------------

Description

This is a method function that extracts the scale coefficient and Hurst parameter associated with a fractional Brownian motion correlation structure object.

Usage

```
## S3 method for class 'covFracBM'
coef(object, unconstrained = TRUE, ...)
```

Arguments

object	An object of class <code>covFracBM</code> , inheriting from <code>corStruct</code> .
unconstrained	A logical value. If TRUE the coefficients are returned in unconstrained form (as used in the optimization algorithm). If FALSE the coefficients are returned in "natural" form.
...	Additional arguments (not used by this method).

Examples

```
cov2<-covFracBM(form=~time|group)
coef(cov2)
```

coef.covIOU	<i>coef.covIOU</i>
-------------	--------------------

Description

This is a method function that extracts the perturbation and Alpha parameters associated with an integrated Ornstein-Uhlenbeck (IOU) process correlation structure object.

Usage

```
## S3 method for class 'covIOU'
coef(object, unconstrained = TRUE, ...)
```

Arguments

object	An object of class <code>covIOU</code> , inheriting from <code>corStruct</code> .
unconstrained	A logical value. If TRUE the coefficients are returned in unconstrained form (as used in the optimization algorithm). If FALSE the coefficients are returned in "natural" form.
...	Additional arguments (not used by this method).

Examples

```
cov3<-covIOU(form=~time|group)
coef(cov3)
```

corMatrix.covBM	<i>corMatrix.covBM</i>
-----------------	------------------------

Description

This method generates a scaled covariance matrix (or list of matrices), for a "covBM" "corStruct" object.

Usage

```
## S3 method for class 'covBM'
corMatrix(object, covariate = getCovariate(object), ...)
```

Arguments

object	An object of class <code>covBM</code> , inheriting from <code>corStruct</code> .
covariate	List of covariate vectors, at which values the correlation matrix, or list of correlation matrices, are to be evaluated, as for <code>corMatrix.corStruct</code> .
...	Additional arguments (not used by this method).

corMatrix.covFracBM *corMatrix.covFracBM*

Description

This method generates a scaled covariance matrix (or list of matrices), for a "covFracBM" "corStruct" object.

Usage

```
## S3 method for class 'covFracBM'
corMatrix(object, covariate = getCovariate(object), ...)
```

Arguments

object	An object of class <code>covFracBM</code> , inheriting from <code>corStruct</code> .
covariate	List of covariate vectors, at which values the correlation matrix, or list of correlation matrices, are to be evaluated, as for <code>corMatrix.corStruct</code> .
...	Additional arguments (not used by this method).

corMatrix.covIOU *corMatrix.covIOU*

Description

This method generates a scaled covariance matrix (or list of matrices), for a "covIOU" "corStruct" object.

Usage

```
## S3 method for class 'covIOU'
corMatrix(object, covariate = getCovariate(object), ...)
```

Arguments

object	An object of class <code>covIOU</code> , inheriting from <code>corStruct</code> .
covariate	List of covariate vectors, at which values the correlation matrix, or list of correlation matrices, are to be evaluated, as for <code>corMatrix.corStruct</code> .
...	Additional arguments (not used by this method).

covBM	<i>covBM</i>
-------	--------------

Description

This is a constructor function for the "covBM" class, representing a Brownian motion component in terms of a continuous variable. The object created is a special type of [corStruct](#).

covBM

Usage

```
covBM(value = 1, form = ~1)
```

Arguments

value	Numeric argument providing starting value for the scale parameter of Brownian motion process relative to residual error variance for optimisation.
form	A one-sided formula of the form $\sim t g$, where t represents a continuous variable (usually time) and g represents a grouping factor, i.e. with a separate Brownian motion process modelled at each level.

Value

An object of class "covBM" and inheriting from "corStruct".

Examples

```
cov1<-covBM(form=~time|group)
```

covFracBM	<i>covFracBM</i>
-----------	------------------

Description

This is a constructor function for the "covFracBM" class, representing a fractional Brownian motion component in terms of a continuous variable. The object created is a special type of [corStruct](#).

Usage

```
covFracBM(value = c(1, 0.5), form = ~1)
```

Arguments

value	Vector of length 2 providing starting values for optimisation of the scale parameter of fractional Brownian motion process relative to residual error variance and the Hurst parameter, respectively.
form	A one-sided formula of the form $\sim t g$, where t represents a continuous variable (usually time) and g represents a grouping factor, i.e. with a separate fractional Brownian motion process modelled at each level.

Value

An object of class "covFracBM" and inheriting from "corStruct".

Examples

```
cov2<-covFracBM(form=~time|group)
```

 covIOU

covIOU

Description

This is a constructor function for the "covIOU" class, representing an integrated Ornstein-Uhlenbeck (IOU) process component in terms of a continuous variable. The object created is a special type of [corStruct](#).

Usage

```
covIOU(value = c(1, 1), form = ~1)
```

Arguments

value	Vector of length 2 providing starting values for optimisation of the perturbation parameter of integrated Ornstein-Uhlenbeck process relative to residual error variance and the Alpha parameter, respectively.
form	A one-sided formula of the form $\sim t g$, where t represents a continuous variable (usually time) and g represents a grouping factor, i.e. with a separate integrated Ornstein-Uhlenbeck process modelled at each level.

Value

An object of class "covIOU" and inheriting from "corStruct".

Examples

```
cov3<-covIOU(form=~time|group)
```

lmeBM

lmeBM

Description

This function is a wrapper for `lme.formula` that allows Brownian motion, fractional Brownian motion or integrated Ornstein-Uhlenbeck components to be included in linear mixed models, with related parameter estimates and confidence intervals returned in their natural parameterisation.

Usage

```
lmeBM(fixed, data, random, covariance = NULL, method = c("REML", "ML"),
      control = list(), keep.data = TRUE)
```

Arguments

fixed	This is as specified for <code>lme.formula</code> .
data	This is as specified for <code>lme.formula</code> .
random	This is as specified for <code>lme.formula</code> .
covariance	An optional <code>corStruct</code> object describing the within-group covariance structure. In addition to those available in <code>nlme</code> , <code>covBM</code> can be used to incorporate a Brownian motion component, <code>covFracBM</code> can be used to incorporate a fractional Brownian motion component and <code>covIOU</code> can be used to incorporate an integrated Ornstein-Uhlenbeck process in relation to a continuous variable.
method	This is as specified for <code>lme.formula</code> .
control	This is as specified for <code>lme.formula</code> .
keep.data	This is as specified for <code>lme.formula</code> .

Value

An object of class "lme" representing the linear mixed effects model fit.

Examples

```
BMmodel<-lmeBM(sqrtcd4~t, data=cd4, random=~t|newpid, covariance=covBM(form=~t|newpid),
method="ML", control=list(opt="link{nlm}"))
```

nlmeBM	<i>nlmeBM</i>
--------	---------------

Description

This function is a wrapper for `nlme.formula` that allows Brownian motion, fractional Brownian motion or integrated Ornstein-Uhlenbeck components to be included in non-linear mixed models, with related parameter estimates and confidence intervals returned in their natural parameterisation.

Usage

```
nlmeBM(model, data, fixed, random, start, covariance = NULL,
        method = c("ML", "REML"), control = list(), verbose = FALSE)
```

Arguments

model	This is as specified for <code>nlme.formula</code> .
data	This is as specified for <code>lme.formula</code> .
fixed	This is as specified for <code>lme.formula</code> .
random	This is as specified for <code>nlme.formula</code> .
start	This is as specified for <code>nlme.formula</code> .
covariance	An optional <code>corStruct</code> object describing the within-group covariance structure. In addition to those available in <code>nlme</code> , <code>covBM</code> can be used to incorporate a Brownian motion component, <code>covFracBM</code> can be used to incorporate a fractional Brownian motion component and <code>covIOU</code> can be used to incorporate an integrated Ornstein-Uhlenbeck process in relation to a continuous variable.
method	This is as specified for <code>lme.formula</code> .
control	This is as specified for <code>nlme.formula</code> .
verbose	This is as specified for <code>nlme.formula</code> .

Value

An object of class "nlme" and inheriting from class "lme" representing the non-linear mixed effects model fit.

Examples

```
data(Milk, package="nlme")
Model_fit<- nlmeBM(protein ~ SSasyp(Time, Asym, R0, lrc), data=Milk,
  fixed = Asym + R0 + lrc ~ 1, random = Asym ~ 1|Cow,
  covariance=covFracBM(form=~Time|Cow),
  start = c(Asym = 3.5, R0 = 4, lrc = -1))
```

```
print.summary.corStructBM
      print.summary.corStructBM
```

Description

print.summary.corStructBM

Usage

```
## S3 method for class 'summary.corStructBM'
print(x, ...)
```

Arguments

x	An object of class "summary.corStructBM", containing information on fitted stochastic process component.
...	Additional arguments (not used for this method).

```
summary.covBM      summary.covBM
```

Description

summary.covBM

Usage

```
## S3 method for class 'covBM'
summary(object, structName = class(object)[1], ...)
```

Arguments

object	An object of class "covBM", containing information on fitted stochastic process component.
structName	An optional character string defining the type of correlation structure associated with object, as for summary.corStruct . Defaults to class(object)[1].
...	Additional arguments (not used for this method).

summary.covFracBM	<i>summary.covFracBM</i>
-------------------	--------------------------

Description

summary.covFracBM

Usage

```
## S3 method for class 'covFracBM'
summary(object, structName = class(object)[1], ...)
```

Arguments

object	An object of class "covFracBM", containing information on fitted stochastic process component.
structName	An optional character string defining the type of correlation structure associated with object, as for summary.corStruct . Defaults to class(object)[1].
...	Additional arguments (not used for this method).

summary.covIOU	<i>summary.covIOU</i>
----------------	-----------------------

Description

summary.covIOU

Usage

```
## S3 method for class 'covIOU'
summary(object, structName = class(object)[1], ...)
```

Arguments

object	An object of class "covIOU", containing information on fitted stochastic process component.
structName	An optional character string defining the type of correlation structure associated with object, as for summary.corStruct . Defaults to class(object)[1].
...	Additional arguments (not used for this method).

Index

* datasets

cd4, [2](#)

cd4, [2](#)

coef.covBM, [3](#)

coef.covFracBM, [3](#)

coef.covIOU, [4](#)

corMatrix.corStruct, [5](#)

corMatrix.covBM, [4](#)

corMatrix.covFracBM, [5](#)

corMatrix.covIOU, [5](#)

corStruct, [3–9](#)

covBM, [3, 5, 6, 8, 9](#)

covBM-package (covBM), [6](#)

covFracBM, [3, 5, 6, 8, 9](#)

covIOU, [4, 5, 7, 8, 9](#)

lme.formula, [8, 9](#)

lmeBM, [8](#)

nlme.formula, [9](#)

nlmeBM, [9](#)

print.summary.corStructBM, [10](#)

summary.corStruct, [10, 11](#)

summary.covBM, [10](#)

summary.covFracBM, [11](#)

summary.covIOU, [11](#)