

Package ‘easySdcTable’

May 8, 2026

Type Package

Title Easy Interface to the Statistical Disclosure Control Package
'sdcTable' Extended with Own Implementation of
'GaussSuppression'

Version 1.1.2

Date 2025-08-18

Author Øyvind Langsrud [aut, cre]

Maintainer Øyvind Langsrud <oyl@ssb.no>

Depends SSBtools

Imports sdcTable, shiny, methods, Matrix

VignetteBuilder knitr

Suggests knitr, rmarkdown, RegSDC, testthat (>= 2.1.0)

Description The main function, ProtectTable(), performs table suppression according to a frequency rule with a data set as the only required input. Within this function, protectTable(), protect_linked_tables() or runArgusBatchFile() in package 'sdcTable' is called. Lists of level-hierarchy (parameter 'dimList') and other required input to these functions are created automatically.
The suppression method Gauss (default) is implemented independently of 'sdcTable'.
The function, PTgui(), starts a graphical user interface based on the 'shiny' package.

License Apache License 2.0 | file LICENSE

RoxygenNote 7.3.2

Encoding UTF-8

URL <https://github.com/statisticsnorway/ssb-easysdctable>,
<https://statisticsnorway.github.io/ssb-easysdctable/>

BugReports <https://github.com/statisticsnorway/ssb-easysdctable/issues>

NeedsCompilation no

Repository CRAN

Date/Publication 2025-08-18 09:40:09 UTC

Contents

EasyData	2
ProtectTable	3
ProtectTable1	8
PTgui	11
PTwrap	12
PTxyz	14
Index	16

EasyData	<i>Function that returns a dataset</i>
----------	--

Description

Function that returns a dataset

Usage

```
EasyData(dataset, path = NULL)
```

Arguments

dataset	Name of data set within the easySdcTable package
path	When non-NULL the data set is read from "path/dataset.RData"

Value

The dataset

Note

The function returns the same datasets as [SSBtoolsData](#).

Examples

```
z <- EasyData("socialFiktiv")
```

ProtectTable	<i>Easy interface to <code>sdctable</code>: Table suppression according to a frequency rule.</i>
--------------	--

Description

[GaussSuppression](#), [protectTable](#) or [protect_linked_tables](#) is run with a data set as the only required input. One (stacked) or several (unstacked) input variables can hold cell counts. `ProtectTableData` is a tidy wrapper function, which returns a single data frame instead of a list (info omitted).

Usage

```
ProtectTable(  
  data,  
  dimVar = 1:NCOL(data),  
  freqVar = NULL,  
  protectZeros = TRUE,  
  maxN = 3,  
  method = "Gauss",  
  findLinked = TRUE,  
  total = "Total",  
  addName = FALSE,  
  sep = "_",  
  removeZeros = FALSE,  
  dimList = NULL,  
  groupVarInd = NULL,  
  ind1 = NULL,  
  ind2 = NULL,  
  rowData = NULL,  
  varNames = paste("var", 1:100, sep = ""),  
  split = NULL,  
  border = sep,  
  revBorder = FALSE,  
  freqName = "values",  
  totalFirst = FALSE,  
  numericOrder = TRUE,  
  namesAsInput = TRUE,  
  orderAsInput = TRUE,  
  sortByReversedColumns = FALSE,  
  doUnstack = TRUE,  
  removeTotal = TRUE,  
  singleOutput = NULL,  
  suppression = NA,  
  outFreq = "freq",  
  outSdcStatus = "sdcStatus",  
  outSuppressed = "suppressed",  
  infoAsFrame = FALSE,
```

```

    IncProgress = IncDefault,
    verbose = FALSE,
    ...
)

```

```
ProtectTableData(data, ...)
```

Arguments

<code>data</code>	data frame
<code>dimVar</code>	The main dimensional variables and additional aggregating variables (name or number).
<code>freqVar</code>	Variable(s) holding counts or NULL in the case of micro data (name or number).
<code>protectZeros</code>	When TRUE empty cells (count=0) is considered sensitive (i.e. same as <code>allowZeros</code> in primarySuppression).
<code>maxN</code>	All cells having counts \leq maxN are set as primary suppressed.
<code>method</code>	<p>Parameter method in protectTable, protect_linked_tables or wrapper methods via PTwrap. Gauss (default) is implemented independently of <code>sdcTable</code>. There is also a similar variant implemented in <code>sdcTable</code> as GAUSS. But this implementation is not as optimal and Gauss is recommended instead.</p> <ul style="list-style-type: none"> "SIMPLEHEURISTIC": This method is default in <code>protectable</code>. "SIMPLEHEURISTIC_OLD": As "SIMPLEHEURISTIC" in <code>sdcTable</code> versions prior to 0.32. "OPT", "HITAS", "HYPERCUBE", "GAUSS": Other methods in <code>protectable</code>. "HYPERCUBE" is not possible in cases with two linked tables. "SimpleSingle": "SIMPLEHEURISTIC_OLD" with <code>detectSingletons=TRUE</code> when <code>protectZeros=FALSE</code> and "SIMPLEHEURISTIC_OLD" with <code>threshold=1</code> (can be overridden by input) when <code>protectZeros=TRUE</code>. "SIMPLEHEURISTICSingle": As "SimpleSingle" with "SIMPLEHEURISTIC" instead of "SIMPLEHEURISTIC_OLD". "Simple": "SIMPLEHEURISTIC_OLD" with <code>detectSingletons=FALSE</code>. "Gauss": GaussSuppression is called with parameters <code>x</code>, <code>candidates</code>, <code>primary</code> and <code>singleton</code> automatically generated. Other parameters (<code>singletonMethod</code>, <code>printInc</code>) can be specified. <p>Alternatively this parameter can be a named list specifying parameters for running tau-argus (see details). See PTwrap for other (experimental) wrapper methods (see details).</p>
<code>findLinked</code>	When TRUE, the function may find two linked tables and run <code>protect_linked_tables</code> .
<code>total</code>	String used to name totals.
<code>addName</code>	When TRUE the variable name is added to the level names, except for variables with most levels.
<code>sep</code>	A character string to separate when <code>addName</code> apply and when creating variable names.
<code>removeZeros</code>	When TRUE, rows with zero count will be removed from the data within the algorithm.

dimList	By default, hierarchies will be automatically found from data (see FindDimLists). With non-NULL dimList, these will be changed. In practice this is done by the function ReplaceDimList .
groupVarInd	Possible manual specification of list defining the hierarchical variable groups. When NULL (default) this information will be found automatically by FindTableGroup .
ind1	Coding of table 1 as indices referring to elements of groupVarInd. This information will be found automatically by FindTableGroup when groupVarInd=NULL.
ind2	Coding of table 2 as indices referring to elements of groupVarInd (as ind1 above).
rowData	Input to Stack used to generate extra dimVar variables when stacking in cases with several freqvar variables. When NULL rowData will be created automatically by AutoSplit using varNames (see below) and the the freqvar names as input.
varNames	The names of the extra dimVar variable(s) made when stacking in cases with several freqvar variables. When length(varNames)>1 several variables may be found by AutoSplit .
split	Parameter to AutoSplit - see varNames and rowData above. When NULL (default), automatic splitting without needing a split string.
border	Parameter to AutoSplit - see varNames and rowData above.
revBorder	Parameter to AutoSplit - see varNames and rowData above..
freqName	Input to Stack . The name of the new freqvar variable obtained when stacking in cases with several input freqvar variables.
totalFirst	Parameter controlling how output is sorted.
numericOrder	Parameter controlling how output is sorted. Output is character but sorting can be based on the numeric input variables.
namesAsInput	When TRUE those output variables (created by unstacking) that correspond to input will be named as input.
orderAsInput	When TRUE output corresponding to input will be ordered as input and kept together as one block.
sortByReversedColumns	When TRUE output will be sorted by variables in opposite order.
doUnstack	When FALSE output will not be unstacked (in cases with sever input freqvar variables)
removeTotal	When TRUE the total string (see total above) will be removed from the names of output variables created by unstacking (in cases with sever input freqvar variables).
singleOutput	When TRUE output will be in as single data set. Default is FALSE for unstacked data (in cases with sever input freqvar variables) and otherwise TRUE.
suppression	Value used for suppressed elements in suppressed output data. Default is NA.
outFreq	String used to name output variable(s)
outSdcStatus	String used to name output variable(s)
outSuppressed	String used to name output variable(s)

infoAsFrame	When TRUE output element info is a data frame (useful in Shiny).
IncProgress	A function to report progress (incProgress in Shiny). Set equal to NULL to turn it off.
verbose	Parameter sent to <code>protectTable</code> , <code>protect_linked_tables</code> or <code>runArgusBatchFile</code> .
...	Further parameters sent to <code>protectTable</code> (possibly via <code>protect_linked_tables</code>) such as <code>timeLimit</code> . Parameters to <code>GaussSuppression</code> , <code>createArgusInput</code> and <code>PTwrap</code> is also possible (see details).

Details

One or two tables are identified automatically and subjected to cell suppression by `protectTable` (single table) or `protect_linked_tables` (two linked tables). The tables can alternatively be specified manually by `groupVarInd`, `ind1` and `ind2`. The output will be on a form similar to input depending on whether `freqVar` is a single variable or not. The status of the cells are coded as "u" (primary suppressed), "x" (secondary suppression), and "s" (can be published). This is taken directly from the output from `sdcTable`. In cases with two linked tables "u" or "x" for common cells are based on output from the first table.

- **To run tau-argus** specify `method` as a named list containing the parameter `exe` for `runArgusBatchFile` and other parameters for `createArgusInput`.
 - One may specify: `method = list(exe="C:/Tau/TauArgus.exe", typ="tabular", path=getwd(), solver="FREE", method="OPT")` However these values of "exe", "path" and "solver" and "method" are set by default so in this case using `method = list(typ="tabular", method="OPT")` is equivalent.
 - If `typ="microdata"` is specified. Necessary transformation to microdata will be made.
- **Wrapper methods (partly experimental):** In the function `PTwrap` several additional methods are defined. If input to `ProtectTable()` is one of these methods `ProtectTable()` will be run via `PTwrap()`. So making explicit call to `PTwrap()` is not needed.
- **Singleton and zeros:** The parameter `detectSingletons` was included in `protecttable` to handle the so-called singleton problem that appears when `protectZeros=FALSE`. Not all problems were solved and the parameter `threshold` has been introduced later. The value of `threshold` needed depends on the number of singletons in one group. It seems that `threshold=3` is equivalent to `detectSingletons=TRUE`. When `protectZeros=TRUE` the related "zero problem" occurs. This problem is solved by `threshold=1`.
- **NOTE:** The use of `numVarInd`, `weightInd` and `sampWeightInd` in `sdcTable` is not implemented. This also limit possible input to `tau-argus`.

Value

When `singleOutput=TRUE` output is a list of two elements.

- `info`: Information as a single column character matrix. This is information about the extra `dimVar` variables created when stacking, information about the identified (linked) table(s) and summary output from `sdcTable`. With `method="Gauss"`, a `sdcTable` function is run with `maxN=0` to create a template for the real output. Some of the summary info is therefore misleading in this case.
- `data`: A data frame where variables are named according to `outFreq`, `outSdcStatus` and `outSuppressed`. When `singleOutput=FALSE` output element `data` is replaced by three elements and these are named according to `outFreq`, `outSdcStatus` and `outSuppressed`.

Note

ProtectTable makes a call to the function [ProtectTable1](#).

See Also

See also the vignettes.

Examples

```
## Not run:

# ==== Example 1 , 8 regions ====
z1 <- EasyData("z1")
ProtectTable(z1,1:2, 3)
ProtectTableData(z1,1:2, 3)
ProtectTable(z1, c("region","hovedint"), "ant") # Input by name
# --- Unstacked input data ---
z1w = EasyData("z1w")
ProtectTable(z1w, 1, 2:5)
ProtectTableData(z1w, 1, 2:5)
ProtectTable(z1w, 1, 2:5, varName="hovedint")
ProtectTable(z1w, 1, 2:5, method="HITAS")
ProtectTable(z1w, 1, 2:5, totalFirst = TRUE, method ="Simple")

# ==== Example 2 , 11 regions ====
z2 <- EasyData("z2")
ProtectTable(z2,c(1,3,4), 5) # With region-variable kostragr
# --- Unstacked input data ---
z2w <- EasyData("z2w")
ProtectTable(z2w, 1:2, 4:7) # With region-variable fylke
ProtectTable(z2w, 1:3, 4:7) # Two linked tables

# ==== Example 3 , 36 regions ====
z3 <- EasyData("z3")
ProtectTable(z3, c(1,4,5), 7) # Three dimensions. No subtotals
ProtectTable(z3, 1:6, 7) # Two linked tables
# --- Unstacked input data with coded column names
z3w <- EasyData("z3w")
ProtectTable(z3w,1:3,4:15, varName="g12") # coding not used when single varName
ProtectTable(z3w,1:3,4:15, varName=c("hovedint","mnd")) # Two variables found automatically
ProtectTable(z3w,1:3,4:15, varName=c("hovedint","mnd"),
             removeTotal=FALSE) # Keep "Total" in variable names
# --- Unstacked input data with three level column name coding
z3wb <- EasyData("z3wb")
ProtectTable(z3wb,1:3,4:15,varName=c("hovedint","mnd","mnd2")) # Two variables found automatically
ProtectTable(z3wb,1:3,4:15,varName=c("hovedint","mnd","mnd2"),
             split="_") # Three variables when splitting
ProtectTable(z3wb,1:3,4:15,varName=c("hovedint","mnd","mnd2"),
             split="_",namesAsInput=FALSE,orderAsInput=FALSE) # Alternative output format

# ==== Examples Tau-Argus ====
exeArgus <- "C:/TauArgus4.1.4/TauArgus.exe" # Change to TauArgus.exe-path in your computer
```

```

pathArgus <- "C:/Users/nnn/Documents"      # Change to an existing folder
z1 = EasyData("z1")
ProtectTable(z1,1:2,3,method=list(exe=exeArgus, path=pathArgus, typ="tabular", method="OPT"))
ProtectTable(z1,1:2,3,method=list(exe=exeArgus, path=pathArgus, typ="tabular", method="MOD"))
ProtectTable(z1,1:2,3,method=list(exe=exeArgus, path=pathArgus, typ="tabular", method="GH"))
ProtectTable(z1,1:2,3,maxN=-1,
  method=list(path=pathArgus, exe=exeArgus, method="OPT",
    primSuppRules= list(list(type="freq", n=4, rg=20))))
z3 <- EasyData("z3")
ProtectTable(z3,c(1:2,4,5),7,maxN=-1,
  method=list(path=pathArgus, exe=exeArgus, method="OPT",
    primSuppRules=list(list(type="freq", n=4, rg=20))))

# ==== Examples with parameter dimList ====
z2 <- EasyData("z2")
dList <- FindDimLists(z2[-5])
ProtectTable(z2[, c(1,4,5)], 1:2, 3, dimList = dList[c(1,3)])
ProtectTable(z2[, c(1,4,5)], 1:2, 3, dimList = dList[2])
ProtectTable(z2[, c(1,4,5)], 1:2, 3, dimList = DimList2Hrc(dList[c(2,3)]))

## End(Not run)

```

ProtectTable1

Easy input interface to sdcTable

Description

protectTable or protect_linked_tables is run with a data set at the only required input.

Usage

```

ProtectTable1(
  data,
  dimVarInd = 1:NCOL(data),
  freqVarInd = NULL,
  protectZeros = TRUE,
  maxN = 3,
  method = "SIMPLEHEURISTIC",
  findLinked = TRUE,
  total = "Total",
  addName = FALSE,
  sep = ".",
  removeZeros = FALSE,
  dimList = NULL,
  groupVarInd = NULL,
  ind1 = NULL,
  ind2 = NULL,

```

```

    dimDataReturn = FALSE,
    IncProgress = IncDefault,
    verbose = FALSE,
    ...
)

```

Arguments

<code>data</code>	Matrix or data frame
<code>dimVarInd</code>	Column-indices of the main dimensional variables and additional aggregating variables.
<code>freqVarInd</code>	Column-indices of a variable holding counts or NULL in the case of micro data.
<code>protectZeros</code>	When TRUE empty cells (count=0) is considered sensitive (i.e. same as <code>allowZeros</code> in <code>primarySuppression</code>).
<code>maxN</code>	All cells having counts \leq <code>maxN</code> are set as primary suppressed.
<code>method</code>	Parameter "method" in <code>protectTable</code> or <code>protect_linked_tables</code> . Alternatively a list defining parameters for running <code>tau-argus</code> (see ProtectTable).
<code>findLinked</code>	When TRUE, the function may find two linked tables and run <code>protect_linked_tables</code> .
<code>total</code>	String used to name totals.
<code>addName</code>	When TRUE the variable name is added to the level names, except for variables with most levels.
<code>sep</code>	A character string to separate when <code>addName</code> apply.
<code>removeZeros</code>	When TRUE, rows with zero count will be removed from the data.
<code>dimList</code>	See ProtectTable .
<code>groupVarInd</code>	Possible manual specification if list defining the hierarchical variable groups
<code>ind1</code>	Coding of table 1 as indices referring to elements of <code>groupVarInd</code>
<code>ind2</code>	Coding of table 2 as indices referring to elements of <code>groupVarInd</code>
<code>dimDataReturn</code>	When TRUE a data frame containing the <code>dimVarInd</code> variables is returned
<code>IncProgress</code>	A function to report progress (<code>incProgress</code> in Shiny).
<code>verbose</code>	Parameter sent to <code>protectTable</code> , <code>protect_linked_tables</code> or <code>runArgusBatchFile</code> .
<code>...</code>	Further parameters sent to <code>protectTable</code> , <code>protect_linked_tables</code> or <code>createArgus-Input</code> .

Details

One or two tables are identified automatically and subjected to cell suppression methods in package `sdCTable`. The tables can alternatively be specified manually by `groupVarInd`, `ind1` and `ind2` (see [FindTableGroup](#)).

Value

Output is a list of three elements.

table1 consists of the following elements:

secondary	Output from protectTable or first element of output from protect_linked_tables or output from runArgusBatchFile .
primary	Output from primarySuppression .
problem	Output from makeProblem .
dimList	Generated input to makeProblem .
ind	Indices referring to elements of groupVarInd in the output element common .

table2 consists of elements of the same type as [table1](#) in cases of two linked tables. Otherwise [table2](#) is NULL.

common consists of the following elements:

commonCells	Input to protect_linked_tables .
groupVarInd	List defining the hierarchical variable groups
info	A table summarizing the tables using variable names
nLevels	The number of levels of each variable (only when groupVarInd input is NULL)
dimData	Data frame containing the dimVarInd variables when dimDataReturn=TRUE . Otherwise NULL.

See Also

[ProtectTable](#), [HierarchicalGroups](#), [FactorLevCorr](#), [FindDimLists](#), [FindCommonCells](#)

Examples

```
## Not run:
z2 <- EasyData("z2")
a <- ProtectTable1(z2, c(1, 3, 4), 5)
head(as.data.frame(sdcTable::getInfo(a[[1]][[1]], type = "finalData"))) # The table (not linked)

z3 <- EasyData("z3")
b <- ProtectTable1(z3, 1:6, 7)
head(as.data.frame(sdcTable::getInfo(b[[1]][[1]], type = "finalData"))) # First table
head(as.data.frame(sdcTable::getInfo(b[[2]][[1]], type = "finalData"))) # Second table

## End(Not run)
```

Description

Run PTgui from the R console or use PTguiApp to make a server application

Usage

```
PTgui(  
  data = NULL,  
  language = "English",  
  exeArgus = NULL,  
  pathArgus = getwd(),  
  maxNchoices = c(1:10, 12, 15, 20),  
  ...  
)
```

```
PTguiApp(  
  language = "English",  
  exeArgus = NULL,  
  pathArgus = "",  
  maxNchoices = c(1:10, 12, 15, 20),  
  ...  
)
```

```
PTguiNO(  
  data = NULL,  
  language = "Norwegian",  
  exeArgus = NULL,  
  pathArgus = getwd(),  
  maxNchoices = c(1:10, 12, 15, 20),  
  ...  
)
```

```
PTguiAppNO(  
  language = "Norwegian",  
  exeArgus = NULL,  
  pathArgus = "",  
  maxNchoices = c(1:10, 12, 15, 20),  
  ...  
)
```

Arguments

data	NULL or a data.frame
language	Menu language, "English" or "Norwegian".

exeArgus	Tau-argus executable
pathArgus	Folder for (temporary) tau-argus files
maxNchoices	Choices of maxN
...	Further parameters sent to ProtectTable

Value

Output from `ProtectTable`. The output is returned invisibly (via `invisible`) which means that it is not automatically printed to the console.

Note

`PTguiApp()`: New for server

Examples

```
## Not run:

# Start the gui.
PTgui()

# Start Norwegian gui with example data and catch output
out <- PTguiNO(data=EasyData("z1w"))

# Note: Change to TauArgus.exe-path in your computer
exeArgus <- "C:/TauArgus4.2.0b2/TauArgus.exe"

# Note: Change to an existing folder
pathArgus <- "C:/Users/nnn/Documents"

# Start the gui with possibility to run tau-argus.
PTgui(exeArgus=exeArgus, pathArgus=pathArgus)

## End(Not run)
```

PTwrap

Wrapper to ProtectTable() with additional methods (partly experimental)

Description

Additional values of "method" is possible. Each new method (wrapper method) will make a call to `ProtectTable()` using a specific parameter setting.

Usage

```

PTwrap(
  ...,
  maxN = 3,
  method = "SimpleSingle",
  exeArgus = "C:/Tau/TauArgus.exe",
  pathArgus = getwd(),
  solverArgus = "FREE",
  methodArgus = "OPT",
  rgArgus = 0
)

```

Arguments

...	Parameters to ProtectTable
maxN	Parameter to ProtectTable
method	Parameter to ProtectTable or a wrapper method (see details)
exeArgus	Parameter to runArgusBatchFile
pathArgus	Parameter to createArgusInput
solverArgus	Parameter "solver" to createArgusInput
methodArgus	Parameter "method" to createArgusInput
rgArgus	Parameter "rg" in "primSuppRules" in createArgusInput

Details

The wrapper methods are:

Simple: "SIMPLEHEURISTIC" with detectSingletons=FALSE

SimpleSingle: "SIMPLEHEURISTIC" with detectSingletons=TRUE when protectZeros=FALSE and "SIMPLEHEURISTIC" with threshold=1 (can be overridden by input) when protectZeros=TRUE

SimpleSingleOld: "SIMPLEHEURISTIC" with detectSingletons=TRUE

TauArgus: Tau-argus will be run according to the settings of the other input parameters.

Using rgArgus=0 is equivalent to calling ProtectTable() with
method = list(exe=exeArgus, typ="tabular", path=pathArgus,
solver=solverArgus, method=methodArgus))

Other values of rgArgus is equivalent to calling ProtectTable() with
method = list(exe=exeArgus, typ="microdata", path=pathArgus,
solver=solverArgus, method=methodArgus,
primSuppRules=list(list(type="freq", n=maxN+1, rg=rgArgus))))

TauArgusOPT: As "TauArgus" with methodArgus="OPT"

TauArgusMOD: As "TauArgus" with methodArgus="MOD"

TauArgusGH: As "TauArgus" with methodArgus="GH"

Value

See [ProtectTable](#)

PTxyz

*ProtectTable with output ready for SuppressDec in package RegSDC***Description**

Assuming correct suppression, suppressed values become decimal numbers (not whole numbers) instead of missing.

Usage

```
PTxyz(data, dimVar, freqVar, ...)
```

Arguments

data	data frame
dimVar	The main dimensional variables and additional aggregating variables (name or number).
freqVar	Variable(s) holding counts (name or number).
...	Further parameters sent to ProtectTable

Details

Within this r package this function will be used for testing

Value

List of three matrices ready as input to SuppressDec

x	Sparse dummy matrix where the dimensions match z and y.
z	Frequencies to be published with suppressed as NA.
y	Inner cell frequencies.

Author(s)

Øyvind Langsrud

Examples

```
## Not run:

# Same examples as in ProtectTable
a1 <- PTxyz(EasyData("z1"), c("region","hovedint"), "ant")
a2 <- PTxyz(EasyData("z2"), c(1,3,4),5)

if (require(RegSDC)) { # RegSDCdata and SuppressDec
  # Same data as in RegSDCdata examples (and in paper)
  data7 <- RegSDCdata("sec7data")
}
```

```

data7 <- data7[!is.na(data7$y), 1:3]
data7

# Generate x, y, z similar to xAll, y, zAllSupp in RegSDCdata examples
# But different suppressed cells and z ordered differently
a <- PTxyz(data7, 1:2, 3, maxN = 3, method = "HITAS")
a

# Suppressed inner cells as decimal numbers
yDec <- SuppressDec(a$x, a$z, a$y, rmse = 1)
yDec

# All cells as decimal numbers
cbind(a$z, t(a$x) %*% cbind(a$y, yDec))

# As ProtectTable example
z1 <- EasyData("z1")
a <- PTxyz(z1, c("region", "hovedint"), "ant")

# Inner cells as decimal numbers. 3 replicates.
yDec <- SuppressDec(a$x, a$z, a$y, nRep = 3)
yDec

# All cells with 3 replicates.
cbind(a$z, t(a$x) %*% cbind(a$y, yDec))
}

if (require(RegSDC)) {
  # An example involving two linked tables.
  # It is demonstrated that the SIMPLEHEURISTIC approach to suppression is not safe.
  # That is, perfect fit (whole numbers) for some suppressed cells.
  a <- PTxyz(EasyData("z3"), 1:5, 7, method = "SIMPLEHEURISTIC", protectZeros= FALSE)
  cbind(a$z, t(a$x) %*% cbind(a$y, SuppressDec(a$x, a$z, rmse=pi/3, nRep=3)))[which(is.na(a$z)), ]
}
## End(Not run)

```

Index

AutoSplit, [5](#)

createArgusInput, [6](#), [13](#)

EasyData, [2](#)

FactorLevCorr, [10](#)

FindCommonCells, [10](#)

FindDimLists, [5](#), [10](#)

FindTableGroup, [5](#), [9](#)

GaussSuppression, [3](#), [4](#), [6](#)

HierarchicalGroups, [10](#)

invisible, [12](#)

makeProblem, [10](#)

primarySuppression, [4](#), [10](#)

protect_linked_tables, [3](#), [4](#), [6](#), [10](#)

ProtectTable, [3](#), [9](#), [10](#), [12–14](#)

protectTable, [3](#), [4](#), [6](#), [10](#)

ProtectTable1, [7](#), [8](#)

ProtectTableData (ProtectTable), [3](#)

PTgui, [11](#)

PTguiApp (PTgui), [11](#)

PTguiAppNO (PTgui), [11](#)

PTguiNO (PTgui), [11](#)

PTwrap, [4](#), [6](#), [12](#)

PTxyz, [14](#)

ReplaceDimList, [5](#)

runArgusBatchFile, [6](#), [10](#), [13](#)

SSBtoolsData, [2](#)

Stack, [5](#)