

Package ‘fullfact’

May 8, 2026

Type Package

Title Full Factorial Breeding Analysis

Version 1.6

Date 2026-03-15

Maintainer Aimee Lee Houde <aimee.lee.houde@gmail.com>

Depends R (>= 3.6)

Imports lme4, reformulas, afex

VignetteBuilder knitr

Suggests knitr, rmarkdown

Description We facilitate the analysis of full factorial mating designs with mixed-effects models. The package contains six vignettes containing detailed examples.

License GPL (>= 2)

NeedsCompilation no

Author Aimee Lee Houde [aut, cre],
Trevor Pitcher [aut]

Repository CRAN

Date/Publication 2026-03-16 03:40:02 UTC

Contents

fullfact-package	2
barMANA	6
boxMANA	7
buildBinary	8
buildMulti	9
chinook_bootL	10
chinook_bootS	11
chinook_jackL	12
chinook_jackS	13
chinook_length	14
chinook_resampL	15

chinook_resampS	17
chinook_survival	18
ciJack	19
ciJack2	21
ciJack3	22
ciMANA	23
ciMANA2	25
ciMANA3	26
JackGlmer	28
JackGlmer2	30
JackGlmer3	32
JackLmer	34
JackLmer2	36
JackLmer3	38
observGlmer	40
observGlmer2	41
observGlmer3	43
observLmer	45
observLmer2	46
observLmer3	48
powerGlmer	50
powerGlmer2	51
powerGlmer3	53
powerLmer	55
powerLmer2	56
powerLmer3	58
resampFamily	60
resampGlmer	61
resampGlmer2	63
resampGlmer3	64
resampLmer	66
resampLmer2	68
resampLmer3	69
resampRepli	71

Index	73
--------------	-----------

fullfact-package	<i>Full Factorial Breeding Analysis</i>
------------------	---

Description

Full factorial breeding designs are useful for quantifying the amount of additive genetic, nonadditive genetic, and maternal variance that explain phenotypic traits. Such variance estimates are important for examining evolutionary potential. Traditionally, full factorial mating designs have been analyzed using a two-way analysis of variance, which may produce negative variance values and is not suited for unbalanced designs. Mixed-effects models do not produce negative variance values and are suited for unbalanced designs. However, extracting the variance components, calculating

significance values, and estimating confidence intervals and/or power values for the components are not straightforward using traditional analytic methods.

In this package we address these issues and facilitate the analysis of full factorial mating designs with mixed-effects models. The observed data functions extract the variance explained by random and fixed effects and provide their significance. We then calculate the additive genetic, nonadditive genetic, and maternal variance components explaining the phenotype. In particular, we integrate nonnormal error structures for estimating these components for nonnormal data types. The resampled data functions are used to produce bootstrap confidence intervals, which can then be plotted using a simple function. This package will facilitate the analyses of full factorial mating designs in R, especially for the analysis of binary, proportion, and/or count data types and for the ability to incorporate additional random and fixed effects and power analyses.

The package contains six vignettes containing detailed examples: `browseVignettes(package="fullfact")`.

The paper associated with the package including worked examples is: Houde ALS, Pitcher TE. 2016. fullfact: an R package for the analysis of genetic and maternal variance components from full factorial mating designs. *Ecology and evolution* 6 (6), 1656-1665. doi: 10.1002/ece3.1943.

Details

The DESCRIPTION file:

```
Package:      fullfact
Type:        Package
Title:       Full Factorial Breeding Analysis
Version:     1.6
Date:       2026-03-15
Authors@R:   c(person(given = c("Aimee", "Lee"),family = "Houde",role = c("aut", "cre"),email = "aimee.lee.houde@gmail.com")
Maintainer:  Aimee Lee Houde <aimee.lee.houde@gmail.com>
Depends:     R (>= 3.6)
Imports:     lme4, reformulas, afex
VignetteBuilder: knitr
Suggests:   knitr, rmarkdown
Description: We facilitate the analysis of full factorial mating designs with mixed-effects models. The package contains
License:     GPL (>=2)
Author:      Aimee Lee Houde [aut, cre], Trevor Pitcher [aut]
```

Index of help topics:

```
JackGlmmer      Jackknife components for non-normal data
JackGlmmer2     Jackknife components for non-normal data 2
JackGlmmer3     Jackknife components for non-normal data 3
JackLmer        Jackknife components for normal data
JackLmer2       Jackknife components for normal data 2
JackLmer3       Jackknife components for normal data 3
barMANA        Bargraph of confidence intervals
boxMANA        Boxplot of resampled results
buildBinary     Convert to a binary data frame
buildMulti      Convert to a multinomial frame
```

chinook_bootL	Chinook salmon length, bootstrap calculations
chinook_bootS	Chinook salmon survival, bootstrap data
chinook_jackL	Chinook salmon length, jackknife data
chinook_jackS	Chinook salmon survival, jackknife data
chinook_length	Chinook salmon length, raw data
chinook_resampL	Chinook salmon length, bootstrap resampled
chinook_resampS	Chinook salmon survival, bootstrap resampled
chinook_survival	Chinook salmon survival, raw data
ciJack	Jackknife confidence intervals
ciJack2	Jackknife confidence intervals 2
ciJack3	Jackknife confidence intervals 3
ciMANA	Bootstrap confidence intervals
ciMANA2	Bootstrap confidence intervals 2
ciMANA3	Bootstrap confidence intervals 3
fullfact-package	Full Factorial Breeding Analysis
observGlm	Variance components for non-normal data
observGlm2	Variance components for non-normal data 2
observGlm3	Variance components for non-normal data 3
observLmer	Variance components for normal data
observLmer2	Variance components for normal data 2
observLmer3	Variance components for normal data 3
powerGlm	Power analysis for non-normal data
powerGlm2	Power analysis for non-normal data 2
powerGlm3	Power analysis for non-normal data 3
powerLmer	Power analysis for normal data
powerLmer2	Power analysis for normal data 2
powerLmer3	Power analysis for normal data 3
resampFamily	Bootstrap resample within families
resampGlm	Bootstrap components for non-normal data
resampGlm2	Bootstrap components for non-normal data 2
resampGlm3	Bootstrap components for non-normal data 3
resampLmer	Bootstrap components for normal data
resampLmer2	Bootstrap components for normal data 2
resampLmer3	Bootstrap components for normal data 3
resampRepli	Bootstrap resample within replicates

Author(s)

Aimee Lee Houde [aut, cre], Trevor Pitcher [aut]

Maintainer: Aimee Lee Houde <aimee.lee.houde@gmail.com>

References

Traditional full factorial breeding design analysis:

Lynch M, Walsh B. 1998. Genetics and Analysis of Quantitative Traits. Sinauer Associates, Massachusetts.

Residual variance component values for generalized linear mixed-effects models:

Nakagawa S, Schielzeth H. 2010. Repeatability for Gaussian and non-Gaussian data: a practical guide for biologists. *Biological Reviews* 85(4): 935-956. DOI: 10.1111/j.1469-185X.2010.00141.x

Fixed effect variance component values for mixed-effects models:

Nakagawa S, Schielzeth H. 2013. A general and simple method for obtaining R^2 from generalized linear mixed-effects models. *Methods in Ecology and Evolution* 4(2): 133-142. DOI: 10.1111/j.2041-210x.2012.00261.x

Confidence intervals (bootstrap resampling, bias and acceleration correction, jackknife resampling):

Efron B, Tibshirani R. 1993. *An introduction to the Bootstrap*. Chapman and Hall, New York.

Martin, H., Westad, F. & Martens, H. (2004). Improved Jackknife Variance Estimates of Bilinear Model Parameters. *COMPSTAT 2004 – Proceedings in Computational Statistics 16th Symposium Held in Prague, Czech Republic, 2004* (ed J. Antoch), pp. 261-275. Physica-Verlag HD, Heidelberg.

Data sources:

Pitcher TE, Neff BD. 2007. Genetic quality and offspring performance in Chinook salmon: implications for supportive breeding. *Conservation Genetics* 8(3):607-616. DOI: 10.1007/s10592-006-9204-z

Examples

```
data(chinook_length) #Chinook salmon offspring length

## Standard additive genetic, non-additive genetic, and maternal variance analysis

length_mod1<- observLmer(observ=chinook_length,dam="dam",sire="sire",response="length")
length_mod1

## Confidence intervals

##Bootstrap resampling of data: replicates within family
## Not run: resampRepli(dat=chinook_length,copy=c(3:8),family="family",replicate="repli",
iter=1000)
## End(Not run)
#saves the files in working directory: one for each replicate and
#one final (combined) file "resamp_datR.csv"

##Import file
#length_datR<- read.csv("resamp_datR.csv")
data(chinook_resampL) #same as length_datR, 5 iterations

##Models for the resampled data: standard analysis
## Not run: length_rcomp<- resampLmer(resamp=length_datR,dam="dam",sire="sire",
response="length",start=1,end=1000)
## End(Not run)

## 1. Uncorrected Bootstrap 95% confidence interval

#ciMANA(comp=length_rcomp)
data(chinook_bootL) #similar to length_rcomp, but 1,000 models
ciMANA(comp=chinook_bootL)
```

```
## 2. Bias and accelerated corrected Bootstrap 95% confidence interval

##Jackknife resampling of data, delete-one: for acceleration estimate
## Not run: length_jack<- JackLmer(observ=chinook_length,dam="dam",sire="sire",
response="length")
## End(Not run)

#ciMANA(comp=length_rcomp,bias=c(0,0.7192,0.2030),accel=length_jack)
data(chinook_jackL) #similar to length_jack, but all observations
ciMANA(comp=chinook_bootL,bias=c(0,0.7192,0.2030),accel=chinook_jackL)

##3. Jackknife 95% confidence interval

#ciJack(comp=length_jack,full=c(0,0.7192,0.2030,1.0404))
ciJack(comp=chinook_jackL,full=c(0,0.7192,0.2030,1.0404))
```

barMANA

Bargraph of confidence intervals

Description

A simple bargraph function for confidence intervals of additive genetic, non-additive genetic, and maternal variance components. Also, plots the median for the bootstrap resampling method or mean of the pseudo-values for the jackknife resampling method.

Usage

```
barMANA(ci_dat, type = "perc", bar_len = 0.1, ymax = NULL, ymin = NULL, yunit = NULL,
leg = "topright", cex_ylab = 1, cex_yaxis = 1, cex_names = 1)
```

Arguments

ci_dat	Data frame of a confidence interval function.
type	Default is "perc" for percentage values of variance components. Other option is "raw" for raw values of variance components.
bar_len	Length of error bar in inches.
ymax	Maximum value of the y-axis.
ymin	Minimum value of the y-axis.
yunit	Unit increment of the y-axis.
leg	Position of the simple legend.
cex_ylab	Magnification of the y-axis label.
cex_yaxis	Magnification of the y-axis units.
cex_names	Optional magnification of trait labels.

Details

Plots a bargraph with the median or mean as the top of the shaded bar and error bars covering the range of the confidence interval. Uses an object produced by any of the bootstrap resampling CI functions, i.e. *ciMANA*, *ciMANA2*, and *ciMANA3* or jackknife resampling functions, i.e. *ciJack*, *ciJack2*, and *ciJack3*. The median is plotted for bootstrap resampling and the mean of pseudo-value for jackknife resampling. Produces a simple legend. The function can plot several bar graphs grouped by *label* to visualize several phenotypic traits.

Examples

```
##Import jackknife resampling results
data(chinook_jackL) #Chinook salmon length
length_ci<- ciJack(comp=chinook_jackL,full=c(0,0.7192,0.2030,1.0404))
barMANA(ci_dat=length_ci) #default plot
barMANA(ci_dat=length_ci,bar_len=0.3,yunit=20,ymax=100,cex_ylab=1.3)

##Group length and survival together in the same plot
data(chinook_bootS) #Chinook salmon survival (bootstrap resampling)
length_ci<- ciJack(comp=chinook_jackL,full=c(0,0.7192,0.2030,1.0404),trait="length")
survival_ci<- ciMANA(comp=chinook_bootS,trait="survival")
colnames(length_ci$raw)[3]<- "median"; colnames(length_ci$percentage)[3]<- "median"
comb_bar<- list(raw=rbind(length_ci$raw,survival_ci$raw),
percentage=rbind(length_ci$percentage,survival_ci$percentage))
#
barMANA(ci_dat=comb_bar) #default plot
barMANA(ci_dat=comb_bar,bar_len=0.3,yunit=20,ymax=100,cex_ylab=1.3)
```

boxMANA

Boxplot of resampled results

Description

A simple boxplot function for bootstrap and jackknife resampled results of additive genetic, non-additive genetic, and maternal variance components.

Usage

```
boxMANA(comp, type = "perc", ymax = NULL, ymin = NULL, yunit = NULL, leg = "topright",
cex_ylab = 1, cex_yaxis = 1, cex_names = 1)
```

Arguments

<code>comp</code>	Data frame of bootstrap or jackknife resampling results.
<code>type</code>	Default is "perc" for percentage values of variance components. Other option is "raw" for raw values of variance components.
<code>ymax</code>	Maximum value of the y-axis.
<code>ymin</code>	Minimum value of the y-axis.

yunit	Unit increment of the y-axis.
leg	Position of the simple legend.
cex_ylab	Magnification of the y-axis label.
cex_yaxis	Magnification of the y-axis units.
cex_names	Optional magnification of trait labels.

Details

Plots an R boxplot. Uses an object produced by any of the bootstrap resampling functions, i.e. *resampLmer*, *resampLmer2*, *resampLmer3*, *resampGlmer*, *resampGlmer2*, and *resampGlmer3*. Or any of the jackknife resampling functions, i.e. *JackLmer*, *JackLmer2*, *JackLmer3*, *JackGlmer*, *JackGlmer2*, and *JackGlmer3*. Produces a simple legend.

Examples

```
##Import bootstrap resampled data model results
data(chinook_bootL) #Chinook salmon length
boxMANA(comp=chinook_bootL) #Default plot
boxMANA(comp=chinook_bootL,yunit=20,ymax=100,cex_ylab=1.3,leg="topleft")

##Group length and survival together in the same plot
data(chinook_bootS) #Chinook salmon survival
chinook_bootL$trait<- "length"; chinook_bootS$trait<- "survival"
comb_boot<- rbind(chinook_bootL[,-2],chinook_bootS) #remove 'tray'
comb_boot$trait<- as.factor(comb_boot$trait)
#
boxMANA(comp=comb_boot) #Default plot
boxMANA(comp=comb_boot,yunit=20,ymax=100,cex_ylab=1.3)
```

buildBinary

Convert to a binary data frame

Description

Assign a binary number (i.e. '0' or '1') to two columns containing the number of offspring. Copy information by the number of times equal to the number of offspring.

Usage

```
buildBinary(dat, copy, one, zero)
```

Arguments

dat	Data frame to convert.
copy	Column numbers to copy.
one	Column name of counts to assign a '1' value.
zero	Column name of counts to assign a '0' value.

Details

Replicate-level data should be converted to the individual-level to not underestimate phenotypic variance, which can influence genetic and maternal estimates (see Puurtinen et al. 2009).

Value

A converted data frame with a number of row matching the total number of individuals.

References

Puurtinen M, Ketola T, Kotiaho JS. 2009. The good-genes and compatible-genes benefits of mate choice. *The American Naturalist* 174(5): 741-752. DOI: 10.1086/606024

See Also

[buildMulti](#)

Examples

```
data(chinook_survival)
chinook_survival2<- buildBinary(dat=chinook_survival,copy=c(1:6,9),one="alive",zero="dead")
```

buildMulti

Convert to a multinomial frame

Description

Assign multiple numbers to multiple columns containing the number of offspring. Copy information by the number of times equal to the number of offspring.

Usage

```
buildMulti(dat, copy, multi)
```

Arguments

`dat` Data frame to convert.

`copy` Column numbers to copy.

`multi` A list containing the numbers to assign and matching column names, e.g. `list(c(2,0,1),c("two","zero","one"))`

Details

Replicate-level data should be converted to the individual-level to not underestimate phenotypic variance, which can influence genetic and maternal estimates (see Puurtinen et al. 2009).

Value

A converted data frame with a number of row matching the total number of individuals.

References

Puurtinen M, Ketola T, Kotiaho JS. 2009. The good-genes and compatible-genes benefits of mate choice. *The American Naturalist* 174(5): 741-752. DOI: 10.1086/606024

See Also

[buildBinary](#)

Examples

```
data(chinook_survival)
chinook_survival$total<- chinook_survival$alive + chinook_survival$dead #create total column
chinook_survival3<- buildMulti(dat=chinook_survival,copy=c(1:6,9),multi=list(c(2,1,0),
c("total","alive","dead")))
```

chinook_bootL

Chinook salmon length, bootstrap calculations

Description

Bootstrap resampled Chinook salmon fork length (mm) at hatch with the amount of additive genetic, non-additive genetic, and maternal variance calculations.

Usage

```
data("chinook_bootL")
```

Format

A data frame with 1000 observations on the following 9 variables.

dam.sire, a numeric vector.

tray, a numeric vector.

sire, a numeric vector.

dam, a numeric vector.

Residual, a numeric vector.

Total, a numeric vector.

additive, a numeric vector.

maternal, a numeric vector.

nonadd, a numeric vector.

Details

Also includes the calculations for the amount of variance explained by position (tray), dam by sire, sire, dam, residual, and total.

Source

<http://link.springer.com.proxy1.lib.uwo.ca/article/10.1007>

References

Pitcher TE, Neff BD. 2007. Genetic quality and offspring performance in Chinook salmon: implications for supportive breeding. *Conservation Genetics* 8(3):607-616. DOI: 10.1007/s10592-006-9204-z

Examples

```
data(chinook_bootL)
## Extract bootstrap confidence interval
ciMANA(comp=chinook_bootL)
```

chinook_bootS	<i>Chinook salmon survival, bootstrap data</i>
---------------	--

Description

Bootstrap resampled Chinook salmon binary survival to hatch (1 is alive, 0 is dead) with the amount of additive genetic, non-additive genetic, and maternal variance calculations.

Usage

```
data("chinook_bootS")
```

Format

A data frame with 1000 observations on the following 8 variables.

dam.sire, a numeric vector.

sire, a numeric vector.

dam, a numeric vector.

Residual, a numeric vector.

Total, a numeric vector.

additive, a numeric vector.

maternal, a numeric vector.

nonadd, a numeric vector.

Details

Also includes the calculations for the amount of variance explained by dam by sire, sire, dam, residual, and total.

Source

<http://link.springer.com.proxy1.lib.uwo.ca/article/10.1007>

References

Pitcher TE, Neff BD. 2007. Genetic quality and offspring performance in Chinook salmon: implications for supportive breeding. *Conservation Genetics* 8(3):607-616. DOI: 10.1007/s10592-006-9204-z

Examples

```
data(chinook_bootS)
## Extract bootstrap confidence interval
ciMANA(comp=chinook_bootS)
```

chinook_jackL

Chinook salmon length, jackknife data

Description

Jackknife resampled Chinook salmon fork length (mm) at hatch with the amount of additive genetic, non-additive genetic, and maternal variance calculations. Jackknife resampling was leave-out-one.

Usage

```
data("chinook_jackL")
```

Format

A data frame with 1210 observations on the following 9 variables.

dam.sire, a numeric vector.

tray, a numeric vector.

sire, a numeric vector.

dam, a numeric vector.

Residual, a numeric vector.

Total, a numeric vector.

additive, a numeric vector.

nonadd, a numeric vector.

maternal, a numeric vector.

Details

Also includes the calculations for the amount of variance explained by position (tray), dam by sire, sire, dam, residual, and total.

Source

<http://link.springer.com.proxy1.lib.uwo.ca/article/10.1007>

References

Pitcher TE, Neff BD. 2007. Genetic quality and offspring performance in Chinook salmon: implications for supportive breeding. *Conservation Genetics* 8(3):607-616. DOI: 10.1007/s10592-006-9204-z

Examples

```
data(chinook_jackL)
## Extract jackknifed confidence interval
ciJack(comp=chinook_jackL,full=c(0,0.7192,0.2030,1.0404))
```

chinook_jackS

Chinook salmon survival, jackknife data

Description

Jackknife resampled Chinook salmon survival with the amount of additive genetic, non-additive genetic, and maternal variance calculations. Jackknife resampling was leave-out-30.

Usage

```
data("chinook_jackS")
```

Format

A data frame with 1210 observations on the following 9 variables.

dam.sire, a numeric vector.

sire, a numeric vector.

dam, a numeric vector.

Residual, a numeric vector.

Total, a numeric vector.

additive, a numeric vector.

nonadd, a numeric vector.

maternal, a numeric vector.

Details

Also includes the calculations for the amount of variance explained by dam by sire, sire, dam, residual, and total.

Source

<http://link.springer.com.proxy1.lib.uwo.ca/article/10.1007>

References

Pitcher TE, Neff BD. 2007. Genetic quality and offspring performance in Chinook salmon: implications for supportive breeding. *Conservation Genetics* 8(3):607-616. DOI: 10.1007/s10592-006-9204-z

Examples

```
data(chinook_jackS)
## Extract jackknifed confidence interval
ciJack(comp=chinook_jackS, full=c(0.6655,0.6692,0.6266,4.4166))
```

chinook_length	<i>Chinook salmon length, raw data</i>
----------------	--

Description

Raw Chinook salmon fork length (mm) at hatch for offspring produced using an 11 x 11 full factorial breeding design.

Usage

```
data("chinook_length")
```

Format

A data frame with 1210 observations on the following 8 variables.

family, a factor with levels: f1 f10 f100 f101 f102 f103 f104 f105 f106 f107 f108 f109 f11 f110 f111 f112 f113 f114 f115 f116 f117 f118 f119 f12 f120 f121 f13 f14 f15 f16 f17 f18 f19 f2 f20 f21 f22 f23 f24 f25 f26 f27 f28 f29 f3 f30 f31 f32 f33 f34 f35 f36 f37 f38 f39 f4 f40 f41 f42 f43 f44 f45 f46 f47 f48 f49 f5 f50 f51 f52 f53 f54 f55 f56 f57 f58 f59 f6 f60 f61 f62 f63 f64 f65 f66 f67 f68 f69 f7 f70 f71 f72 f73 f74 f75 f76 f77 f78 f79 f8 f80 f81 f82 f83 f84 f85 f86 f87 f88 f89 f9 f90 f91 f92 f93 f94 f95 f96 f97 f98 f99

repli, a factor with levels: r1 r2

dam, a factor with levels: d1 d10 d11 d2 d3 d4 d5 d6 d7 d8 d9

sire, a factor with levels: s1 s10 s11 s2 s3 s4 s5 s6 s7 s8 s9

tray, a factor with levels: t1 t10 t11 t12 t13 t14 t15 t16 t2 t3 t4 t5 t6 t7 t8 t9

cell, a factor with levels: 1A 1B 1C 1D 2A 2B 2C 2D 3A 3B 3C 3D 4A 4B 4C 4D

length, a numeric vector.

egg_size, a numeric vector.

Details

Also includes family identity, family replicate, incubator position (tray and cell), and average female egg size (mm) information.

Source

<http://link.springer.com.proxy1.lib.uwo.ca/article/10.1007>

References

Pitcher TE, Neff BD. 2007. Genetic quality and offspring performance in Chinook salmon: implications for supportive breeding. *Conservation Genetics* 8(3):607-616. DOI: 10.1007/s10592-006-9204-z

Examples

```
data(chinook_length)
## Standard additive genetic, non-additive genetic, and maternal variance analysis
length_mod1<- observLmer(observ=chinook_length,dam="dam",sire="sire",response="length")
length_mod1
```

chinook_resampL

Chinook salmon length, bootstrap resampled

Description

Bootstrap resampled Chinook salmon fork length (mm) at hatch. Number of iterations was 5.

Usage

```
data("chinook_resampL")
```

Format

A data frame with 1210 observations on the following 30 variables.

dam1, a numeric vector
sire1, a numeric vector
tray1, a numeric vector
cell1, a numeric vector
length1, a numeric vector
egg_size1, a numeric vector
dam2, a numeric vector
sire2, a numeric vector
tray2, a numeric vector

cell2, a numeric vector
length2, a numeric vector
egg_size2, a numeric vector
dam3, a numeric vector
sire3, a numeric vector
tray3, a numeric vector
cell3, a numeric vector
length3, a numeric vector
egg_size3, a numeric vector
dam4, a numeric vector
sire4, a numeric vector
tray4, a numeric vector
cell4, a numeric vector
length4, a numeric vector
egg_size4, a numeric vector
dam5, a numeric vector
sire5, a numeric vector
tray5, a numeric vector
cell5, a numeric vector
length5, a numeric vector
egg_size5, a numeric vector

Source

Pitcher TE, Neff BD. 2007. Genetic quality and offspring performance in Chinook salmon: implications for supportive breeding. *Conservation Genetics* 8(3):607-616. DOI: 10.1007/s10592-006-9204-z

Examples

```
data(chinook_resampL)
#the five models
length_rcomp1<- resampLmer(resamp=chinook_resampL,dam="dam",sire="sire",response="length",
start=1,end=5) #full analysis should use 1,000 models
```

chinook_resampS	<i>Chinook salmon survival, bootstrap resampled</i>
-----------------	---

Description

Bootstrap resampled Chinook salmon binary survival to hatch (1 is alive, 0 is dead). Number of iterations was 5.

Usage

```
data("chinook_resampS")
```

Format

A data frame with 36300 observations on the following 30 variables.

status1, a numeric vector
dam1, a numeric vector
sire1, a numeric vector
tray1, a numeric vector
cell1, a numeric vector
egg_size1, a numeric vector
status2, a numeric vector
dam2, a numeric vector
sire2, a numeric vector
tray2, a numeric vector
cell2, a numeric vector
egg_size2, a numeric vector
status3, a numeric vector
dam3, a numeric vector
sire3, a numeric vector
tray3, a numeric vector
cell3, a numeric vector
egg_size3, a numeric vector
status4, a numeric vector
dam4, a numeric vector
sire4, a numeric vector
tray4, a numeric vector
cell4, a numeric vector
egg_size4, a numeric vector

status5, a numeric vector
 dam5, a numeric vector
 sire5, a numeric vector
 tray5, a numeric vector
 cell5, a numeric vector
 egg_size5, a numeric vector

Source

Pitcher TE, Neff BD. 2007. Genetic quality and offspring performance in Chinook salmon: implications for supportive breeding. *Conservation Genetics* 8(3):607-616. DOI: 10.1007/s10592-006-9204-z

Examples

```
data(chinook_resampS)
## Not run: survival_rcomp<- resampGlmmer(resamp=chinook_resampS,dam="dam",sire="sire",
response="status",fam_link=binomial(link="logit"),start=1,end=1000)
## End(Not run)
```

chinook_survival	<i>Chinook salmon survival, raw data</i>
------------------	--

Description

Raw Chinook salmon numbers alive and dead to hatching of offspring produced using an 11 x 11 full factorial breeding design.

Usage

```
data("chinook_survival")
```

Format

A data frame with 242 observations on the following 9 variables.

family, a factor with levels: f1 f10 f100 f101 f102 f103 f104 f105 f106 f107 f108 f109 f11 f110 f111 f112 f113 f114 f115 f116 f117 f118 f119 f12 f120 f121 f13 f14 f15 f16 f17 f18 f19 f2 f20 f21 f22 f23 f24 f25 f26 f27 f28 f29 f3 f30 f31 f32 f33 f34 f35 f36 f37 f38 f39 f4 f40 f41 f42 f43 f44 f45 f46 f47 f48 f49 f5 f50 f51 f52 f53 f54 f55 f56 f57 f58 f59 f6 f60 f61 f62 f63 f64 f65 f66 f67 f68 f69 f7 f70 f71 f72 f73 f74 f75 f76 f77 f78 f79 f8 f80 f81 f82 f83 f84 f85 f86 f87 f88 f89 f9 f90 f91 f92 f93 f94 f95 f96 f97 f98 f99

repli, a factor with levels: r1 r2

dam, a factor with levels: d1 d10 d11 d2 d3 d4 d5 d6 d7 d8 d9

sire, a factor with levels: s1 s10 s11 s2 s3 s4 s5 s6 s7 s8 s9

tray, a factor with levels: t1 t10 t11 t12 t13 t14 t15 t16 t2 t3 t4 t5 t6 t7 t8 t9

cell, a factor with levels: 1A 1B 1C 1D 2A 2B 2C 2D 3A 3B 3C 3D 4A 4B 4C 4D

alive, a numeric vector.

dead, a numeric vector.

egg_size, a numeric vector.

Details

Also includes family identity, family replicate, incubator position (tray and cell), and average female egg size (mm) information.

Source

<http://link.springer.com.proxy1.lib.uwo.ca/article/10.1007>

References

Pitcher TE, Neff BD. 2007. Genetic quality and offspring performance in Chinook salmon: implications for supportive breeding. *Conservation Genetics* 8(3):607-616. DOI: 10.1007/s10592-006-9204-z

Examples

```
data(chinook_survival)
## Convert replicate-level recorded data to individual-level (binary) data
chinook_survival2<- buildBinary(dat=chinook_survival,copy=c(2:6,9),one="alive",zero="dead")

## Standard additive genetic, non-additive genetic, and maternal variance analysis
## Not run: survival_mod1<- observGlmmer(observ=chinook_survival2,dam="dam",sire="sire",
response="status",fam_link=binomial(link="logit"))
survival_mod1
## End(Not run)
```

ciJack

Jackknife confidence intervals

Description

Extracts jackknife confidence intervals for additive genetic, non-additive genetic, and maternal variance components.

Usage

```
ciJack(comp, full, level = 95, rnd_r = 3, rnd_p = 1, trait = NULL)
```

Arguments

<code>comp</code>	Data frame of jackknife resampling results.
<code>full</code>	A vector of raw observed additive, non-additive, maternal, and total variance component values for from the full observed data set, i.e. <code>c(additive, non-additive, maternal, total)</code> .
<code>level</code>	Confidence level, as a percentage. Default is 95.
<code>rnd_r</code>	Number of decimal places to round the confidence interval of raw values.
<code>rnd_p</code>	Number of decimal places to round the confidence interval of percentage values.
<code>trait</code>	Optional label for the phenotypic trait.

Details

Used for jackknife resampling results produced using *JackLmer* for normal data or *JackGlmer* for non-normal data. Jackknife confidence intervals, using pseudo-values are described by Efron and Tibshirani (1993). The standard errors are calculated from the pseudo-values and the Student's *t* distribution is used to provide the lower and upper confidence values. For delete-*d* jackknife resampling, *M* degrees of freedom are used for producing the confidence interval (Martin et al. 2004): $M = N / d$, where *N* is the total number of observations and *d* is the number of deleted observations. That is, *M* is the number of row in the jackknife resampling results. Large values of *M*, such as 1,000, can translate to the delete-*d* jackknife resampling method approaching bootstrap resampling expectations (Efron & Tibshirani 1993).

Value

Prints a data frame containing the lower, median, and upper values of the jackknife confidence interval for additive genetic, non-additive genetic, and maternal variance components. Values are presented as raw and percentages of the total variance value within each row.

References

- Efron B, Tibshirani R. 1993. An introduction to the Bootstrap. Chapman and Hall, New York.
- Martin, H., Westad, F. & Martens, H. (2004). Improved Jackknife Variance Estimates of Bilinear Model Parameters. COMPSTAT 2004 – Proceedings in Computational Statistics 16th Symposium Held in Prague, Czech Republic, 2004 (ed J. Antoch), pp. 261-275. Physica-Verlag HD, Heidelberg.

See Also

[ciJack2](#), [ciJack3](#)

Examples

```
data(chinook_jackL) #Chinook salmon offspring length, delete-one jackknife
ciJack(chinook_jackL,c(0,0.7192,0.2030,1.0404))
```

ciJack2

Jackknife confidence intervals 2

Description

Extracts jackknife confidence intervals for additive genetic, non-additive genetic, and maternal variance components. Also extracts intervals for optional position and block variance components.

Usage

```
ciJack2(comp, full, level = 95, rnd_r = 3, rnd_p = 1, position = NULL, block = NULL,
trait = NULL)
```

Arguments

comp	Data frame of jackknife resampling results.
full	A vector of raw observed additive, non-additive, maternal, and total variance component values for from the full observed data set, i.e. c(additive, non-additive, maternal, total, position/block). If there is a position and a block c(..., total, position, block).
level	Confidence level, as a percentage. Default is 95.
rnd_r	Number of decimal places to round the confidence interval of raw values.
rnd_p	Number of decimal places to round the confidence interval of percentage values.
position	Optional column name containing position factor information.
block	Optional column name containing block factor information.
trait	Optional label for the phenotypic trait.

Details

Used for jackknife resampling results produced using *JackLmer2* for normal data or *JackGlmer2* for non-normal data. Jackknife confidence intervals, using pseudo-values are described by Efron and Tibshirani (1993). The standard errors are calculated from the pseudo-values and the Student's *t* distribution is used to provide the lower and upper confidence values. For delete-*d* jackknife resampling, *M* degrees of freedom are used for producing the confidence interval (Martin et al. 2004): $M = N / d$, where *N* is the total number of observations and *d* is the number of deleted observations. That is, *M* is the number of row in the jackknife resampling results. Large values of *M*, such as 1,000, can translate to the delete-*d* jackknife resampling method approaching bootstrap resampling expectations (Efron & Tibshirani 1993).

Value

Prints a data frame containing the lower, median, and upper values of the jackknife confidence interval for additive genetic, non-additive genetic, maternal variance components, and optional position and/or block variance components. Values are presented as raw and percentages of the total variance value within each row.

References

- Efron B, Tibshirani R. 1993. An introduction to the Bootstrap. Chapman and Hall, New York.
- Martin, H., Westad, F. & Martens, H. (2004). Improved Jackknife Variance Estimates of Bilinear Model Parameters. COMPSTAT 2004 – Proceedings in Computational Statistics 16th Symposium Held in Prague, Czech Republic, 2004 (ed J. Antoch), pp. 261-275. Physica-Verlag HD, Heidelberg.

See Also

[ciJack](#), [ciJack3](#)

Examples

```
data(chinook_jackL) #Chinook salmon offspring length, delete-one jackknife
ciJack2(chinook_jackL, position="tray", c(0, 0.7192, 0.2030, 1.0404, 0.1077))
```

ciJack3

Jackknife confidence intervals 3

Description

Extracts jackknife confidence intervals for additive genetic, non-additive genetic, and maternal variance components. Also extracts intervals for additional fixed and/or random effects.

Usage

```
ciJack3(comp, full, remain = NULL, level = 95, rnd_r = 3, rnd_p = 1, trait = NULL)
```

Arguments

<code>comp</code>	Data frame of jackknife resampling results
<code>full</code>	A vector of raw observed additive, non-additive, maternal, and total variance component values for from the full observed data set, i.e. <code>c(additive, non-additive, maternal, total)</code> . Followed by any other components in the order of the vector <i>remain</i> , i.e. <code>c(additive, non-additive, maternal, total, component1, component2, etc.)</code> .
<code>remain</code>	Vector of column names for additional effects
<code>level</code>	Confidence level, as a percentage. Default is 95.
<code>rnd_r</code>	Number of decimal places to round the confidence interval of raw values.
<code>rnd_p</code>	Number of decimal places to round the confidence interval of percentage values.
<code>trait</code>	Optional label for the phenotypic trait.

Details

Used for jackknife resampling results produced using *JackLmer3* for normal data or *JackGlmer3* for non-normal data. Jackknife confidence intervals, using pseudo-values are described by Efron and Tibshirani (1993). The standard errors are calculated from the pseudo-values and the Student's *t* distribution is used to provide the lower and upper confidence values. For delete-*d* jackknife resampling, *M* degrees of freedom are used for producing the confidence interval (Martin et al. 2004): $M = N / d$, where *N* is the total number of observations and *d* is the number of deleted observations. That is, *M* is the number of row in the jackknife resampling results. Large values of *M*, such as 1,000, can translate to the delete-*d* jackknife resampling method approaching bootstrap resampling expectations (Efron & Tibshirani 1993).

Value

Prints a data frame containing the lower, median, and upper values of the jackknife confidence interval for additive genetic, non-additive genetic, maternal variance components, and any additional fixed effect and/or random effect variance components. Values are presented as raw and percentages of the total variance value within each row.

References

- Efron B, Tibshirani R. 1993. An introduction to the Bootstrap. Chapman and Hall, New York.
- Martin, H., Westad, F. & Martens, H. (2004). Improved Jackknife Variance Estimates of Bilinear Model Parameters. COMPSTAT 2004 – Proceedings in Computational Statistics 16th Symposium Held in Prague, Czech Republic, 2004 (ed J. Antoch), pp. 261-275. Physica-Verlag HD, Heidelberg.

See Also

[ciJack](#), [ciJack2](#)

Examples

```
data(chinook_jackL) #Chinook salmon offspring length, delete-one jackknife
ciJack3(chinook_jackL, remain=c("tray", "Residual"), c(0, 0.7192, 0.2030, 1.0404, 0.1077, 0.5499))
```

ciMANA

Bootstrap confidence intervals

Description

Extracts bootstrap-*t* confidence intervals for additive genetic, non-additive genetic, and maternal variance components.

Usage

```
ciMANA(comp, level = 95, rnd_r = 3, rnd_p = 1, bias = NULL, accel = NULL, trait = NULL)
```

Arguments

<code>comp</code>	Data frame of bootstrap resampling results.
<code>level</code>	Confidence level, as a percentage. Default is 95.
<code>rnd_r</code>	Number of decimal places to round the confidence interval of raw values.
<code>rnd_p</code>	Number of decimal places to round the confidence interval of percentage values.
<code>bias</code>	Optional vector of raw observed additive, non-additive, and maternal, variance component values for bias correction, i.e. <code>c(additive, non-additive, maternal)</code> .
<code>accel</code>	Optional data frame of jackknifed data model results for acceleration correction.
<code>trait</code>	Optional label for the phenotypic trait.

Details

Used for bootstrap resampling results produced using *resampLmer* for normal data or *resampGlmer* for non-normal data. Bootstrap-*t* confidence intervals, including bias and acceleration correction methods are described by Efron and Tibshirani (1993). Jackknife data model results for acceleration correction can be produced using *JackLmer*, for normal data or *JackGlmer* for non-normal data. The 'bias fail' warning is if the bias calculation is Inf or -Inf, e.g. *bias* contains a zero value, so the uncorrected confidence interval is displayed.

Value

Prints a data frame containing the lower, median, and upper values of the bootstrap-*t* confidence interval for additive genetic, non-additive genetic, and maternal variance components. Values are presented as raw and percentages of the total variance value within each row.

References

Efron B, Tibshirani R. 1993. An introduction to the Bootstrap. Chapman and Hall, New York.

See Also

[ciMANA2](#), [ciMANA3](#)

Examples

```
#Import bootstrap resampled data model results
data(chinook_bootL) #Chinook salmon offspring length

#Extract un-corrected confidence interval
ciMANA(comp=chinook_bootL)

#Extract bias corrected confidence interval
ciMANA(comp=chinook_bootL,bias=c(0,0.7192,0.2030))
#see details for 'bias' fail

#Extract bias and accelerated corrected confidence interval
#Import jackknife resampled data model results
data(chinook_jackL)
```

```
#
ciMANA(comp=chinook_bootL,bias=c(0,0.7192,0.2030),accel=chinook_jackL)
#see details for 'bias' fail
```

ciMANA2

Bootstrap confidence intervals 2

Description

Extracts bootstrap-*t* confidence intervals for additive genetic, non-additive genetic, and maternal variance components. Also extracts intervals for optional position and block variance components.

Usage

```
ciMANA2(comp, level = 95, rnd_r = 3, rnd_p = 1, position = NULL, block = NULL,
bias = NULL, accel = NULL, trait = NULL)
```

Arguments

<code>comp</code>	Data frame of bootstrap resampling results.
<code>level</code>	Confidence level, as a percentage. Default is 95.
<code>rnd_r</code>	Number of decimal places to round the confidence interval of raw values.
<code>rnd_p</code>	Number of decimal places to round the confidence interval of percentage values.
<code>position</code>	Optional column name containing position factor information.
<code>block</code>	Optional column name containing block factor information.
<code>bias</code>	Optional vector of raw observed additive, non-additive, maternal, position and/or block variance component values for bias correction, i.e. <code>c(additive, non-additive, maternal, position/block)</code> . If there is a position and a block <code>c(..., maternal, position, block)</code> .
<code>accel</code>	Optional data frame of jackknifed data model results for acceleration correction.
<code>trait</code>	Optional label for the phenotypic trait.

Details

Used for bootstrap resampling results produced using *resampLmer2* for normal data or *resampGlmer2* for non-normal data. Bootstrap-*t* confidence intervals, including bias and acceleration correction methods are described by Efron and Tibshirani (1993). Jackknife data model results for acceleration correction can be produced using *JackLmer2*, for normal data or *JackGlmer2* for non-normal data. The 'bias fail' warning is if the bias calculation is Inf or -Inf, e.g. *bias* contains a zero value, so the uncorrected confidence interval is displayed.

Value

Prints a data frame containing the lower, median, and upper values of the bootstrap-*t* confidence interval for additive genetic, non-additive genetic, maternal, and optional position and/or block variance components. Values are presented as raw and percentages of the total variance value within each row.

References

Efron B, Tibshirani R. 1993. An introduction to the Bootstrap. Chapman and Hall, New York.

See Also

[ciMANA](#), [ciMANA3](#)

Examples

```
#Import bootstrap resampled data model results
data(chinook_bootL) #Chinook salmon offspring length

#Extract un-corrected confidence interval
ciMANA2(comp=chinook_bootL,position="tray")

#Extract bias corrected confidence interval
ciMANA2(comp=chinook_bootL,position="tray",bias=c(0,0.7192,0.2030,0.1077))
#see details for 'bias' fail

#Extract bias and accelerated corrected confidence interval
#Import jackknife resampled data model results
data(chinook_jackL)
#
ciMANA2(comp=chinook_bootL,position="tray",
bias=c(0,0.7192,0.2030,0.1077),accel=chinook_jackL)
#see details for 'bias' fail
```

ciMANA3

Bootstrap confidence intervals 3

Description

Extracts bootstrap-*t* confidence intervals for additive genetic, non-additive genetic, and maternal variance components. Also extracts intervals for additional fixed and/or random effects.

Usage

```
ciMANA3(comp, level = 95, rnd_r = 3, rnd_p = 1, bias = NULL, accel = NULL,
remain = NULL, trait = NULL)
```

Arguments

comp	Data frame of bootstrap resampling results.
level	Confidence level, as a percentage. Default is 95.
rnd_r	Number of decimal places to round the confidence interval of raw values.
rnd_p	Number of decimal places to round the confidence interval of percentage values.

bias	Optional vector of raw observed additive, non-additive, and maternal variance components for bias correction. Followed by any other components in the order of the vector <i>remain</i> , i.e. <code>c(additive, non-additive, maternal, component1, component2, etc.)</code> .
accel	Optional data frame of jackknifed data model results for acceleration correction.
remain	Vector of column names for additional effects.
trait	Optional label for the phenotypic trait.

Details

Used for bootstrap resampling results produced using *resampLmer3* for normal data or *resampGlmer3* for non-normal data. Bootstrap-*t* confidence intervals, including bias and acceleration correction methods are described by Efron and Tibshirani (1993). Jackknife data model results for acceleration correction can be produced using *JackLmer3*, for normal data or *JackGlmer3* for non-normal data. The 'bias fail' warning is if the bias calculation is Inf or -Inf, e.g. *bias* contains a zero value, so the uncorrected confidence interval is displayed.

Value

Prints a data frame containing the lower, median, and upper values of the bootstrap-*t* confidence interval for additive genetic, non-additive genetic, maternal, and any additional fixed effect and/or random effect variance components. Values are presented as raw and percentages of the total variance value within each row.

References

Efron B, Tibshirani R. 1993. An introduction to the Bootstrap. Chapman and Hall, New York.

See Also

[ciMANA](#), [ciMANA2](#)

Examples

```
#Import bootstrap resampled data model results
data(chinook_bootL) #Chinook salmon offspring length

#Extract un-corrected confidence interval
ciMANA3(comp=chinook_bootL,remain=c("tray","Residual"))

#Extract bias corrected confidence interval
ciMANA3(comp=chinook_bootL,remain=c("tray","Residual"),
bias=c(0,0.7192,0.2030,0.1077,0.5499))
#see details for 'bias' fail

#Extract bias and accelerated corrected confidence interval
#Import jackknife resampled data model results
data(chinook_jackL)
#
ciMANA3(comp=chinook_bootL,remain=c("tray","Residual"),
bias=c(0,0.7192,0.2030,0.1077,0.5499),accel=chinook_jackL)
```

 JackGlmer

Jackknife components for non-normal data

Description

Extracts additive genetic, non-additive genetic, and maternal variance components from a linear mixed-effect model using the *lmer* function of the *lme4* package. Model random effects are dam, sire, and dam by sire.

Usage

```
JackGlmer(observ, dam, sire, response, fam_link, quasi = F, size = 1, first = NULL)
```

Arguments

<code>observ</code>	Data frame of observed data.
<code>dam</code>	Column name containing dam (female) parent identity information.
<code>sire</code>	Column name containing sire (male) parent identity information.
<code>response</code>	Column name containing the offspring (response) phenotype values.
<code>fam_link</code>	The family and link in family(link) format. Supported options are <code>binomial(link="logit")</code> , <code>binomial(link="probit")</code> , <code>poisson(link="log")</code> , and <code>poisson(link="sqrt")</code> .
<code>quasi</code>	Incorporate overdispersion or quasi-error structure.
<code>size</code>	Default is 1 for delete-one jackknife resampling. If <code>size > 1</code> , delete- <i>d</i> jackknife resampling occurs removing a block <i>d</i> equal to <code>size</code> .
<code>first</code>	Number of initial sub-samples to run. Useful for examining if there is variation among sub-samples before jackknife resampling the entire data set. There can be little variation for delete-one jackknife resampling with large data sets, and delete- <i>d</i> jackknife resampling should be considered.

Details

Uses delete-one jackknife resampling (Efron & Tibshirani 1993, p. 141-145). For the option of delete-*d* jackknife resampling, the rows of the observed data frame are shuffled and a block of observations of size *d* is deleted sequentially. Laplace approximation parameter estimation is used, which is a true likelihood method (Bolker et al. 2009). For the overdispersion option, an observation-level random effect is added to the model (Atkins et al. 2013). Extracts the dam, sire, dam, and dam by sire variance components. The residual variance component for the *fam_links* are described by Nakagawa and Schielzeth (2010, 2013). Calculates the total variance component. Calculates the additive genetic, non-additive genetic, and maternal variance components (see Lynch and Walsh 1998, p. 603).

Value

A data frame with columns containing the raw variance components for dam, sire, dam by sire, residual, total, additive genetic, non-additive genetic, and maternal. The number of rows in the data frame matches the total number of observations (N) for delete-one jackknife resampling or M groups for delete- d jackknife resampling to the lowest integer. Each row represents a deleted single observation or deleted d observations group.

Note

The Laplace approximation is used because there were fewer disadvantages relative to penalized quasi-likelihood and Gauss-Hermite quadrature parameter estimation (Bolker et al. 2009). That is, penalized quasi-likelihood is not recommended for count responses with means less than 5 and binary responses with less than 5 successes per group. Gauss-Hermite quadrature is not recommended for more than two or three random effects because of the rapidly declining analytical speed with the increasing number of random effects.

References

- Atkins DC, Baldwin SA, Zheng C, Gallop RJ, Neighbors C. 2013. A tutorial on count regression and zero-altered count models for longitudinal substance use data. *Psychology of Addictive Behaviors* 27(1): 166-177. DOI: 10.1037/a0029508
- Bolker BM, Brooks ME, Clark CJ, Geange SW, Poulsen JR, Stevens MHH, White J-SS. 2009. Generalized linear mixed models: a practical guide for ecology and evolution. *Trends in Ecology and Evolution* 24(3): 127-135. DOI: 10.1016/j.tree.2008.10.008
- Efron B, Tibshirani R. 1993. *An introduction to the Bootstrap*. Chapman and Hall, New York.
- Lynch M, Walsh B. 1998. *Genetics and Analysis of Quantitative Traits*. Sinauer Associates, Massachusetts.
- Nakagawa S, Schielzeth H. 2010. Repeatability for Gaussian and non-Gaussian data: a practical guide for biologists. *Biological Reviews* 85(4): 935-956. DOI: 10.1111/j.1469-185X.2010.00141.x
- Nakagawa S, Schielzeth H. 2013. A general and simple method for obtaining R^2 from generalized linear mixed-effects models. *Methods in Ecology and Evolution* 4(2): 133-142. DOI: 10.1111/j.2041-210x.2012.00261.x

See Also

[JackGlmer2](#), [JackGlmer3](#)

Examples

```
data(chinook_survival) #Chinook salmon offspring survival
## Convert replicate-level recorded data to individual-level (binary) data
chinook_survival2<- buildBinary(dat=chinook_survival,copy=c(1:6,9),one="alive",zero="dead")

#Delete-one
## Not run: survival_jack1<- JackGlmer(observ=chinook_survival2,dam="dam",sire="sire",
response="status",fam_link=binomial(link="logit"))
## End(Not run)
```

```
#Delete-d, d=30
## Not run: survival_jack1.2<- JackGlmer(observ=chinook_survival2,dam="dam",sire="sire",
response="status",fam_link=binomial(link="logit"),size=30)
## End(Not run)
```

 JackGlmer2

Jackknife components for non-normal data 2

Description

Extracts additive genetic, non-additive genetic, and maternal variance components from a linear mixed-effect model using the *lmer* function of the *lme4* package. Model random effects are dam, sire, and dam by sire. Options to include one random position and/or one random block effect(s).

Usage

```
JackGlmer2(observ, dam, sire, response, fam_link, position = NULL, block = NULL,
quasi = F, size = 1, first = NULL)
```

Arguments

observ	Data frame of observed data.
dam	Column name containing dam (female) parent identity information.
sire	Column name containing sire (male) parent identity information.
response	Column name containing the offspring (response) phenotype values
.	
fam_link	The family and link in family(link) format. Supported options are binomial(link="logit"), binomial(link="probit"), poisson(link="log"), and poisson(link="sqrt").
position	Optional column name containing position factor information.
block	Optional column name containing block factor information.
quasi	Incorporate overdispersion or quasi-error structure.
size	Default is 1 for delete-one jackknife resampling. If <i>size</i> > 1, delete- <i>d</i> jackknife resampling occurs removing a block <i>d</i> equal to <i>size</i> .
first	Number of initial sub-samples to run. Useful for examining if there is variation among sub-samples before jackknife resampling the entire data set. There can be little variation for delete-one jackknife resampling with large data sets, and delete- <i>d</i> jackknife resampling should be considered.

Details

Uses delete-one jackknife resampling (Efron & Tibshirani 1993, p. 141-145). For the option of delete- d jackknife resampling, the rows of the observed data frame are shuffled and a block of observations of size d is deleted sequentially. Laplace approximation parameter estimation is used, which is a true likelihood method (Bolker et al. 2009). For the overdispersion option, an observation-level random effect is added to the model (Atkins et al. 2013). Extracts the dam, sire, dam, and dam by sire variance components. Extracts optional position and block variance components. The residual variance component for the *fam_links* are described by Nakagawa and Schielzeth (2010, 2013). Calculates the total variance component. Calculates the additive genetic, non-additive genetic, and maternal variance components (see Lynch and Walsh 1998, p. 603).

Value

A data frame with columns containing the raw variance components for dam, sire, dam by sire, residual, total, additive genetic, non-additive genetic, and maternal. Also columns containing the raw variance components for the options of position and/or block. The number of rows in the data frame matches the total number of observations (N) for delete-one jackknife resampling or M groups for delete- d jackknife resampling to the lowest integer. Each row represents a deleted single observation or deleted d observations group.

Note

The Laplace approximation is used because there were fewer disadvantages relative to penalized quasi-likelihood and Gauss-Hermite quadrature parameter estimation (Bolker et al. 2009). That is, penalized quasi-likelihood is not recommended for count responses with means less than 5 and binary responses with less than 5 successes per group. Gauss-Hermite quadrature is not recommended for more than two or three random effects because of the rapidly declining analytical speed with the increasing number of random effects.

References

- Atkins DC, Baldwin SA, Zheng C, Gallop RJ, Neighbors C. 2013. A tutorial on count regression and zero-altered count models for longitudinal substance use data. *Psychology of Addictive Behaviors* 27(1): 166-177. DOI: 10.1037/a0029508
- Bolker BM, Brooks ME, Clark CJ, Geange SW, Poulsen JR, Stevens MHH, White J-SS. 2009. Generalized linear mixed models: a practical guide for ecology and evolution. *Trends in Ecology and Evolution* 24(3): 127-135. DOI: 10.1016/j.tree.2008.10.008
- Efron B, Tibshirani R. 1993. *An introduction to the Bootstrap*. Chapman and Hall, New York.
- Lynch M, Walsh B. 1998. *Genetics and Analysis of Quantitative Traits*. Sinauer Associates, Massachusetts.
- Nakagawa S, Schielzeth H. 2010. Repeatability for Gaussian and non-Gaussian data: a practical guide for biologists. *Biological Reviews* 85(4): 935-956. DOI: 10.1111/j.1469-185X.2010.00141.x
- Nakagawa S, Schielzeth H. 2013. A general and simple method for obtaining R^2 from generalized linear mixed-effects models. *Methods in Ecology and Evolution* 4(2): 133-142. DOI: 10.1111/j.2041-210x.2012.00261.x

See Also

[JackGlmer](#), [JackGlmer3](#)

Examples

```
data(chinook_survival) #Chinook salmon offspring survival
## Convert replicate-level recorded data to individual-level (binary) data
chinook_survival2<- buildBinary(dat=chinook_survival,copy=c(1:6,9),one="alive",zero="dead")

#Delete-one
## Not run: survival_jack2<- JackGlmer2(observ=chinook_survival2,dam="dam",sire="sire",
response="status",fam_link=binomial(link="logit"),position="tray")
## End(Not run)

#Delete-d, d=30
## Not run: survival_jack2.2<- JackGlmer2(observ=chinook_survival2,dam="dam",sire="sire",
response="status",fam_link=binomial(link="logit"),position="tray",size=30)
## End(Not run)
```

JackGlmer3

Jackknife components for non-normal data 3

Description

Extracts additive genetic, non-additive genetic, and maternal variance components from a linear mixed-effect model using the *lmer* function of the *lme4* package. Model random effects are dam, sire, dam by sire, and any additional fixed and/or random effects.

Usage

```
JackGlmer3(observ, dam, sire, response, fam_link, remain, quasi = F, size = 1,
first = NULL)
```

Arguments

observ	Data frame of observed data.
dam	Column name containing dam (female) parent identity information.
sire	Column name containing sire (male) parent identity information.
response	Column name containing the offspring (response) phenotype values.
fam_link	The family and link in family(link) format. Supported options are binomial(link="logit"), binomial(link="probit"), poisson(link="log"), and poisson(link="sqrt").
remain	Remaining formula using <i>lme4</i> package formula.
quasi	Incorporate overdispersion or quasi-error structure.
size	Default is 1 for delete-one jackknife resampling. If <i>size</i> > 1, delete- <i>d</i> jackknife resampling occurs removing a block <i>d</i> equal to <i>size</i> .

first Number of initial sub-samples to run. Useful for examining if there is variation among sub-samples before jackknife resampling the entire data set. There can be little variation for delete-one jackknife resampling with large data sets, and delete- d jackknife resampling should be considered.

Details

Uses delete-one jackknife resampling (Efron & Tibshirani 1993, p. 141-145). For the option of delete- d jackknife resampling, the rows of the observed data frame are shuffled and a block of observations of size d is deleted sequentially. Laplace approximation parameter estimation is used, which is a true likelihood method (Bolker et al. 2009). For the overdispersion option, an observation-level random effect is added to the model (Atkins et al. 2013). Extracts the dam, sire, dam by sire variance components. Extracts any additional fixed effect and random effect variance components. The fixed-effect variance component is as a single group using the method described by Nakagawa and Schielzeth (2013). The residual variance component for the *fam_links* are described by Nakagawa and Schielzeth (2010, 2013). Calculates the total variance component. Calculates the additive genetic, non-additive genetic, and maternal variance components (see Lynch and Walsh 1998, p. 603).

Value

A data frame with columns containing the raw variance components for dam, sire, dam by sire, residual, total, additive genetic, non-additive genetic, and maternal. Also columns containing the raw variance components for remaining formula components. The number of rows in the data frame matches the total number of observations (N) for delete-one jackknife resampling or M groups for delete- d jackknife resampling to the lowest integer. Each row represents a deleted single observation or deleted d observations group.

Note

The Laplace approximation is used because there were fewer disadvantages relative to penalized quasi-likelihood and Gauss-Hermite quadrature parameter estimation (Bolker et al. 2009). That is, penalized quasi-likelihood is not recommended for count responses with means less than 5 and binary responses with less than 5 successes per group. Gauss-Hermite quadrature is not recommended for more than two or three random effects because of the rapidly declining analytical speed with the increasing number of random effects.

References

- Atkins DC, Baldwin SA, Zheng C, Gallop RJ, Neighbors C. 2013. A tutorial on count regression and zero-altered count models for longitudinal substance use data. *Psychology of Addictive Behaviors* 27(1): 166-177. DOI: 10.1037/a0029508
- Bolker BM, Brooks ME, Clark CJ, Geange SW, Poulsen JR, Stevens MHH, White J-SS. 2009. Generalized linear mixed models: a practical guide for ecology and evolution. *Trends in Ecology and Evolution* 24(3): 127-135. DOI: 10.1016/j.tree.2008.10.008
- Efron B, Tibshirani R. 1993. *An introduction to the Bootstrap*. Chapman and Hall, New York.
- Lynch M, Walsh B. 1998. *Genetics and Analysis of Quantitative Traits*. Sinauer Associates, Massachusetts.

Nakagawa S, Schielzeth H. 2010. Repeatability for Gaussian and non-Gaussian data: a practical guide for biologists. *Biological Reviews* 85(4): 935-956. DOI: 10.1111/j.1469-185X.2010.00141.x

Nakagawa S, Schielzeth H. 2013. A general and simple method for obtaining R² from generalized linear mixed-effects models. *Methods in Ecology and Evolution* 4(2): 133-142. DOI: 10.1111/j.2041-210x.2012.00261.x

See Also

[JackGlmmer](#), [JackGlmmer2](#)

Examples

```
data(chinook_survival) #Chinook salmon offspring survival
## Convert replicate-level recorded data to individual-level (binary) data
chinook_survival2<- buildBinary(dat=chinook_survival,copy=c(1:6,9),one="alive",zero="dead")

#Delete-one
## Not run: survival_jack3<- JackGlmmer3(observ=chinook_survival2,dam="dam",sire="sire",
response="status",fam_link=binomial(link="logit"),remain="egg_size + (1|tray)")
## End(Not run)

#Delete-d, d=30
## Not run: survival_jack3.2<- JackGlmmer3(observ=chinook_survival2,dam="dam",sire="sire",
response="status",fam_link=binomial(link="logit"),remain="egg_size + (1|tray)",size=30)
## End(Not run)
```

JackLmer

Jackknife components for normal data

Description

Extracts additive genetic, non-additive genetic, and maternal variance components from a linear mixed-effect model using the *lmer* function of the *lme4* package. Model random effects are dam, sire, and dam by sire.

Usage

```
JackLmer(observ, dam, sire, response, ml = F, size = 1, first = NULL)
```

Arguments

observ	Data frame of observed data.
dam	Column name containing dam (female) parent identity information.
sire	Column name containing sire (male) parent identity information.
response	Column name containing the offspring (response) phenotype values.
ml	Default is FALSE for restricted maximum likelihood. Change to TRUE for maximum likelihood.

size	Default is 1 for delete-one jackknife resampling. If <i>size</i> > 1, delete- <i>d</i> jackknife resampling occurs removing a block <i>d</i> equal to <i>size</i> .
first	Number of initial sub-samples to run. Useful for examining if there is variation among sub-samples before jackknife resampling the entire data set. There can be little variation for delete-one jackknife resampling with large data sets, and delete- <i>d</i> jackknife resampling should be considered.

Details

Uses delete-one jackknife resampling (Efron & Tibshirani 1993, p. 141-145). For the option of delete-*d* jackknife resampling, the rows of the observed data frame are shuffled and a block of observations of size *d* is deleted sequentially. Extracts the dam, sire, dam, dam by sire, and residual variance components. Calculates the total variance component. Calculates the additive genetic, non-additive genetic, and maternal variance components (see Lynch and Walsh 1998, p. 603).

Value

A data frame with columns containing the raw variance components for dam, sire, dam by sire, residual, total, additive genetic, non-additive genetic, and maternal. The number of rows in the data frame matches the total number of observations (*N*) for delete-one jackknife resampling or *M* groups for delete-*d* jackknife resampling to the lowest integer. Each row represents a deleted single observation or deleted *d* observations group.

Note

Maximum likelihood (ML) estimates the parameters that maximize the likelihood of the observed data and has the advantage of using all the data and accounting for non-independence (Lynch and Walsh 1998, p. 779; Bolker et al. 2009). On the other hand, ML has the disadvantage of assuming that all fixed effects are known without error, producing a downward bias in the estimation of the residual variance component. This bias can be large if there are lots of fixed effects, especially if sample sizes are small. Restricted maximum likelihood (REML) has the advantage of not assuming the fixed effects are known and averages over the uncertainty, so there can be less bias in the estimation of the residual variance component. However, REML only maximizes a portion of the likelihood to estimate the effect parameters, but is the preferred method for analyzing large data sets with complex structure.

References

- Efron B, Tibshirani R. 1993. An introduction to the Bootstrap. Chapman and Hall, New York.
- Lynch M, Walsh B. 1998. Genetics and Analysis of Quantitative Traits. Sinauer Associates, Massachusetts.

See Also

[JackLmer2](#), [JackLmer3](#)

Examples

```
data(chinook_length) #Chinook salmon offspring length

#Delete-one
#length_jack1<- JackLmer(observ=chinook_length,dam="dam",sire="sire",response="length")
length_jack1<- JackLmer(observ=chinook_length,dam="dam",sire="sire",response="length",
first=2) #first 2

#Delete-d, d=5
#length_jackD<- JackLmer(observ=chinook_length,dam="dam",sire="sire",response="length",
#size=5)
length_jackD<- JackLmer(observ=chinook_length,dam="dam",sire="sire",response="length",
size=5,first=2) #first 2
```

JackLmer2

Jackknife components for normal data 2

Description

Extracts additive genetic, non-additive genetic, and maternal variance components from a linear mixed-effect model using the *lmer* function of the *lme4* package. Model random effects are dam, sire, and dam by sire. Options to include one random position and/or one random block effect(s).

Usage

```
JackLmer2(observ, dam, sire, response, position = NULL, block = NULL, ml = F, size = 1,
first = NULL)
```

Arguments

<code>observ</code>	Data frame of observed data.
<code>dam</code>	Column name containing dam (female) parent identity information.
<code>sire</code>	Column name containing sire (male) parent identity information.
<code>response</code>	Column name containing the offspring (response) phenotype values.
<code>position</code>	Optional column name containing position factor information.
<code>block</code>	Optional column name containing block factor information.
<code>ml</code>	Default is FALSE for restricted maximum likelihood. Change to TRUE for maximum likelihood.
<code>size</code>	Default is 1 for delete-one jackknife resampling. If <i>size</i> > 1, delete- <i>d</i> jackknife resampling occurs removing a block <i>d</i> equal to <i>size</i> .
<code>first</code>	Number of initial sub-samples to run. Useful for examining if there is variation among sub-samples before jackknife resampling the entire data set. There can be little variation for delete-one jackknife resampling with large data sets, and delete- <i>d</i> jackknife resampling should be considered.

Details

Uses delete-one jackknife resampling (Efron & Tibshirani 1993, p. 141-145). For the option of delete- d jackknife resampling, the rows of the observed data frame are shuffled and a block of observations of size d is deleted sequentially. Extracts the dam, sire, dam, dam by sire, and residual variance components. Extracts optional position and block variance components. Calculates the total variance component. Calculates the additive genetic, non-additive genetic, and maternal variance components (see Lynch and Walsh 1998, p. 603).

Value

A data frame with columns containing the raw variance components for dam, sire, dam by sire, residual, total, additive genetic, non-additive genetic, and maternal. Also columns containing the raw variance components for the options of position and/or block. The number of rows in the data frame matches the total number of observations (N) for delete-one jackknife resampling or M groups for delete- d jackknife resampling to the lowest integer. Each row represents a deleted single observation or deleted d observations group.

Note

Maximum likelihood (ML) estimates the parameters that maximize the likelihood of the observed data and has the advantage of using all the data and accounting for non-independence (Lynch and Walsh 1998, p. 779; Bolker et al. 2009). On the other hand, ML has the disadvantage of assuming that all fixed effects are known without error, producing a downward bias in the estimation of the residual variance component. This bias can be large if there are lots of fixed effects, especially if sample sizes are small. Restricted maximum likelihood (REML) has the advantage of not assuming the fixed effects are known and averages over the uncertainty, so there can be less bias in the estimation of the residual variance component. However, REML only maximizes a portion of the likelihood to estimate the effect parameters, but is the preferred method for analyzing large data sets with complex structure.

References

- Efron B, Tibshirani R. 1993. An introduction to the Bootstrap. Chapman and Hall, New York.
- Lynch M, Walsh B. 1998. Genetics and Analysis of Quantitative Traits. Sinauer Associates, Massachusetts.

See Also

[JackLmer](#), [JackLmer3](#)

Examples

```
data(chinook_length) #Chinook salmon offspring length

#Delete-one
#length_jack2<- JackLmer2(observ=chinook_length,dam="dam",sire="sire",response="length",
#position="tray")
length_jack2<- JackLmer2(observ=chinook_length,dam="dam",sire="sire",response="length",
position="tray",first=2) #first 2
```

```
#Delete-d, d=5
#length_jack2.2<- JackLmer2(observ=chinook_length,dam="dam",sire="sire",response="length",
#position="tray",size=5)
length_jack2.2<- JackLmer2(observ=chinook_length,dam="dam",sire="sire",response="length",
position="tray",size=5,first=2) #first 2
```

 JackLmer3

Jackknife components for normal data 3

Description

Extracts additive genetic, non-additive genetic, and maternal variance components from a linear mixed-effect model using the *lmer* function of the *lme4* package. Model random effects are dam, sire, dam by sire, and any additional fixed and/or random effects.

Usage

```
JackLmer3(observ, dam, sire, response, remain, ml = F, size = 1, first = NULL)
```

Arguments

<code>observ</code>	Data frame of observed data
<code>dam</code>	Column name containing dam (female) parent identity information.
<code>sire</code>	Column name containing sire (male) parent identity information.
<code>response</code>	Column name containing the offspring (response) phenotype values.
<code>remain</code>	Remaining formula using <i>lme4</i> package format.
<code>ml</code>	Default is FALSE for restricted maximum likelihood. Change to TRUE for maximum likelihood.
<code>size</code>	Default is 1 for delete-one jackknife resampling. If <i>size</i> > 1, delete- <i>d</i> jackknife resampling occurs removing a block <i>d</i> equal to <i>size</i> .
<code>first</code>	Number of initial sub-samples to run. Useful for examining if there is variation among sub-samples before jackknife resampling the entire data set. There can be little variation for delete-one jackknife resampling with large data sets, and delete- <i>d</i> jackknife resampling should be considered.

Details

Uses delete-one jackknife resampling (Efron & Tibshirani 1993, p. 141-145). For the option of delete-*d* jackknife resampling, the rows of the observed data frame are shuffled and a block of observations of size *d* is deleted sequentially. Extracts the dam, sire, dam, dam by sire, and residual variance components. Extracts any additional fixed effect and random effect variance components. The fixed-effect variance component is as a single group using the method described by Nakagawa and Schielzeth (2013). Calculates the total variance component. Calculates the additive genetic, non-additive genetic, and maternal variance components (see Lynch and Walsh 1998, p. 603).

Value

A data frame with columns containing the raw variance components for dam, sire, dam by sire, residual, total, additive genetic, non-additive genetic, and maternal. Also columns containing the raw variance components for remaining formula components. The number of rows in the data frame matches the total number of observations (N) for delete-one jackknife resampling or M groups for delete- d jackknife resampling to the lowest integer. Each row represents a deleted single observation or deleted d observations group.

Note

Maximum likelihood (ML) estimates the parameters that maximize the likelihood of the observed data and has the advantage of using all the data and accounting for non-independence (Lynch and Walsh 1998, p. 779; Bolker et al. 2009). On the other hand, ML has the disadvantage of assuming that all fixed effects are known without error, producing a downward bias in the estimation of the residual variance component. This bias can be large if there are lots of fixed effects, especially if sample sizes are small. Restricted maximum likelihood (REML) has the advantage of not assuming the fixed effects are known and averages over the uncertainty, so there can be less bias in the estimation of the residual variance component. However, REML only maximizes a portion of the likelihood to estimate the effect parameters, but is the preferred method for analyzing large data sets with complex structure.

References

- Efron B, Tibshirani R. 1993. An introduction to the Bootstrap. Chapman and Hall, New York.
- Lynch M, Walsh B. 1998. Genetics and Analysis of Quantitative Traits. Sinauer Associates, Massachusetts.
- Nakagawa S, Schielzeth H. 2013. A general and simple method for obtaining R^2 from generalized linear mixed-effects models. *Methods in Ecology and Evolution* 4(2): 133-142. DOI: 10.1111/j.2041-210x.2012.00261.x

See Also

[JackLmer](#), [JackLmer2](#)

Examples

```
data(chinook_length) #Chinook salmon offspring length

#Delete-one
#length_jack3<- JackLmer3(observ=chinook_length,dam="dam",sire="sire",response="length",
#remain="egg_size + (1|tray)")
length_jack3<- JackLmer3(observ=chinook_length,dam="dam",sire="sire",response="length",
remain="egg_size + (1|tray)",first=2) #first 2

#Delete-d, d=5
#length_jack3.2<- JackLmer3(observ=chinook_length,dam="dam",sire="sire",response="length",
#remain="egg_size + (1|tray)",size=5)
length_jack3.2<- JackLmer3(observ=chinook_length,dam="dam",sire="sire",response="length",
remain="egg_size + (1|tray)",size=5,first=2) #first 2
```

observGlmr	<i>Variance components for non-normal data</i>
------------	--

Description

Extracts additive genetic, non-additive genetic, and maternal variance components from a generalized linear mixed-effect model using the *glmer* function of the *lme4* package. Model random effects are dam, sire, and dam by sire.

Usage

```
observGlmr(observ, dam, sire, response, fam_link, quasi = F)
```

Arguments

observ	Data frame of observed data.
dam	Column name containing dam (female) parent identity information.
sire	Column name containing sire (male) parent identity information.
response	Column name containing the offspring (response) phenotype values.
fam_link	The family and link in family(link) format. Supported options are binomial(link="logit"), binomial(link="probit"), poisson(link="log"), and poisson(link="sqrt").
quasi	Incorporate overdispersion or quasi-error structure.

Details

Laplace approximation parameter estimation is used, which is a true likelihood method (Bolker et al. 2009). For the overdispersion option, an observation-level random effect is added to the model (Atkins et al. 2013). Extracts the dam, sire, dam, and dam by sire variance components. The residual variance component for the *fam_links* are described by Nakagawa and Schielzeth (2010, 2013). Calculates the total variance component. Calculates the additive genetic, non-additive genetic, and maternal variance components (see Lynch and Walsh 1998, p. 603). Significance values for the random effects are determined using likelihood ratio tests (Bolker et al. 2009).

Value

A list object containing the raw variance components, the variance components as a percentage of the total variance component. Also, contains the difference in AIC and BIC, and likelihood ratio test Chi-square and p-value for all random effects.

Note

The Laplace approximation is used because there were fewer disadvantages relative to penalized quasi-likelihood and Gauss-Hermite quadrature parameter estimation (Bolker et al. 2009). That is, penalized quasi-likelihood is not recommended for count responses with means less than 5 and binary responses with less than 5 successes per group. Gauss-Hermite quadrature is not recommended for more than two or three random effects because of the rapidly declining analytical speed with the increasing number of random effects.

References

- Atkins DC, Baldwin SA, Zheng C, Gallop RJ, Neighbors C. 2013. A tutorial on count regression and zero-altered count models for longitudinal substance use data. *Psychology of Addictive Behaviors* 27(1): 166-177. DOI: 10.1037/a0029508
- Bolker BM, Brooks ME, Clark CJ, Geange SW, Poulsen JR, Stevens MHH, White J-SS. 2009. Generalized linear mixed models: a practical guide for ecology and evolution. *Trends in Ecology and Evolution* 24(3): 127-135. DOI: 10.1016/j.tree.2008.10.008
- Lynch M, Walsh B. 1998. *Genetics and Analysis of Quantitative Traits*. Sinauer Associates, Massachusetts.
- Nakagawa S, Schielzeth H. 2010. Repeatability for Gaussian and non-Gaussian data: a practical guide for biologists. *Biological Reviews* 85(4): 935-956. DOI: 10.1111/j.1469-185X.2010.00141.x
- Nakagawa S, Schielzeth H. 2013. A general and simple method for obtaining R² from generalized linear mixed-effects models. *Methods in Ecology and Evolution* 4(2): 133-142. DOI: 10.1111/j.2041-210x.2012.00261.x

See Also

[observGlm2](#), [observGlm3](#)

Examples

```
data(chinook_survival) #Chinook salmon offspring survival
## Convert replicate-level recorded data to individual-level (binary) data
chinook_survival2<- buildBinary(dat=chinook_survival,copy=c(2:6,9),one="alive",zero="dead")
#
## Not run: survival_mod1<- observGlm2(observ=chinook_survival2,dam="dam",sire="sire",
response="status",fam_link=binomial(link="logit")) #a few minutes
survival_mod1
## End(Not run)
```

observGlm2

Variance components for non-normal data 2

Description

Extracts additive genetic, non-additive genetic, and maternal variance components from a generalized linear mixed-effect model using the *glmer* function of the *lme4* package. Model random effects are dam, sire, and dam by sire. Options to include one random position and/or one random block effect(s).

Usage

```
observGlm2(observ, dam, sire, response, fam_link, position = NULL, block = NULL,
quasi = F)
```

Arguments

observ	Data frame of observed data.
dam	Column name containing dam (female) parent identity information.
sire	Column name containing sire (male) parent identity information.
response	Column name containing the offspring (response) phenotype values.
fam_link	The family and link in family(link) format. Supported options are binomial(link="logit"), binomial(link="probit"), poisson(link="log"), and poisson(link="sqrt").
position	Optional column name containing position factor information.
block	Optional column name containing block factor information.
quasi	Incorporate overdispersion or quasi-error structure.

Details

Laplace approximation parameter estimation is used, which is a true likelihood method (Bolker et al. 2009). For the overdispersion option, an observation-level random effect is added to the model (Atkins et al. 2013). Extracts the dam, sire, dam, and dam by sire variance components. Extracts optional position and block variance components. The residual variance component for the *fam_links* are described by Nakagawa and Schielzeth (2010, 2013). Calculates the total variance component. Calculates the additive genetic, non-additive genetic, and maternal variance components (see Lynch and Walsh 1998, p. 603). Significance values for the random effects are determined using likelihood ratio tests (Bolker et al. 2009).

Value

A list object containing the raw variance components, the variance components as a percentage of the total variance component. Also, contains the difference in AIC and BIC, and likelihood ratio test Chi-square and p-value for all random effects.

Note

The Laplace approximation is used because there were fewer disadvantages relative to penalized quasi-likelihood and Gauss-Hermite quadrature parameter estimation (Bolker et al. 2009). That is, penalized quasi-likelihood is not recommended for count responses with means less than 5 and binary responses with less than 5 successes per group. Gauss-Hermite quadrature is not recommended for more than two or three random effects because of the rapidly declining analytical speed with the increasing number of random effects.

References

- Atkins DC, Baldwin SA, Zheng C, Gallop RJ, Neighbors C. 2013. A tutorial on count regression and zero-altered count models for longitudinal substance use data. *Psychology of Addictive Behaviors* 27(1): 166-177. DOI: 10.1037/a0029508
- Bolker BM, Brooks ME, Clark CJ, Geange SW, Poulsen JR, Stevens MHH, White J-SS. 2009. Generalized linear mixed models: a practical guide for ecology and evolution. *Trends in Ecology and Evolution* 24(3): 127-135. DOI: 10.1016/j.tree.2008.10.008

Lynch M, Walsh B. 1998. Genetics and Analysis of Quantitative Traits. Sinauer Associates, Massachusetts.

Nakagawa S, Schielzeth H. 2010. Repeatability for Gaussian and non-Gaussian data: a practical guide for biologists. *Biological Reviews* 85(4): 935-956. DOI: 10.1111/j.1469-185X.2010.00141.x

Nakagawa S, Schielzeth H. 2013. A general and simple method for obtaining R² from generalized linear mixed-effects models. *Methods in Ecology and Evolution* 4(2): 133-142. DOI: 10.1111/j.2041-210x.2012.00261.x

See Also

[observGlm](#), [observGlm3](#)

Examples

```
data(chinook_survival) #Chinook salmon offspring survival
## Convert replicate-level recorded data to individual-level (binary) data
chinook_survival2<- buildBinary(dat=chinook_survival,copy=c(2:6,9),one="alive",zero="dead")
#
## Not run: survival_mod2<- observGlm2(observ=chinook_survival2,dam="dam",sire="sire",
response="status",fam_link=binomial(link="logit"),position="tray") #a few minutes
survival_mod2
## End(Not run)
```

observGlm3

Variance components for non-normal data 3

Description

Extracts additive genetic, non-additive genetic, and maternal variance components from a generalized linear mixed-effect model using the *glmer* function of the *lme4* package. Model random effects are dam, sire, dam by sire, and any additional fixed and/or random effects.

Usage

```
observGlm3(observ, dam, sire, response, fam_link, remain, quasi = F, iter = 1000)
```

Arguments

observ	Data frame of observed data.
dam	Column name containing dam (female) parent identity information.
sire	Column name containing sire (male) parent identity information.
response	Column name containing the offspring (response) phenotype values.
fam_link	The family and link in family(link) format. Supported options are binomial(link="logit"), binomial(link="probit"), poisson(link="log"), and poisson(link="sqrt").
remain	Remaining formula using <i>lme4</i> package format.
quasi	Incorporate overdispersion or quasi-error structure.
iter	Number of iterations for computing the parametric bootstrap significance value for any fixed effects.

Details

Laplace approximation parameter estimation is used, which is a true likelihood method (Bolker et al. 2009). For the overdispersion option, an observation-level random effect is added to the model (Atkins et al. 2013). Extracts the dam, sire, dam, and dam by sire variance components. Extracts any additional fixed effect and random effect variance components. The fixed-effect variance component is as a single group using the method described by Nakagawa and Schielzeth (2013). The residual variance component for the *fam_links* are described by Nakagawa and Schielzeth (2010, 2013). Calculates the total variance component. Calculates the additive genetic, non-additive genetic, and maternal variance components (see Lynch and Walsh 1998, p. 603). Significance values for the random effects are determined using likelihood ratio tests (Bolker et al. 2009). Significance values for any fixed effects are determined using likelihood ratio tests and a parametric bootstrap method (Bolker et al. 2009) from the *mixed* function of the *afex* package.

Value

A list object containing the raw variance components, the variance components as a percentage of the total variance component. Contains the difference in AIC and BIC, likelihood ratio test Chi-square and p-value for random and/or fixed effects. Also contains the parametric bootstrap Chi-square and p-value for any fixed effects.

Note

The Laplace approximation is used because there were fewer disadvantages relative to penalized quasi-likelihood and Gauss-Hermite quadrature parameter estimation (Bolker et al. 2009). That is, penalized quasi-likelihood is not recommended for count responses with means less than 5 and binary responses with less than 5 successes per group. Gauss-Hermite quadrature is not recommended for more than two or three random effects because of the rapidly declining analytical speed with the increasing number of random effects.

References

- Atkins DC, Baldwin SA, Zheng C, Gallop RJ, Neighbors C. 2013. A tutorial on count regression and zero-altered count models for longitudinal substance use data. *Psychology of Addictive Behaviors* 27(1): 166-177. DOI: 10.1037/a0029508
- Bolker BM, Brooks ME, Clark CJ, Geange SW, Poulsen JR, Stevens MHH, White J-SS. 2009. Generalized linear mixed models: a practical guide for ecology and evolution. *Trends in Ecology and Evolution* 24(3): 127-135. DOI: 10.1016/j.tree.2008.10.008
- Lynch M, Walsh B. 1998. *Genetics and Analysis of Quantitative Traits*. Sinauer Associates, Massachusetts.
- Nakagawa S, Schielzeth H. 2010. Repeatability for Gaussian and non-Gaussian data: a practical guide for biologists. *Biological Reviews* 85(4): 935-956. DOI: 10.1111/j.1469-185X.2010.00141.x
- Nakagawa S, Schielzeth H. 2013. A general and simple method for obtaining R² from generalized linear mixed-effects models. *Methods in Ecology and Evolution* 4(2): 133-142. DOI: 10.1111/j.2041-210x.2012.00261.x

See Also

[observGlmr](#), [observGlmr2](#)

Examples

```
data(chinook_survival) #Chinook salmon offspring survival
## Convert replicate-level recorded data to individual-level (binary) data
chinook_survival2<- buildBinary(dat=chinook_survival,copy=c(2:6,9),one="alive",zero="dead")
#just a few iterations for the p-value of fixed effect
## Not run: survival_mod3<- observGlm3(observ=chinook_survival2,dam="dam",sire="sire",
response="status",fam_link=binomial(link="logit"),remain="egg_size + (1|tray)",iter=5)
survival_mod3
## End(Not run)
```

 observLmer

Variance components for normal data

Description

Extracts additive genetic, non-additive genetic, and maternal variance components from a linear mixed-effect model using the *lmer* function of the *lme4* package. Model random effects are dam, sire, and dam by sire.

Usage

```
observLmer(observ, dam, sire, response, ml = F)
```

Arguments

observ	Data frame of observed data.
dam	Column name containing dam (female) parent identity information.
sire	Column name containing sire (male) parent identity information.
response	Column name containing the offspring (response) phenotype values.
ml	Default is FALSE for restricted maximum likelihood. Change to TRUE for maximum likelihood.

Details

Extracts the dam, sire, dam, dam by sire, and residual variance components. Calculates the total variance component. Calculates the additive genetic, non-additive genetic, and maternal variance components (see Lynch and Walsh 1998, p. 603). Significance values for the random effects are determined using likelihood ratio tests (Bolker et al. 2009).

Value

A list object containing the raw variance components, the variance components as a percentage of the total variance component. Also, contains the difference in AIC and BIC, and likelihood ratio test Chi-square and p-value for all random effects.

Note

Maximum likelihood (ML) estimates the parameters that maximize the likelihood of the observed data and has the advantage of using all the data and accounting for non-independence (Lynch and Walsh 1998, p. 779; Bolker et al. 2009). On the other hand, ML has the disadvantage of assuming that all fixed effects are known without error, producing a downward bias in the estimation of the residual variance component. This bias can be large if there are lots of fixed effects, especially if sample sizes are small. Restricted maximum likelihood (REML) has the advantage of not assuming the fixed effects are known and averages over the uncertainty, so there can be less bias in the estimation of the residual variance component. However, REML only maximizes a portion of the likelihood to estimate the effect parameters, but is the preferred method for analyzing large data sets with complex structure.

References

Bolker BM, Brooks ME, Clark CJ, Geange SW, Poulsen JR, Stevens MHH, White J-SS. 2009. Generalized linear mixed models: a practical guide for ecology and evolution. *Trends in Ecology and Evolution* 24(3): 127-135. DOI: 10.1016/j.tree.2008.10.008

Lynch M, Walsh B. 1998. *Genetics and Analysis of Quantitative Traits*. Sinauer Associates, Massachusetts.

See Also

[observLmer2](#), [observLmer3](#)

Examples

```
data(chinook_length) #Chinook salmon offspring length
length_mod1<- observLmer(observ=chinook_length,dam="dam",sire="sire",response="length")
length_mod1
```

observLmer2

Variance components for normal data 2

Description

Extracts additive genetic, non-additive genetic, and maternal variance components from a linear mixed-effect model using the *lmer* function of the *lme4* package. Model random effects are dam, sire, and dam by sire. Options to include one random position and/or one random block effect(s).

Usage

```
observLmer2(observ, dam, sire, response, position = NULL, block = NULL, ml = F)
```

Arguments

observ	Data frame of observed data.
dam	Column name containing dam (female) parent identity information.
sire	Column name containing sire (male) parent identity information.
response	Column name containing the offspring (response) phenotype values.
position	Optional column name containing position factor information.
block	Optional column name containing block factor information.
ml	Default is FALSE for restricted maximum likelihood. Change to TRUE for maximum likelihood.

Details

Extracts the dam, sire, dam, dam by sire, and residual variance components. Extracts optional position and block variance components. Calculates the total variance component. Calculates the additive genetic, non-additive genetic, and maternal variance components (see Lynch and Walsh 1998, p. 603). Significance values for the random effects are determined using likelihood ratio tests (Bolker et al. 2009).

Value

A list object containing the raw variance components, the variance components as a percentage of the total variance component. Also, contains the difference in AIC and BIC, and likelihood ratio test Chi-square and p-value for all random effects.

Note

Maximum likelihood (ML) estimates the parameters that maximize the likelihood of the observed data and has the advantage of using all the data and accounting for non-independence (Lynch and Walsh 1998, p. 779; Bolker et al. 2009). On the other hand, ML has the disadvantage of assuming that all fixed effects are known without error, producing a downward bias in the estimation of the residual variance component. This bias can be large if there are lots of fixed effects, especially if sample sizes are small. Restricted maximum likelihood (REML) has the advantage of not assuming the fixed effects are known and averages over the uncertainty, so there can be less bias in the estimation of the residual variance component. However, REML only maximizes a portion of the likelihood to estimate the effect parameters, but is the preferred method for analyzing large data sets with complex structure.

References

- Bolker BM, Brooks ME, Clark CJ, Geange SW, Poulsen JR, Stevens MHH, White J-SS. 2009. Generalized linear mixed models: a practical guide for ecology and evolution. *Trends in Ecology and Evolution* 24(3): 127-135. DOI: 10.1016/j.tree.2008.10.008
- Lynch M, Walsh B. 1998. *Genetics and Analysis of Quantitative Traits*. Sinauer Associates, Massachusetts.

See Also

[observLmer](#), [observLmer3](#)

Examples

```
data(chinook_length) #Chinook salmon offspring length
length_mod2<- observLmer2(observ=chinook_length,dam="dam",sire="sire",response="length",
position="tray")
length_mod2
```

observLmer3

Variance components for normal data 3

Description

Extracts additive genetic, non-additive genetic, and maternal variance components from a linear mixed-effect model using the *lmer* function of the *lme4* package. Model random effects are dam, sire, dam by sire, and any additional fixed and/or random effects.

Usage

```
observLmer3(observ, dam, sire, response, remain, ml = F, iter = 1000)
```

Arguments

observ	Data frame of observed data.
dam	Column name containing dam (female) parent identity information.
sire	Column name containing sire (male) parent identity information.
response	Column name containing the offspring (response) phenotype values.
remain	Remaining formula using <i>lme4</i> package format.
ml	Default is FALSE for restricted maximum likelihood. Change to TRUE for maximum likelihood.
iter	Number of iterations for computing the parametric bootstrap significance value for any fixed effects.

Details

Extracts the dam, sire, dam, dam by sire, and residual variance components. Extracts any additional fixed effect and random effect variance components. The fixed-effect variance component is as a single group using the method described by Nakagawa and Schielzeth (2013). Calculates the total variance component. Calculates the additive genetic, non-additive genetic, and maternal variance components (see Lynch and Walsh 1998, p. 603). Significance values for the random effects are determined using likelihood ratio tests (Bolker et al. 2009). Significance values for any fixed effects are determined using likelihood ratio tests and a parametric bootstrap method (Bolker et al. 2009) from the *mixed* function of the *afex* package.

Value

A list object containing the raw variance components, the variance components as a percentage of the total variance component. Contains the difference in AIC and BIC, likelihood ratio test Chi-square and p-value for random and/or fixed effects. Also contains the parametric bootstrap Chi-square and p-value for any fixed effects.

Note

Maximum likelihood (ML) estimates the parameters that maximize the likelihood of the observed data and has the advantage of using all the data and accounting for non-independence (Lynch and Walsh 1998, p. 779; Bolker et al. 2009). On the other hand, ML has the disadvantage of assuming that all fixed effects are known without error, producing a downward bias in the estimation of the residual variance component. This bias can be large if there are lots of fixed effects, especially if sample sizes are small. Restricted maximum likelihood (REML) has the advantage of not assuming the fixed effects are known and averages over the uncertainty, so there can be less bias in the estimation of the residual variance component. However, REML only maximizes a portion of the likelihood to estimate the effect parameters, but is the preferred method for analyzing large data sets with complex structure.

References

Bolker BM, Brooks ME, Clark CJ, Geange SW, Poulsen JR, Stevens MHH, White J-SS. 2009. Generalized linear mixed models: a practical guide for ecology and evolution. *Trends in Ecology and Evolution* 24(3): 127-135. DOI: 10.1016/j.tree.2008.10.008

Lynch M, Walsh B. 1998. *Genetics and Analysis of Quantitative Traits*. Sinauer Associates, Massachusetts.

Nakagawa S, Schielzeth H. 2013. A general and simple method for obtaining R² from generalized linear mixed-effects models. *Methods in Ecology and Evolution* 4(2): 133-142. DOI: 10.1111/j.2041-210x.2012.00261.x

See Also

[observLmer](#), [observLmer2](#)

Examples

```
data(chinook_length) #Chinook salmon offspring length
#just a few iterations for the p-value of fixed effect
length_mod3<- observLmer3(observ=chinook_length,dam="dam",sire="sire",response="length",
remain="egg_size + (1|tray)",iter=5)
length_mod3
```

powerGlmr

*Power analysis for non-normal data***Description**

Extracts the power values of dam, sire, and dam by sire variance components from a generalized linear mixed-effect model using the *glmer* function of the *lme4* package.

Usage

```
powerGlmr(varcomp, nval, fam_link, alpha = 0.05, nsim = 100, poisLog = NULL)
```

Arguments

varcomp	Vector of known dam, sire, and dam by sire variance components, i.e. c(dam, sire, dam x sire).
nval	Vector of known dam, sire, and offspring per family sample sizes, i.e. c(dam, sire, offspring).
fam_link	The family and link in family(link) format. Supported options are binomial(link="logit"), binomial(link="probit"), poisson(link="log"), and poisson(link="sqrt").
alpha	Statistical significance value. Default is 0.05.
nsim	Number of simulations. Default is 100.
poisLog	The residual variance component value if using poisson(link="log").

Details

Extracts the dam, sire, dam, and dam by sire power values. The residual variance component for the *fam_links* are described by Nakagawa and Schielzeth (2010, 2013). Power values are calculated by stochastically simulation data and then calculating the proportion of significance values less than *alpha* for each component (Bolker 2008). Significance values for the random effects are determined using likelihood ratio tests (Bolker et al. 2009).

Value

Prints a data frame with the sample sizes, variance component inputs, variance component outputs, and power values.

Note

The Laplace approximation is used because there were fewer disadvantages relative to penalized quasi-likelihood and Gauss-Hermite quadrature parameter estimation (Bolker et al. 2009). That is, penalized quasi-likelihood is not recommended for count responses with means less than 5 and binary responses with less than 5 successes per group. Gauss-Hermite quadrature is not recommended for more than two or three random effects because of the rapidly declining analytical speed with the increasing number of random effects.

References

- Bolker BM. 2008. Ecological models and data in R. Princeton University Press, New Jersey.
- Bolker BM, Brooks ME, Clark CJ, Geange SW, Poulsen JR, Stevens MHH, White J-SS. 2009. Generalized linear mixed models: a practical guide for ecology and evolution. *Trends in Ecology and Evolution* 24(3): 127-135. DOI: 10.1016/j.tree.2008.10.008
- Lynch M, Walsh B. 1998. *Genetics and Analysis of Quantitative Traits*. Sinauer Associates, Massachusetts.
- Nakagawa S, Schielzeth H. 2010. Repeatability for Gaussian and non-Gaussian data: a practical guide for biologists. *Biological Reviews* 85(4): 935-956. DOI: 10.1111/j.1469-185X.2010.00141.x
- Nakagawa S, Schielzeth H. 2013. A general and simple method for obtaining R² from generalized linear mixed-effects models. *Methods in Ecology and Evolution* 4(2): 133-142. DOI: 10.1111/j.2041-210x.2012.00261.x

See Also

[powerGlm2](#), [powerGlm3](#)

Examples

```
#100 simulations
## Not run: powerGlm2(varcomp=c(0.7930,0.1664,0.1673),nval=c(11,11,300),
fam_link=binomial(link="logit"))
## End(Not run)
```

powerGlm2

Power analysis for non-normal data 2

Description

Extracts the power values of dam, sire, and dam by sire variance components from a generalized linear mixed-effect model using the *glmer* function of the *lme4* package. Options to include one random position and/or one random block effect(s).

Usage

```
powerGlm2(varcomp, nval, fam_link, alpha = 0.05, nsim = 100, position = NULL,
block = NULL, poisLog = NULL)
```

Arguments

- | | |
|---------|--|
| varcomp | Vector of known dam, sire, dam by sire, and position and/or block variance components, i.e. c(dam, sire, dam x sire, position/block). If there is a position and a block c(..., dam x sire, position, block). |
| nval | Vector of known dam, sire, offspring per family, and offspring per position or number of blocks sample sizes, i.e. c(dam, sire, offspring, position/block). If there is a position and a block c(..., offspring, position, block). |

fam_link	The family and link in family(link) format. Supported options are binomial(link="logit"), binomial(link="probit"), poisson(link="log"), and poisson(link="sqrt").
alpha	Statistical significance value. Default is 0.05.
nsim	Number of simulations. Default is 100.
position	Optional number of positions.
block	Optional vector of dams and sires per block, e.g. c(2,2).
poisLog	The residual variance component value if using poisson(link="log").

Details

Extracts the dam, sire, dam, dam by sire, and position and/or block power values. The residual variance component for the *fam_links* are described by Nakagawa and Schielzeth (2010, 2013). Power values are calculated by stochastically simulation data and then calculating the proportion of significance values less than *alpha* for each component (Bolker 2008). Significance values for the random effects are determined using likelihood ratio tests (Bolker et al. 2009).

Value

Prints a data frame with the sample sizes, variance component inputs, variance component outputs, and power values.

Note

The Laplace approximation is used because there were fewer disadvantages relative to penalized quasi-likelihood and Gauss-Hermite quadrature parameter estimation (Bolker et al. 2009). That is, penalized quasi-likelihood is not recommended for count responses with means less than 5 and binary responses with less than 5 successes per group. Gauss-Hermite quadrature is not recommended for more than two or three random effects because of the rapidly declining analytical speed with the increasing number of random effects.

References

- Bolker BM. 2008. Ecological models and data in R. Princeton University Press, New Jersey.
- Bolker BM, Brooks ME, Clark CJ, Geange SW, Poulsen JR, Stevens MHH, White J-SS. 2009. Generalized linear mixed models: a practical guide for ecology and evolution. *Trends in Ecology and Evolution* 24(3): 127-135. DOI: 10.1016/j.tree.2008.10.008
- Lynch M, Walsh B. 1998. Genetics and Analysis of Quantitative Traits. Sinauer Associates, Massachusetts.
- Nakagawa S, Schielzeth H. 2010. Repeatability for Gaussian and non-Gaussian data: a practical guide for biologists. *Biological Reviews* 85(4): 935-956. DOI: 10.1111/j.1469-185X.2010.00141.x
- Nakagawa S, Schielzeth H. 2013. A general and simple method for obtaining R² from generalized linear mixed-effects models. *Methods in Ecology and Evolution* 4(2): 133-142. DOI: 10.1111/j.2041-210x.2012.00261.x

See Also

[powerGlm](#), [powerGlm3](#)

Examples

```
#100 simulations
## Not run: powerGlmer2(varcomp=c(0.7880,0.1667,0.1671,0.0037),nval=c(11,11,300,3300),
position=11,fam_link=binomial(link="logit"))
## End(Not run)
```

powerGlmer3

Power analysis for non-normal data 3

Description

Extracts the power values of dam, sire, and dam by sire variance components from a generalized linear mixed-effect model using the *glmer* function of the *lme4* package. Model can include additional fixed and/or random effects.

Usage

```
powerGlmer3(var_rand, n_rand, design, remain, fam_link, var_fix = NULL, n_fix = NULL,
alpha = 0.05, nsim = 100, poisLog = NULL, ftest = "LR", iter = NULL)
```

Arguments

var_rand	Vector of known dam, sire, dam by sire, and remaining random variance components, i.e. c(dam,sire, dam by sire, rand1, rand2, etc.).
n_rand	Vector of known dam, sire, family, and remaining random sample sizes, i.e. c(dam, sire, family, rand1, rand2,etc.).
design	A data frame of the experimental design, using only integers. First three columns must contain and be named "dam", "sire", "family". Remaining columns are the random effects followed by the fixed effects. Continuous fixed effects are a column containing the values 1:nrow(design).
remain	Remaining formula using <i>lme4</i> package format. Must be random effects followed by fixed effects. No interactions or random slopes; formulate as intercepts in design.
fam_link	The family and link in family(link) format. Supported options are binomial(link="logit"), binomial(link="probit"), poisson(link="log"), and poisson(link="sqrt").
var_fix	Vector of known fixed variance components, i.e. c(fix1, fix2, etc.). Continuous fixed random values are sorted to match column values.
n_fix	Vector of known fixed sample sizes, i.e. c(fix1, fix2, etc.). Continuous fixed effects must have a sample size of 1.
alpha	Statistical significance value. Default is 0.05.
nsim	Number of simulations. Default is 100.
poisLog	The residual variance component value if using poisson(link="log").
ftest	Default is "LR" for likelihood ratio test for fixed effects. Option "PB" is for parametric bootstrap.
iter	Number of iterations for computing the parametric bootstrap significance value for any fixed effects.

Details

Extracts the dam, sire, dam, dam by sire, and any remaining random and fixed effects power values. The residual variance component for the *fam_links* are described by Nakagawa and Schielzeth (2010, 2013). Power values are calculated by stochastically simulation data and then calculating the proportion of significance values less than *alpha* for each component (Bolker 2008). Significance values for the random effects are determined using likelihood ratio tests (Bolker et al. 2009). Significance values for any fixed effects are determined using likelihood ratio tests or parametric bootstrap method (Bolker et al. 2009) from the *mixed* function of the *afex* package.

Value

Prints a data frame with the sample sizes, variance component inputs, variance component outputs, and power values.

Note

The Laplace approximation is used because there were fewer disadvantages relative to penalized quasi-likelihood and Gauss-Hermite quadrature parameter estimation (Bolker et al. 2009). That is, penalized quasi-likelihood is not recommended for count responses with means less than 5 and binary responses with less than 5 successes per group. Gauss-Hermite quadrature is not recommended for more than two or three random effects because of the rapidly declining analytical speed with the increasing number of random effects.

References

- Bolker BM. 2008. Ecological models and data in R. Princeton University Press, New Jersey.
- Bolker BM, Brooks ME, Clark CJ, Geange SW, Poulsen JR, Stevens MHH, White J-SS. 2009. Generalized linear mixed models: a practical guide for ecology and evolution. *Trends in Ecology and Evolution* 24(3): 127-135. DOI: 10.1016/j.tree.2008.10.008
- Lynch M, Walsh B. 1998. Genetics and Analysis of Quantitative Traits. Sinauer Associates, Massachusetts.
- Nakagawa S, Schielzeth H. 2010. Repeatability for Gaussian and non-Gaussian data: a practical guide for biologists. *Biological Reviews* 85(4): 935-956. DOI: 10.1111/j.1469-185X.2010.00141.x
- Nakagawa S, Schielzeth H. 2013. A general and simple method for obtaining R² from generalized linear mixed-effects models. *Methods in Ecology and Evolution* 4(2): 133-142. DOI: 10.1111/j.2041-210x.2012.00261.x

See Also

[powerGlm](#), [powerGlm2](#)

Examples

```
##design object: 2 remaining random effects and 1 continous fixed effect
block=c(2,2); blocN=4; position=16; posN=20; offN=20
dam0<- stack(as.data.frame(matrix(1:(block[1]*blocN),ncol=blocN,nrow=block[1])))
sire0<- stack(as.data.frame(matrix(1:(block[2]*blocN),ncol=blocN,nrow=block[2])))
observ0<- merge(dam0,sire0, by="ind")
```

```

levels(observ0[,1])<- 1:blockN; colnames(observ0)<- c("block","dam","sire")
observ0$family<- 1:nrow(observ0) #add family
#expand for offspring, observ0 x offN
observ1<- do.call("rbind", replicate(offN,observ0,simplify=FALSE))
observ1$position<- rep(1:position,each=posN)
observ1$position<- sample(observ1$position,nrow(observ1)) #shuffle
desn<- observ1[,c(2,3,4,5,1)];rm(observ0,observ1) #dam,sire,family,position,block
desn$egg_size<- 1:nrow(desn)

#100 simulations
## Not run: powerGlm3(var_rand=c(1,0.15,0.11,0.5,0.3),n_rand=c(8,8,16,16,4),
fam_link=binomial(link="logit"),var_fix=0.1,n_fix=1,design=desn,
remain="(1|position)+(1|block)+egg_size")
## End(Not run)

```

powerLmer

*Power analysis for normal data***Description**

Extracts the power values of dam, sire, and dam by sire variance components from a linear mixed-effect model using the *lmer* function of the *lme4* package.

Usage

```
powerLmer(varcomp, nval, alpha = 0.05, nsim = 100, ml = F)
```

Arguments

varcomp	Vector of known dam, sire, dam by sire, and residual variance components, i.e. c(dam, sire, dam x sire, residual).
nval	Vector of known dam, sire, and offspring per family sample sizes, i.e. c(dam, sire, offspring).
alpha	Statistical significance value. Default is 0.05.
nsim	Number of simulations. Default is 100.
ml	Default is FALSE for restricted maximum likelihood. Change to TRUE for maximum likelihood.

Details

Extracts the dam, sire, dam, and dam by sire power values. Power values are calculated by stochastically simulation data and then calculating the proportion of significance values less than *alpha* for each component (Bolker 2008). Significance values for the random effects are determined using likelihood ratio tests (Bolker et al. 2009).

Value

Prints a data frame with the sample sizes, variance component inputs, variance component outputs, and power values.

Note

Maximum likelihood (ML) estimates the parameters that maximize the likelihood of the observed data and has the advantage of using all the data and accounting for non-independence (Lynch and Walsh 1998, p. 779; Bolker et al. 2009). On the other hand, ML has the disadvantage of assuming that all fixed effects are known without error, producing a downward bias in the estimation of the residual variance component. This bias can be large if there are lots of fixed effects, especially if sample sizes are small. Restricted maximum likelihood (REML) has the advantage of not assuming the fixed effects are known and averages over the uncertainty, so there can be less bias in the estimation of the residual variance component. However, REML only maximizes a portion of the likelihood to estimate the effect parameters, but is the preferred method for analyzing large data sets with complex structure.

References

- Bolker BM. 2008. Ecological models and data in R. Princeton University Press, New Jersey.
- Bolker BM, Brooks ME, Clark CJ, Geange SW, Poulsen JR, Stevens MHH, White J-SS. 2009. Generalized linear mixed models: a practical guide for ecology and evolution. *Trends in Ecology and Evolution* 24(3): 127-135. DOI: 10.1016/j.tree.2008.10.008
- Lynch M, Walsh B. 1998. *Genetics and Analysis of Quantitative Traits*. Sinauer Associates, Massachusetts.

See Also

[powerLmer2](#), [powerLmer3](#)

Examples

```
#100 simulations
#powerLmer(varcomp=c(0.1900,0,0.1719,0.6315),nval=c(11,11,10))
#
#5 simulations
powerLmer(varcomp=c(0.1900,0,0.1719,0.6315),nval=c(11,11,10),nsim=5)
```

powerLmer2

Power analysis for normal data 2

Description

Extracts the power values of dam, sire, and dam by sire variance components from a linear mixed-effect model using the *lmer* function of the *lme4* package. Options to include one random position and/or one random block effect(s).

Usage

```
powerLmer2(varcomp, nval, alpha = 0.05, nsim = 100, position = NULL, block = NULL,
ml = F)
```

Arguments

varcomp	Vector of known dam, sire, dam by sire, residual, and position and/or block variance components, i.e. c(dam, sire, dam x sire, residual, position/block). If there is a position and a block c(..., residual, position, block).
nval	Vector of known dam, sire, offspring per family, and offspring per position or number of blocks sample sizes, i.e. c(dam, sire, offspring, position/block). If there is a position and a block c(..., offspring, position, block).
alpha	Statistical significance value. Default is 0.05.
nsim	Number of simulations. Default is 100.
position	Optional number of positions.
block	Optional vector of dams and sires per block, e.g. c(2,2).
ml	Default is FALSE for restricted maximum likelihood. Change to TRUE for maximum likelihood.

Details

Extracts the dam, sire, dam, dam by sire, and position and/or block power values. Power values are calculated by stochastically simulation data and then calculating the proportion of significance values less than *alpha* for each component (Bolker 2008). Significance values for the random effects are determined using likelihood ratio tests (Bolker et al. 2009).

Value

Prints a data frame with the sample sizes, variance component inputs, variance component outputs, and power values.

Note

Maximum likelihood (ML) estimates the parameters that maximize the likelihood of the observed data and has the advantage of using all the data and accounting for non-independence (Lynch and Walsh 1998, p. 779; Bolker et al. 2009). On the other hand, ML has the disadvantage of assuming that all fixed effects are known without error, producing a downward bias in the estimation of the residual variance component. This bias can be large if there are lots of fixed effects, especially if sample sizes are small. Restricted maximum likelihood (REML) has the advantage of not assuming the fixed effects are known and averages over the uncertainty, so there can be less bias in the estimation of the residual variance component. However, REML only maximizes a portion of the likelihood to estimate the effect parameters, but is the preferred method for analyzing large data sets with complex structure.

References

- Bolker BM. 2008. Ecological models and data in R. Princeton University Press, New Jersey.
- Bolker BM, Brooks ME, Clark CJ, Geange SW, Poulsen JR, Stevens MHH, White J-SS. 2009. Generalized linear mixed models: a practical guide for ecology and evolution. Trends in Ecology and Evolution 24(3): 127-135. DOI: 10.1016/j.tree.2008.10.008
- Lynch M, Walsh B. 1998. Genetics and Analysis of Quantitative Traits. Sinauer Associates, Massachusetts.

See Also

[powerLmer](#), [powerLmer3](#)

Examples

```
#100 simulations
#position only, e.g. 8 tanks
## Not run: powerLmer2(varcomp=c(0.2030,0,0.1798,0.5499,0.1077),nval=c(8,8,20,160),position=8)
#block only, e.g. four 2 x 2
## Not run: powerLmer2(varcomp=c(0.2030,0,0.1798,0.5499,0.1077),nval=c(8,8,20,4),block=c(2,2))
#position and block
## Not run: powerLmer2(varcomp=c(0.2030,0,0.1798,0.5499,0.1077,0.1077),nval=c(8,8,20,40,4),
position=8,block=c(2,2))
## End(Not run)
```

powerLmer3

Power analysis for normal data 3

Description

Extracts the power values of dam, sire, and dam by sire variance components from a linear mixed-effect model using the *lmer* function of the *lme4* package. Model can include additional fixed and/or random effects.

Usage

```
powerLmer3(var_rand, n_rand, design, remain, var_fix = NULL, n_fix = NULL,
alpha = 0.05, nsim = 100, ml = F, ftest = "LR", iter = NULL)
```

Arguments

var_rand	Vector of known dam, sire, dam by sire, residual, and remaining random variance components, i.e. c(dam, sire, dam x sire, residual, rand1, rand2, etc.).
n_rand	Vector of known dam, sire, family, and remaining random sample sizes, i.e. c(dam, sire, family, rand1, rand2, etc.).
design	A data frame of the experimental design, using only integers. First three columns must contain and be named "dam", "sire", "family". Remaining columns are the random effects followed by the fixed effects. Continuous fixed effects are a column containing the values 1:nrow(design).
remain	Remaining formula using <i>lme4</i> package format. Must be random effects followed by fixed effects. No interactions or random slopes; formulate as intercepts in design.
var_fix	Vector of known fixed variance components, i.e. c(fix1, fix2, etc.). Continuous fixed random values are sorted to match column values.
n_fix	Vector of known fixed sample sizes, i.e. c(fix1, fix2, etc.). Continuous fixed effects must have a sample size of 1.

<code>alpha</code>	Statistical significance value. Default is 0.05.
<code>nsim</code>	Number of simulations. Default is 100.
<code>ml</code>	Default is FALSE for restricted maximum likelihood. Change to TRUE for maximum likelihood.
<code>ftest</code>	Default is "LR" for likelihood ratio test for fixed effects. Option "PB" is for parametric bootstrap.
<code>iter</code>	Number of iterations for computing the parametric bootstrap significance value for any fixed effects.

Details

Extracts the dam, sire, dam, dam by sire, and any remaining random and fixed effects power values. Power values are calculated by stochastically simulation data and then calculating the proportion of significance values less than *alpha* for each component (Bolker 2008). Significance values for the random effects are determined using likelihood ratio tests (Bolker et al. 2009). Significance values for any fixed effects are determined using likelihood ratio tests or parametric bootstrap method (Bolker et al. 2009) from the *mixed* function of the *afex* package.

Value

Prints a data frame with the sample sizes, variance component inputs, variance component outputs, and power values.

Note

Maximum likelihood (ML) estimates the parameters that maximize the likelihood of the observed data and has the advantage of using all the data and accounting for non-independence (Lynch and Walsh 1998, p. 779; Bolker et al. 2009). On the other hand, ML has the disadvantage of assuming that all fixed effects are known without error, producing a downward bias in the estimation of the residual variance component. This bias can be large if there are lots of fixed effects, especially if sample sizes are small. Restricted maximum likelihood (REML) has the advantage of not assuming the fixed effects are known and averages over the uncertainty, so there can be less bias in the estimation of the residual variance component. However, REML only maximizes a portion of the likelihood to estimate the effect parameters, but is the preferred method for analyzing large data sets with complex structure.

References

- Bolker BM. 2008. Ecological models and data in R. Princeton University Press, New Jersey.
- Bolker BM, Brooks ME, Clark CJ, Geange SW, Poulsen JR, Stevens MHH, White J-SS. 2009. Generalized linear mixed models: a practical guide for ecology and evolution. *Trends in Ecology and Evolution* 24(3): 127-135. DOI: 10.1016/j.tree.2008.10.008
- Lynch M, Walsh B. 1998. Genetics and Analysis of Quantitative Traits. Sinauer Associates, Massachusetts.

See Also

[powerLmer](#), [powerLmer2](#)

Examples

```
##design object: 2 remaining random effects and 1 continous fixed effect
block=c(2,2); blocN=4; position=16; posN=20; offN=20
dam0<- stack(as.data.frame(matrix(1:(block[1]*blocN),ncol=blocN,nrow=block[1])))
sire0<- stack(as.data.frame(matrix(1:(block[2]*blocN),ncol=blocN,nrow=block[2])))
observ0<- merge(dam0,sire0, by="ind")
levels(observ0[,1])<- 1:blocN; colnames(observ0)<- c("block","dam","sire")
observ0$family<- 1:nrow(observ0) #add family
#expand for offspring, observ0 x offN
observ1<- do.call("rbind", replicate(offN,observ0,simplify=FALSE))
observ1$position<- rep(1:position,each=posN)
observ1$position<- sample(observ1$position,nrow(observ1)) #shuffle
desn<- observ1[,c(2,3,4,5,1)];rm(observ0,observ1) #dam,sire,family,position,block
desn$egg_size<- 1:nrow(desn)

#100 simulations
## Not run: powerLmer3(var_rand=c(0.19,0.03,0.02,0.51,0.1,0.05),n_rand=c(8,8,16,16,4),
var_fix=0.1,n_fix=1,design=desn,remain="(1|position)+ (1|block)+ egg_size")
## End(Not run)
```

resampFamily

Bootstrap resample within families

Description

Bootstrap resample observations grouped by family identities for a specified number of iterations to create a resampled data set.

Usage

```
resampFamily(dat, copy, family, iter)
```

Arguments

dat	Data frame observed data to resample.
copy	Column numbers to copy.
family	Column name containing family identity information.
iter	Number of iterations for resampling.

Details

The resampled data can be used for producing bootstrap confidence intervals.

Value

Because of the large file sizes that can be produced, the resampling of each family X is saved separately as a common separated (X_resampF.csv) file in the working directory. These files are merged to create the final resampled data set (resamp_datF.csv).

See Also[resampRepli](#)**Examples**

```
data(chinook_length) #Chinook salmon offspring length
#resampFamily(dat=chinook_length,copy=c(3:8),family="family",iter=1000)
#example with a couple iterations
#resampFamily(dat=chinook_length,copy=c(3:8),family="family",iter=2)
```

resampGlmr

*Bootstrap components for non-normal data***Description**

Extracts additive genetic, non-additive genetic, and maternal variance components from a generalized linear mixed-effect model using the *glmer* function of the *lme4* package. Model random effects are dam, sire, and dam by sire.

Usage

```
resampGlmr(resamp, dam, sire, response, fam_link, start, end, quasi = F)
```

Arguments

resamp	Data frame of bootstrap resampled data.
dam	Column name containing dam (female) parent identity information.
sire	Column name containing sire (male) parent identity information.
response	Column name containing the offspring (response) phenotype values.
fam_link	The family and link in family(link) format. Supported options are binomial(link="logit"), binomial(link="probit"), poisson(link="log"), and poisson(link="sqrt").
start	Starting model number.
end	Ending model number.
quasi	Incorporate overdispersion or quasi-error structure.

Details

Used for bootstrap resampled data set produced using *resampRepli* or *resampFamily*. Laplace approximation parameter estimation is used, which is a true likelihood method (Bolker et al. 2009). For the overdispersion option, an observation-level random effect is added to the model (Atkins et al. 2013). Extracts the dam, sire, dam, and dam by sire variance components. The residual variance component for the *fam_links* are described by Nakagawa and Schielzeth (2010, 2013). Calculates the total variance component. Calculates the additive genetic, non-additive genetic, and maternal variance components (see Lynch and Walsh 1998, p. 603).

Value

A data frame with columns containing the raw variance components for dam, sire, dam by sire, residual, total, additive genetic, non-additive genetic, and maternal. The number of rows in the data frame matches the number of iterations in the resampled data set and each row represents a model number.

Note

The Laplace approximation is used because there were fewer disadvantages relative to penalized quasi-likelihood and Gauss-Hermite quadrature parameter estimation (Bolker et al. 2009). That is, penalized quasi-likelihood is not recommended for count responses with means less than 5 and binary responses with less than 5 successes per group. Gauss-Hermite quadrature is not recommended for more than two or three random effects because of the rapidly declining analytical speed with the increasing number of random effects.

References

- Atkins DC, Baldwin SA, Zheng C, Gallop RJ, Neighbors C. 2013. A tutorial on count regression and zero-altered count models for longitudinal substance use data. *Psychology of Addictive Behaviors* 27(1): 166-177. DOI: 10.1037/a0029508
- Bolker BM, Brooks ME, Clark CJ, Geange SW, Poulsen JR, Stevens MHH, White J-SS. 2009. Generalized linear mixed models: a practical guide for ecology and evolution. *Trends in Ecology and Evolution* 24(3): 127-135. DOI: 10.1016/j.tree.2008.10.008
- Lynch M, Walsh B. 1998. *Genetics and Analysis of Quantitative Traits*. Sinauer Associates, Massachusetts.
- Nakagawa S, Schielzeth H. 2010. Repeatability for Gaussian and non-Gaussian data: a practical guide for biologists. *Biological Reviews* 85(4): 935-956. DOI: 10.1111/j.1469-185X.2010.00141.x
- Nakagawa S, Schielzeth H. 2013. A general and simple method for obtaining R² from generalized linear mixed-effects models. *Methods in Ecology and Evolution* 4(2): 133-142. DOI: 10.1111/j.2041-210x.2012.00261.x

See Also

[resampGlmr2](#), [resampGlmr3](#)

Examples

```
data(chinook_resampS) #5 iterations

#survival_rcomp<- resampGlmr(resamp=survival_datR,dam="dam",sire="sire",
#response="status",fam_link=binomial(link="logit"),start=1,end=1000)
## Not run: survival_rcomp<- resampGlmr(resamp=chinook_resampS,dam="dam",sire="sire",
response="status",fam_link=binomial(link="logit"),start=1,end=5)
## End(Not run)
```

resampG1mer2

*Bootstrap components for non-normal data 2***Description**

Extracts additive genetic, non-additive genetic, and maternal variance components from a generalized linear mixed-effect model using the *glmer* function of the *lme4* package. Model random effects are dam, sire, and dam by sire. Options to include one random position and/or one random block effect(s).

Usage

```
resampG1mer2(resamp, dam, sire, response, fam_link, start, end, position = NULL,
             block = NULL, quasi = F)
```

Arguments

resamp	Data frame of bootstrap resampled data.
dam	Column name containing dam (female) parent identity information.
sire	Column name containing sire (male) parent identity information.
response	Column name containing the offspring (response) phenotype values.
fam_link	The family and link in family(link) format. Supported options are binomial(link="logit"), binomial(link="probit"), poisson(link="log"), and poisson(link="sqrt").
start	Starting model number.
end	Ending model number.
position	Optional column name containing position factor information.
block	Optional column name containing block factor information.
quasi	Incorporate overdispersion or quasi-error structure.

Details

Used for bootstrap resampled data set produced using *resampRepli* or *resampFamily*. Laplace approximation parameter estimation is used, which is a true likelihood method (Bolker et al. 2009). For the overdispersion option, an observation-level random effect is added to the model (Atkins et al. 2013). Extracts the dam, sire, dam, and dam by sire variance components. Extracts optional position and block variance components. The residual variance component for the *fam_links* are described by Nakagawa and Schielzeth (2010, 2013). Calculates the total variance component. Calculates the additive genetic, non-additive genetic, and maternal variance components (see Lynch and Walsh 1998, p. 603).

Value

A data frame with columns containing the raw variance components for dam, sire, dam by sire, residual, total, additive genetic, non-additive genetic, and maternal. Also columns containing the raw variance components for the options of position and/or block. The number of rows in the data frame matches the number of iterations in the resampled data set and each row represents a model number.

Note

The Laplace approximation is used because there were fewer disadvantages relative to penalized quasi-likelihood and Gauss-Hermite quadrature parameter estimation (Bolker et al. 2009). That is, penalized quasi-likelihood is not recommended for count responses with means less than 5 and binary responses with less than 5 successes per group. Gauss-Hermite quadrature is not recommended for more than two or three random effects because of the rapidly declining analytical speed with the increasing number of random effects.

References

- Atkins DC, Baldwin SA, Zheng C, Gallop RJ, Neighbors C. 2013. A tutorial on count regression and zero-altered count models for longitudinal substance use data. *Psychology of Addictive Behaviors* 27(1): 166-177. DOI: 10.1037/a0029508
- Bolker BM, Brooks ME, Clark CJ, Geange SW, Poulsen JR, Stevens MHH, White J-SS. 2009. Generalized linear mixed models: a practical guide for ecology and evolution. *Trends in Ecology and Evolution* 24(3): 127-135. DOI: 10.1016/j.tree.2008.10.008
- Lynch M, Walsh B. 1998. *Genetics and Analysis of Quantitative Traits*. Sinauer Associates, Massachusetts.
- Nakagawa S, Schielzeth H. 2010. Repeatability for Gaussian and non-Gaussian data: a practical guide for biologists. *Biological Reviews* 85(4): 935-956. DOI: 10.1111/j.1469-185X.2010.00141.x
- Nakagawa S, Schielzeth H. 2013. A general and simple method for obtaining R² from generalized linear mixed-effects models. *Methods in Ecology and Evolution* 4(2): 133-142. DOI: 10.1111/j.2041-210x.2012.00261.x

See Also

[resampGlm3](#), [resampGlm3](#)

Examples

```
data(chinook_resampS) #5 iterations

#survival_rcomp2<- resampGlm3(resamp=survival_datR,dam="dam",sire="sire",
#response="status",fam_link=binomial(link="logit"),position="tray",start=1,end=1000)
## Not run: survival_rcomp2<- resampGlm3(resamp=chinook_resampS,dam="dam",sire="sire",
response="status",fam_link=binomial(link="logit"),position="tray",start=1,end=5)
## End(Not run)
```

resampGlm3

Bootstrap components for non-normal data 3

Description

Extracts additive genetic, non-additive genetic, and maternal variance components from a generalized linear mixed-effect model using the *glmer* function of the *lme4* package. Model random effects are dam, sire, dam by sire, and any additional fixed and/or random effects.

Usage

```
resampGlm3(resamp, dam, sire, response, fam_link, start, end, remain, quasi = F)
```

Arguments

resamp	Data frame of bootstrap resampled data.
dam	Column name containing dam (female) parent identity information.
sire	Column name containing sire (male) parent identity information.
response	Column name containing the offspring (response) phenotype values.
fam_link	The family and link in family(link) format. Supported options are binomial(link="logit"), binomial(link="probit"), poisson(link="log"), and poisson(link="sqrt").
start	Starting model number.
end	Ending model number.
remain	Remaining formula using <i>lme4</i> package format with # sign (see column names), e.g. fixed# + (1 random#).
quasi	Incorporate overdispersion or quasi-error structure.

Details

Used for bootstrap resampled data set produced using *resampRepli* or *resampFamily*. Laplace approximation parameter estimation is used, which is a true likelihood method (Bolker et al. 2009). For the overdispersion option, an observation-level random effect is added to the model (Atkins et al. 2013). Extracts the dam, sire, dam, and dam by sire variance components. Extracts any additional fixed effect and random effect variance components. The fixed-effect variance component is as a single group using the method described by Nakagawa and Schielzeth (2013). The residual variance component for the *fam_links* are described by Nakagawa and Schielzeth (2010, 2013). Calculates the total variance component. Calculates the additive genetic, non-additive genetic, and maternal variance components (see Lynch and Walsh 1998, p. 603).

Value

A data frame with columns containing the raw variance components for dam, sire, dam by sire, residual, total, additive genetic, non-additive genetic, and maternal. Also columns containing the raw variance components for remaining formula components. The number of rows in the data frame matches the number of iterations in the resampled data set and each row represents a model number.

Note

The Laplace approximation is used because there were fewer disadvantages relative to penalized quasi-likelihood and Gauss-Hermite quadrature parameter estimation (Bolker et al. 2009). That is, penalized quasi-likelihood is not recommended for count responses with means less than 5 and binary responses with less than 5 successes per group. Gauss-Hermite quadrature is not recommended for more than two or three random effects because of the rapidly declining analytical speed with the increasing number of random effects.

References

- Atkins DC, Baldwin SA, Zheng C, Gallop RJ, Neighbors C. 2013. A tutorial on count regression and zero-altered count models for longitudinal substance use data. *Psychology of Addictive Behaviors* 27(1): 166-177. DOI: 10.1037/a0029508
- Bolker BM, Brooks ME, Clark CJ, Geange SW, Poulsen JR, Stevens MHH, White J-SS. 2009. Generalized linear mixed models: a practical guide for ecology and evolution. *Trends in Ecology and Evolution* 24(3): 127-135. DOI: 10.1016/j.tree.2008.10.008
- Lynch M, Walsh B. 1998. *Genetics and Analysis of Quantitative Traits*. Sinauer Associates, Massachusetts.
- Nakagawa S, Schielzeth H. 2010. Repeatability for Gaussian and non-Gaussian data: a practical guide for biologists. *Biological Reviews* 85(4): 935-956. DOI: 10.1111/j.1469-185X.2010.00141.x
- Nakagawa S, Schielzeth H. 2013. A general and simple method for obtaining R² from generalized linear mixed-effects models. *Methods in Ecology and Evolution* 4(2): 133-142. DOI: 10.1111/j.2041-210x.2012.00261.x

See Also

[resampGlm](#), [resampGlm2](#)

Examples

```
data(chinook_resampS) #5 iterations

#survival_rcomp3<- resampGlm3(resamp=survival_datR,dam="dam",sire="sire",
#response="status",fam_link=binomial(link="logit"),remain="egg_size# + (1|tray#)",
#start=1,end=1000)
## Not run: survival_rcomp3<- resampGlm3(resamp=survival_datR,dam="dam",sire="sire",
response="status",fam_link=binomial(link="logit"),remain="egg_size# + (1|tray#)",
start=1,end=5)
## End(Not run)
```

resampLmer

Bootstrap components for normal data

Description

Extracts additive genetic, non-additive genetic, and maternal variance components from a linear mixed-effect model using the *lmer* function of the *lme4* package. Model random effects are dam, sire, and dam by sire.

Usage

```
resampLmer(resamp, dam, sire, response, start, end, ml = F)
```

Arguments

resamp	Data frame of bootstrap resampled data.
dam	Column name containing dam (female) parent identity information.
sire	Column name containing sire (male) parent identity information.
response	Column name containing the offspring (response) phenotype values.
start	Starting model number.
end	Ending model number.
ml	Default is FALSE for restricted maximum likelihood. Change to TRUE for maximum likelihood.

Details

Used for bootstrap resampled data set produced using *resampRepli* or *resampFamily*. Extracts the dam, sire, dam, dam by sire, and residual variance components. Calculates the total variance component. Calculates the additive genetic, non-additive genetic, and maternal variance components (see Lynch and Walsh 1998, p. 603).

Value

A data frame with columns containing the raw variance components for dam, sire, dam by sire, residual, total, additive genetic, non-additive genetic, and maternal. The number of rows in the data frame matches the number of iterations in the resampled data set and each row represents a model number.

Note

Maximum likelihood (ML) estimates the parameters that maximize the likelihood of the observed data and has the advantage of using all the data and accounting for non-independence (Lynch and Walsh 1998, p. 779; Bolker et al. 2009). On the other hand, ML has the disadvantage of assuming that all fixed effects are known without error, producing a downward bias in the estimation of the residual variance component. This bias can be large if there are lots of fixed effects, especially if sample sizes are small. Restricted maximum likelihood (REML) has the advantage of not assuming the fixed effects are known and averages over the uncertainty, so there can be less bias in the estimation of the residual variance component. However, REML only maximizes a portion of the likelihood to estimate the effect parameters, but is the preferred method for analyzing large data sets with complex structure.

References

- Bolker BM, Brooks ME, Clark CJ, Geange SW, Poulsen JR, Stevens MHH, White J-SS. 2009. Generalized linear mixed models: a practical guide for ecology and evolution. *Trends in Ecology and Evolution* 24(3): 127-135. DOI: 10.1016/j.tree.2008.10.008
- Lynch M, Walsh B. 1998. *Genetics and Analysis of Quantitative Traits*. Sinauer Associates, Massachusetts.

See Also

[resampLmer2](#), [resampLmer3](#)

Examples

```
data(chinook_resampL) #5 iterations

#length_rcomp1<- resampLmer(resamp=length_datR,dam="dam",sire="sire",response="length",
#start=1,end=1000)
length_rcomp1<- resampLmer(resamp=chinook_resampL,dam="dam",sire="sire",response="length",
start=1,end=5)
```

resampLmer2

*Bootstrap components for normal data 2***Description**

Extracts additive genetic, non-additive genetic, and maternal variance components from a linear mixed-effect model using the *lmer* function of the *lme4* package. Model random effects are dam, sire, and dam by sire. Options to include one random position and/or one random block effect(s).

Usage

```
resampLmer2(resamp, dam, sire, response, start, end, position = NULL, block = NULL,
ml = F)
```

Arguments

resamp	Data frame of bootstrap resampled data.
dam	Column name containing dam (female) parent identity information.
sire	Column name containing sire (male) parent identity information.
response	Column name containing the offspring (response) phenotype values.
start	Starting model number.
end	Ending model number.
position	Optional column name containing position factor information.
block	Optional column name containing block factor information.
ml	Default is FALSE for restricted maximum likelihood. Change to TRUE for maximum likelihood.

Details

Used for bootstrap resampled data set produced using *resampRepli* or *resampFamily*. Extracts the dam, sire, dam, dam by sire, and residual variance components. Extracts optional position and block variance components. Calculates the total variance component. Calculates the additive genetic, non-additive genetic, and maternal variance components (see Lynch and Walsh 1998, p. 603).

Value

A data frame with columns containing the raw variance components for dam, sire, dam by sire, residual, total, additive genetic, non-additive genetic, and maternal. Also columns containing the raw variance components for the options of position and/or block. The number of rows in the data frame matches the number of iterations in the resampled data set and each row represents a model number.

Note

Maximum likelihood (ML) estimates the parameters that maximize the likelihood of the observed data and has the advantage of using all the data and accounting for non-independence (Lynch and Walsh 1998, p. 779; Bolker et al. 2009). On the other hand, ML has the disadvantage of assuming that all fixed effects are known without error, producing a downward bias in the estimation of the residual variance component. This bias can be large if there are lots of fixed effects, especially if sample sizes are small. Restricted maximum likelihood (REML) has the advantage of not assuming the fixed effects are known and averages over the uncertainty, so there can be less bias in the estimation of the residual variance component. However, REML only maximizes a portion of the likelihood to estimate the effect parameters, but is the preferred method for analyzing large data sets with complex structure.

References

- Bolker BM, Brooks ME, Clark CJ, Geange SW, Poulsen JR, Stevens MHH, White J-SS. 2009. Generalized linear mixed models: a practical guide for ecology and evolution. *Trends in Ecology and Evolution* 24(3): 127-135. DOI: 10.1016/j.tree.2008.10.008
- Lynch M, Walsh B. 1998. *Genetics and Analysis of Quantitative Traits*. Sinauer Associates, Massachusetts.

See Also

[resampLmer](#), [resampLmer3](#)

Examples

```
data(chinook_resampL) #5 iterations

#length_rcomp2<- resampLmer2(resamp=length_datR,dam="dam",sire="sire",response="length",
#start=1,end=1000,position="tray")
length_rcomp2<- resampLmer2(resamp=chinook_resampL,dam="dam",sire="sire",response="length",
start=1,end=5,position="tray")
```

Description

Extracts additive genetic, non-additive genetic, and maternal variance components from a linear mixed-effect model using the *lmer* function of the *lme4* package. Model random effects are dam, sire, dam by sire, and any additional fixed and/or random effects.

Usage

```
resampLmer3(resamp, dam, sire, response, start, end, remain, ml = F)
```

Arguments

resamp	Data frame of bootstrap resampled data.
dam	Column name containing dam (female) parent identity information.
sire	Column name containing sire (male) parent identity information.
response	Column name containing the offspring (response) phenotype values.
start	Starting model number.
end	Ending model number.
remain	Remaining formula using <i>lme4</i> package format with # sign (see column names), e.g. fixed# + (1 random#).
ml	Default is FALSE for restricted maximum likelihood. Change to TRUE for maximum likelihood.

Details

Used for bootstrap resampled data set produced using *resampRepli* or *resampFamily*. Extracts the dam, sire, dam, dam by sire, and residual variance components. Extracts any additional fixed effect and random effect variance components. The fixed-effect variance component is as a single group using the method described by Nakagawa and Schielzeth (2013). Calculates the total variance component. Calculates the additive genetic, non-additive genetic, and maternal variance components (see Lynch and Walsh 1998, p. 603).

Value

A data frame with columns containing the raw variance components for dam, sire, dam by sire, residual, total, additive genetic, non-additive genetic, and maternal. Also columns containing the raw variance components for remaining formula components. The number of rows in the data frame matches the number of iterations in the resampled data set and each row represents a model number.

Note

Maximum likelihood (ML) estimates the parameters that maximize the likelihood of the observed data and has the advantage of using all the data and accounting for non-independence (Lynch and Walsh 1998, p. 779; Bolker et al. 2009). On the other hand, ML has the disadvantage of assuming that all fixed effects are known without error, producing a downward bias in the estimation of the residual variance component. This bias can be large if there are lots of fixed effects, especially if sample sizes are small. Restricted maximum likelihood (REML) has the advantage of not assuming the fixed effects are known and averages over the uncertainty, so there can be less bias in the

estimation of the residual variance component. However, REML only maximizes a portion of the likelihood to estimate the effect parameters, but is the preferred method for analyzing large data sets with complex structure.

References

Bolker BM, Brooks ME, Clark CJ, Geange SW, Poulsen JR, Stevens MHH, White J-SS. 2009. Generalized linear mixed models: a practical guide for ecology and evolution. *Trends in Ecology and Evolution* 24(3): 127-135. DOI: 10.1016/j.tree.2008.10.008

Lynch M, Walsh B. 1998. *Genetics and Analysis of Quantitative Traits*. Sinauer Associates, Massachusetts.

Nakagawa S, Schielzeth H. 2013. A general and simple method for obtaining R² from generalized linear mixed-effects models. *Methods in Ecology and Evolution* 4(2): 133-142. DOI: 10.1111/j.2041-210x.2012.00261.x

See Also

[resampLmer](#), [resampLmer2](#)

Examples

```
data(chinook_resampL)

#length_rcomp3<- resampLmer3(resamp=length_datR,dam="dam",sire="sire",response="length",
#start=1,end=1000,remain="egg_size# + (1|tray#)")
length_rcomp3<- resampLmer3(resamp=chinook_resampL,dam="dam",sire="sire",response="length",
start=1,end=5,remain="egg_size# + (1|tray#)")
```

resampRepli

Bootstrap resample within replicates

Description

Bootstrap resample observations grouped by replicate identities within family identities for a specified number of iterations to create a resampled data set.

Usage

```
resampRepli(dat, copy, family, replicate, iter)
```

Arguments

dat	Data frame observed data to resample.
copy	Column numbers to copy.
family	Column name containing family identity information.
replicate	Column name containing replicate identity information.
iter	Number of iterations for resampling.

Details

The resampled data can be used for producing bootstrap confidence intervals.

Value

Because of the large file sizes that can be produced, the resampling of each replicate Y per family X is saved separately as a common separated (X_Y_resampR.csv) file in the working directory. These files are merged to create the final resampled data set (resamp_datR.csv).

See Also

[resampFamily](#)

Examples

```
data(chinook_length) #Chinook salmon offspring length
#resampRepli(dat=chinook_length,copy=c(3:8),family="family",replicate="repli",iter=1000)
#example with a couple iterations
#resampRepli(dat=chinook_length,copy=c(3:8),family="family",replicate="repli",iter=2)
```

Index

* datasets

- chinook_bootL, 10
- chinook_bootS, 11
- chinook_jackL, 12
- chinook_jackS, 13
- chinook_length, 14
- chinook_resampL, 15
- chinook_resampS, 17
- chinook_survival, 18

* package

- fullfact-package, 2

barMANA, 6

boxMANA, 7

buildBinary, 8, 10

buildMulti, 9, 9

chinook_bootL, 10

chinook_bootS, 11

chinook_jackL, 12

chinook_jackS, 13

chinook_length, 14

chinook_resampL, 15

chinook_resampS, 17

chinook_survival, 18

ciJack, 19, 22, 23

ciJack2, 20, 21, 23

ciJack3, 20, 22, 22

ciMANA, 23, 26, 27

ciMANA2, 24, 25, 27

ciMANA3, 24, 26, 26

fullfact (fullfact-package), 2

fullfact-package, 2

JackGlm, 28, 32, 34

JackGlm2, 29, 30, 34

JackGlm3, 29, 32, 32

JackLmer, 34, 37, 39

JackLmer2, 35, 36, 39

JackLmer3, 35, 37, 38

observGlm, 40, 43, 44

observGlm2, 41, 41, 44

observGlm3, 41, 43, 43

observLmer, 45, 47, 49

observLmer2, 46, 46, 49

observLmer3, 46, 47, 48

powerGlm, 50, 52, 54

powerGlm2, 51, 51, 54

powerGlm3, 51, 52, 53

powerLmer, 55, 58, 59

powerLmer2, 56, 56, 59

powerLmer3, 56, 58, 58

resampFamily, 60, 72

resampGlm, 61, 64, 66

resampGlm2, 62, 63, 66

resampGlm3, 62, 64, 64

resampLmer, 66, 69, 71

resampLmer2, 67, 68, 71

resampLmer3, 67, 69, 69

resampRepli, 61, 71