

# Package ‘kinematics’

May 8, 2026

**Type** Package

**Title** Studying Sampled Trajectories

**Version** 1.0.0

**Author** Pablo Rodriguez-

Sanchez (<https://pabrod.github.io>) and Sanne J. P. van den Berg (<https://www.wur.nl/en/Persons/Sanne-dr.-SJP-Sanne-van-den-Berg.htm>)

**Maintainer** Pablo Rodriguez-Sanchez <[pablo.rodriguez.sanchez@gmail.com](mailto:pablo.rodriguez.sanchez@gmail.com)>

**Description** Allows analyzing time series representing two-dimensional movements.

It accepts a data frame with a time (t), horizontal (x) and vertical (y) coordinate as columns, and returns several dynamical properties such as speed, acceleration or curvature.

**License** MIT + file LICENSE

**Encoding** UTF-8

**LazyData** true

**RoxygenNote** 7.1.1

**VignetteBuilder** knitr

**Suggests** testthat, knitr, utils, markdown, rmarkdown, ggplot2

**Imports** numDeriv, stats

**Depends** R (>= 3.5.0)

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2021-07-19 07:30:02 UTC

## Contents

accel . . . . .	2
append_displacement . . . . .	2
append_dynamics . . . . .	3
approx_derivative . . . . .	4
curvature . . . . .	4
curvature_radius . . . . .	5

displacement . . . . .	5
example_mov . . . . .	6
get_polar_coordinates . . . . .	6
speed . . . . .	7

<b>Index</b>	<b>8</b>
--------------	----------

---

accel	<i>Return accelerations</i>
-------	-----------------------------

---

### Description

Return accelerations

### Usage

```
accel(t, x, y)
```

### Arguments

t	The times vector
x	The x positions
y	The y positions

### Value

The accelerations

### See Also

[speed](#), [approx\\_derivative](#)

---

append_displacement	<i>Return a dataframe with information about the time-to-time displacements</i>
---------------------	---

---

### Description

The displacement is a bit more complicated than other dynamical variables, as it depends on the sampling frequency. If you are subsampling, always re-run `append_displacement` after subsampling.

### Usage

```
append_displacement(data)
```

**Arguments**

data                    A dataframe containing t, x and y

**Value**

A data frame including all the dynamical information, including displacements

**See Also**

[append\\_dynamics](#), [speed](#)

---

append\_dynamics                    *Return a data frame with extra columns with dynamical information*

---

**Description**

Return a data frame with extra columns with dynamical information

**Usage**

```
append_dynamics(data, append.displacement = TRUE)
```

**Arguments**

data                    A dataframe containing t, x and y

append.displacement

(Optional) Set it to FALSE to not calculate displacements. Useful if the data is going to be resampled

**Value**

A data frame including instantaneous dynamical variables, such as speed and acceleration

**See Also**

[speed](#), [accel](#), [append\\_displacement](#)

---

`approx_derivative`      *Approximate derivative*

---

**Description**

Approximate derivative

**Usage**

```
approx_derivative(t, x)
```

**Arguments**

<code>t</code>	Vector of times
<code>x</code>	Vector of values

**Value**

A vector (of the same size of `t`) representing the numerical derivative

**See Also**

[speed](#), [accel](#)

---

`curvature`      *Return curvatures*

---

**Description**

Return curvatures

**Usage**

```
curvature(t, x, y)
```

**Arguments**

<code>t</code>	The times vector
<code>x</code>	The x positions
<code>y</code>	The y positions

**Value**

The local curvature

**See Also**

[speed](#), [accel](#), [curvature\\_radius](#)

---

curvature\_radius      *Return curvature radius*

---

**Description**

Return curvature radius

**Usage**

```
curvature_radius(t, x, y)
```

**Arguments**

t	The times vector
x	The x positions
y	The y positions

**Value**

The local curvature radius

**See Also**

[speed](#), [accel](#), [curvature](#)

---

displacement      *Return displacements*

---

**Description**

Return displacements

**Usage**

```
displacement(x, y)
```

**Arguments**

x	The x positions
y	The y positions

**Value**

The displacements between a position and its previous

---

example\_mov

*Example data set*

---

### Description

Experimental sample of 3000 positions of a macroinvertebrate

### Format

A data frame with 3000 observations of:

**x** horizontal position

**y** vertical position

**t** time ...

---

get\_polar\_coordinates *Get polar coordinates*

---

### Description

Get polar coordinates

### Usage

```
get_polar_coordinates(x, y, origin = c(0, 0))
```

### Arguments

**x** Vector of x coordinates  
**y** Vector of y coordinates  
**origin** (Default = c(0, 0)) Position of the origin of coordinates

### Value

Data frame with radius (r) and angle vectors (th)

---

speed	<i>Return speeds</i>
-------	----------------------

---

**Description**

Return speeds

**Usage**

speed(t, x, y)

**Arguments**

t	The times vector
x	The x positions
y	The y positions

**Value**

The speeds

**See Also**

[accel](#), [approx\\_derivative](#)

# Index

accel, [2](#), [3–5](#), [7](#)  
append\_displacement, [2](#), [3](#)  
append\_dynamics, [3](#), [3](#)  
approx\_derivative, [2](#), [4](#), [7](#)  
  
curvature, [4](#), [5](#)  
curvature\_radius, [4](#), [5](#)  
  
displacement, [5](#)  
  
example\_mov, [6](#)  
  
get\_polar\_coordinates, [6](#)  
  
speed, [2–5](#), [7](#)