

Package ‘lin.eval’

May 8, 2026

Type Package

Title Perform Polynomial Evaluation of Linearity

Version 0.1.2

Author Vishesh Shrivastav

Maintainer Vishesh Shrivastav <vishesh2k6@gmail.com>

Description Evaluates whether the relationship between two vectors is linear or nonlinear. Performs a test to determine how well a linear model fits the data compared to higher order polynomial models. Jhang et al. (2004) <[doi:10.1043/1543-2165\(2004\)128%3C44:EOLITC%3E2.0.CO;2](https://doi.org/10.1043/1543-2165(2004)128%3C44:EOLITC%3E2.0.CO;2)>.

Imports broom

License MIT + file LICENSE

Encoding UTF-8

LazyData true

RoxygenNote 6.1.1

Suggests knitr

VignetteBuilder knitr

NeedsCompilation no

Repository CRAN

Date/Publication 2019-02-22 00:00:03 UTC

Contents

calculate_adl	2
poly_eval	2

Index	3
--------------	----------

calculate_adl	<i>Computes average deviation from linearity adl.</i>
---------------	---

Description

Computes average deviation from linearity adl.

Usage

```
calculate_adl(predicted.poly, predicted.lm)
```

Arguments

predicted.poly vector of predicted values from best-fitting polynomial model
 predicted.lm vector of predicted values from linear model

Value

value for average deviation from linearity as a percentage

poly_eval	<i>Establishes if relationship between two vectors is linear or nonlinear. Does not return any value. Prints details of the relationship between x and y.</i>
-----------	---

Description

Establishes if relationship between two vectors is linear or nonlinear. Does not return any value. Prints details of the relationship between x and y.

Usage

```
poly_eval(y, x, threshold)
```

Arguments

y vector of response values
 x vector of predictor values
 threshold optional argument. Threshold percentage value for average deviation from linearity. Defaults to 5.

Examples

```
foo <- c(1000, 4000, 5000, 4500, 3000, 4000, 9000, 11000, 15000, 12000, 7000, 3000)
bar <- c(9914, 40487, 54324, 50044, 34719, 42551, 94871, 118914, 158484, 131348, 78504, 36284)
poly_eval(bar, foo)
```

Index

`calculate_adl`, [2](#)

`poly_eval`, [2](#)