

Package ‘maptree’

May 8, 2026

Version 1.4-9

Date 2025-08-22

Title Mapping, Pruning, and Graphing Tree Models

Maintainer Robert B. Gramacy <rbg@vt.edu>

Depends R (>= 2.14), cluster, rpart

Description Functions with example data for graphing, pruning, and mapping models from hierarchical clustering, and classification and regression trees.

License Unlimited

Repository CRAN

Date/Publication 2025-07-22 23:50:33 UTC

NeedsCompilation no

Author Robert B. Gramacy [cre, aut],
Denis White [aut]

Contents

clip.clust	2
clip.rpart	3
draw.clust	4
draw.tree	5
group.clust	6
group.tree	7
kgs	8
map.groups	9
map.key	10
ngon	12
oregon.bird.dist	13
oregon.bird.names	14
oregon.border	15
oregon.env.vars	15
oregon.grid	16
twins.to.hclust	17

clip.clust	<i>Prunes a Hierarchical Cluster Tree</i>
------------	-------------------------------------------

Description

Reduces a hierarchical cluster tree to a smaller tree either by pruning until a given number of observation groups remain, or by pruning tree splits below a given height.

Usage

```
clip.clust (cluster, data=NULL, k=NULL, h=NULL)
```

Arguments

cluster	object of class hclust or twins.
data	clustered dataset for hclust application.
k	desired number of groups.
h	height at which to prune for grouping.

At least one of k or h must be specified; k takes precedence if both are given.

Details

Used with [draw.clust](#). See example.

Value

Pruned cluster object of class hclust.

Author(s)

Denis White

See Also

[hclust](#), [twins.object](#), [cutree](#), [draw.clust](#)

Examples

```
library (cluster)
data (oregon.bird.dist)

draw.clust (clip.clust (agnes (oregon.bird.dist), k=6))
```

`clip.rpart`*Prunes an Rpart Classification or Regression Tree*

Description

Reduces a prediction tree produced by [rpart](#) to a smaller tree by specifying either a cost-complexity parameter, or a number of nodes to which to prune.

Usage

```
clip.rpart (tree, cp=NULL, best=NULL)
```

Arguments

`tree` object of class `rpart`.
`cp` cost-complexity parameter.
`best` number of nodes to which to prune.
If both `cp` and `best` are not `NULL`, then `cp` is used.

Details

A minor enhancement of the existing [prune.rpart](#) to incorporate the parameter `best` as it is used in the (now defunct) `prune.tree` function in the old **tree** package. See example.

Value

Pruned tree object of class `rpart`.

Author(s)

Denis White

See Also

[rpart](#), [prune.rpart](#)

Examples

```
library (rpart)
data (oregon.env.vars, oregon.border, oregon.grid)

draw.tree (clip.rpart (rpart (oregon.env.vars), best=7),
           nodeinfo=TRUE, units="species", cases="cells", digits=0)

group <- group.tree (clip.rpart (rpart (oregon.env.vars), best=7))
names(group) <- row.names(oregon.env.vars)
map.groups (oregon.grid, group)
lines (oregon.border)
```

```
map.key (0.05, 0.65, labels=as.character(seq(6)),
        size=1, new=FALSE, sep=0.5, pch=19, head="node")
```

draw.clust

Graph a Hierarchical Cluster Tree

Description

Graph a hierarchical cluster tree of class `twins` or `hclust` using colored symbols at observations.

Usage

```
draw.clust (cluster, data=NULL, cex=par("cex"), pch=par("pch"), size=2.5*cex,
           col=NULL, nodeinfo=FALSE, cases="obs", new=TRUE)
```

Arguments

<code>cluster</code>	object of class <code>hclust</code> or <code>twins</code> .
<code>data</code>	clustered dataset for <code>hclust</code> application.
<code>cex</code>	size of text, <code>par</code> parameter.
<code>pch</code>	shape of symbol at leaves, <code>par</code> parameter.
<code>size</code>	size in <code>cex</code> units of symbol at leaves.
<code>col</code>	vector of colors from hsv , rgb , etc, or if <code>NULL</code> , then use rainbow .
<code>nodeinfo</code>	if <code>TRUE</code> , add a line at each node with number of observations included in each leaf.
<code>cases</code>	label for type of observations.
<code>new</code>	if <code>TRUE</code> , call plot.new .

Details

An alternative to [plot.hclust](#).

Value

The vector of colors supplied or generated.

Author(s)

Denis White

See Also

[agnes](#), [diana](#), [hclust](#), [draw.tree](#), [map.groups](#)

Examples

```
library (cluster)
data (oregon.bird.dist)

draw.clust (clip.clust (agnes (oregon.bird.dist), k=6))
```

draw.tree

*Graph a Classification or Regression Tree***Description**

Graph a classification or regression tree with a hierarchical tree diagram, optionally including colored symbols at leaves and additional info at intermediate nodes.

Usage

```
draw.tree (tree, cex=par("cex"), pch=par("pch"), size=2.5*cex,
  col=NULL, nodeinfo=FALSE, units="", cases="obs",
  digits=getOption("digits"), print.levels=TRUE,
  new=TRUE)
```

Arguments

tree	object of class <code>rpart</code> or <code>tree</code> .
cex	size of text, <code>par</code> parameter.
pch	shape of symbol at leaves, <code>par</code> parameter.
size	if <code>size=0</code> , draw terminal symbol at leaves else a symbol of size in <code>cex</code> units.
col	vector of colors from hsv , rgb , etc, or if <code>NULL</code> , then use rainbow .
nodeinfo	if <code>TRUE</code> , add a line at each node with mean value of response, number of observations, and percent deviance explained (or classified correct).
units	label for units of mean value of response, if regression tree.
cases	label for type of observations.
digits	number of digits to round mean value of response, if regression tree.
print.levels	if <code>TRUE</code> , print levels of factors at splits, otherwise only the factor name.
new	if <code>TRUE</code> , call plot.new .

Details

As in `plot.rpart(, uniform=TRUE)`, each level has constant depth. Specifying `nodeinfo=TRUE`, shows the deviance explained or the classification rate at each node.

A split is shown, for numerical variables, as `variable <> value` when the cases with lower values go left, or as `variable >< value` when the cases with lower values go right. When the splitting variable is a factor, and `print.levels=TRUE`, the split is shown as `levels = factor = levels` with the cases on the left having factor levels equal to those on the left of the factor name, and correspondingly for the right.

Value

The vector of colors supplied or generated.

Author(s)

Denis White

See Also

[rpart](#), [draw.clust](#), [map.groups](#)

Examples

```
library (rpart)
data (oregon.env.vars)

draw.tree (clip.rpart (rpart (oregon.env.vars), best=7),
           nodeinfo=TRUE, units="species", cases="cells", digits=0)
```

group.clust

Observation Groups for a Hierarchical Cluster Tree

Description

Alternative to [cutree](#) that orders pruned groups from left to right in draw order.

Usage

```
group.clust (cluster, k=NULL, h=NULL)
```

Arguments

cluster object of class hclust or twins.

k desired number of groups.

h height at which to prune for grouping.

At least one of k or h must be specified; k takes precedence if both are given.

Details

Normally used with [map.groups](#). See example.

Value

Vector of pruned cluster membership

Author(s)

Denis White

See Also

[hclust](#), [twins.object](#), [cutree](#), [map.groups](#)

Examples

```
data (oregon.bird.dist, oregon.grid)

group <- group.clust (hclust (dist (oregon.bird.dist)), k=6)
names(group) <- row.names(oregon.bird.dist)
map.groups (oregon.grid, group)
```

group.tree

Observation Groups for Classification or Regression Tree

Description

Alternative to `tree[["where"]]` that orders groups from left to right in draw order.

Usage

```
group.tree (tree)
```

Arguments

tree object of class rpart or tree.

Details

Normally used with [map.groups](#). See example.

Value

Vector of rearranged `tree[["where"]]`

Author(s)

Denis White

See Also

[rpart](#), [map.groups](#)

Examples

```
library (rpart)
data (oregon.env.vars, oregon.grid)

group <- group.tree (clip.rpart (rpart (oregon.env.vars), best=7))
names(group) <- row.names(oregon.env.vars)
map.groups (oregon.grid, group=group)
```

`kgs`*KGS Measure for Pruning Hierarchical Clusters*

Description

Computes the Kelley-Gardner-Sutcliffe penalty function for a hierarchical cluster tree.

Usage

```
kgs (cluster, diss, alpha=1, maxclust=NULL)
```

Arguments

<code>cluster</code>	object of class <code>hclust</code> or <code>twins</code> .
<code>diss</code>	object of class <code>dissimilarity</code> or <code>dist</code> .
<code>alpha</code>	weight for number of clusters.
<code>maxclust</code>	maximum number of clusters for which to compute measure.

Details

Kelley et al. (see reference) proposed a method that can help decide where to prune a hierarchical cluster tree. At any level of the tree the mean across all clusters of the mean within clusters of the dissimilarity measure is calculated. After normalizing, the number of clusters times alpha is added. The minimum of this function corresponds to the suggested pruning size.

The current implementation has complexity $O(n*n*maxclust)$, thus very slow with large n . For improvements, at least it should only calculate the spread for clusters that are split at each level, rather than over again for all.

Value

Vector of the penalty function for trees of size $2:maxclust$. The names of vector elements are the respective numbers of clusters.

Author(s)

Denis White

References

Kelley, L.A., Gardner, S.P., Sutcliffe, M.J. (1996) An automated approach for clustering an ensemble of NMR-derived protein structures into conformationally-related subfamilies, *Protein Engineering*, **9**, 1063-1065.

See Also

[twins.object](#), [dissimilarity.object](#), [hclust](#), [dist](#), [clip.clust](#),

Examples

```
library (cluster)
data (votes.repub)

a <- agnes (votes.repub, method="ward")
b <- kgs (a, a$diss, maxclust=20)
plot (names (b), b, xlab="# clusters", ylab="penalty")
```

map.groups

Map Groups of Observations

Description

Draws maps of groups of observations created by clustering, classification or regression trees, or some other type of classification.

Usage

```
map.groups (pts, group, pch=par("pch"), size=2, col=NULL,
            border=NULL, new=TRUE)
```

Arguments

pts	matrix or data frame with components "x", and "y" for each observation (see details).
group	vector of integer class numbers corresponding to pts (see details), and indexing colors in col.
pch	symbol number from par("pch") if < 100, otherwise parameter n for ngon.
size	size in cex units of point symbol.
col	vector of fill colors from hsv , rgb , etc, or if NULL, then use rainbow .
border	vector of border colors from hsv , rgb , etc, or if NULL, then use rainbow .
new	if TRUE, call plot.new .

Details

If the number of rows of pts is not equal to the length of group, then (1) pts are assumed to represent polygons and [polygon](#) is used, (2) the identifiers in group are matched to the polygons in pts through names(group) and pts\$x[is.na(pts\$y)], and (3) these identifiers are mapped to dense integers to reference colours. Otherwise, group is assumed to parallel pts, and, if pch < 100, then [points](#) is used, otherwise [ngon](#), to draw shaded polygon symbols for each observation in pts.

Value

The vector of fill colors supplied or generated.

Author(s)

Denis White

See Also[ngon](#), [polygon](#), [group.clust](#), [group.tree](#), [map.key](#)**Examples**

```

data (oregon.bird.names, oregon.env.vars, oregon.bird.dist)
data (oregon.border, oregon.grid)

# range map for American Avocet
spp <- match ("American avocet", oregon.bird.names[["common.name"]])
group <- oregon.bird.dist[,spp] + 1
names(group) <- row.names(oregon.bird.dist)
kol <- gray (seq(0.8,0.2,length.out=length (table (group))))
map.groups (oregon.grid, group=group, col=kol)
lines (oregon.border)

# distribution of January temperatures
cuts <- quantile (oregon.env.vars[["jan.temp"]], probs=seq(0,1,1/5))
group <- cut (oregon.env.vars[["jan.temp"]], cuts, labels=FALSE,
  include.lowest=TRUE)
names(group) <- row.names(oregon.env.vars)
kol <- gray (seq(0.8,0.2,length.out=length (table (group))))
map.groups (oregon.grid, group=group, col=kol)
lines (oregon.border)

# January temperatures using point symbols rather than polygons
map.groups (oregon.env.vars, group, col=kol, pch=19)
lines (oregon.border)

```

map.key

Draw Key to accompany Map of Groups

Description

Draws legends for maps of groups of observations.

Usage

```

map.key (x, y, labels=NULL, cex=par("cex"), pch=par("pch"),
  size=2.5*cex, col=NULL, head="", sep=0.25*cex, new=FALSE)

```

Arguments

x, y	coordinates of lower left position of key in proportional units (0-1) of plot.
labels	vector of labels for classes, or if NULL, then integers 1:length(col), or 1.
size	size in cex units of shaded key symbol.
pch	symbol number for <code>par</code> if < 100, otherwise parameter n for <code>ngon</code> .
cex	pointsize of text, <code>par</code> parameter.
head	text heading for key.
sep	separation in cex units between adjacent symbols in key. If <code>sep=0</code> , assume a continuous scale, use square symbols, and put labels at breaks between squares.
col	vector of colors from <code>hsv</code> , <code>rgb</code> , etc, or if NULL, then use <code>rainbow</code> .
new	if TRUE, call <code>plot</code> .

Details

Uses `points` or `ngon`, depending on value of `pch`, to draw shaded polygon symbols for key.

Value

The vector of colors supplied or generated.

Author(s)

Denis White

See Also

[ngon](#), [map.groups](#)

Examples

```
data (oregon.env.vars)

# key for examples in help(map.groups)
# range map for American Avocet
kol <- gray (seq(0.8,0.2,length.out=2))
map.key (0.2, 0.2, labels=c("absent","present"), pch=106,
        col=kol, head="key", new=TRUE)
# distribution of January temperatures
cuts <- quantile (oregon.env.vars[["jan.temp"]], probs=seq(0,1,1/5))
kol <- gray (seq(0.8,0.2,length.out=5))
map.key (0.2, 0.2, labels=as.character(round(cuts,0)),
        col=kol, sep=0, head="key", new=TRUE)

# key for example in help file for group.tree
map.key (0.2, 0.2, labels=as.character(seq(6)),
        pch=19, head="node", new=TRUE)
```

ngon *Outline or Fill a Regular Polygon*

Description

Draws a regular polygon at specified coordinates as an outline or shaded.

Usage

```
ngon (xydc, n=4, angle=0, type=1)
```

Arguments

xydc	four element vector with x and y coordinates of center, d diameter in mm, and c color.
n	number of sides for polygon (>8 => circle).
angle	rotation angle of figure, in degrees.
type	type=1 => interior filled, type=2 => edge, type=3 => both.

Details

Uses [polygon](#) to draw shaded polygons and [lines](#) for outline. If n is odd, there is a vertex at (0, d/2), otherwise the midpoint of a side is at (0, d/2).

Value

Invisible.

Author(s)

Denis White

See Also

[polygon](#), [lines](#), [map.key](#), [map.groups](#)

Examples

```
plot (c(0,1), c(0,1), type="n")
ngon (c(.5, .5, 10, "blue"), angle=30, n=3)
apply (cbind (runif(8), runif(8), 6, 2), 1, ngon)
```

oregon.bird.dist *Presence/Absence of Bird Species in Oregon, USA*

Description

Binary matrix (1 = present) for distributions of 248 native breeding bird species for 389 grid cells in Oregon, USA.

Usage

data (oregon.bird.dist)

Format

A data frame with 389 rows and 248 columns.

Details

Row names are hexagon identifiers from White et al. (1992). Column names are species element codes developed by The Nature Conservancy (TNC), the Oregon Natural Heritage Program (ONHP), and NatureServe.

Source

Denis White

References

Master, L. (1996) Predicting distributions for vertebrate species: some observations, *Gap Analysis: A Landscape Approach to Biodiversity Planning*, Scott, J.M., Tear, T.H., and Davis, F.W., editors, American Society for Photogrammetry and Remote Sensing, Bethesda, MD, pp. 171-176.

White, D., Preston, E.M., Freemark, K.E., Kiester, A.R. (1999) A hierarchical framework for conserving biodiversity, *Landscape ecological analysis: issues and applications*, Klopatek, J.M., Gardner, R.H., editors, Springer-Verlag, pp. 127-153.

White, D., Kimerling, A.J., Overton, W.S. (1992) Cartographic and geometric components of a global sampling design for environmental monitoring, *Cartography and Geographic Information Systems*, **19**(1), 5-22.

TNC, <https://www.nature.org/en-us/>

ONHP, <https://inr.oregonstate.edu/orbic>

NatureServe, <https://www.natureserve.org/>

See Also

[oregon.env.vars](#), [oregon.bird.names](#), [oregon.grid](#), [oregon.border](#)

oregon.bird.names *Names of Bird Species in Oregon, USA*

Description

Scientific and common names for 248 native breeding bird species in Oregon, USA.

Usage

```
data (oregon.bird.names)
```

Format

A data frame with 248 rows and 2 columns.

Details

Row names are species element codes. Columns are "scientific.name" and "common.name". Data are provided by The Nature Conservancy (TNC), the Oregon Natural Heritage Program (ONHP), and NatureServe.

Source

Denis White

References

Master, L. (1996) Predicting distributions for vertebrate species: some observations, *Gap Analysis: A Landscape Approach to Biodiversity Planning*, Scott, J.M., Tear, T.H., and Davis, F.W., editors, American Society for Photogrammetry and Remote Sensing, Bethesda, MD, pp. 171-176.

TNC, <https://www.nature.org/en-us/>

ONHP, <https://inr.oregonstate.edu/orbic>

NatureServe, <https://www.natureserve.org/>

See Also

[oregon.bird.dist](#)

oregon.border	<i>Boundary of Oregon, USA</i>
---------------	--------------------------------

Description

The boundary of the state of Oregon, USA, in [lines](#) format.

Usage

```
data (oregon.border)
```

Format

A data frame with 485 rows and 2 columns (the components "x" and "y").

Details

The map projection for this boundary, as well as the point coordinates in [oregon.env.vars](#), is the Lambert Conformal Conic with standard parallels at 33 and 45 degrees North latitude, with the longitude of the central meridian at 120 degrees, 30 minutes West longitude, and with the projection origin latitude at 41 degrees, 45 minutes North latitude.

Source

Denis White

oregon.env.vars	<i>Environmental Variables for Oregon, USA</i>
-----------------	------------------------------------------------

Description

Distributions of 10 environmental variables for 389 grid cells in Oregon, USA.

Usage

```
data (oregon.env.vars)
```

Format

A data frame with 389 rows and 10 columns.

Details

Row names are hexagon identifiers from White et al. (1992). Variables (columns) are

bird.spp	number of native breeding bird species
x	x coordinate of center of grid cell
y	y coordinate of center of grid cell
jan.temp	mean minimum January temperature (C)
jul.temp	mean maximum July temperature (C)
rng.temp	mean difference between July and January temperatures (C)
ann.ppt	mean annual precipitation (mm)
min.elev	minimum elevation (m)
rng.elev	range of elevation (m)
max.slope	maximum slope (percent)

Source

Denis White

References

White, D., Preston, E.M., Freemark, K.E., Kiester, A.R. (1999) A hierarchical framework for conserving biodiversity, *Landscape ecological analysis: issues and applications*, Klopatek, J.M., Gardner, R.H., editors, Springer-Verlag, pp. 127-153.

White, D., Kimerling, A.J., Overton, W.S. (1992) Cartographic and geometric components of a global sampling design for environmental monitoring, *Cartography and Geographic Information Systems*, **19**(1), 5-22.

See Also

[oregon.bird.dist](#), [oregon.grid](#), [oregon.border](#)

oregon.grid

Hexagonal Grid Cell Polygons covering Oregon, USA

Description

Polygon borders for 389 hexagonal grid cells covering Oregon, USA, in [polygon](#) format.

Usage

data (oregon.grid)

Format

A data frame with 3112 rows and 2 columns (the components "x" and "y").

Details

The polygon format used for these grid cell boundaries is a slight variation from the standard R/S format. Each cell polygon is described by seven coordinate pairs, the last repeating the first. Prior to the first coordinate pair of each cell is a row containing NA in the "y" column and, in the "x" column, an identifier for the cell. The identifiers are the same as the row names in [oregon.bird.dist](#) and [oregon.env.vars](#). See [map.groups](#) for how the linkage is made in mapping.

These grid cells are extracted from a larger set covering the conterminous United States and adjacent parts of Canada and Mexico, as described in White et al. (1992). Only cells with at least 50 percent of their area contained within the state of Oregon are included.

The map projection for the coordinates, as well as the point coordinates in [oregon.env.vars](#), is the Lambert Conformal Conic with standard parallels at 33 and 45 degrees North latitude, with the longitude of the central meridian at 120 degrees, 30 minutes West longitude, and with the projection origin latitude at 41 degrees, 45 minutes North latitude.

Source

Denis White

References

White, D., Kimerling, A.J., Overton, W.S. (1992) Cartographic and geometric components of a global sampling design for environmental monitoring, *Cartography and Geographic Information Systems*, **19**(1), 5-22.

twins.to.hclust

Converts agnes or diana object to hclust object

Description

Alternative to [as.hclust](#) that retains cluster data.

Usage

```
twins.to.hclust (cluster)
```

Arguments

cluster object of class twins.

Details

Used internally in with [clip.clust](#) and [draw.clust](#).

Value

hclust object

Author(s)

Denis White

See Also

[hclust](#), [twins.object](#)

Index

- * **aplot**
 - map.key, 10
 - ngon, 12
- * **cluster**
 - clip.clust, 2
 - clip.rpart, 3
 - draw.clust, 4
 - group.clust, 6
 - kgs, 8
 - map.groups, 9
 - twins.to.hclust, 17
- * **datasets**
 - oregon.bird.dist, 13
 - oregon.bird.names, 14
 - oregon.border, 15
 - oregon.env.vars, 15
 - oregon.grid, 16
- * **hplot**
 - draw.clust, 4
 - draw.tree, 5
 - map.groups, 9
 - map.key, 10
- * **manip**
 - clip.clust, 2
 - clip.rpart, 3
 - group.clust, 6
 - group.tree, 7
 - kgs, 8
 - twins.to.hclust, 17
- * **tree**
 - draw.tree, 5
 - group.tree, 7
 - map.groups, 9
- agnes, 4
- as.hclust, 17
- clip.clust, 2, 8, 17
- clip.rpart, 3
- cutree, 2, 6, 7
- diana, 4
- dissimilarity.object, 8
- dist, 8
- draw.clust, 2, 4, 6, 17
- draw.tree, 4, 5
- group.clust, 6, 10
- group.tree, 7, 10
- hclust, 2, 4, 7, 8, 18
- hsv, 4, 5, 9, 11
- kgs, 8
- lines, 12, 15
- map.groups, 4, 6, 7, 9, 11, 12, 17
- map.key, 10, 10, 12
- ngon, 9–11, 12
- oregon.bird.dist, 13, 14, 16, 17
- oregon.bird.names, 13, 14
- oregon.border, 13, 15, 16
- oregon.env.vars, 13, 15, 15, 17
- oregon.grid, 13, 16, 16
- par, 11
- plot, 11
- plot.hclust, 4
- plot.new, 4, 5, 9
- points, 9, 11
- polygon, 9, 10, 12, 16
- prune.rpart, 3
- rainbow, 4, 5, 9, 11
- rgb, 4, 5, 9, 11
- rpart, 3, 6, 7
- twins.object, 2, 7, 8, 18
- twins.to.hclust, 17