

Package ‘mashr’

May 8, 2026

Type Package

Encoding UTF-8

Title Multivariate Adaptive Shrinkage

Version 0.2.79

Date 2023-10-18

Description Implements the multivariate adaptive shrinkage (mash) method of Urbut et al (2019) <[DOI:10.1038/s41588-018-0268-8](https://doi.org/10.1038/s41588-018-0268-8)> for estimating and testing large numbers of effects in many conditions (or many outcomes). Mash takes an empirical Bayes approach to testing and effect estimation; it estimates patterns of similarity among conditions, then exploits these patterns to improve accuracy of the effect estimates. The core linear algebra is implemented in C++ for fast model fitting and posterior computation.

URL <https://github.com/stephenslab/mashr>

BugReports <https://github.com/stephenslab/mashr/issues>

License BSD_3_clause + file LICENSE

Copyright file COPYRIGHTS

Depends R (>= 3.3.0), ashR (>= 2.2-22)

Imports assertthat, utils, stats, plyr, rmeta, Rcpp (>= 1.0.8), mvtnorm, abind, softImpute

LinkingTo Rcpp, RcppArmadillo, RcppGSL (>= 0.3.8)

Suggests MASS, REBayes, corrplot (>= 0.90), testthat, kableExtra, knitr, rmarkdown, profmem, flashier, ebnm

VignetteBuilder knitr

NeedsCompilation yes

Biarch true

RoxygenNote 7.2.3

Author Matthew Stephens [aut],
Sarah Urbut [aut],
Gao Wang [aut],

Yuxin Zou [aut],
 Yunqi Yang [ctb],
 Sam Roweis [cph],
 David Hogg [cph],
 Jo Bovy [cph],
 Peter Carbonetto [aut, cre]

Maintainer Peter Carbonetto <peter.carbonetto@gmail.com>

Repository CRAN

Date/Publication 2023-10-18 16:20:02 UTC

Contents

contrast_matrix	3
cov_canonical	3
cov_ed	4
cov_flash	5
cov_pca	6
cov_udi	7
estimate_null_correlation_simple	8
extreme_deconvolution	8
get_estimated_pi	11
get_log10bf	12
get_n_significant_conditions	13
get_pairwise_sharing	13
get_pairwise_sharing_from_samples	14
get_samples	15
get_significant_results	16
mash	16
mash_1by1	19
mash_compute_loglik	19
mash_compute_posterior_matrices	20
mash_compute_vloglik	21
mash_estimate_corr_em	22
mash_plot_meta	24
mash_set_data	24
mash_update_data	25
simple_sims	26
simple_sims2	27
sim_contrast1	27
sim_contrast2	28

Index

29

contrast_matrix	<i>Create contrast matrix</i>
-----------------	-------------------------------

Description

Create contrast matrix

Usage

```
contrast_matrix(R, ref, name = 1:R)
```

Arguments

R	the number of column for the contrast matrix
ref	the reference group. It could be a number between 1,..., R, R is number of conditions, or the name of reference group. If there is no reference group, it can be the string 'mean'.
name	a length R vector contains the name for conditions

Examples

```
contrast_matrix(5, 'mean')
```

cov_canonical	<i>Compute a list of canonical covariance matrices</i>
---------------	--

Description

Compute a list of canonical covariance matrices

Usage

```
cov_canonical(
  data,
  cov_methods = c("identity", "singletons", "equal_effects", "simple_het")
)
```

Arguments

data	a mash data object, eg as created by mash_set_data
cov_methods	a vector of strings indicating the matrices to be used: "identity" for the identity (effects are independent among conditions); "singletons" for the set of matrices with just one non-zero entry $x_{jj} = 1, j = 1, \dots, R$; (effect specific to condition j); "equal_effects" for the matrix of all 1s (effects are equal among conditions); "simple_het" for a set of matrices with 1s on the diagonal and all off-diagonal elements equal to 0.25, 0.5 or 0.75; see cov_simple_het for details; (effects are correlated among conditions).

Details

The default is that this function computes covariance matrices corresponding to the "bmalite" models.

Value

a list of covariance matrices

Examples

```
data = mash_set_data(Bhat = cbind(c(1,2),c(3,4)), Shat = cbind(c(1,1),c(1,1)))
cov_canonical(data)
cov_canonical(data,"singletons")
cov_canonical(data,c("id","sing")) # can use partial matching of names
```

cov_ed	<i>Perform "extreme deconvolution" (Bovy et al) on a subset of the data</i>
--------	---

Description

Perform "extreme deconvolution" (Bovy et al) on a subset of the data

Usage

```
cov_ed(data, Ulist_init, subset = NULL, algorithm = c("bovy", "teem"), ...)
```

Arguments

data	a mash data object
Ulist_init	a named list of covariance matrices to use to initialize ED; default is to use matrices from PCs
subset	a subset of data to be used when ED is run (set to NULL for all the data)
algorithm	algorithm to run ED
...	other arguments to be passed to ED algorithm, see extreme_deconvolution for algorithm 'bovy', or teem_wrapper for algorithm 'teem'

Details

Runs the extreme deconvolution algorithm from Bovy et al (Annals of Applied Statistics) to estimate data-driven covariance matrices. It can be initialized with, for example running `cov_pca` with, say, 5 PCs.

Examples

```
## Not run:
data = mash_set_data(Bhat = cbind(c(1,2),c(3,4)), Shat = cbind(c(1,1),c(1,1)))
U_pca = cov_pca(data,2)
U_x = apply(data$Bhat, 2, function(x) x - mean(x))
U_xx = t(U_x) %*% U_x / nrow(U_x)
cov_ed(data,c(U_pca, list(xx = U_xx)))

## End(Not run)
```

cov_flash	<i>Perform Empirical Bayes Matrix Factorization using flashier, and return a list of candidate covariance matrices</i>
-----------	--

Description

Perform Empirical Bayes Matrix Factorization using flashier, and return a list of candidate covariance matrices

Usage

```
cov_flash(
  data,
  factors = c("default", "nonneg"),
  subset = NULL,
  remove_singleton = FALSE,
  tag = NULL,
  output_model = NULL,
  greedy_args = list(),
  backfit_args = list()
)
```

Arguments

data	A “mash” data object.
factors	If factors = “default”, the factors and loadings are both unconstrained. If factors = “nonneg”, the factors are constrained to be non-negative, and the loadings are unconstrained.
subset	Data samples (rows) used to estimate the covariances. Sset to NULL to use all the data.
remove_singleton	If remove_singleton = TRUE, factors corresponding to singleton matrices will be removed from the output.
tag	How to name the covariance matrices.
output_model	The fitted flash model will be saved to this file (using saveRDS).
greedy_args	List containing additional parameters passed to flashier::flash_greedy.
backfit_args	List containing additional parameters passed to flashier::flash_backfit.

Value

A list of covariance matrices.

Examples

```
# See https://stephenslab.github.io/mashr/articles/flash\_mash.html  
# for an example
```

cov_pca	<i>Perform PCA on data and return list of candidate covariance matrices</i>
---------	---

Description

Perform PCA on data and return list of candidate covariance matrices

Usage

```
cov_pca(data, npc, subset = NULL)
```

Arguments

data	a mash data object
npc	the number of PCs to use
subset	indices of the subset of data to use (set to NULL for all data)

Value

Returns a list of covariance matrices: the npc rank-one covariance matrices based on the first npc PCs, and the rank npc covariance matrix. If flashier did not identify any factors, NULL is returned.

Examples

```
data = mash_set_data(Bhat = cbind(c(1,2),c(3,4)), Shat = cbind(c(1,1),c(1,1)))  
cov_pca(data,2)
```

cov_udi	<i>Compute a list of covariance matrices corresponding to the "Unassociated", "Directly associated" and "Indirectly associated" models</i>
---------	--

Description

Compute a list of covariance matrices corresponding to the "Unassociated", "Directly associated" and "Indirectly associated" models

Usage

```
cov_udi(data, model = udi_model_matrix(n_conditions(data)))
```

Arguments

data	a mash data object, eg as created by mash_set_data
model	a model matrix with R columns, where R is the number of conditions in the data; each row should be a vector of length R with elements "U", "D" and "I" indicating whether each effect is Unassociated, Directly associated or Indirectly associated

Details

If model is specified then this returns the covariance matrices for those models. The default creates all possible models. For a description of the "Unassociated", "Directly associated" and "Indirectly associated" models see Stephens M (2013), A unified framework for Association Analysis with Multiple Related Phenotypes, PLoS ONE.

Value

a named list of covariance matrices

Examples

```
data = mash_set_data(Bhat = cbind(c(1,2),c(3,4)), Shat = cbind(c(1,1),c(1,1)))
cov_udi(data)
cov_udi(data,c('I','D'))
```

```
estimate_null_correlation_simple
```

Estimate null correlations (simple)

Description

Estimates a null correlation matrix from data using simple z score threshold

Usage

```
estimate_null_correlation_simple(data, z_thresh = 2, est_cor = TRUE)
```

Arguments

data	a mash data object, eg as created by <code>mash_set_data</code>
z_thresh	the z score threshold below which to call an effect null
est_cor	whether to estimate correlation matrix (TRUE) or the covariance matrix (FALSE).

Details

Returns a simple estimate of the correlation matrix (or covariance matrix) among conditions under the null. Specifically, the simple estimate is the empirical correlation (or covariance) matrix of the z scores for those effects that have (absolute) z score $< z_thresh$ in all conditions.

Examples

```
simdata = simple_sims(50,5,1)
data = mash_set_data(simdata$Bhat, simdata$Shat)
estimate_null_correlation_simple(data)
```

extreme_deconvolution *Density estimation using Gaussian mixtures in the presence of noisy, heterogeneous and incomplete data*

Description

We present a general algorithm to infer a d-dimensional distribution function given a set of heterogeneous, noisy observations or samples. This algorithm reconstructs the error-deconvolved or 'underlying' distribution function common to all samples, even when the individual samples have unique error and missing-data properties. The underlying distribution is modeled as a mixture of Gaussians, which is completely general. Model parameters are chosen to optimize a justified, scalar objective function: the logarithm of the probability of the data under the error-convolved model, where the error convolution is different for each data point. Optimization is performed by an Expectation Maximization (EM) algorithm, extended by a regularization technique and 'split-and-merge' procedure. These extensions mitigate problems with singularities and local maxima, which are often encountered when using the EM algorithm to estimate Gaussian density mixtures.

Usage

```

extreme_deconvolution(
  ydata,
  ycovar,
  xamp,
  xmean,
  xcovar,
  projection = NULL,
  weight = NULL,
  fixamp = NULL,
  fixmean = NULL,
  fixcovar = NULL,
  tol = 1e-06,
  maxiter = 1e+09,
  w = 0,
  logfile = NULL,
  splitnmerge = 0,
  maxsnm = FALSE,
  likeonly = FALSE,
  logweight = FALSE
)

```

Arguments

ydata	[ndata,dy] matrix of observed quantities
ycovar	[ndata,dy] / [ndata,dy,dy] / [dy,dy,ndata] matrix, list or 3D array of observational error covariances (if [ndata,dy] then the error correlations are assumed to vanish)
xamp	[ngauss] array of initial amplitudes (*not* [1,ngauss])
xmean	[ngauss,dx] matrix of initial means
xcovar	[ngauss,dx,dx] list of matrices of initial covariances
projection	[ndata,dy,dx] list of projection matrices
weight	[ndata] array of weights to be applied to the data points
fixamp	(default=None) None, True/False, or list of bools
fixmean	(default=None) None, True/False, or list of bools
fixcovar	(default=None) None, True/False, or list of bools
tol	(double, default=1.e-6) tolerance for convergence
maxiter	(long, default= 10**9) maximum number of iterations to perform
w	(double, default=0.) covariance regularization parameter (of the conjugate prior)
logfile	basename for several logfiles (_c.log has output from the c-routine; _loglike.log has the log likelihood path of all the accepted routes, i.e. only parts which increase the likelihood are included, during splitnmerge)
splitnmerge	(int, default=0) depth to go down the splitnmerge path
maxsnm	(Bool, default=False) use the maximum number of split 'n' merge steps, $K*(K-1)*(K-2)/2$

likeonly (Bool, default=False) only compute the total log likelihood of the data
 logweight (bool, default=False) if True, weight is actually log(weight)

Value

avgloglikedata avgloglikedata after convergence
 xamp updated xamp
 xmean updated xmean
 xcovar updated xcovar

Author(s)

Jo Bovy, David W. Hogg, & Sam T. Roweis

References

Inferring complete distribution functions from noisy, heterogeneous and incomplete observations
 Jo Bovy, David W. Hogg, & Sam T. Roweis, Submitted to AOAS (2009) [arXiv/0905.2979]

Examples

```
## Not run:
ydata <-
c(2.62434536, 0.38824359, 0.47182825, -0.07296862, 1.86540763,
-1.30153870, 2.74481176, 0.23879310, 1.31903910, 0.75062962,
2.46210794, -1.06014071, 0.67758280, 0.61594565, 2.13376944,
-0.09989127, 0.82757179, 0.12214158, 1.04221375, 1.58281521,
-0.10061918, 2.14472371, 1.90159072, 1.50249434, 1.90085595,
0.31627214, 0.87710977, 0.06423057, 0.73211192, 1.53035547,
0.30833925, 0.60324647, 0.31282730, 0.15479436, 0.32875387,
0.98733540, -0.11731035, 1.23441570, 2.65980218, 1.74204416,
0.80816445, 0.11237104, 0.25284171, 2.69245460, 1.05080775,
0.36300435, 1.19091548, 3.10025514, 1.12015895, 1.61720311,
1.30017032, 0.64775015, -0.14251820, 0.65065728, 0.79110577,
1.58662319, 1.83898341, 1.93110208, 1.28558733, 1.88514116,
0.24560206, 2.25286816, 1.51292982, 0.70190717, 1.48851815,
0.92442829, 2.13162939, 2.51981682, 3.18557541, -0.39649633,
-0.44411380, 0.49553414, 1.16003707, 1.87616892, 1.31563495,
-1.02220122, 0.69379599, 1.82797464, 1.23009474, 1.76201118,
0.77767186, 0.79924193, 1.18656139, 1.41005165, 1.19829972,
1.11900865, 0.32933771, 1.37756379, 1.12182127, 2.12948391,
2.19891788, 1.18515642, 0.62471505, 0.36126959, 1.42349435,
1.07734007, 0.65614632, 1.04359686, 0.37999916, 1.69803203,
0.55287144, 2.22450770, 1.40349164, 1.59357852, -0.09491185,
1.16938243, 1.74055645, 0.04629940, 0.73378149, 1.03261455,
-0.37311732, 1.31515939, 1.84616065, 0.14048406, 1.35054598,
-0.31228341, 0.96130449, -0.61577236, 2.12141771, 1.40890054,
0.97538304, 0.22483838, 2.27375593, 2.96710175, -0.85798186,
2.23616403, 2.62765075, 1.33801170, -0.19926803, 1.86334532,
0.81907970, 0.39607937, -0.23005814, 1.55053750, 1.79280687,
0.37646927, 1.52057634, -0.14434139, 1.80186103, 1.04656730,
```

```

0.81343023, 0.89825413, 1.86888616, 1.75041164, 1.52946532,
1.13770121, 1.07782113, 1.61838026, 1.23249456, 1.68255141,
0.68988323, -1.43483776, 2.03882460, 3.18697965, 1.44136444,
0.89984477, 0.86355526, 0.88094581, 1.01740941, -0.12201873,
0.48290554, 0.00297317, 1.24879916, 0.70335885, 1.49521132,
0.82529684, 1.98633519, 1.21353390, 3.19069973, -0.89636092,
0.35308331, 1.90148689, 3.52832571, 0.75136522, 1.04366899,
0.77368576, 2.33145711, 0.71269214, 1.68006984, 0.68019840,
-0.27255875, 1.31354772, 1.50318481, 2.29322588, 0.88955297,
0.38263794, 1.56276110, 1.24073709, 1.28066508, 0.92688730,
2.16033857, 1.36949272, 2.90465871, 2.11105670, 1.65904980,
-0.62743834, 1.60231928, 1.42028220, 1.81095167, 2.04444209)

ydata <- matrix(ydata,length(ydata),1)
N <- dim(ydata)[1]
ycovar <- ydata*0 + 0.01
xamp <- c(0.5,0.5)
xmean <- matrix(c(0.86447943, 0.67078879, 0.322681, 0.45087394),2,2)
xcovar <-
  list(matrix(c(0.03821028, 0.04014796, 0.04108113, 0.03173839),2,2),
        matrix(c(0.06219194, 0.09738021, 0.04302473, 0.06778009),2,2))
projection <- list()
for (i in 1:N)
  projection[[i]] = matrix(c(i%2,(i+1)%2),1,2)
res <- extreme_deconvolution(ydata, ycovar, xamp, xmean, xcovar,
  projection=projection, logfile="ExDeconDemo")

## End(Not run)

```

get_estimated_pi *Return the estimated mixture proportions*

Description

Return the estimated mixture proportions

Usage

```
get_estimated_pi(m, dimension = c("cov", "grid", "all"))
```

Arguments

m	the mash result
dimension	indicates whether you want the mixture proportions for the covariances, grid, or all

Details

If the fit was done with 'usepointmass=TRUE' then the first element of the returned vector will correspond to the null, and the remaining elements to the non-null covariance matrices. Suppose the fit was done with K covariances and a grid of length L . If 'dimension=cov' then the returned vector will be of length K (or $K+1$ if 'usepointmass=TRUE'). If 'dimension=grid' then the returned vector will be of length L (or $L+1$). If 'dimension=all' then the returned vector will be of length LK (or $LK+1$). The names of the vector will be informative for which combination each element corresponds to.

Value

a named vector containing the estimated mixture proportions.

get_log10bf	<i>Return the Bayes Factor for each effect</i>
-------------	--

Description

Return the Bayes Factor for each effect

Usage

```
get_log10bf(m)
```

Arguments

`m` the mash result (from joint or lbyl analysis); must have been computed using usepointmass=TRUE

Value

if `m` was fitted using usepointmass=TRUE then returns a vector of the $\log_{10}(\text{bf})$ values for each effect. That is, the j th element $\text{lbf}[j]$ is $\log_{10}(\text{Pr}(B_j \mid g=\text{ghat-nonnull})/\text{Pr}(B_j \mid g = 0))$ where `ghat-nonnull` is the non-null part of `ghat`. Otherwise returns NULL.

Examples

```
simdata = simple_sims(50,5,1)
data = mash_set_data(simdata$Bhat, simdata$Shat)
m = mash(data, cov_canonical(data))
get_log10bf(m)
```

get_n_significant_conditions
Count number of conditions each effect is significant in

Description

Count number of conditions each effect is significant in

Usage

```
get_n_significant_conditions(  
  m,  
  thresh = 0.05,  
  conditions = NULL,  
  sig_fn = get_lfsr  
)
```

Arguments

m	the mash result (from joint or lbyl analysis)
thresh	indicates the threshold below which to call signals significant
conditions	which conditions to include in check (default to all)
sig_fn	the significance function used to extract significance from mash object; eg could be ashrr::get_lfsr or ashrr::get_lfdr

Value

a vector containing the number of significant conditions

Examples

```
simdata = simple_sims(50,5,1)  
data = mash_set_data(simdata$Bhat, simdata$Shat)  
m = mash(data, cov_canonical(data))  
get_n_significant_conditions(m)
```

get_pairwise_sharing *Compute the proportion of (significant) signals shared by magnitude in each pair of conditions, based on the poterior mean*

Description

Compute the proportion of (significant) signals shared by magnitude in each pair of conditions, based on the poterior mean

Usage

```
get_pairwise_sharing(m, factor = 0.5, lfsr_thresh = 0.05, FUN = identity)
```

Arguments

m	the mash fit
factor	a number in [0,1] the factor within which effects are considered to be shared
lfsr_thresh	the lfsr threshold for including an effect in the assessment
FUN	a function to be applied to the estimated effect sizes before assessing sharing. The most obvious choice beside the default 'FUN=identity' would be 'FUN=abs' if you want to ignore the sign of the effects when assessing sharing.

Details

For each pair of tissues, first identify the effects that are significant (by $lfsr < lfsr_thresh$) in at least one of the two tissues. Then compute what fraction of these have an estimated (posterior mean) effect size within a factor 'factor' of one another. The results are returned as an R by R matrix.

Examples

```
simdata = simple_sims(50,5,1)
data = mash_set_data(simdata$Bhat, simdata$Shat)
m = mash(data, cov_canonical(data))
get_pairwise_sharing(m) # sharing by magnitude (same sign)
get_pairwise_sharing(m, factor=0) # sharing by sign
get_pairwise_sharing(m, FUN=abs) # sharing by magnitude when sign is ignored
```

```
get_pairwise_sharing_from_samples
```

Compute the proportion of (significant) signals shared by magnitude in each pair of conditions

Description

Compute the proportion of (significant) signals shared by magnitude in each pair of conditions

Usage

```
get_pairwise_sharing_from_samples(
  m,
  factor = 0.5,
  lfsr_thresh = 0.05,
  FUN = identity
)
```

Arguments

m	the mash fit with samples from posteriors
factor	a number in [0,1] the factor within which effects are considered to be shared
lfsr_thresh	the lfsr threshold for including an effect in the assessment
FUN	a function to be applied to the estimated effect sizes before assessing sharing. The most obvious choice beside the default 'FUN=identity' would be 'FUN=abs' if you want to ignore the sign of the effects when assessing sharing.

Details

For each pair of conditions, compute the fraction of effects that are within a factor 'factor' of one another. The results are returned as an R by R matrix.

Examples

```
simdata = simple_sims(50,5,1)
data = mash_set_data(simdata$Bhat, simdata$Shat)
m = mash(data, cov_canonical(data), posterior_samples=5, algorithm='R')
get_pairwise_sharing_from_samples(m) # sharing by magnitude (same sign)
get_pairwise_sharing_from_samples(m, factor=0) # sharing by sign
get_pairwise_sharing_from_samples(m, FUN=abs) # sharing by magnitude when sign is ignored
```

get_samples	<i>Return samples from a mash object</i>
-------------	--

Description

Return samples from a mash object

Usage

```
get_samples(m)
```

Arguments

m	The mash fit.
---	---------------

Examples

```
simdata = simple_sims(50,5,1)
data = mash_set_data(simdata$Bhat, simdata$Shat)
m = mash(data, cov_canonical(data), posterior_samples=5, algorithm='R')
get_samples(m)
```

```
get_significant_results
```

Find effects that are significant in at least one condition

Description

Find effects that are significant in at least one condition

Usage

```
get_significant_results(m, thresh = 0.05, conditions = NULL, sig_fn = get_lfsr)
```

Arguments

<code>m</code>	the mash result (from joint or 1by1 analysis)
<code>thresh</code>	indicates the threshold below which to call signals significant
<code>conditions</code>	which conditions to include in check (default to all)
<code>sig_fn</code>	the significance function used to extract significance from mash object; eg could be <code>ashr::get_lfsr</code> or <code>ashr::get_lfdr</code> . (Small values must indicate significant.)

Value

a vector containing the indices of the significant effects, by order of most significant to least

Examples

```
simdata = simple_sims(50,5,1)
data = mash_set_data(simdata$Bhat, simdata$Shat)
m = mash(data, cov_canonical(data))
get_significant_results(m)
```

```
mash
```

Apply mash method to data

Description

Apply mash method to data

Usage

```

mash(
  data,
  Ulist = NULL,
  gridmult = sqrt(2),
  grid = NULL,
  normalizeU = TRUE,
  usepointmass = TRUE,
  g = NULL,
  fixg = FALSE,
  prior = c("nullbiased", "uniform"),
  nullweight = 10,
  optmethod = c("mixSQP", "mixIP", "mixEM", "cxxMixSquarem"),
  control = list(),
  verbose = TRUE,
  add.mem.profile = FALSE,
  algorithm.version = c("Rcpp", "R"),
  pi_thresh = 1e-10,
  A = NULL,
  posterior_samples = 0,
  seed = 123,
  outputlevel = 2,
  output_lfdr = FALSE
)

```

Arguments

<code>data</code>	a mash data object containing the Bhat matrix, standard errors, alpha value; created using <code>mash_set_data</code> or <code>mash_set_data_contrast</code>
<code>Ulist</code>	a list of covariance matrices to use (see <code>normalizeU</code> for rescaling these matrices)
<code>gridmult</code>	scalar indicating factor by which adjacent grid values should differ; close to 1 for fine grid
<code>grid</code>	vector of grid values to use (scaling factors ω in paper)
<code>normalizeU</code>	whether or not to normalize the U covariances to have maximum of 1 on diagonal
<code>usepointmass</code>	whether to include a point mass at 0, corresponding to null in every condition
<code>g</code>	the value of g obtained from a previous mash fit - an alternative to supplying <code>Ulist</code> , <code>grid</code> and <code>usepointmass</code>
<code>fixg</code>	if g is supplied, allows the mixture proportions to be fixed rather than estimated; e.g., useful for fitting mash to test data after fitting it to training data
<code>prior</code>	indicates what penalty to use on the likelihood, if any
<code>nullweight</code>	scalar, the weight put on the prior under "nullbiased" specification, see "prior".
<code>optmethod</code>	name of optimization method to use
<code>control</code>	A list of control parameters passed to <code>optmethod</code> .
<code>verbose</code>	If TRUE, print progress to R console.

<code>add.mem.profile</code>	If TRUE, print memory usage to R console (requires R library ‘ <code>profmem</code> ’).
<code>algorithm.version</code>	Indicates whether to use R or Rcpp version
<code>pi_thresh</code>	threshold below which mixture components are ignored in computing posterior summaries (to speed calculations by ignoring negligible components)
<code>A</code>	the linear transformation matrix, $Q \times R$ matrix. This is used to compute the posterior for Ab .
<code>posterior_samples</code>	the number of samples to be drawn from the posterior distribution of each effect.
<code>seed</code>	A random number seed to use when sampling from the posteriors. It is used when <code>posterior_samples > 0</code> .
<code>outputlevel</code>	controls amount of computation / output; 1: output only estimated mixture component proportions, 2: and posterior estimates, 3: and posterior covariance matrices, 4: and likelihood matrices
<code>output_lfdr</code>	If <code>output_lfdr = TRUE</code> , output local false discovery rate estimates. The lfdr tends to be sensitive to mis-estimated covariance matrices, and generally we do not recommend using them; we recommend using the local false sign rate (lfsr) instead, which is always returned, even when <code>output_lfdr = TRUE</code> .

Value

a list with elements `result`, `loglik` and `fitted_g`

Examples

```
Bhat = matrix(rnorm(100),ncol=5) # create some simulated data
Shat = matrix(rep(1,100),ncol=5)
data = mash_set_data(Bhat,Shat, alpha=1)
U.c = cov_canonical(data)
res.mash = mash(data,U.c)

# Run mash with penalty exponent on null term equal to 100.
# See "False discovery rates: a new deal" (M. Stephens 2017),
# supplementary material S.2.5 for more details.
set.seed(1)
simdata = simple_sims(500,5,1)
data = mash_set_data(simdata$Bhat,simdata$Shat)
U.c = cov_canonical(data)
res0 = mash(data,U.c)
res1 = mash(data,U.c,prior = "nullbiased",nullweight = 101)
plot(res0$fitted_g$pi,res1$fitted_g$pi,pch = 20)
abline(a = 0,b = 1,col = "skyblue",lty = "dashed")
```

mash_1by1	<i>Perform condition-by-condition analyses</i>
-----------	--

Description

Performs simple "condition-by-condition" analysis by running ash from package ash on data from each condition, one at a time. May be a useful first step to identify top hits in each condition before a mash analysis.

Usage

```
mash_1by1(data, alpha = 0, ...)
```

Arguments

data	A list with the following two elements: Bhat an n by R matrix of observations (n units in R conditions); and Shat, an n by R matrix of standard errors (n units in R conditions),
alpha	Numeric value of alpha parameter in the model. alpha = 0 for Exchangeable Effects (EE), alpha = 1 for Exchangeable Z-scores (EZ).
...	optionally, other parameters to be passed to ash

Value

A list similar to the output of mash, particularly including posterior matrices.

Examples

```
simdata = simple_sims(50,5,1)
mash_1by1(simdata)
```

mash_compute_loglik	<i>Compute loglikelihood for fitted mash object on new data.</i>
---------------------	--

Description

Compute loglikelihood for fitted mash object on new data.

Usage

```
mash_compute_loglik(g, data, algorithm.version = c("Rcpp", "R"))
```

Arguments

g A mash object or the fitted_g from a mash object.
data A set of data on which to compute the loglikelihood.
algorithm.version Indicate R or Rcpp version

Details

The log-likelihood for each element is $p(Bhat_j|Shat_j, g, \alpha)$ where $Bhat_j|B_j, Shat_j \sim N(B_j, Shat_j)$ and $B_j/Shat_j^\alpha|Shat_j \sim g$.

Value

The log-likelihood for data computed using g.

Examples

```

simdata = simple_sims(50,5,1)
data = mash_set_data(simdata$Bhat, simdata$Shat)
m = mash(data, cov_canonical(data))
mash_compute_loglik(m,data)

```

mash_compute_posterior_matrices

Compute posterior matrices for fitted mash object on new data

Description

Compute posterior matrices for fitted mash object on new data

Usage

```

mash_compute_posterior_matrices(
  g,
  data,
  pi_thresh = 1e-10,
  algorithm.version = c("Rcpp", "R"),
  A = NULL,
  output_posterior_cov = FALSE,
  posterior_samples = 0,
  seed = 123
)

```

Arguments

<code>g</code>	a mash object or the fitted_g from a mash object.
<code>data</code>	a set of data on which to compute the posterior matrices
<code>pi_thresh</code>	threshold below which mixture components are ignored in computing posterior summaries (to speed calculations by ignoring negligible components)
<code>algorithm.version</code>	Indicates whether to use R or Rcpp version
<code>A</code>	the linear transformation matrix, Q x R matrix. This is used to compute the posterior for Ab.
<code>output_posterior_cov</code>	whether or not to output posterior covariance matrices for all effects
<code>posterior_samples</code>	the number of samples to be drawn from the posterior distribution of each effect.
<code>seed</code>	a random number seed to use when sampling from the posteriors. It is used when <code>posterior_samples > 0</code> .

Value

A list of posterior matrices

Examples

```
simdata = simple_sims(50,5,1)
data = mash_set_data(simdata$Bhat, simdata$Shat)
m = mash(data, cov_canonical(data))
mash_compute_posterior_matrices(m,data)
```

`mash_compute_vloglik` *Compute vector of loglikelihood for fitted mash object on new data*

Description

Compute vector of loglikelihood for fitted mash object on new data

Usage

```
mash_compute_vloglik(g, data, algorithm.version = c("Rcpp", "R"))
```

Arguments

<code>g</code>	A mash object.
<code>data</code>	A set of data on which to compute the loglikelihood.
<code>algorithm.version</code>	Indicate R or Rcpp version

Details

The log-likelihood for each element is $p(Bhat_j|Shat_j, g, \alpha)$ where $Bhat_j|B_j, Shat_j \sim N(B_j, Shat_j)$ and $B_j/Shat_j^\alpha|Shat_j \sim g$. Here the value of α is set when setting up the data object in 'mash_set_data'. If g is a mash object (safest!) then the function will check that this value matches the α used when fitting 'mash'. Note: as a convenience, this function can also be called with g a mixture distribution with same structure as the fitted_ g from a mash object. This is mostly useful when doing simulations, where you might want to compute the likelihood under the "true" g . When used in this way the user is responsible for making sure that the g makes sense with the alpha set in data.

Value

The vector of log-likelihoods for each data point computed using g .

Examples

```
simdata = simple_sims(50,5,1)
data = mash_set_data(simdata$Bhat, simdata$Shat)
m = mash(data, cov_canonical(data))
mash_compute_vloglik(m,data)
```

mash_estimate_corr_em *Fit mash model and estimate residual correlations using EM algorithm*

Description

Estimates a residual correlation matrix from data using an ad hoc EM algorithm.

Usage

```
mash_estimate_corr_em(
  data,
  Ulist,
  init,
  max_iter = 30,
  tol = 1,
  est_cor = TRUE,
  track_fit = FALSE,
  prior = c("nullbiased", "uniform"),
  details = TRUE,
  ...
)
```

Arguments

<code>data</code>	a mash data object, eg as created by <code>mash_set_data</code>
<code>Ulist</code>	a list of covariance matrices to use
<code>init</code>	the initial value for the residual correlation. If it is not given, we use result from <code>estimate_null_correlation_simple</code>
<code>max_iter</code>	maximum number of iterations to perform
<code>tol</code>	convergence tolerance
<code>est_cor</code>	whether to estimate correlation matrix (TRUE) or the covariance matrix (FALSE)
<code>track_fit</code>	add an attribute <code>trace</code> to output that saves current values of all iterations
<code>prior</code>	indicates what penalty to use on the likelihood, if any
<code>details</code>	whether to return details of the model, if it is TRUE, the mash model, the number of iterations and the value of objective functions will be returned
<code>...</code>	other parameters pass to <code>mash</code>

Details

Returns the estimated residual correlation matrix among conditions. We estimate the residual correlation matrix using an ad hoc em algorithm. The update in the ad hoc M step is not guaranteed to increase the likelihood, therefore, the EM algorithm is stopped before the likelihood drops. The residual correlation matrix V is estimated using the posterior second moment of the noise.

Warning: This method could take some time. The `estimate_null_correlation_simple` gives a quick approximation for the null correlation matrix.

Value

the estimated correlation matrix and the fitted mash model

<code>V</code>	estimated residual correlation matrix
<code>mash.model</code>	fitted mash model

Examples

```
simdata = simple_sims(100,5,1)
m.1by1 = mash_1by1(mash_set_data(simdata$Bhat,simdata$Shat))
strong.subset = get_significant_results(m.1by1,0.05)
random.subset = sample(1:nrow(simdata$Bhat),20)
data.strong = mash_set_data(simdata$Bhat[strong.subset,], simdata$Shat[strong.subset,])
data.tmp = mash_set_data(simdata$Bhat[random.subset,], simdata$Shat[random.subset,])
U_pca = cov_pca(data.strong, 3)
U_ed = cov_ed(data.strong, U_pca)
Vhat = mash_estimate_corr_em(data.tmp, U_ed)
```

mash_plot_meta	<i>Plot metaplot for an effect based on posterior from mash</i>
----------------	---

Description

Plot metaplot for an effect based on posterior from mash

Usage

```
mash_plot_meta(m, i, xlab = "Effect size", ylab = "Condition", ...)
```

Arguments

m	the result of a mash fit
i	index of the effect to plot
xlab	Character string specifying x-axis label.
ylab	Character string specifying y-axis label.
...	Additional arguments passed to metaplot .

Examples

```
simdata = simple_sims(50,5,1)
data = mash_set_data(simdata$Bhat, simdata$Shat)
m = mash(data, cov_canonical(data))
mash_plot_meta(m,1)
```

mash_set_data	<i>Create a data object for mash analysis.</i>
---------------	--

Description

Create a data object for mash analysis.

Usage

```
mash_set_data(
  Bhat,
  Shat = NULL,
  alpha = 0,
  df = Inf,
  pval = NULL,
  V = diag(ncol(Bhat)),
  zero_check_tol = .Machine$double.eps,
  zero_Bhat_Shat_reset = 0,
  zero_Shat_reset = 0
)
```

Arguments

Bhat	An N by R matrix of observed estimates.
Shat	An N by R matrix of corresponding standard errors. Shat can be a scalar if all standard errors are equal. This is most useful if Bhat is a matrix of Z scores, so elements of Shat are all 1. Default is 1.
alpha	Numeric value of alpha parameter in the model. alpha = 0 for Exchangeable Effects (EE), alpha = 1 for Exchangeable Z-scores (EZ). Default is 0. Please refer to equation (3.2) of M. Stephens 2016, Biostatistics for a discussion on alpha.
df	An N by R matrix of corresponding degrees of freedom of the t-statistic Bhat/Shat. Can be a scalar if all degrees of freedom are equal. Default is inf (for large samples).
pval	An N by R matrix of p-values of t-statistic Bhat/Shat. Shat and df should not be specified when pval is provided.
V	an R by R matrix / [R x R x N] array of effect specific correlation matrix of error correlations; must be positive definite. [So Bhat_j distributed as $N(B_j, \text{diag}(Shat_j) V[,j] \text{diag}(Shat_j))$ where $_j$ denotes the jth row of a matrix]. Defaults to identity.
zero_check_tol	a small positive number as threshold for Shat to be considered zero if any Shat is smaller or equal to this number.
zero_Bhat_Shats_reset	Replace zeros in Shat matrix to given value if the corresponding Bhat are also zeros.
zero_Shats_reset	Replace zeros in Shat matrix to given value.

Value

A data object for passing into mash functions.

Examples

```
simdata = simple_sims(50,5,1)
data = mash_set_data(simdata$Bhat, simdata$Shat)
```

mash_update_data	<i>Update the data object for mash analysis.</i>
------------------	--

Description

This function can update two parts of the mash data. The first one is setting the reference group, so the mash data can be used for commonbaseline analysis. The other one is updating the null correlation matrix.

Usage

```
mash_update_data(mashdata, ref = NULL, V = NULL)
```

Arguments

mashdata	mash data object containing the Bhat matrix, standard errors, V; created using mash_set_data
ref	the reference group. It could be a number between 1,..., R, R is number of conditions, or the name of reference group. If there is no reference group, it can be the string 'mean'.
V	an R by R matrix / [R x R x N] array of correlation matrix of error correlations

Value

a updated mash data object

Examples

```
simdata = simple_sims(50,5,1)
data = mash_set_data(simdata$Bhat, simdata$Shat)
mash_update_data(data, 'mean')
```

simple_sims

Create some simple simulated data for testing purposes

Description

Create some simple simulated data for testing purposes

Usage

```
simple_sims(nsamp = 100, ncond = 5, err_sd = 0.01)
```

Arguments

nsamp	number of samples of each type
ncond	number of conditions
err_sd	the standard deviation of the errors

Details

The simulation consists of equal numbers of four different types of effects: null, equal among conditions, present only in first condition, independent across conditions

Examples

```
simple_sims(100, 5)
```

simple_sims2	<i>Create some more simple simulated data for testing purposes</i>
--------------	--

Description

Create some more simple simulated data for testing purposes

Usage

```
simple_sims2(nsamp = 100, err_sd = 0.01)
```

Arguments

nsamp	number of samples of each type
err_sd	the standard deviation of the errors

Details

The simulation consists of five conditions with two types of effects those present (and identical) in first two conditions and those present (and identical) in last three conditions

Examples

```
simple_sims2(100, 5)
```

sim_contrast1	<i>Create simplest simulation, $c_j = \mu_1$ data used for contrast analysis</i>
---------------	---

Description

Create simplest simulation, $c_j = \mu_1$ data used for contrast analysis

Usage

```
sim_contrast1(nsamp = 100, ncond = 5, err_sd = sqrt(0.5))
```

Arguments

nsamp	number of samples of each type
ncond	number of conditions
err_sd	the standard deviation of the errors

Details

There is no true deviation exists in this case

Examples

```
sim_contrast1(100,5)
```

sim_contrast2	<i>Create simulation with signal data used for contrast analysis.</i>
---------------	---

Description

Create simulation with signal data used for contrast analysis.

Usage

```
sim_contrast2(nsamp = 1000, ncond = 5, err_sd = sqrt(0.5))
```

Arguments

nsamp	Number of samples of each type.
ncond	Number of conditions.
err_sd	The standard deviation of the errors.

Details

The first condition is the reference group. The deviations are the difference between the subsequent conditions with the reference group. The simulation consists of 90 10 different types of deviations: equal among conditions, present only in the first subsequent condition, independent across conditions.

Examples

```
sim_contrast2(100,5)
```

Index

contrast_matrix, 3
cov_canonical, 3
cov_ed, 4
cov_flash, 5
cov_pca, 6
cov_udi, 7

estimate_null_correlation_simple, 8, 23
extreme_deconvolution, 4, 8

get_estimated_pi, 11
get_log10bf, 12
get_n_significant_conditions, 13
get_pairwise_sharing, 13
get_pairwise_sharing_from_samples, 14
get_samples, 15
get_significant_results, 16

mash, 16
mash_1by1, 19
mash_compute_loglik, 19
mash_compute_posterior_matrices, 20
mash_compute_vloglik, 21
mash_estimate_corr_em, 22
mash_plot_meta, 24
mash_set_data, 24
mash_update_data, 25
metaplot, 24

saveRDS, 5
sim_contrast1, 27
sim_contrast2, 28
simple_sims, 26
simple_sims2, 27

teem_wrapper, 4