

Package ‘midasml’

May 8, 2026

Type Package

Title Estimation and Prediction Methods for High-Dimensional Mixed Frequency Time Series Data

Version 0.1.11

Maintainer Jonas Striaukas <jonas.striaukas@gmail.com>

Description The 'midasml' package implements estimation and prediction methods for high-dimensional mixed-frequency (MIDAS) time-series and panel data regression models. The regularized MIDAS models are estimated using orthogonal (e.g. Legendre) polynomials and sparse-group LASSO (sg-LASSO) estimator. For more information on the 'midasml' approach see Babii, Ghysels, and Striaukas (2021, JBES forthcoming) <doi:10.1080/07350015.2021.1899933>. The package is equipped with the fast implementation of the sg-LASSO estimator by means of proximal block coordinate descent. High-dimensional mixed frequency time-series data can also be easily manipulated with functions provided in the package.

BugReports <https://github.com/jstriaukas/midasml/issues>

License GPL (>= 2)

Depends Matrix, R (>= 3.5.0)

Imports doRNG, doParallel, foreach, graphics, randtoolbox, snow, methods, lubridate, stats

Encoding UTF-8

RoxygenNote 7.3.2

NeedsCompilation yes

Author Jonas Striaukas [cre, aut],
Andrii Babii [aut],
Jad Beyhum [aut],
Eric Ghysels [aut],
Alex Kostrov [ctb] (Contributions to analytical gradients for non-linear low-dimensional MIDAS estimation code)

Repository CRAN

Date/Publication 2025-10-09 06:00:02 UTC

Contents

| | |
|-------------------------|-----------|
| midasml-package | 2 |
| alfred_vintages | 3 |
| cv.panel.sglfit | 3 |
| cv.sglfit | 5 |
| dateMatch | 7 |
| fa.sglfit | 8 |
| gb | 9 |
| ic.panel.sglfit | 10 |
| ic.sglfit | 11 |
| lb | 12 |
| market_ret | 13 |
| midas.ardl | 14 |
| mixed_freq_data | 15 |
| mixed_freq_data_single | 16 |
| monthBegin | 17 |
| monthEnd | 18 |
| predict.cv.panel.sglfit | 19 |
| predict.cv.sglfit | 20 |
| predict.fa.sglfit | 20 |
| predict.ic.panel.sglfit | 21 |
| predict.ic.sglfit | 22 |
| predict.sglpath | 23 |
| reg.panel.sgl | 24 |
| reg.sgl | 25 |
| rgdp_dates | 27 |
| rgdp_vintages | 27 |
| sglfit | 28 |
| thetafit | 30 |
| tscv.sglfit | 31 |
| us_rgdp | 33 |
| Index | 35 |

| | |
|-----------------|----------------|
| midasml-package | <i>midasml</i> |
|-----------------|----------------|

Description

Estimation and Prediction Methods for High-Dimensional Mixed Frequency Time Series Data

Author(s)

Jonas Striaukas (maintainer) <jonas.striaukas@gmail.com>, Andrii Babii <andrii@email.unc.edu>, Eric Ghysels <eghysels@unc.edu>

See Also

Useful links:

- Report bugs at <https://github.com/jstriaukas/midasml/issues>

| | |
|-----------------|---|
| alfred_vintages | <i>ALFRED monthly and quarterly series vintages</i> |
|-----------------|---|

Description

ALFRED monthly and quarterly series vintages

Usage

```
data(alfred_vintages)
```

Format

A `list` objects

Source

ALFRED

Examples

```
data(alfred_vintages)
i <- 1
alfred_vintages[[i]] # ith variable
```

| | |
|-----------------|--|
| cv.panel.sglfit | <i>Cross-validation fit for panel sg-LASSO</i> |
|-----------------|--|

Description

Does k-fold cross-validation for panel data sg-LASSO regression model.

The function runs `sglfit` `nfolds+1` times; the first to get the path solution in `lambda` sequence, the rest to compute the fit with each of the folds omitted. The average error and standard deviation over the folds is computed, and the optimal regression coefficients are returned for `lam.min` and `lam.1se`. Solutions are computed for a fixed γ .

Usage

```
cv.panel.sglfit(x, y, lambda = NULL, gamma = 1.0, gindex = 1:p, nfolds = 10,
  foldid, method = c("pooled", "fe"), nf = NULL, parallel = FALSE, ...)
```

Arguments

| | |
|----------|---|
| x | NT by p data matrix, where NT and p respectively denote the sample size of pooled data and the number of regressors. |
| y | NT by 1 response variable. |
| lambda | a user-supplied lambda sequence. By leaving this option unspecified (recommended), users can have the program compute its own λ sequence based on <code>nlambda</code> and <code>gamma lambda.factor</code> . It is better to supply, if necessary, a decreasing sequence of lambda values than a single (small) value, as warm-starts are used in the optimization algorithm. The program will ensure that the user-supplied lambda sequence is sorted in decreasing order before fitting the model. |
| gamma | sg-LASSO mixing parameter. $\gamma = 1$ gives LASSO solution and $\gamma = 0$ gives group LASSO solution. |
| gindex | p by 1 vector indicating group membership of each covariate. |
| nfolds | number of folds of the cv loop. Default set to 10. |
| foldid | the fold assignments used. |
| method | choose between 'pooled' and 'fe'; 'pooled' forces the intercept to be fitted in <code>sglfit</code> , 'fe' computes the fixed effects. User must input the number of fixed effects <code>nf</code> for <code>method = 'fe'</code> , and it is recommended to do so for <code>method = 'pooled'</code> . Program uses supplied <code>nf</code> to construct <code>foldsid</code> . Default is set to <code>method = 'pooled'</code> . |
| nf | number of fixed effects. Used only if <code>method = 'fe'</code> . |
| parallel | if TRUE, use parallel foreach to fit each fold. Must register parallel before hand, such as <code>doMC</code> or others. See the example below. |
| ... | Other arguments that can be passed to <code>sglfit</code> . |

Details

The cross-validation is run for sg-LASSO linear model. The sequence of linear regression models implied by λ vector is fit by block coordinate-descent. The objective function is either (case `method='pooled'`)

$$\|y - \iota\alpha - x\beta\|_{NT}^2 + 2\lambda\Omega_\gamma(\beta),$$

where $\iota \in R^{NT}$ and α is common intercept to all N items or (case `method='fe'`)

$$\|y - B\alpha - x\beta\|_{NT}^2 + 2\lambda\Omega_\gamma(\beta),$$

where $B = I_N \times \iota$ and $\|u\|_{NT}^2 = \langle u, u \rangle / NT$ is the empirical inner product. The penalty function $\Omega_\gamma(\cdot)$ is applied on β coefficients and is

$$\Omega_\gamma(\beta) = \gamma|\beta|_1 + (1 - \gamma)|\beta|_{2,1},$$

a convex combination of LASSO and group LASSO penalty functions.

Value

cv.panel.sglfit object.

Author(s)

Jonas Striaukas

Examples

```

set.seed(1)
x = matrix(rnorm(100 * 20), 100, 20)
beta = c(5,4,3,2,1,rep(0, times = 15))
y = x%%beta + rnorm(100)
gindex = sort(rep(1:4,times=5))
cv.panel.sglfit(x = x, y = y, gindex = gindex, gamma = 0.5, method = "fe", nf = 10,
  standardize = FALSE, intercept = FALSE)
## Not run:
# Parallel
require(doMC)
registerDoMC(cores = 2)
x = matrix(rnorm(1000 * 20), 1000, 20)
beta = c(5,4,3,2,1,rep(0, times = 15))
y = x%%beta + rnorm(1000)
gindex = sort(rep(1:4,times=5))
system.time(cv.panel.sglfit(x = x, y = y, gindex = gindex, gamma = 0.5, method = "fe", nf = 10,
  standardize = FALSE, intercept = FALSE))
system.time(cv.panel.sglfit(x = x, y = y, gindex = gindex, gamma = 0.5, method = "fe", nf = 10,
  standardize = FALSE, intercept = FALSE, parallel = TRUE))

## End(Not run)

```

cv.sglfit

*Cross-validation fit for sg-LASSO***Description**

Does k-fold cross-validation for sg-LASSO regression model.

The function runs `sglfit` `nfolds+1` times; the first to get the path solution in lambda sequence, the rest to compute the fit with each of the folds omitted. The average error and standard deviation over the folds is computed, and the optimal regression coefficients are returned for `lam.min` and `lam.1se`. Solutions are computed for a fixed γ .

Usage

```

cv.sglfit(x, y, lambda = NULL, gamma = 1.0, gindex = 1:p,
  nfolds = 10, foldid, parallel = FALSE, ...)

```

Arguments

`x` T by p data matrix, where T and p respectively denote the sample size and the number of regressors.

`y` T by 1 response variable.

| | |
|----------|---|
| lambda | a user-supplied lambda sequence. By leaving this option unspecified (recommended), users can have the program compute its own λ sequence based on <code>nlambda</code> and <code>gamma lambda.factor</code> . It is better to supply, if necessary, a decreasing sequence of lambda values than a single (small) value, as warm-starts are used in the optimization algorithm. The program will ensure that the user-supplied lambda sequence is sorted in decreasing order before fitting the model. |
| gamma | sg-LASSO mixing parameter. $\gamma = 1$ gives LASSO solution and $\gamma = 0$ gives group LASSO solution. |
| gindex | p by 1 vector indicating group membership of each covariate. |
| nfolds | number of folds of the cv loop. Default set to 10. |
| foldid | the fold assignments used. |
| parallel | if TRUE, use parallel foreach to fit each fold. Must register parallel before hand, such as <code>doMC</code> or others. See the example below. |
| ... | Other arguments that can be passed to sglfit . |

Details

The cross-validation is run for sg-LASSO linear model. The sequence of linear regression models implied by λ vector is fit by block coordinate-descent. The objective function is

$$\|y - \iota\alpha - x\beta\|_T^2 + 2\lambda\Omega_\gamma(\beta),$$

where $\iota \in R^T$ and $\|u\|_T^2 = \langle u, u \rangle / T$ is the empirical inner product. The penalty function $\Omega_\gamma(\cdot)$ is applied on β coefficients and is

$$\Omega_\gamma(\beta) = \gamma|\beta|_1 + (1 - \gamma)|\beta|_{2,1},$$

a convex combination of LASSO and group LASSO penalty functions.

Value

cv.sglfit object.

Author(s)

Jonas Striaukas

Examples

```
set.seed(1)
x = matrix(rnorm(100 * 20), 100, 20)
beta = c(5,4,3,2,1,rep(0, times = 15))
y = x%*%beta + rnorm(100)
gindex = sort(rep(1:4,times=5))
cv.sglfit(x = x, y = y, gindex = gindex, gamma = 0.5,
  standardize = FALSE, intercept = FALSE)
## Not run:
# Parallel
require(doMC)
```

```
registerDoMC(cores = 2)
x = matrix(rnorm(1000 * 20), 1000, 20)
beta = c(5,4,3,2,1,rep(0, times = 15))
y = x%%beta + rnorm(1000)
gindex = sort(rep(1:4,times=5))
system.time(cv.sglfit(x = x, y = y, gindex = gindex, gamma = 0.5,
  standardize = FALSE, intercept = FALSE))
system.time(cv.sglfit(x = x, y = y, gindex = gindex, gamma = 0.5,
  standardize = FALSE, intercept = FALSE, parallel = TRUE))

## End(Not run)
```

dateMatch

Match dates

Description

Change the date to the beginning of the month date.

Usage

```
dateMatch(x, y)
```

Arguments

x date vector to match with y date vector.
y date vector.

Value

changed date vector.

Author(s)

Jonas Striaukas

Examples

```
x <- seq(as.Date("2020-01-01"), as.Date("2020-12-01"), by = "day")
set.seed(100)
x <- x[-sample(1:336, 100)]
y <- seq(as.Date("2020-01-01"), as.Date("2020-12-01"), by = "month")
dateMatch(x,y)
```

fa.sglfit

*Estimates factor-augmented sparse MIDAS regression model***Description**

Estimates factor-augmented sparse MIDAS regression model

The function first computes factors on MIDAS-weighted regressors x . Then the function runs [cv.sglfit](#) to fit the model. The output can be passed to [predict.fa.sglfit](#) to obtain predictions.

Usage

```
fa.sglfit(x, y, f = NULL, K = NULL, gamma = 1.0, gindex = 1:nvars,
  ...)
```

Arguments

| | |
|----------|---|
| x | T by p data matrix, where T and p respectively denote the sample size and the number of regressors. |
| y | T by 1 response variable. |
| f | T by K latent factors. If null, the factors are estimated by using Principal Component Analysis (PCA). In this case, the number of optimal factors is selected by applying eigenvalue ratio estimator of Ahn and Horenstein (2013). |
| K | number of factors. If f is not provided, the number of factors is estimated by applying eigenvalue ratio estimator of Ahn and Horenstein (2013) in case $K=$ NULL. Else, first K Principal Components are used. |
| γ | sg-LASSO mixing parameter. $\gamma = 1$ gives LASSO solution and $\gamma = 0$ gives group LASSO solution. |
| $gindex$ | p by 1 vector indicating group membership of each covariate. |
| ... | Other arguments that can be passed to cv.sglfit . |

Details

The cross-validation is run for sg-LASSO linear model. The sequence of linear regression models implied by λ vector is fit by block coordinate-descent. The objective function is

$$\|y - \iota\alpha - f\phi - x\beta\|_T^2 + 2\lambda\Omega_\gamma(\beta),$$

where $\iota \in R^T$ and $\|u\|_T^2 = \langle u, u \rangle / T$ is the empirical inner product. The penalty function $\Omega_\gamma(\cdot)$ is applied on β coefficients and is

$$\Omega_\gamma(\beta) = \gamma|\beta|_1 + (1 - \gamma)|\beta|_{2,1},$$

a convex combination of LASSO and group LASSO penalty functions.

Value

fa.sglfit object.

Examples

```

set.seed(1)
x = matrix(rnorm(100 * 20), 100, 20)
beta = c(5,4,3,2,1,rep(0, times = 15))
f = matrix(rnorm(100 * 2), 100, 2)
g = c(0.5, 0.5)
y = x%%beta + f%%g + rnorm(100)
gindex = sort(rep(1:4,times=5))
fa.sglfit(x = x, y = y, f = f, gindex = gindex, gamma = 0.5,
          standardize = FALSE, intercept = FALSE)

```

gb

*Gegenbauer polynomials shifted to [a,b]***Description**

For a given set of points in X , computes the orthonormal Gegenbauer polynomials basis of $L_2 [a,b]$ for a given degree and α parameter. The Gegenbauer polynomials are a special case of more general Jacobi polynomials. In turn, you may get Legendre polynomials from Gegenbauer by setting $\alpha = 0$, or Chebychev's polynomials by setting $\alpha = 1/2$ or $-1/2$.

Usage

```
gb(degree, alpha, a = 0, b = 1, jmax = NULL, X = NULL)
```

Arguments

| | |
|--------|-----------------------------------|
| degree | polynomial degree. |
| alpha | Gegenbauer polynomials parameter. |
| a | lower shift value (default - 0). |
| b | upper shift value (default - 1). |
| jmax | number of high-frequency lags. |
| X | optional evaluation grid vector. |

Value

Psi weight matrix with Gegenbauer functions upto degree.

Author(s)

Jonas Striaukas

Examples

```

degree <- 3
alpha <- 1
jmax <- 66
gb(degree = degree, alpha = alpha, a = 0, b = 1, jmax = jmax)

```

ic.panel.sglfit *Information criteria fit for panel sg-LASSO*

Description

Does information criteria for panel data sg-LASSO regression model.

The function runs [sglfit](#) 1 time; computes the path solution in lambda sequence. Solutions for BIC, AIC and AICc information criteria are returned.

Usage

```
ic.panel.sglfit(x, y, lambda = NULL, gamma = 1.0, gindex = 1:p,
               method = c("pooled", "fe"), nf = NULL, ...)
```

Arguments

| | |
|--------|--|
| x | NT by p data matrix, where NT and p respectively denote the sample size of pooled data and the number of regressors. |
| y | NT by 1 response variable. |
| lambda | a user-supplied lambda sequence. By leaving this option unspecified (recommended), users can have the program compute its own λ sequence based on <code>nlambda</code> and <code>lambda.factor</code> . It is better to supply, if necessary, a decreasing sequence of lambda values than a single (small) value, as warm-starts are used in the optimization algorithm. The program will ensure that the user-supplied λ sequence is sorted in decreasing order before fitting the model. |
| gamma | sg-LASSO mixing parameter. $\gamma = 1$ gives LASSO solution and $\gamma = 0$ gives group LASSO solution. |
| gindex | p by 1 vector indicating group membership of each covariate. |
| method | choose between 'pooled' and 'fe'; 'pooled' forces the intercept to be fitted in sglfit , 'fe' computes the fixed effects. User must input the number of fixed effects <code>nf</code> for <code>method = 'fe'</code> . Default is set to <code>method = 'pooled'</code> . |
| nf | number of fixed effects. Used only if <code>method = 'fe'</code> . |
| ... | Other arguments that can be passed to sglfit . |

Details

The sequence of linear regression models implied by λ vector is fit by block coordinate-descent. The objective function is either (case `method='pooled'`)

$$\|y - \iota\alpha - x\beta\|_{NT}^2 + 2\lambda\Omega_\gamma(\beta),$$

where $\iota \in R^{NT}$ and α is common intercept to all N items or (case `method='fe'`)

$$\|y - B\alpha - x\beta\|_{NT}^2 + 2\lambda\Omega_\gamma(\beta),$$

where $B = I_N \times \iota$ and $\|u\|_{NT}^2 = \langle u, u \rangle / NT$ is the empirical inner product. The penalty function $\Omega_\gamma(\cdot)$ is applied on β coefficients and is

$$\Omega_\gamma(\beta) = \gamma|\beta|_1 + (1 - \gamma)|\beta|_{2,1},$$

a convex combination of LASSO and group LASSO penalty functions.

Value

ic.panel.sglfit object.

Author(s)

Jonas Striaukas

Examples

```
set.seed(1)
x = matrix(rnorm(100 * 20), 100, 20)
beta = c(5,4,3,2,1,rep(0, times = 15))
y = x%*%beta + rnorm(100)
gindex = sort(rep(1:4,times=5))
ic.panel.sglfit(x = x, y = y, gindex = gindex, gamma = 0.5,
  standardize = FALSE, intercept = FALSE)
```

ic.sglfit

Information criteria fit for sg-LASSO

Description

Does information criteria for sg-LASSO regression model.

The function runs [sglfit](#) 1 time; computes the path solution in lambda sequence. Solutions for BIC, AIC and AICc information criteria are returned.

Usage

```
ic.sglfit(x, y, lambda = NULL, gamma = 1.0, gindex = 1:p, ...)
```

Arguments

| | |
|--------|--|
| x | T by p data matrix, where T and p respectively denote the sample size and the number of regressors. |
| y | T by 1 response variable. |
| lambda | a user-supplied lambda sequence. By leaving this option unspecified (recommended), users can have the program compute its own λ sequence based on <code>nlambda</code> and <code>lambda.factor</code> . It is better to supply, if necessary, a decreasing sequence of lambda values than a single (small) value, as warm-starts are used in the optimization algorithm. The program will ensure that the user-supplied λ sequence is sorted in decreasing order before fitting the model. |

| | |
|--------|---|
| gamma | sg-LASSO mixing parameter. $\gamma = 1$ gives LASSO solution and $\gamma = 0$ gives group LASSO solution. |
| gindex | p by 1 vector indicating group membership of each covariate. |
| ... | Other arguments that can be passed to sglfit . |

Details

The sequence of linear regression models implied by λ vector is fit by block coordinate-descent. The objective function is

$$\|y - \iota\alpha - x\beta\|_T^2 + 2\lambda\Omega_\gamma(\beta),$$

where $\iota \in R^T$ and $\|u\|_T^2 = \langle u, u \rangle / T$ is the empirical inner product. The penalty function $\Omega_\gamma(\cdot)$ is applied on β coefficients and is

$$\Omega_\gamma(\beta) = \gamma|\beta|_1 + (1 - \gamma)|\beta|_{2,1},$$

a convex combination of LASSO and group LASSO penalty functions.

Value

ic.sglfit object.

Author(s)

Jonas Striaukas

Examples

```
set.seed(1)
x = matrix(rnorm(100 * 20), 100, 20)
beta = c(5,4,3,2,1,rep(0, times = 15))
y = x%%beta + rnorm(100)
gindex = sort(rep(1:4,times=5))
ic.sglfit(x = x, y = y, gindex = gindex, gamma = 0.5,
  standardize = FALSE, intercept = FALSE)
```

 lb

Legendre polynomials shifted to [a,b]

Description

For a given set of points in X, computes the orthonormal Legendre polynomials basis of L2 [a,b] for a given degree.

Usage

```
lb(degree, a = 0, b = 1, jmax = NULL, X = NULL)
```

Arguments

| | |
|--------|----------------------------------|
| degree | polynomial degree. |
| a | lower shift value (default - 0). |
| b | upper shift value (default - 1). |
| jmax | number of high-frequency lags. |
| X | optional evaluation grid vector. |

Value

Psi weight matrix with Legendre functions upto degree.

Author(s)

Jonas Striaukas

Examples

```
degree <- 3
jmax <- 66
lb(degree = degree, a = 0, b = 1, jmax = jmax)
```

market_ret

SNP500 returns

Description

SNP500 returns

Usage

```
data(market_ret)
```

Format

A `data.frame` object.

Source

market_ret - [FRED](#)

Examples

```
data(market_ret)
market_ret$snp500ret
```

midas.ardl

*MIDAS regression***Description**

Fits MIDAS regression model with single high-frequency covariate. Options include linear-in-parameters polynomials (e.g. Legendre) or non-linear polynomials (e.g. exponential Almon). Non-linear polynomial optimization routines are equipped with analytical gradients, which allows fast and accurate optimization.

Usage

```
midas.ardl(y, x, z = NULL, loss_choice = c("mse", "logit"),
          poly_choice = c("legendre", "expalmon", "beta"),
          poly_spec = 0, legendre_degree = 3, nbtrials = 500)
```

Arguments

| | |
|-----------------|--|
| y | response variable. Continuous for loss_choice = "mse", binary for loss_choice = "logit". |
| x | high-frequency covariate lags. |
| z | other lower-frequency covariate(s) or AR lags (both can be supplied in an appended matrix). Either must be supplied. |
| loss_choice | which loss function to fit: loss_choice="mse" fits least squares MIDAS regression, loss_choice="logit" fits logit MIDAS regression. |
| poly_choice | which MIDAS lag polynomial function to use: poly_choice="expalmon" - exponential Almon polynomials, poly_choice="beta" - Beta density function (need to set poly_spec), poly_choice="legendre" - legendre polynomials (need to set legendre_degree). Default is set to poly_choice="expalmon". |
| poly_spec | which Beta density function specification to apply (applicable only for poly_choice="beta"). poly_spec = 0 - all three parameters are fitted, poly_spec = 1 (θ_2, θ_3) are fitted, poly_spec = 2 (θ_1, θ_2) are fitted, poly_spec = 3 (θ_2) is fitted. Default is set to poly_spec = 0. |
| legendre_degree | the degree of legendre polynomials (applicable only for legendre="beta"). Default is set to 3. |
| nbtrials | number of initial values tried in multistart optimization. Default is set to poly_spec = 500. |

Details

Several polynomial functional forms are available (poly_choice):

- beta: Beta polynomial
- expalmon: Exp Almon polynomial
- legendre: Legendre polynomials.

The ARDL-MIDAS model is:

$$y_t = \mu + \sum_p \rho_p y_{t-p} + \beta \sum_j \omega_j(\theta) x_{t-1}$$

where $\mu, \beta, \theta, \rho_p$ are model parameters, p is number of low-frequency and ω is the weight function.

Value

midas.ardl object.

Author(s)

Jonas Striaukas

Examples

```
set.seed(1)
x = matrix(rnorm(100 * 20), 100, 20)
z = rnorm(100)
y = rnorm(100)
midas.ardl(y = y, x = x, z = z)
```

| | |
|-----------------|-----------------------------|
| mixed_freq_data | <i>MIDAS data structure</i> |
|-----------------|-----------------------------|

Description

Creates a MIDAS data structure for a single high-frequency covariate and a single low-frequency dependent variable.

Usage

```
mixed_freq_data(data.y, data.ydate, data.x, data.xdate, x.lag, y.lag,
  horizon, est.start, est.end, disp.flag = TRUE)
```

Arguments

| | |
|------------|--|
| data.y | n by 1 low-frequency time series data vector. |
| data.ydate | n by 1 low-frequency time series date vector. |
| data.x | m by 1 high-frequency time series data vector. |
| data.xdate | m by 1 high-frequency time series date vector. |
| x.lag | number of high-frequency lags to construct in high-frequency time units. |
| y.lag | number of low-frequency lags to construct in low-frequency time units. |
| horizon | forecast horizon relative to data.ydate date in high-frequency time units. |

| | |
|-----------|--|
| est.start | estimation start date, taken as the first |
| est.end | estimation end date, taken as the last Remaining data after this date is dropped to out-of-sample evaluation data. |
| disp.flag | display flag to indicate whether or not to display obtained MIDAS data structure in console. |

Value

a list of MIDAS data structure.

Author(s)

Jonas Striaukas

Examples

```
data(us_rgdg)
rgdp <- us_rgdg$rgdp
payems <- us_rgdg$payems
payems[-1, 2] <- log(payems[-1, 2]/payems[-dim(payems)[1], 2])*100
payems <- payems[-1, ]
rgdp[-1, 2] <- ((rgdp[-1, 2]/rgdp[-dim(rgdp)[1], 2])^4-1)*100
rgdp <- rgdp[-1, ]
est.start <- as.Date("1990-01-01")
est.end <- as.Date("2002-03-01")
mixed_freq_data(rgdp[,2], as.Date(rgdp[,1]), payems[,2],
  as.Date(payems[,1]), x.lag = 9, y.lag = 4, horizon = 1,
  est.start, est.end, disp.flag = FALSE)
```

mixed_freq_data_single

MIDAS data structure

Description

Creates a MIDAS data structure for a single high-frequency covariate based on low-frequency reference date.

Usage

```
mixed_freq_data_single(data.refdate, data.x, data.xdate, x.lag, horizon,
  est.start, est.end, disp.flag = TRUE)
```

Arguments

| | |
|--------------|--|
| data.refdate | n by 1 date vector. |
| data.x | m by 1 high-frequency time series data vector. |
| data.xdate | m by 1 high-frequency time series date vector. |
| x.lag | number of high-frequency lags to construct in high-frequency time units. |
| horizon | forecast horizon relative to data.refdate date in high-frequency time units. |
| est.start | estimation start date, taken as the first |
| est.end | estimation end date, taken as the last Remaining data after this date is dropped to out-of-sample evaluation data. |
| disp.flag | display flag to indicate whether or not to display obtained MIDAS data structure in console. |

Value

a list of midas data structure.

Author(s)

Jonas Striaukas

Examples

```
data(us_rgdg)
rgdp <- us_rgdg$rgdp
cfnai <- us_rgdg$cfnai
data.refdate <- rgdp$date
data.x <- cfnaio$cfnai
data.xdate <- cfnaio$date
est.start <- as.Date("1990-01-01")
est.end <- as.Date("2002-03-01")
mixed_freq_data_single(data.refdate, data.x, data.xdate, x.lag = 12, horizon = 1,
  est.start, est.end, disp.flag = FALSE)
```

monthBegin

Beginning of the month date

Description

Change the date to the beginning of the month date.

Usage

```
monthBegin(x)
```

Arguments

x date value.

Value

changed date value.

Author(s)

Jonas Striaukas

Examples

```
monthBegin(as.Date("2020-05-15"))
```

monthEnd

End of the month date

Description

Change the date to the end of the month date.

Usage

```
monthEnd(x)
```

Arguments

x date value.

Value

changed date value.

Author(s)

Jonas Striaukas

Examples

```
monthEnd(as.Date("2020-05-15"))
```

`predict.cv.panel.sglfit`*Computes prediction*

Description

Similar to other predict methods, this functions predicts fitted values from a fitted sglfit object.

Usage

```
## S3 method for class 'cv.panel.sglfit'
predict(
  object,
  newx,
  s = c("lam.min", "lam.lse"),
  type = c("response"),
  method = c("pooled", "fe"),
  ...
)
```

Arguments

| | |
|---------------------|--|
| <code>object</code> | fitted <code>cv.panel.sglfit</code> model object. |
| <code>newx</code> | matrix of new values for x at which predictions are to be made. NOTE: newx must be a matrix, predict function does not accept a vector or other formats of newx. |
| <code>s</code> | choose between 'lam.min' and 'lam.lse'. |
| <code>type</code> | type of prediction required. Only response is available. Gives predicted response for regression problems. |
| <code>method</code> | choose between 'pooled', and 'fe'. |
| <code>...</code> | Not used. Other arguments to predict. |

Details

s is the new vector at which predictions are to be made. If s is not in the lambda sequence used for fitting the model, the predict function will use linear interpolation to make predictions. The new values are interpolated using a fraction of predicted values from both left and right *lambda* indices.

Value

The object returned depends on type.

predict.cv.sglfit *Computes prediction*

Description

Similar to other predict methods, this functions predicts fitted values from a fitted sglfit object.

Usage

```
## S3 method for class 'cv.sglfit'
predict(object, newx, s = c("lam.min", "lam.1se"), type = c("response"), ...)
```

Arguments

| | |
|--------|--|
| object | fitted <code>cv.sglfit</code> model object. |
| newx | matrix of new values for x at which predictions are to be made. NOTE: newx must be a matrix, predict function does not accept a vector or other formats of newx. |
| s | choose between 'lam.min' and 'lam.1se'. |
| type | type of prediction required. Only response is available. Gives predicted response for regression problems. |
| ... | Not used. Other arguments to predict. |
| method | choose between 'single', 'pooled', and 'fe'. |

Details

s is the new vector at which predictions are to be made. If s is not in the lambda sequence used for fitting the model, the predict function will use linear interpolation to make predictions. The new values are interpolated using a fraction of predicted values from both left and right *lambda* indices.

Value

The object returned depends on type.

predict.fa.sglfit *Computes prediction*

Description

Similar to other predict methods, this functions predicts fitted values from a fitted sglfit object.

Usage

```
## S3 method for class 'fa.sglfit'
predict(object, newx, s = c("lam.min", "lam.1se"), type = c("response"), ...)
```

Arguments

| | |
|--------|---|
| object | fitted <code>fa.sglfit</code> model object. |
| newx | matrix of new values for x at which predictions are to be made. NOTE: newx must be a matrix, predict function does not accept a vector or other formats of newx. In addition, note that x should be binded with columns of out-of-sample factors. |
| s | choose between 'lam.min' and 'lam.lse'. |
| type | type of prediction required. Only response is available. Gives predicted response for regression problems. |
| ... | Not used. Other arguments to predict. |
| method | choose between 'single', 'pooled', and 'fe'. |

Details

s is the new vector at which predictions are to be made. If s is not in the lambda sequence used for fitting the model, the predict function will use linear interpolation to make predictions. The new values are interpolated using a fraction of predicted values from both left and right *lambda* indices.

Value

The object returned depends on type.

```
predict.ic.panel.sglfit
```

Computes prediction

Description

Similar to other predict methods, this functions predicts fitted values from a fitted sglfit object.

Usage

```
## S3 method for class 'ic.panel.sglfit'
predict(
  object,
  newx,
  s = c("bic", "aic", "aicc"),
  type = c("response"),
  method = c("pooled", "fe"),
  ...
)
```

Arguments

| | |
|--------|--|
| object | fitted <code>ic.panel.sglfit</code> model object. |
| newx | matrix of new values for x at which predictions are to be made. NOTE: newx must be a matrix, predict function does not accept a vector or other formats of newx. |
| s | choose between 'bic', 'aic', and 'aicc'. |
| type | type of prediction required. Only response is available. Gives predicted response for regression problems. |
| method | choose between 'pooled', and 'fe'. |
| ... | Not used. Other arguments to predict. |

Details

s is the new vector at which predictions are to be made. If s is not in the lambda sequence used for fitting the model, the predict function will use linear interpolation to make predictions. The new values are interpolated using a fraction of predicted values from both left and right *lambda* indices.

Value

The object returned depends on type.

| | |
|-------------------|----------------------------|
| predict.ic.sglfit | <i>Computes prediction</i> |
|-------------------|----------------------------|

Description

Similar to other predict methods, this functions predicts fitted values from a fitted sglfit object.

Usage

```
## S3 method for class 'ic.sglfit'
predict(object, newx, s = c("bic", "aic", "aicc"), type = c("response"), ...)
```

Arguments

| | |
|--------|--|
| object | fitted <code>cv.sglfit</code> model object. |
| newx | matrix of new values for x at which predictions are to be made. NOTE: newx must be a matrix, predict function does not accept a vector or other formats of newx. |
| s | choose between 'bic', 'aic', and 'aicc'. |
| type | type of prediction required. Only response is available. Gives predicted response for regression problems. |
| ... | Not used. Other arguments to predict. |

Details

s is the new vector at which predictions are to be made. If s is not in the λ sequence used for fitting the model, the predict function will use linear interpolation to make predictions. The new values are interpolated using a fraction of predicted values from both left and right λ indices.

Value

The object returned depends on type.

| | |
|-----------------|----------------------------|
| predict.sglpath | <i>Computes prediction</i> |
|-----------------|----------------------------|

Description

Similar to other predict methods, this functions predicts fitted values from a fitted sglfit object.

Usage

```
## S3 method for class 'sglpath'
predict(
  object,
  newx,
  s = NULL,
  type = c("response"),
  method = c("single", "pooled", "fe"),
  ...
)
```

Arguments

| | |
|--------|--|
| object | fitted <code>sglfit</code> model object. |
| newx | matrix of new values for x at which predictions are to be made. NOTE: newx must be a matrix, predict function does not accept a vector or other formats of newx. |
| s | value(s) of the penalty parameter λ at which predictions are to be made. Default is the entire sequence used to create the model. |
| type | type of prediction required. Only response is available. Gives predicted response for regression problems. |
| method | choose between 'single', 'pooled', and 'fe'. |
| ... | Not used. Other arguments to predict. |

Details

s is the new vector at which predictions are to be made. If s is not in the λ sequence used for fitting the model, the predict function will use linear interpolation to make predictions. The new values are interpolated using a fraction of predicted values from both left and right λ indices.

Value

The object returned depends on type.

| | |
|---------------|--|
| reg.panel.sgl | <i>Regression fit for panel sg-LASSO</i> |
|---------------|--|

Description

Fits panel data sg-LASSO regression model.

The function fits sg-LASSO regression based on chosen tuning parameter selection method_choice. Options include cross-validation and information criteria.

Usage

```
reg.panel.sgl(x, y, gamma = NULL, gindex, intercept = TRUE,
             method_choice = c("ic", "cv"), nfolds = 10,
             method = c("pooled", "fe"), nf = NULL,
             verbose = FALSE, ...)
```

Arguments

| | |
|---------------|---|
| x | NT by p data matrix, where NT and p respectively denote the sample size of pooled data and the number of regressors. |
| y | NT by 1 response variable. |
| gamma | sg-LASSO mixing parameter. $\gamma = 1$ gives LASSO solution and $\gamma = 0$ gives group LASSO solution. |
| gindex | p by 1 vector indicating group membership of each covariate. |
| intercept | whether intercept be fitted (TRUE) or set to zero (FALSE). Default is TRUE. |
| method_choice | choose between ic and cv. ic gives fit based on information criteria (BIC, AIC or AICc) by running ic.fit, while cv gives fit based on cross-validation by running cv.sglfit. If cv is chosen, optional number of folds nfolds can be supplied. |
| nfolds | number of folds of the cv loop. Default set to 10. |
| method | choose between 'pooled' and 'fe'; 'pooled' forces the intercept to be fitted in sglfit , 'fe' computes the fixed effects. User must input the number of fixed effects nf for method = 'fe', and it is recommended to do so for method = 'pooled'. Program uses supplied nf to construct foldsid if method_choice = 'cv' is chosen. Default is set to method = 'pooled'. |
| nf | number of fixed effects. Used only if method = 'fe'. |
| verbose | flag to print information. |
| ... | Other arguments that can be passed to sglfit. |

Details

The sequence of linear regression models implied by λ vector is fit by block coordinate-descent. The objective function is either (case method='pooled')

$$\|y - \iota\alpha - x\beta\|_T^2 + 2\lambda\Omega_\gamma(\beta),$$

where $\iota \in R^{NT}$ and α is common intercept to all N items or (case method='fe')

$$\|y - B\alpha - x\beta\|_T^2 + 2\lambda\Omega_\gamma(\beta),$$

where $B = I_N \times \iota$ and $\|u\|_{NT}^2 = \langle u, u \rangle / NT$ is the empirical inner product. The penalty function $\Omega_\gamma(\cdot)$ is applied on β coefficients and is

$$\Omega_\gamma(\beta) = \gamma|\beta|_1 + (1 - \gamma)|\beta|_{2,1},$$

a convex combination of LASSO and group LASSO penalty functions.

Value

reg.panel.sgl object.

Author(s)

Jonas Striaukas

Examples

```
set.seed(1)
x = matrix(rnorm(100 * 20), 100, 20)
beta = c(5,4,3,2,1,rep(0, times = 15))
y = x%*%beta + rnorm(100)
gindex = sort(rep(1:4,times=5))
reg.panel.sgl(x = x, y = y,
  gindex = gindex, gamma = 0.5,
  method = "fe", nf = 10,
  standardize = FALSE, intercept = FALSE)
```

reg.sgl

Fit for sg-LASSO regression

Description

Fits sg-LASSO regression model.

The function fits sg-LASSO regression based on chosen tuning parameter selection method_choice. Options include cross-validation and information criteria.

Usage

```
reg.sgl(x, y, gamma = NULL, gindex, intercept = TRUE,
  method_choice = c("tscv", "ic", "cv"), verbose = FALSE, ...)
```

Arguments

| | |
|---------------|--|
| x | T by p data matrix, where T and p respectively denote the sample size and the number of regressors. |
| y | T by 1 response variable. |
| gamma | sg-LASSO mixing parameter. $\gamma = 1$ gives LASSO solution and $\gamma = 0$ gives group LASSO solution. |
| gindex | p by 1 vector indicating group membership of each covariate. |
| intercept | whether intercept be fitted (TRUE) or set to zero (FALSE). Default is TRUE. |
| method_choice | choose between tscv ic and cv. tscv fits sg-LASSO based on time series cross-validation (see tscv.sglfit), ic fits sg-LASSO based on information criteria (BIC, AIC or AICc, see ic.sglfit), cv fits sg-LASSO based on cross-validation (see cv.sglfit). Additional arguments for each method choice are passed on to the relevant functions. |
| verbose | flag to print information. |
| ... | Other arguments that can be passed to <code>sglfit</code> . |

Details

The sequence of linear regression models implied by λ vector is fit by block coordinate-descent. The objective function is

$$\|y - \iota\alpha - x\beta\|_T^2 + 2\lambda\Omega_\gamma(\beta),$$

where $\iota \in R^T$ and $\|u\|_T^2 = \langle u, u \rangle / T$ is the empirical inner product. The penalty function $\Omega_\gamma(\cdot)$ is applied on β coefficients and is

$$\Omega_\gamma(\beta) = \gamma|\beta|_1 + (1 - \gamma)|\beta|_{2,1},$$

a convex combination of LASSO and group LASSO penalty functions.

Value

reg.sgl object.

Author(s)

Jonas Striaukas

Examples

```
set.seed(1)
x = matrix(rnorm(100 * 20), 100, 20)
beta = c(5,4,3,2,1,rep(0, times = 15))
y = x*%beta + rnorm(100)
gindex = sort(rep(1:4,times=5))
reg.sgl(x = x, y = y, gamma = 0.5, gindex = gindex)
```

| | |
|------------|-------------------------------|
| rgdp_dates | <i>Real GDP release dates</i> |
|------------|-------------------------------|

Description

Real GDP release dates

Usage

```
data(rgdp_dates)
```

Format

A [list](#) objects

Source

[ALFRED](#)

Examples

```
data(rgdp_dates)
rgdp_dates$Quarter_q # reference quarters in quarters
rgdp_dates$Quarter_m # reference quarters in months
rgdp_dates$Quarter_d # reference quarters in days
rgdp_dates$`First release` # first release date for the reference
rgdp_dates$`Second release` # second release date for the reference
rgdp_dates$`Third release` # third release date for the reference
```

| | |
|---------------|--------------------------|
| rgdp_vintages | <i>Real GDP vintages</i> |
|---------------|--------------------------|

Description

Real GDP vintages

Usage

```
data(rgdp_vintages)
```

Format

A [list](#) objects

Source

ALFRED

Examples

```
data(rgdp_vintages)
rgdp_vintages$date # dates
rgdp_vintages$time_series # series, q-q annual rate
rgdp_vintages$realtime_period # real time dates
```

sglfit

*Fits sg-LASSO regression***Description**

Fits sg-LASSO regression model. The function fits sg-LASSO regression model for a sequence of λ tuning parameter and fixed γ tuning parameter. The optimization is based on block coordinate-descent. Optionally, fixed effects are fitted.

Usage

```
sglfit(x, y, gamma = 1.0, nlambda = 100L, method = c("single", "pooled", "fe"),
      nf = NULL, lambda.factor = ifelse(nobs < nvars, 1e-02, 1e-04),
      lambda = NULL, pf = rep(1, nvars), gindex = 1:nvars,
      dfmax = nvars + 1, pmax = min(dfmax * 1.2, nvars), standardize = FALSE,
      intercept = FALSE, eps = 1e-08, maxit = 100000L, peps = 1e-08)
```

Arguments

| | |
|---------|---|
| x | T by p data matrix, where T and p respectively denote the sample size and the number of regressors. |
| y | T by 1 response variable. |
| gamma | sg-LASSO mixing parameter. $\gamma = 1$ gives LASSO solution and $\gamma = 0$ gives group LASSO solution. |
| nlambda | number of λ 's to use in the regularization path; used if lambda = NULL. |
| method | choose between 'single', 'pooled' and 'fe'; 'single' implies standard sg-LASSO regression, 'pooled' forces the intercept to be fitted, 'fe' computes the fixed effects. User needs to input the number of fixed effects nf. Default is set to 'single'. |
| nf | number of fixed effects. Used only if method = 'fe'. |

| | |
|---------------|---|
| lambda.factor | The factor for getting the minimal λ in the λ sequence, where $\min(\text{lambda}) = \text{lambda.factor} * \max(\text{lambda})$. $\max(\text{lambda})$ is the smallest value of lambda for which all coefficients are zero. λ_{max} is determined for each γ tuning parameter separately. The default depends on the relationship between T (the sample size) and p (the number of predictors). If $T < p$, the default is 0.01 . If $T > p$, the default is 0.0001 , closer to zero. The smaller the value of lambda.factor is, the denser is the fit for λ_{min} . Used only if lambda = NULL. |
| lambda | a user-supplied lambda sequence. By leaving this option unspecified (recommended), users can have the program compute its own lambda sequence based on nlambda and lambda.factor. It is better to supply, if necessary, a decreasing sequence of lambda values than a single (small) value, as warm-starts are used in the optimization algorithm. The program will ensure that the user-supplied λ sequence is sorted in decreasing order before fitting the model. |
| pf | the ℓ_1 penalty factor of length p used for the adaptive sg-LASSO. Separate ℓ_1 penalty weights can be applied to each coefficient to allow different $\ell_1 + \ell_{2,1}$ shrinkage. Can be 0 for some variables, which imposes no shrinkage, and results in that variable always be included in the model. Default is 1 for all variables. |
| gindex | p by 1 vector indicating group membership of each covariate. |
| dfmax | the maximum number of variables allowed in the model. Useful for very large p when a partial path is desired. Default is $p+1$. In case method='fe', dfmax is ignored. |
| pmax | the maximum number of coefficients allowed ever to be nonzero. For example, once $\beta_i \neq 0$ for some $i \in [p]$, no matter how many times it exits or re-enters the model through the path, it will be counted only once. Default is $\min(\text{dfmax} * 1.2, p)$. |
| standardize | logical flag for variable standardization, prior to fitting the model sequence. The coefficients are always returned to the original scale. It is recommended to keep standardize=TRUE. Default is FALSE. |
| intercept | whether intercept be fitted (TRUE) or set to zero (FALSE). Default is FALSE. In case method='pooled', intercept=TRUE is forced. In case method='fe', intercept=FALSE is forced and entity specific intercepts are fitted in a separate output variable a_0 . |
| eps | convergence threshold for block coordinate descent. Each inner block coordinate-descent loop continues until the maximum change in the objective after any coefficient update is less than thresh times the null deviance. Defaults value is $1e-8$. |
| maxit | maximum number of outer-loop iterations allowed at fixed lambda values. Default is $1e6$. If the algorithm does not converge, consider increasing maxit. |
| peps | convergence threshold for proximal map of sg-LASSO penalty. Each loop continues until G group difference sup-norm, $\ \beta_G^k - \beta_G^{k-1}\ _\infty$, is less than peps. Defaults value is $1e-8$. |

Details

The sequence of linear regression models implied by λ vector is fit by block coordinate-descent. The objective function is

$$\|y - \iota\alpha - x\beta\|_T^2 + 2\lambda\Omega_\gamma(\beta),$$

where $u \in R^T$ and $\|u\|_T^2 = \langle u, u \rangle / T$ is the empirical inner product. The penalty function $\Omega_\gamma(\cdot)$ is applied on β coefficients and is

$$\Omega_\gamma(\beta) = \gamma|\beta|_1 + (1 - \gamma)|\beta|_{2,1},$$

a convex combination of LASSO and group LASSO penalty functions.

Value

sglfit object.

Author(s)

Jonas Striaukas

Examples

```
set.seed(1)
x = matrix(rnorm(100 * 20), 100, 20)
beta = c(5,4,3,2,1,rep(0, times = 15))
y = x%%beta + rnorm(100)
gindex = sort(rep(1:4,times=5))
sglfit(x = x, y = y, gindex = gindex, gamma = 0.5)
```

thetafit

Nodewise LASSO regressions to fit the precision matrix Θ

Description

Fits the precision matrix Θ by running nodewise LASSO regressions.

Usage

```
thetafit(x, parallel = FALSE, ncores = getOption("mc.cores", NULL),
         intercept = FALSE, K = 20, l = 5, seed = NULL, verbose = FALSE,
         registerpar = TRUE, ...)
```

Arguments

| | |
|-----------|---|
| x | T by p data matrix, where T and p respectively denote the sample size and the number of regressors. |
| parallel | if TRUE, use parallel foreach to fit nodewise LASSO regressions. Parallel registered within the function. |
| ncores | number of cores used in parallelization |
| intercept | whether intercept be fitted (TRUE) or set to zero (FALSE). Default is FALSE. |
| K | number of folds of the cv loop. Default set to 20. |
| l | the gap used to drop observations round test set data. See tscv.sglfit for more details. |

| | |
|-------------|--|
| seed | set a value for seed to control results replication, i.e. <code>set.seed(seed)</code> is used. seed is stored in the output list. Default set to <code>as.numeric(Sys.Date())</code> . |
| verbose | if TRUE, prints progress bar. Default set to FALSE. |
| registerpar | if TRUE, register parallelization using <code>registerDoParallel</code> . Default set to TRUE. |
| ... | Other arguments that can be passed to tscv.sglfit . |

Details

The function runs [tscv.sglfit](#) p times by regressing j -th covariate on all other covariates excluding j -th covariate. The precision matrix is then constructed based on LASSO estimates. Each nodewise LASSO regression tuning parameter λ is optimized using time series cross-validation. See [tscv.sglfit](#) for more details on cross-validation implementation.

Value

thetafit object.

Author(s)

Jonas Striaukas

Examples

```
set.seed(1)
x = matrix(rnorm(100 * 20), 100, 20)
thetafit(x = x, parallel = FALSE)
```

tscv.sglfit

Time series cross-validation fit for sg-LASSO

Description

Does k -fold time series cross-validation for sg-LASSO regression model.

The function runs [sglfit](#) $K+1$ times; the first to get the path solution in lambda sequence, the rest to compute the fit with each of the test observation $k \in K$. The average error and standard deviation over the folds is computed, and the optimal regression coefficients are returned for `lam.min` and `lam.1se`. Solutions are computed for a fixed γ .

Usage

```
tscv.sglfit(x, y, lambda = NULL, gamma = 1.0, gindex = 1:p,
            K = 20, l = 5, parallel = FALSE, seed = NULL, ...)
```

Arguments

| | |
|----------|---|
| x | T by p data matrix, where T and p respectively denote the sample size and the number of regressors. |
| y | T by 1 response variable. |
| lambda | a user-supplied lambda sequence. By leaving this option unspecified (recommended), users can have the program compute its own λ sequence based on <code>nlambda</code> and <code>gamma lambda.factor</code> . It is better to supply, if necessary, a decreasing sequence of lambda values than a single (small) value, as warm-starts are used in the optimization algorithm. The program will ensure that the user-supplied lambda sequence is sorted in decreasing order before fitting the model. |
| gamma | sg-LASSO mixing parameter. $\gamma = 1$ gives LASSO solution and $\gamma = 0$ gives group LASSO solution. |
| gindex | p by 1 vector indicating group membership of each covariate. |
| K | number of observations drawn for the test set. Default set to 20. |
| l | the gap used to drop observations round the test set data point. Default set to 5. |
| parallel | if TRUE, use parallel foreach to fit each fold. Must register parallel before hand, such as <code>doMC</code> or others. See the example below. |
| seed | set a value for seed to control results replication, i.e. <code>set.seed(seed)</code> is used. seed is stored in the output list. Default set to <code>as.numeric(Sys.Date())</code> . |
| ... | Other arguments that can be passed to sglfit . |

Details

The cross-validation is run for sg-LASSO linear model. The sequence of linear regression models implied by λ vector is fit by block coordinate-descent. The objective function is

$$\|y - \iota\alpha - x\beta\|_T^2 + 2\lambda\Omega_\gamma(\beta),$$

where $\iota \in R^T$ and $\|u\|_T^2 = \langle u, u \rangle / T$ is the empirical inner product. The penalty function $\Omega_\gamma(\cdot)$ is applied on β coefficients and is

$$\Omega_\gamma(\beta) = \gamma|\beta|_1 + (1 - \gamma)|\beta|_{2,1},$$

a convex combination of LASSO and group LASSO penalty functions.

Value

tscv.sglfit object.

Author(s)

Jonas Striaukas

Examples

```

set.seed(1)
x = matrix(rnorm(100 * 20), 100, 20)
beta = c(5,4,3,2,1,rep(0, times = 15))
y = x%%beta + rnorm(100)
gindex = sort(rep(1:4,times=5))
tscv.sglfit(x = x, y = y, gindex = gindex, gamma = 0.5,
  standardize = FALSE, intercept = FALSE)
## Not run:
# Parallel
require(doMC)
registerDoMC(cores = 2)
x = matrix(rnorm(1000 * 20), 1000, 20)
beta = c(5,4,3,2,1,rep(0, times = 15))
y = x%%beta + rnorm(1000)
gindex = sort(rep(1:4,times=5))
system.time(tscv.sglfit(x = x, y = y, gindex = gindex, gamma = 0.5,
  standardize = FALSE, intercept = FALSE))
system.time(tscv.sglfit(x = x, y = y, gindex = gindex, gamma = 0.5,
  standardize = FALSE, intercept = FALSE, parallel = TRUE))

## End(Not run)

```

us_rgdg

US real GDP data with several high-frequency predictors

Description

US real GDP, Chicago National Activity Index, Nonfarm payrolls and ADS Index

Usage

```
data(us_rgdg)
```

Format

A `list` object.

Source

```

rgdp
cfnai
payems
ads

```

Examples

```
data(us_rgd)
us_rgd$rgdp # - GDP data
us_rgd$cfnai # - CFNAI predictor data
us_rgd$payems # - Nonfarm payrolls predictor data
us_rgd$ads # - ADS predictor data
```

Index

* datasets

- alfred_vintages, 3
- market_ret, 13
- rgdp_dates, 27
- rgdp_vintages, 27
- us_rgdp, 33

* package

- midasml-package, 2

alfred_vintages, 3

cv.panel.sglfit, 3, 19
cv.sglfit, 5, 8, 20, 22, 26

data.frame, 13
dateMatch, 7

fa.sglfit, 8, 21

gb, 9

ic.panel.sglfit, 10, 22
ic.sglfit, 11, 26

lb, 12
list, 3, 27, 33

market_ret, 13
midas.ardl, 14
midasml (midasml-package), 2
midasml-package, 2
mixed_freq_data, 15
mixed_freq_data_single, 16
monthBegin, 17
monthEnd, 18

predict.cv.panel.sglfit, 19
predict.cv.sglfit, 20
predict.fa.sglfit, 8, 20
predict.ic.panel.sglfit, 21
predict.ic.sglfit, 22

predict.sglpath, 23

reg.panel.sgl, 24
reg.sgl, 25
rgdp_dates, 27
rgdp_vintages, 27

sglfit, 3–6, 10–12, 23, 24, 28, 31, 32

thetafit, 30
tscv.sglfit, 26, 30, 31, 31

us_rgdp, 33