

Package ‘mkssd’

May 8, 2026

Version 1.2

Date 2022-02-21

Title Efficient Multi-Level k-Circulant Supersaturated Designs

Author B N Mandal <mandal.stat@gmail.com>

Maintainer B N Mandal <mandal.stat@gmail.com>

Depends R(>= 2.13.0)

Description Generates efficient balanced non-aliased multi-level k-circulant supersaturated designs by interchanging the elements of the generator vector. Attempts to generate a supersaturated design that has chisquare efficiency more than user specified efficiency level (mef). Displays the progress of generation of an efficient multi-level k-circulant design through a progress bar. The progress of 100% means that one full round of interchange is completed. More than one full round (typically 4-5 rounds) of interchange may be required for larger designs.

License GPL (>= 2)

NeedsCompilation no

Repository CRAN

Date/Publication 2022-02-22 09:10:05 UTC

Contents

mkssd	1
Index	4

mkssd	<i>Efficient multi-level k-circulant supersaturated designs</i>
-------	---

Description

mkssd is a package that generates efficient balanced non-aliased multi-level k-circulant supersaturated designs by interchanging the elements of the generator vector. The package tries to generate a supersaturated design that has chisquare efficiency more than user specified efficiency level (mef). The package also displays the progress of generation of an efficient multi-level k-circulant design through a progress bar. The progress of 100 per cent means that one full round of interchange is completed. More than one full round (typically 4-5 rounds) of interchange may be required for larger designs.

Usage

```
mkssd(m, n, q, k, mef)
```

Arguments

m	number of factors
n	number of runs
q	number of levels
k	order of circulation
mef	minimum efficiency required, should be between 0 to 1

Value

A list containing following items

m	number of factors
n	number of runs
q	number of levels
k	order of circulation
generator.vector	generator vector
design	design
efficiency	chi-square efficiency
max.chisq	maximum chi-square
time.taken	time taken to generate the design
number.aliased.pairs	number of aliased pairs

Author(s)

B N Mandal

References

B. N. Mandal, V. K. Gupta & Rajender Parsad (2014) Construction of Efficient Multi-Level k-Circulant Supersaturated Designs, Communications in Statistics - Theory and Methods, 43:3, 599-615

mkssd

3

Examples

`mkssd(10,6,3,2,1)`

Index

- * **efficiency**
mkssd, 1
- * **k-circulant**
mkssd, 1
- * **mkssd**
mkssd, 1
- * **multi-level**
mkssd, 1
- * **supersaturated design**
mkssd, 1

mkssd, 1