

Package ‘modest’

May 9, 2026

Title Model-Based Dose-Escalation Trials

Version 0.3-1

Date 2017-11-03

Description User-friendly Shiny apps for designing and evaluating phase I cancer clinical trials, with the aim to estimate the maximum tolerated dose (MTD) of a novel drug, using a Bayesian decision procedure based on logistic regression.

License GPL-2

Imports knitr, rhandsontable, shiny, shinyBS

VignetteBuilder knitr

BugReports <https://github.com/PhilipPallmann/modest/issues/>

NeedsCompilation no

Author Philip Pallmann [aut, cre],
Fang Wan [aut]

Maintainer Philip Pallmann <pallmannp@cardiff.ac.uk>

Repository CRAN

Date/Publication 2017-11-16 22:24:10 UTC

Contents

apps	1
Index	3

apps	<i>Shiny GUIs for model-based dose-escalation studies</i>
------	---

Description

A user-friendly tool to design and evaluate phase I cancer clinical trials, with the aim to estimate the maximum tolerated dose (MTD) of a novel drug. This is a point-and-click implementation of the dose-escalation study design proposed by Zhou & Whitehead (2003) that uses a Bayesian logistic regression method. The graphical user interfaces (GUIs) are based on R’s Shiny system.

Usage

```
design()  
conduct()
```

Details

This package contains two separate modules:

1) The design module allows to investigate different design options and parameters, and to simulate their operating characteristics under various scenarios. Type `design()` and the GUI will open in a browser window.

2) The conduct module provides guidance for dose selection throughout the study, and a recommendation for the MTD at the end. Type `conduct()` and the GUI will open in a browser window.

Both modules generate a variety of graphs to visualise data and design properties, and create downloadable PDF reports of simulation results and study data analyses.

Author(s)

Philip Pallmann (<pallmannp@cardiff.ac.uk>)

References

Zhou Y, Whitehead J (2003) Practical implementation of Bayesian dose-escalation procedures. *Drug Information Journal*, **37**(1), 45–59.

Examples

```
design()  
conduct()
```

Index

* **misc**

apps, 1

apps, 1

conduct (apps), 1

design (apps), 1