

# Package ‘mxkssd’

May 9, 2026

**Version** 1.2

**Date** 2022-02-21

**Title** Efficient Mixed-Level k-Circulant Supersaturated Designs

**Author** B N Mandal <mandal.stat@gmail.com>

**Maintainer** B N Mandal <mandal.stat@gmail.com>

**Depends** R(>= 2.13.0)

**Description** Generates efficient balanced mixed-level k-circulant supersaturated designs by interchanging the elements of the generator vector. Attempts to generate a supersaturated design that has EfNOD efficiency more than user specified efficiency level (mef). Displays the progress of generation of an efficient mixed-level k-circulant design through a progress bar. The progress of 100 per cent means that one full round of interchange is completed. More than one full round (typically 4-5 rounds) of interchange may be required for larger designs. For more details, please see Mandal, B.N., Gupta V. K. and Parsad, R. (2011). Construction of Efficient Mixed-Level k-Circulant Supersaturated Designs, Journal of Statistical Theory and Practice, 5:4, 627-648, <doi:10.1080/15598608.2011.10483735>.

**License** GPL (>= 2)

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2022-02-23 12:50:15 UTC

## Contents

mxkssd . . . . .	2
<b>Index</b>	<b>4</b>

---

 mxkssd

*Efficient mixed-level k-circulant supersaturated designs*


---

## Description

mxkssd is a package that generates efficient balanced mixed-level k-circulant supersaturated designs by interchanging the elements of the generator vector. The package tries to generate a supersaturated design that has EfNOD efficiency more than user specified efficiency level (mef). The package also displays the progress of generation of an efficient mixed-level k-circulant design through a progress bar. The progress of 100 per cent means that one full round of interchange is completed. More than one full round (typically 4-5 rounds) of interchange may be required for larger designs.

## Usage

```
mxkssd(m,n,level_vec,k,mef)
```

## Arguments

m	number of factors
n	number of runs
level_vec	level vector containing the levels of the factors such that (n-1) factors have each of these levels
k	order of circulation
mef	minimum efficiency required, should be between 0 to 1

## Value

A list containing following items

m	number of factors
n	number of runs
level_vec	level vector containing the levels of the factors such that (n-1) factors have each of these levels
k	order of circulation
generator.vector	generator vector
design	design
EfNOD.efficiency	EfNOD efficiency
max.fNOD	maximum fNOD
time.taken	time taken to generate the design
number.aliased.pairs	number of aliased pairs of columns

**Author(s)**

B N Mandal

**References**

B. N. Mandal, V. K. Gupta & Rajender Parsad (2011) Construction of Efficient Mixed-Level k-Circulant Supersaturated Designs, *Journal of Statistical Theory and Practice*, 5:4, 627-648, DOI: 10.1080/15598608.2011.10483735

**Examples**

```
##To generate an efficient mixed level 2-circulant supersaturated design
#with 8 runs and 14 factors such that 7 factors have number of levels 2 and
#another 7 factors have number of levels 4. So the level_vec is c(2,4).
#The required minimum efficiency is 1.
mxkssd(14,8,c(2,4),2,1)
```

# Index

- \* **efficiency**  
mxkssd, 2
- \* **k-circulant**  
mxkssd, 2
- \* **mixed-level**  
mxkssd, 2
- \* **mxkssd**  
mxkssd, 2
- \* **supersaturated design**  
mxkssd, 2

mxkssd, 2