

Package ‘nimblewomble’

May 9, 2026

Type Package

Title Bayesian Wombling using 'nimble'

Version 0.1.0

Description A software package to perform Wombling, or boundary analysis, using the 'nimble' Bayesian hierarchical modeling environment. Wombling is used widely to track regions of rapid change within the spatial reference domain. Specific functions in the package implement Gaussian process models for point-referenced spatial data followed by predictive inference on rates of change over curves using line integrals. We demonstrate model based Bayesian inference using posterior distributions featuring simple analytic forms while offering uncertainty quantification over curves. For more details on wombling please see, Banerjee and Gelfand (2006) <[doi:10.1198/016214506000000041](https://doi.org/10.1198/016214506000000041)> and Halder, Banerjee and Dey (2024) <[doi:10.1080/01621459.2023.2177166](https://doi.org/10.1080/01621459.2023.2177166)>.

License MIT + file LICENSE

Encoding UTF-8

Imports nimble, ggplot2, MBA, metR, ggspatial, sf, terra, sp, coda, methods

RoxygenNote 7.3.2

NeedsCompilation no

Author Aritra Halder [aut, cre],
Sudipto Banerjee [aut]

Maintainer Aritra Halder <aritra.halder@drexel.edu>

Repository CRAN

Date/Publication 2025-04-09 10:00:10 UTC

Contents

curvatures_gaussian	2
curvatures_matern2	3
gamma1.mcov1	4
gamma1n2.gauss	5
gamma1n2.mcov2	6
gamma_int	7

gaussian	8
gp_fit	9
gradients_matern1	10
materncov1	11
materncov2	12
pnorm_nimble	13
significance	14
sprates	15
spwombling	17
sp_ggplot	20
wombling_gaussian	21
wombling_matern1	22
wombling_matern2	24
zbeta_gaussian	25
zbeta_matern1	26
zbeta_matern2	27
zbeta_samples	28
zXbeta	29
Index	31

curvatures_gaussian	<i>Posterior samples of rates of change (gradients and curvatures) for the Matern kernel with $\nu \rightarrow \infty$ producing the squared exponential kernel.</i>
---------------------	---

Description

For internal use only.

Usage

```
curvatures_gaussian(dists.1, dists.2, dists.3, z, phi, sigma2)
```

Arguments

dists.1	distance matrix generated from coordinates
dists.2	distance of grid from coordinates
dists.3	delta = coordinate - grid
z	posterior samples of $Z(s)$
phi	posterior samples of ϕ
sigma2	posterior samples of σ^2

Value

A matrix of posterior samples for the gradient and curvatures. For internal use only.

Author(s)

Aritra Halder <aritra.halder@drexel.edu>,
Sudipto Banerjee <sudipto@ucla.edu>

Examples

```
## Not run:
#####
# Internal use only #
#####
# Example usage inside of nimblewomble::sprates()
CG = compileNimble(curvatures_gaussian)
sprates = CG(dists.1 = distM,
             dists.2 = dist.2,
             dists.3 = dist.3,
             z = z,
             phi = phi,
             sigma2 = sigma2)

## End(Not run)
```

curvatures_matern2	<i>Posterior samples of rates of change (gradients and curvatures) for the Matern kernel with $\nu = 5/2$</i>
--------------------	--

Description

For internal use only.

Usage

```
curvatures_matern2(dists.1, dists.2, dists.3, z, phi, sigma2)
```

Arguments

dists.1	distance matrix generated from coordinates
dists.2	distance of grid from coordinates
dists.3	delta = coordinate - grid
z	posterior samples of $Z(s)$
phi	posterior samples of ϕ
sigma2	posterior samples of σ^2

Value

A matrix of posterior samples for the gradient and curvatures. For internal use only.

Author(s)

Aritra Halder <aritra.halder@drexel.edu>
 Sudipto Banerjee <sudipto@ucla.edu>

Examples

```
## Not run:
#####
# Internal use only #
#####
# Example usage inside of nimblewomble::sprates()
CM2 = compileNimble(curvatures_matern2)
sprates = CM2(dists.1 = distM,
              dists.2 = dist.2,
              dists.3 = dist.3,
              z = z,
              phi = phi,
              sigma2 = sigma2)

## End(Not run)
```

 gamma1.mcov1

Cross-covariance terms for the posterior distribution of wombling measures for Matern $\nu = 3/2$.

Description

For internal use only. Performs one-dimensional quadrature using integral as a limit of a sum.

Usage

```
gamma1.mcov1(coords, t, u, s0, phi)
```

Arguments

coords	coordinates
t	value of t
u	vector of u
s0	starting point on curve s_0
phi	posterior sample of ϕ

Value

A matrix of cross-covariance terms. For internal use only.

Author(s)

Aritra Halder <aritra.halder@drexel.edu>
 Sudipto Banerjee <sudipto@ucla.edu>

Examples

```
## Not run:
#####
# Internal use only #
#####
# Example usage inside nimblewomble::wombling_matern1(...)
gamma1.mcov1(coords = coords[1:ncoords, 1:2], t = tvec[j],
             u = umat[j, 1:2], s0 = curve[j, 1:2], phi = phi[i])

## End(Not run)
```

gamma1n2.gauss	<i>Cross-covariance terms for the posterior distribution of wombling measures for Matern $\nu \rightarrow \infty$, the squared exponential kernel.</i>
----------------	---

Description

For internal use only. Performs one-dimensional quadrature using integral as a limit of a sum.

Usage

```
gamma1n2.gauss(coords, t, u, s0, phi)
```

Arguments

coords	coordinates
t	value of t
u	vector of u
s0	starting point on curve s_0
phi	posterior sample of ϕ

Value

A matrix of cross-covariance terms. For internal use only.

Author(s)

Aritra Halder <aritra.halder@drexel.edu>
 Sudipto Banerjee <sudipto@ucla.edu>

Examples

```
## Not run:
#####
# Internal use only #
#####
# Example usage inside nimblewomble::wombling_gaussian(...)
gamma1n2.gauss(coords = coords[1:ncoords, 1:2], t = tvec[j],
               u = umat[j, 1:2], s0 = curve[j, 1:2], phi = phi[i])

## End(Not run)
```

gamma1n2.mcov2	<i>Cross-covariance terms for the posterior distribution of wombling measures for Matern $\nu = 5/2$, the squared exponential kernel.</i>
----------------	--

Description

For internal use only. Performs one-dimensional quadrature using integral as a limit of a sum.

Usage

```
gamma1n2.mcov2(coords, t, u, s0, phi)
```

Arguments

coords	coordinates
t	value of t
u	vector of u
s0	starting point on curve s_0
phi	posterior sample of ϕ

Value

A matrix of cross-covariance terms. For internal use only.

Author(s)

Aritra Halder <aritra.halder@drexel.edu>,
Sudipto Banerjee <sudipto@ucla.edu>

Examples

```
## Not run:
#####
# Internal use only #
#####
# Example usage inside nimblewomble::wombling_matern2(...)
gammaInt2.mcov2(coords = coords[1:ncoords, 1:2], t = tvec[j],
                u = umat[j, 1:2], s0 = curve[j, 1:2], phi = phi[i])

## End(Not run)
```

gamma_int

*Incomplete Gamma Function***Description**

For internal use only. Use integration as a limit of a sum to numerically compute the incomplete gamma integral

Usage

```
gamma_int(x, a, b)
```

Arguments

x	gamma quantile
a	shape parameter
b	scale parameter

Value

A scalar value of the integral. For internal use only.

Author(s)

Aritra Halder <aritra.halder@drexel.edu>,
Sudipto Banerjee <sudipto@ucla.edu>

Examples

```
#####
# Internal use only #
#####
# Example usage in nimblewomble::wombling_matern1(...) or,
# nimblewomble::wombling_matern2(...)
require(nimble)

Gint = compileNimble(gamma_int)
Gint(x = 1, a = 1, b = 1)
```

 gaussian

Squared Exponential Covariance kernel

Description

Computes the Matern covariance matrix with fractal parameter $\nu \rightarrow \infty$.

Usage

```
gaussian(dists, phi, sigma2, tau2)
```

Arguments

dists	distance matrix
phi	spatial range
sigma2	spatial variance
tau2	nugget variance

Details

Has the option to compute $\Sigma_{d \times d} + \tau^2 I_d$.

Value

A matrix of covariance terms. For internal use only.

Author(s)

Aritra Halder <aritra.halder@drexel.edu>,
Sudipto Banerjee <sudipto@ucla.edu>

Examples

```
#####
# Internal use only #
#####
# Used across multiple functions
# Example usage
require(nimble)
require(nimblewomble)

set.seed(1)
# Generated Simulated Data
N = 1e2
tau = 1
coords = matrix(runif(2 * N, -10, 10), ncol = 2)
colnames(coords) = c("x", "y")
dists = as.matrix(dist(coords))
```

```
cGaussian = compileNimble(gaussian)
cGaussian(dists = dists[1:N, 1:N], phi = 1, sigma2 = 1, tau2 = 0)
```

gp_fit

Fit a Gaussian process

Description

Fits a Gaussian process with the choice of three kernels. Uses ‘nimble’ to generate posterior samples.

Usage

```
gp_fit(
  coords = NULL,
  y = NULL,
  X = NULL,
  kernel = c("matern1", "matern2", "gaussian"),
  niter = NULL,
  nburn = NULL
)
```

Arguments

coords	spatial coordinats (supply as a matrix)
y	response
X	covariates (supply as a matrix without the intercept)
kernel	choice of kernel; must be one of "matern1", "matern2", "gaussian"
niter	number of iterations
nburn	burn-in

Value

A list of MCMC samples containing the covariance parameters and the parameter estimates with associated 95

Author(s)

Aritra Halder <aritra.halder@drexel.edu>,
Sudipto Banerjee <sudipto@ucla.edu>

Examples

```

require(nimble)
require(nimblewomble)

set.seed(1)
# Generated Simulated Data
N = 1e2
tau = 1
coords = matrix(runif(2 * N, -10, 10), ncol = 2)
colnames(coords) = c("x", "y")
y = rnorm(N, mean = 20 * sin(sqrt(coords[, 1]^2 + coords[, 2]^2)), sd = tau)
# Posterior samples for theta
mc_sp = gp_fit(coords = coords, y = y, kernel = "matern2")
mc_sp$estimates

```

gradients_matern1	<i>Posterior samples of rates of change (gradients) for the Matern kernel with $\nu = 3/2$</i>
-------------------	---

Description

For internal use only.

Usage

```
gradients_matern1(dists.1, dists.2, dists.3, z, phi, sigma2)
```

Arguments

dists.1	distance matrix generated from coordinates
dists.2	distance of grid from coordinates
dists.3	delta = coordinate - grid
z	posterior samples of $Z(s)$
phi	posterior samples of ϕ
sigma2	posterior samples of σ^2

Value

Returns a matrix of gradients. For internal use only.

Author(s)

Aritra Halder <aritra.halder@drexel.edu>,
Sudipto Banerjee <sudipto@ucla.edu>

Examples

```
## Not run:
#####
# Internal use only #
#####
# Example usage inside of nimblewomble::sprates()
GM1 = compileNimble(gradients_matern1)
sprates = GM1(dists.1 = distM,
              dists.2 = dist.2,
              dists.3 = dist.3,
              z = z,
              phi = phi,
              sigma2 = sigma2)

## End(Not run)
```

materncov1

Matern Covariance kernel with $\nu = 3/2$

Description

Computes the Matern covariance matrix with fractal parameter $\nu = 3/2$. Has the option to compute $\Sigma_{d \times d} + \tau^2 I_d$.

Usage

```
materncov1(dists, phi, sigma2, tau2)
```

Arguments

dists	distance matrix
phi	spatial range
sigma2	spatial variance
tau2	nugget variance

Value

A matrix of covariance terms. For internal use only.

Author(s)

Aritra Halder <aritra.halder@drexel.edu>,
Sudipto Banerjee <sudipto@ucla.edu>

Examples

```
#####
# Internal use only #
#####
# Used across multiple functions
# Example usage
require(nimble)
require(nimblewomble)

set.seed(1)
# Generated Simulated Data
N = 1e2
tau = 1
coords = matrix(runif(2 * N, -10, 10), ncol = 2)
colnames(coords) = c("x", "y")
dists = as.matrix(dist(coords))

cMaterncov1 = compileNimble(materncov1)
cMaterncov1(dists = dists[1:N, 1:N], phi = 1, sigma2 = 1, tau2 = 0)
```

materncov2

Matern Covariance kernel with $\nu = 5/2$

Description

Computes the Matern covariance matrix with fractal parameter $\nu = 5/2$. Has the option to compute $\Sigma_{d \times d} + \tau^2 I_d$.

Usage

```
materncov2(dists, phi, sigma2, tau2)
```

Arguments

dists	distance matrix
phi	spatial range
sigma2	spatial variance
tau2	nugget variance

Value

A matrix of covariance terms. For internal use only.

Author(s)

Aritra Halder <aritra.halder@drexel.edu>,
Sudipto Banerjee <sudipto@ucla.edu>

Examples

```
#####
# Internal use only #
#####
# Used across multiple functions
# Example usage
require(nimble)
require(nimblewomble)

set.seed(1)
# Generated Simulated Data
N = 1e2
tau = 1
coords = matrix(runif(2 * N, -10, 10), ncol = 2)
colnames(coords) = c("x", "y")
dists = as.matrix(dist(coords))

cMaterncov1 = compileNimble(materncov1)
cMaterncov1(dists = dists[1:N, 1:N], phi = 1, sigma2 = 1, tau2 = 0)
```

pnorm_nimble

Computes the Cumulative Distribution Function (CDF) for the standard Gaussian probability distribution

Description

For internal use only.

Usage

```
pnorm_nimble(x)
```

Arguments

x standard Gaussian quantile

Value

A numeric value of the CDF. For internal use only.

Author(s)

Aritra Halder <aritra.halder@drexel.edu>,
Sudipto Banerjee <sudipto@ucla.edu>

Examples

```
#####
# Internal use only #
#####
# Example usage inside of nimblewomble::wombling_gaussian()
require(nimble)
require(nimblewomble)

cPnorm_nimble = compileNimble(pnorm_nimble)
cPnorm_nimble(1)
```

significance

Determines significance for posterior estimates

Description

For internal use only.

Usage

```
significance(data_frame = NULL)
```

Arguments

`data_frame` data frame consisting of median, lower and upper confidence interval for estimates

Value

A data frame consisting median, lower and upper confidence interval for estimates and significance (0 or 1). For internal use only.

Author(s)

Aritra Halder <aritra.halder@drexel.edu>,
Sudipto Banerjee <sudipto@ucla.edu>

Examples

```
## Not run:
#####
# Internal use only #
#####
# Example usage inside of nimblewomble::spwombling(...)
estimate.wm$sig = significance(estimate.wm)

## End(Not run)
```

sprates	<i>Posterior samples for rates of change</i>
---------	--

Description

Posterior samples for rates of change

Usage

```
sprates(
  coords = NULL,
  grid = NULL,
  model = NULL,
  kernel = c("matern1", "matern2", "gaussian")
)
```

Arguments

coords	coordinates
grid	grid for sampling the rates of change
model	posterior samples of $Z(s)$, ϕ , σ^2
kernel	choice of kernel; must be one of "matern1", "matern2", "gaussian"

Value

A list containing MCMC samples for gradients and curvatures and the associated estimates and 95

Author(s)

Aritra Halder <aritra.halder@drexel.edu>
Sudipto Banerjee <sudipto@ucla.edu>

Examples

```
require(nimble)
require(nimblewomble)

set.seed(1)
# Generated Simulated Data
N = 1e2
tau = 1
coords = matrix(runif(2 * N, -10, 10), ncol = 2); colnames(coords) = c("x", "y")
y = rnorm(N, mean = 20 * sin(sqrt(coords[, 1]^2 + coords[, 2]^2)), sd = tau)

# Create equally spaced grid of points
xsplitted = ysplitted = seq(-10, 10, by = 1)[-c(1, 21)]
grid = as.matrix(expand.grid(xsplitted, ysplitted), ncol = 2)
colnames(grid) = c("x", "y")
```

```
#####
# Process for True Rates of Change #
#####
# Gradient along x
true_sx = round(20 * cos(sqrt(grid[,1]^2 + grid[,2]^2)) *
                grid[,1]/sqrt(grid[,1]^2 + grid[,2]^2), 3)
# Gradient along y
true_sy = round(20 * cos(sqrt(grid[,1]^2 + grid[,2]^2)) *
                grid[,2]/sqrt(grid[,1]^2 + grid[,2]^2), 3)
# Curvature along x
true_sxx = round(20 * cos(sqrt(grid[,1]^2 + grid[,2]^2))/
                sqrt(grid[,1]^2 + grid[,2]^2) -
                20 * cos(sqrt(grid[,1]^2 + grid[,2]^2)) *
                grid[,1]^2/(grid[,1]^2 + grid[,2]^2)^(3/2) -
                20 * sin(sqrt(grid[,1]^2 + grid[,2]^2)) *
                grid[,1]^2/(grid[,1]^2 + grid[,2]^2), 3)
# Mixed Curvature
true_sxy = round(-20 * (cos(sqrt(grid[,1]^2 + grid[,2]^2)) -
                sin(sqrt(grid[,1]^2 + grid[,2]^2))) * grid[,1]
                * grid[,2]/(grid[,1]^2 + grid[,2]^2), 3)
# Curvature along y
true_syy = round(20 * cos(sqrt(grid[,1]^2 + grid[,2]^2))/
                sqrt(grid[,1]^2 + grid[,2]^2) -
                20 * cos(sqrt(grid[,1]^2 + grid[,2]^2)) *
                grid[,2]^2/(grid[,1]^2 + grid[,2]^2)^(3/2) -
                20 * sin(sqrt(grid[,1]^2 + grid[,2]^2)) *
                grid[,2]^2/(grid[,1]^2 + grid[,2]^2), 3)
# Create the plots
p1 = sp_ggplot(data_frame = data.frame(coords, z = y))
p2 = sp_ggplot(data_frame = data.frame(grid[-which(is.nan(true_sx)),],
                z = true_sx[-which(is.nan(true_sx))]))
p3 = sp_ggplot(data_frame = data.frame(grid[-which(is.nan(true_sy)),],
                z = true_sy[-which(is.nan(true_sy))]))
p4 = sp_ggplot(data_frame = data.frame(grid[-which(is.nan(true_sxx)),],
                z = true_sxx[-which(is.nan(true_sxx))]))
p5 = sp_ggplot(data_frame = data.frame(grid[-which(is.nan(true_sxy)),],
                z = true_sxy[-which(is.nan(true_sxy))]))
p6 = sp_ggplot(data_frame = data.frame(grid[-which(is.nan(true_syy)),],
                z = true_syy[-which(is.nan(true_syy))]))

#####
# Fit a Gaussian Process #
#####
# Posterior samples for theta
mc_sp = gp_fit(coords = coords, y = y, kernel = "matern2")
# Posterior samples for Z(s) and beta
model = zbeta_samples(y = y, coords = coords,
                    model = mc_sp$mcmc,
                    kernel = "matern2")

#####
# Rates of Change #
```

```
#####
gradients = sprates(grid = grid,
                   coords = coords,
                   model = model,
                   kernel = "matern2")
p8 = sp_ggplot(data_frame = data.frame(grid,
                                       z = gradients$estimate.sx[, "50%"],
                                       sig = gradients$estimate.sx$sig))
p9 = sp_ggplot(data_frame = data.frame(grid,
                                       z = gradients$estimate.sy[, "50%"],
                                       sig = gradients$estimate.sy$sig))
p10 = sp_ggplot(data_frame = data.frame(grid,
                                       z = gradients$estimate.sxx[, "50%"],
                                       sig = gradients$estimate.sxx$sig))
p11 = sp_ggplot(data_frame = data.frame(grid,
                                       z = gradients$estimate.sxy[, "50%"],
                                       sig = gradients$estimate.sxy$sig))
p12 = sp_ggplot(data_frame = data.frame(grid,
                                       z = gradients$estimate.syy[, "50%"],
                                       sig = gradients$estimate.syy$sig))
```

spwombling

Posterior samples for wombling measures

Description

Posterior samples for wombling measures

Usage

```
spwombling(
  coords = NULL,
  curve = NULL,
  model = NULL,
  kernel = c("matern1", "matern2", "gaussian")
)
```

Arguments

coords	coordinates
curve	coordinates of the curve for wombling
model	posterior samples of $Z(s)$, ϕ , σ^2
kernel	choice of kernel; must be one of "matern1", "matern2", "gaussian"

Value

A list containing posterior samples of wombling measures and associated estimates and their 95

Author(s)

Aritra Halder <aritra.halder@drexel.edu>
 Sudipto Banerjee <sudipto@ucla.edu>

Examples

```
## Not run:
require(nimble)
require(nimblewomble)

set.seed(1)
# Generated Simulated Data
N = 1e2
tau = 1
coords = matrix(runif(2 * N, -10, 10), ncol = 2)
  colnames(coords) = c("x", "y")
y = rnorm(N, mean = 20 * sin(sqrt(coords[, 1]^2 + coords[, 2]^2)), sd = tau)

# Create equally spaced grid of points
xsplit = ysplit = seq(-10, 10, by = 1)[-c(1, 21)]
grid = as.matrix(expand.grid(xsplit, ysplit), ncol = 2)
colnames(grid) = c("x", "y")

#####
# Fit a Gaussian Process #
#####
# Posterior samples for theta
mc_sp = gp_fit(coords = coords, y = y, kernel = "matern2")
# Posterior samples for Z(s) and beta
model = zbeta_samples(y = y, coords = coords,
                      model = mc_sp$mcmc,
                      kernel = "matern2")

#####
# Wombling #
#####
# Pick any curve (contour) of your choice
# curve = your contour
tvec = sapply(1:(nrow(curve) - 1), function(x){
  sqrt(sum((curve[(x + 1),] - curve[x,])^2))})
umat = as.matrix(t(sapply(1:(nrow(curve) - 1), function(x){
  (curve[(x + 1),] - curve[x,])}))/tvec)

wm = spwombling(coords = coords,
                curve = curve,
                model = model,
                kernel = "matern2")

# Total wombling measure for gradient
colSums(wm$estimate.wm.1[, -4]); colSums(wm$estimate.wm.1[, -4])/sum(tvec)
# Total wombling measure for curvature
colSums(wm$estimate.wm.2[, -4]); colSums(wm$estimate.wm.2[, -4])/sum(tvec)
```

```

# Color code points based on significance
col.pts.1 = sapply(wm$estimate.wm.1$sig, function(x){
  if(x == 1) return("green")
  else if(x == -1) return("cyan")
  else return(NA)
})

col.pts.2 = sapply(wm$estimate.wm.2$sig, function(x){
  if(x == 1) return("green")
  else if(x == -1) return("cyan")
  else return(NA)
})

p13 = sp_ggplot(data_frame = data.frame(coords, y))
p14 = p13 + geom_path(curve, mapping = aes(x, y), linewidth = 2)
p15 = p13 + geom_path(curve, mapping = aes(x, y), linewidth = 2) +
  geom_path(curve, mapping = aes(x, y),
    colour = c(col.pts.1, NA), linewidth = 1, na.rm = TRUE)
p16 = p13 + geom_path(curve, mapping = aes(x, y), linewidth = 2) +
  geom_path(curve, mapping = aes(x, y),
    colour = c(col.pts.2, NA), linewidth = 1, na.rm = TRUE)

#####
# True Values #
#####
truth = matrix(0, nrow = nrow(curve) - 1, ncol = 2)
rule = seq(0, 1, by = 0.01)

for(i in 1:(nrow(curve) - 1)){
  u.perp = c(umat[i, 2], -umat[i, 1])
  s0 = curve[i,]

  truth.lsegment = sapply(rule * tvec[i], function(x){
    s.t = s0 + x * umat[i,]
    true_sx = 20 * cos(sqrt(s.t[1]^2 + s.t[2]^2)) * s.t[1]/
      sqrt(s.t[1]^2 + s.t[2]^2)
    true_sy = 20 * cos(sqrt(s.t[1]^2 + s.t[2]^2)) * s.t[2]/
      sqrt(s.t[1]^2 + s.t[2]^2)
    true_sx * u.perp[1] + true_sy * u.perp[2]
  })

  truth[i, 1] = sum(truth.lsegment * (tvec[i]/101))

  truth.lsegment = sapply(rule * tvec[i], function(x){
    s.t = s0 + x * umat[i,]
    true_sxx = 20 * cos(sqrt(s.t[1]^2 + s.t[2]^2))/sqrt(s.t[1]^2 + s.t[2]^2) -
      20 * cos(sqrt(s.t[1]^2 + s.t[2]^2)) *
        s.t[1]^2/(s.t[1]^2 + s.t[2]^2)^(3/2) -
      20 * sin(sqrt(s.t[1]^2 + s.t[2]^2)) * s.t[1]^2/(s.t[1]^2 + s.t[2]^2)
    true_sxy = -20 * (cos(sqrt(s.t[1]^2 + s.t[2]^2)) -
      sin(sqrt(s.t[1]^2 + s.t[2]^2))) *

```

```

        s.t[1] * s.t[2]/(s.t[1]^2 + s.t[2]^2)
true_syy = 20 * cos(sqrt(s.t[1]^2 + s.t[2]^2))/sqrt(s.t[1]^2 + s.t[2]^2) -
  20 * cos(sqrt(s.t[1]^2 + s.t[2]^2)) *
    s.t[2]^2/(s.t[1]^2 + s.t[2]^2)^(3/2) -
  20 * sin(sqrt(s.t[1]^2 + s.t[2]^2)) * s.t[2]^2/(s.t[1]^2 + s.t[2]^2)
true_sxx * u.perp[1]^2 + 2 * true_sxy * u.perp[1] * u.perp[2] +
  true_syy * u.perp[2]^2
})
truth[i, 2] = sum(truth.lsegment * (tvec[i]/101))
}
true.total = colSums(truth); true.total
true.avg.total = true.total/sum(tvec); true.avg.total

## End(Not run)

```

sp_ggplot

Spatial Plot Function

Description

Spatial Plot Function

Usage

```

sp_ggplot(
  data_frame = NULL,
  sp = FALSE,
  shape = NULL,
  legend.key.height = 0.7,
  legend.key.width = 0.4,
  text.size = 10,
  point.size = 0.7,
  clr.pt = "black",
  palette = "Spectral",
  extend = TRUE,
  title = NULL,
  bound.box = NULL
)

```

Arguments

data_frame	data frame consisting of coordinates and data
sp	logical parameter indicating whether to make a spatial plot
shape	if sp = TRUE shape file should be provided (should be an sf object)
legend.key.height	height of legend (defaults to .7)
legend.key.width	width of legend (defaults to .4)

text.size	size of legend text (defaults to 10)
point.size	size of points to be plotted (defaults to 0.7)
clr.pt	color of point to be plotted (defaults to black)
palette	(optional) color palette
extend	logical parameter indicating whether to extend the interpolation (defaults to TRUE)
title	title of the plot (defaults to NULL)
bound.box	bounding box for spatial maps (leave as NULL if not known)

Value

A ggplot object.

Author(s)

Aritra Halder <aritra.halder@drexel.edu>,
Sudipto Banerjee <sudipto@ucla.edu>

Examples

```
require(nimblewomble)

set.seed(1)
# Generated Simulated Data
N = 1e2
tau = 1
coords = matrix(runif(2 * N, -10, 10), ncol = 2)
colnames(coords) = c("x", "y")
y = rnorm(N, mean = 20 * sin(sqrt(coords[, 1]^2 + coords[, 2]^2)), sd = tau)

sp_ggplot(data_frame = data.frame(coords, z = y))
```

wombling_gaussian	<i>Posterior samples for wombling measures for the squared exponential kernel</i>
-------------------	---

Description

For internal use only.

Usage

```
wombling_gaussian(coords, curve, dists, tvec, umat, z, phi, sigma2)
```

Arguments

coords	coordinates
curve	curve coordinates
dists	distance matrix
tvec	vector of t's
umat	matrix of u's
z	posterior samples of $Z(s)$
phi	posterior samples of ϕ
sigma2	posterior samples of σ^2

Value

A matrix of wombling measures. For internal use only.

Author(s)

Aritra Halder <aritra.halder@drexel.edu>,
Sudipto Banerjee <sudipto@ucla.edu>

Examples

```
## Not run:
#####
# Internal use only #
#####
# Example usage inside of nimblewomble::spwombling(...)
WG = compileNimble(wombling_gaussian)
wmeasure = WG(coords = coords,
              curve = curve,
              dists = distM,
              tvec = tvec,
              umat = umat,
              z = z,
              phi = phi,
              sigma2 = sigma2)

## End(Not run)
```

wombling_matern1	<i>Posterior samples for wombling measures from the Matern kernel with $\nu = 3/2$</i>
------------------	---

Description

For internal use only.

Usage

```
wombling_matern1(coords, curve, dists, tvec, umat, z, phi, sigma2)
```

Arguments

coords	coordinates
curve	curve coordinates
dists	distance matrix
tvec	vector of t's
umat	matrix of u's
z	posterior samples of $Z(s)$
phi	posterior samples of ϕ
sigma2	posterior samples of σ^2

Value

A matrix of wombling measures. For internal use only.

Author(s)

Aritra Halder <aritra.halder@drexel.edu>,
Sudipto Banerjee <sudipto@ucla.edu>

Examples

```
## Not run:
#####
# Internal use only #
#####
# Example usage inside of nimblewomble::spwombling(...)
WM1 = compileNimble(wombling_matern1)
wmeasure = WM1(coords = coords,
               curve = curve,
               dists = distM,
               tvec = tvec,
               umat = umat,
               z = z,
               phi = phi,
               sigma2 = sigma2)

## End(Not run)
```

wombling_matern2 *Posterior samples for wombling measures from the Matern kernel with $\nu = 5/2$*

Description

For internal use only.

Usage

```
wombling_matern2(coords, curve, dists, tvec, umat, z, phi, sigma2)
```

Arguments

coords	coordinates
curve	curve coordinates
dists	distance matrix
tvec	vector of t's
umat	matrix of u's
z	posterior samples of $Z(s)$
phi	posterior samples of ϕ
sigma2	posterior samples of σ^2

Value

A matrix of wombling measures. For internal use only.

Author(s)

Aritra Halder <aritra.halder@drexel.edu>,
Sudipto Banerjee <sudipto@ucla.edu>

Examples

```
## Not run:
#####
# Internal use only #
#####
# Example usage inside of nimblewomble::spwombling(...)
WM2 = compileNimble(wombling_matern2)
wmeasure = WM2(coords = coords,
               curve = curve,
               dists = distM,
               tvec = tvec,
               umat = umat,
               z = z,
```

```

        phi = phi,
        sigma2 = sigma2)

## End(Not run)

```

zbeta_gaussian	<i>Posterior samples of spatial effects and intercept for the squared exponential kernel</i>
----------------	--

Description

For internal use only.

Usage

```
zbeta_gaussian(y, dists, phi, sigma2, tau2)
```

Arguments

y	response
dists	distance matrix derived from coordinates
phi	posterior samples of ϕ
sigma2	posterior samples of σ^2
tau2	posterior samples of τ^2

Value

A matrix of spatial effects and intercept. For internal use only.

Author(s)

Aritra Halder <aritra.halder@drexel.edu>,
Sudipto Banerjee <sudipto@ucla.edu>

Examples

```

## Not run:
#####
# Internal use only #
#####
# Example usage inside of nimblewomble::zbeta_samples(...)
zbG = compileNimble(zbeta_gaussian)
zb.samples = zbG(y = y, dists = dists, phi = phi, sigma2 = sigma2,
                tau2 = tau2)

## End(Not run)

```

zbeta_matern1	<i>Posterior samples of spatial effects and intercept for the Matern kernel with $\nu = 3/2$</i>
---------------	---

Description

For internal use only.

Usage

```
zbeta_matern1(y, dists, phi, sigma2, tau2)
```

Arguments

y	response
dists	distance matrix derived from coordinates
phi	posterior samples of ϕ
sigma2	posterior samples of σ^2
tau2	posterior samples of τ^2

Value

A matrix of spatial effects and intercept. For internal use only.

Author(s)

Aritra Halder <aritra.halder@drexel.edu>,
Sudipto Banerjee <sudipto@ucla.edu>

Examples

```
## Not run:
#####
# Internal use only #
#####
# Example usage inside of nimblewomble::zbeta_samples(...)
zbM1 = compileNimble(zbeta_matern1)
zb.samples = zbM1(y = y, dists = dists, phi = phi, sigma2 = sigma2,
                 tau2 = tau2)

## End(Not run)
```

zbeta_matern2	<i>Posterior samples of spatial effects and intercept for the Matern kernel with $\nu = 5/2$</i>
---------------	---

Description

For internal use only.

Usage

```
zbeta_matern2(y, dists, phi, sigma2, tau2)
```

Arguments

y	response
dists	distance matrix derived from coordinates
phi	posterior samples of ϕ
sigma2	posterior samples of σ^2
tau2	posterior samples of τ^2

Value

A matrix of spatial effects and intercept. For internal use only.

Author(s)

Aritra Halder <aritra.halder@drexel.edu>,
Sudipto Banerjee <sudipto@ucla.edu>

Examples

```
## Not run:
#####
# Internal use only #
#####
# Example usage inside of nimblewomble::zbeta_samples(...)
zbM2 = compileNimble(zbeta_matern2)
zb.samples = zbM2(y = y, dists = dists, phi = phi, sigma2 = sigma2,
                 tau2 = tau2)

## End(Not run)
```

zbeta_samples	<i>Posterior samples of spatial effects and intercept for Matern with $\nu = 3/2$</i>
---------------	--

Description

For internal use only.

Usage

```
zbeta_samples(
  coords = NULL,
  y = NULL,
  X = NULL,
  model = NULL,
  kernel = c("matern1", "matern2", "gaussian")
)
```

Arguments

coords	coordinates
y	response
X	covariates (supply as a matrix without intercept)
model	matrix of posterior samples of ϕ , σ^2 and τ^2
kernel	choice of kernel; must be one of "matern1", "matern2", "gaussian"

Value

A matrix containing posterior samples of spatial effects and the intercept.

Author(s)

Aritra Halder <aritra.halder@drexel.edu>,
Sudipto Banerjee <sudipto@ucla.edu>

Examples

```
require(nimble)
require(nimblewomble)

set.seed(1)
# Generated Simulated Data
N = 1e2
tau = 1
coords = matrix(runif(2 * N, -10, 10), ncol = 2); colnames(coords) = c("x", "y")
y = rnorm(N, mean = 20 * sin(sqrt(coords[, 1]^2 + coords[, 2]^2)), sd = tau)
```

```

# Posterior samples for theta
mc_sp = gp_fit(coords = coords, y = y, kernel = "matern2")
# Posterior samples for Z(s) and beta
model = zbeta_samples(y = y, coords = coords,
                     model = mc_sp$mcmc,
                     kernel = "matern2")
estimates = t(round(apply(model, 2, quantile,
                        probs = c(0.5, 0.025, 0.975)), 3))
yfit = estimates[paste0("z[", 1:N, "]"), "50%"] +
       estimates["beta[0]", "50%"]
ylo = estimates[paste0("z[", 1:N, "]"), "2.5%"] +
      estimates["beta[0]", "2.5%"]
yhi = estimates[paste0("z[", 1:N, "]"), "97.5%"] +
      estimates["beta[0]", "97.5%"]
fit_frame = data.frame(true = round(y, 3),
                      est = yfit, `2.5%` = ylo, `97.5%` = yhi)
fit_frame$sig = significance(data_frame = data.frame(fit_frame[, -1]))

# Plot
sp_ggplot(data_frame = data.frame(coords, z = yfit, sig = fit_frame$sig))

```

zXbeta

Posterior samples of spatial effects and intercept for all kernels in the presence of covariates

Description

For internal use only.

Usage

```
zXbeta(y, X, beta)
```

Arguments

y	response
X	covariates (supply as a matrix without intercept)
beta	posterior samples of β (supply as a matrix)

Value

A matrix of spatial effects and intercept. For internal use only.

Author(s)

Aritra Halder <aritra.halder@drexel.edu>,
Sudipto Banerjee <sudipto@ucla.edu>

Examples

```
## Not run:
#####
# Internal use only #
#####
# Example usage inside of nimblewomble::zbeta_samples(...)
zXb = nimble::compileNimble(zXbeta)
zb.samples = zXb(y = y, X = X, beta = beta)

## End(Not run)
```

Index

- * **curvatures_gaussian**
 - curvatures_gaussian, 2
 - * **curvatures_matern2**
 - curvatures_matern2, 3
 - * **gamma1.mcov1**
 - gamma1.mcov1, 4
 - * **gamma1n2.gauss**
 - gamma1n2.gauss, 5
 - * **gamma1n2.mcov2**
 - gamma1n2.mcov2, 6
 - * **gamma_int**
 - gamma_int, 7
 - * **gp_fit**
 - gp_fit, 9
 - * **gradients_matern1**
 - gradients_matern1, 10
 - * **materncov1**
 - materncov1, 11
 - * **materncov2**
 - gaussian, 8
 - materncov2, 12
 - * **pnorm_nimble**
 - pnorm_nimble, 13
 - * **significance**
 - significance, 14
 - * **sp_plot**
 - sp_ggplot, 20
 - * **sprates**
 - sprates, 15
 - spwombling, 17
 - * **wombling_gaussian**
 - wombling_gaussian, 21
 - * **wombling_matern1**
 - wombling_matern1, 22
 - * **wombling_matern2**
 - wombling_matern2, 24
 - * **zXbeta**
 - zXbeta, 29
 - * **zbeta_gaussian**
 - zbeta_gaussian, 25
 - * **zbeta_matern1**
 - zbeta_matern1, 26
 - * **zbeta_matern2**
 - zbeta_matern2, 27
 - * **zbeta_samples**
 - zbeta_samples, 28
- curvatures_gaussian, 2
curvatures_matern2, 3
- gamma1.mcov1, 4
gamma1n2.gauss, 5
gamma1n2.mcov2, 6
gamma_int, 7
gp_fit, 9
gradients_matern1, 10
materncov1, 11
materncov2, 12
pnorm_nimble, 13
significance, 14
sp_ggplot, 20
sprates, 15
spwombling, 17
wombling_gaussian, 21
wombling_matern1, 22
wombling_matern2, 24
zbeta_gaussian, 25
zbeta_matern1, 26
zbeta_matern2, 27
zbeta_samples, 28
zXbeta, 29