

Package ‘normfluodbf’

May 9, 2026

Type Package

Title Cleans and Normalizes FLUOstar DBF and DAT Files from 'Liposome' Flux Assays

Version 2.0.3

Description Cleans and Normalizes FLUOstar DBF and DAT Files obtained from liposome flux assays. Users should verify extended usage of the package on files from other assay types.

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.3.2

Suggests knitr, learnr, rmarkdown

Config/testthat/edition 3

Imports shiny, tidyr (>= 1.3.1), tibble, emojiFont, stats, badger, stringr, magrittr (>= 2.0.3), assertthat, forcats, gridExtra, pkgsearch, purrr (>= 1.0.2), rlang (>= 1.1.3), rstudioapi, wesanderson, hexSticker, pbdZMQ, httr2, glue, cli, testthat (>= 3.2.1)

Depends R (>= 4.3.0), dplyr (>= 1.1.4), foreign (>= 0.8.86), ggplot2 (>= 3.5.0), plotly (>= 4.10.4), data.table (>= 1.15.2)

LazyData true

URL <https://github.com/AlphaPrime7/normfluodbf>,
<https://alphaprime7.github.io/normfluodbf/>

BugReports <https://github.com/AlphaPrime7/normfluodbf/issues>

VignetteBuilder knitr

NeedsCompilation no

Author Tingwei Adeck [aut, cre, cph] (ORCID:
<<https://orcid.org/0009-0009-7450-8863>>),
Tesla Adeck [cph],
Amina Adeck [cph]

Maintainer Tingwei Adeck <awesome.tingwei@outlook.com>

Repository CRAN

Date/Publication 2025-10-10 10:50:02 UTC

Contents

add_package_namespace	4
analyze	4
average_fluorescence_by_row_cycle	5
capitalize	6
check_broken_packages	6
check_dirt	7
check_package_usage	7
childtype	8
clean_commas	8
clean_odddat_optimus	9
comma_cleaner	10
comment_out_lines	11
dat_1	11
dat_2	12
dat_3	12
dat_4	12
dat_5	13
dat_6	13
dat_7	13
dat_col_names_horizontal	14
dat_col_names_optimus	15
dat_col_names_prime	16
dat_col_names_rigid	17
defineparams	19
definestatus	20
definesteps	21
detectoutliers	22
dirutils	23
find_random_port	24
formatplatedata	25
getfilename	26
get_wells_used	27
globalcache	27
isnormalized	28
launch	28
liposomes_214	29
liposomes_215	29
liposomes_216	29
liposomes_218	30
liposomes_221	30
liposomes_227	30
liposome_fluor_dbfs	31
loadplatedata	33
loadplatemeta	33
modifyplatedata	34
move_file	35

multiplot	36
normalize	36
normalizebywell	37
normalizingagents	38
normfluodbfplots	40
normfluordat	42
parenttype	45
plate	46
platedata	47
platemeta	48
platename	49
plate_data_summary	49
plate_types_tbl	50
printer	51
quiet	52
removeoutliers	52
remove_leading_zero	54
replace_word_in_file	54
resample_dat_scale	55
resample_dat_vect	58
run_demo	60
run_demo_bg	61
run_demo_in_background	61
run_demo_script	62
sampledata	62
saveloadutils	63
setsteps	64
set_assiette_type	65
set_plate_type	65
set_plate_version	66
shiny_random_port	67
status	67
stepspipeline	68
stepsutils	69
test_boilerplate	70
type	71
uploadplatedata	71
viewerpane_background_normfluodbf	72
wait_for_bg_shinyapp	73
xycoordinates	73
%there%	74

add_package_namespace *Add Package Namespace*

Description

Add Package Namespace

Usage

```
add_package_namespace(dir, package)
```

Arguments

dir	dir
package	package

Value

modified file

Examples

```
## Not run: add_package_namespace(dir, package)
```

analyze *Analyze*

Description

Analyze

Usage

```
analyze_ready(plate)

## Default S3 method:
analyze_ready(plate)

## S3 method for class ``96well_plate``
analyze_ready(plate)

## S3 method for class ``384well_plate``
analyze_ready(plate)

## S3 method for class ``1536well_plate_t1``
analyze_ready(plate)
```

```
## S3 method for class ``1536well_plate_t2``  
analyze_ready(plate)
```

Arguments

plate plate

Value

plate
plate
plate
plate
plate
plate
plate

Examples

```
## Not run: analyze_ready(plate)
```

average_fluorescence_by_row_cycle
Capitalize

Description

Capitalize

Usage

```
average_fluorescence_by_row_cycle(plate)
```

Arguments

plate plate

Value

capital letter

Examples

```
## Not run: average_fluorescence_by_row_cycle(plate)
```

capitalize

Capitalize

Description

Capitalize

Usage

```
capitalize(x)
```

Arguments

x well

Value

capital letter

Examples

```
## Not run: capitalize('a1')
```

check_broken_packages *Check Broken Packages*

Description

Check Broken Packages

Usage

```
check_broken_packages()
```

Value

broken packages

check_dirt	<i>Check Dirt</i>
------------	-------------------

Description

Check Dirt

Usage

```
check_dirt(plate)
```

Arguments

plate	plate
-------	-------

Value

plate

See Also

Other plate_utils: [get_wells_used\(\)](#), [plate_data_summary\(\)](#), [platename](#), [remove_leading_zero\(\)](#), [saveloadutils](#), [set_plate_version\(\)](#), [type\(\)](#)

check_package_usage	<i>Check package or function Usage</i>
---------------------	--

Description

Check package or function Usage

Usage

```
check_package_usage(directory, package_name)
```

Arguments

directory	directory
package_name	package or string

Value

use location

Examples

```
## Not run: check_package_usage('R', 'capitalize')
```

childtype	<i>Child Type</i>
-----------	-------------------

Description

Child Type

Usage

```
child_plate_type(plate, child_type = NULL)
```

```
## Default S3 method:
```

```
child_plate_type(plate, child_type = NULL)
```

```
## S3 method for class 'normfluodbf_plate'
```

```
child_plate_type(plate, child_type = NULL)
```

Arguments

plate	plate
child_type	child type

Value

plate

plate

Examples

```
## Not run: child_plate_type()
```

clean_commas	<i>DAT file data frame cleaner.</i>
--------------	-------------------------------------

Description

The function takes the dirty data frame obtained from reading the FLUOstar DAT file and applies a function called `comma_cleaner()` to the dirty data frame, which automatically inserts NAs in place of the special characters, and rows with NAs only are removed.

Usage

```
clean_commas(df)
```

Arguments

df A dirty data frame obtained from the FLUOstar DAT file.

Value

A clean data frame with clean NA values retained.

Author(s)

Tingwei Adeck

Examples

```
## Not run: clean_commas(df)
```

clean_odddat_optimus *DAT file wrangler.*

Description

The function takes the dirty data frame obtained from reading the FLUOstar DAT file, applies an original algorithm that inserts NAs in place of the special characters, and then applies a function called `comma_cleaner()` to the dirty data frame for the removal of commas, and finally, rows with NAs only are removed.

Usage

```
clean_odddat_optimus(df)
```

```
clean_even_dat(df)
```

Arguments

df df

Value

A clean data frame with clean NA values retained.

df

Author(s)

Tingwei Adeck

Examples

```
## Not run:
fpath <- system.file("extdata", "dat_1.dat", package = "normfluodbf", mustWork = TRUE)
dat_df <- read.table(file=fpath)
partial_cleaned_dat <- clean_odddat_optimus(dat_df)
## End(Not run)
## Not run: clean_even_dat(df)
```

comma_cleaner

Comma Cleaner function.

Description

This modular function, in the context of this package, is responsible for removing commas from attribute(s) values. Removal of commas facilitates the conversion of attributes into the numeric class.

Usage

```
comma_cleaner(comma_df)
```

Arguments

comma_df A dirty data frame obtained from the FLUOstar DAT file.

Value

A clean data frame with numeric no-comma values for attribute(s).

Author(s)

Tingwei Adeck

Examples

```
## Not run:
fpath <- system.file("extdata", "dat_1.dat", package = "normfluodbf", mustWork = TRUE)
dat_df <- read.table(file=fpath)
nocomma_dat <- comma_cleaner(dat_df)
## End(Not run)
```

comment_out_lines	<i>Comment Out</i>
-------------------	--------------------

Description

Comment Out

Usage

```
comment_out_lines(input_file, output_file)
```

Arguments

input_file	file
output_file	file

Value

file

Examples

```
## Not run: comment_out_lines('tests/testthat/test_pipeline.R', 'tests/testthat/test_pipeline.R')
```

dat_1	<i>dat_1.</i>
-------	---------------

Description

FLUOstar .dat files used for creation of the update and unusable for immediate data analysis.

Usage

```
dat_1
```

Format

An object of class `data.frame` with 320 rows and 12 columns.

dat_2	<i>dat_2.</i>
-------	---------------

Description

FLUOstar .dat files used for creation of the update and unusable for immediate data analysis.

Usage

dat_2

Format

An object of class `data.frame` with 320 rows and 12 columns.

dat_3	<i>dat_3.</i>
-------	---------------

Description

FLUOstar .dat files used for creation of the update and unusable for immediate data analysis. This file is unique because it validates a major bug fix to ensure that users get the right output.

Usage

dat_3

Format

An object of class `data.frame` with 320 rows and 12 columns.

dat_4	<i>dat_4.</i>
-------	---------------

Description

FLUOstar .dat files used for creation of the update and unusable for immediate data analysis. This file is unique because it validates a major bug fix to ensure that users get the right output.

Usage

dat_4

Format

An object of class `data.frame` with 320 rows and 1 columns.

dat_5	<i>dat_5.</i>
-------	---------------

Description

FLUOstar .dat files used for creation of the update and unusable for immediate data analysis. This file is unique because it validates a major bug fix to ensure that users get the right output.

Usage

dat_5

Format

An object of class `data.frame` with 105 rows and 1 columns.

dat_6	<i>dat_6.</i>
-------	---------------

Description

FLUOstar .dat files used for creation of the update and unusable for immediate data analysis. This file is unique because it validates a major bug fix to ensure that users get the right output.

Usage

dat_6

Format

An object of class `data.frame` with 105 rows and 2 columns.

dat_7	<i>dat_7.</i>
-------	---------------

Description

FLUOstar .dat files used for creation of the update and unusable for immediate data analysis. This file is unique because it validates a major bug fix to ensure that users get the right output.

Usage

dat_7

Format

An object of class `data.frame` with 105 rows and 3 columns.

`dat_col_names_horizontal`*Attribute(s) naming function.*

Description

This function is used to name attribute(s). Attribute(s) names, in this case, are equivalent to the well labels found on the microplate reader. An attribute for a sample loaded into row A - column 1 will be named A1. In short, the function takes a clean data frame and returns attribute names that match the FLUOstar plate layout often presented as an Excel file.

Usage

```
dat_col_names_horizontal(dat = NULL, df, rows_used = NULL, cols_used = NULL)
```

Arguments

<code>dat</code>	A string ("dat_1.dat") if the file is found within the present working directory (pwd) OR a path pointing directly to a ".dat" file.
<code>df</code>	A data frame that requires attribute labels.
<code>rows_used</code>	A character vector indicating the rows or tuples used on the microplate (usually a 96-well microplate). Initialized as NULL.
<code>cols_used</code>	A numeric vector indicating the plate columns or attributes used. Initialized as NULL.

Value

Returns a character or numeric vector of attribute(s) names for the normalized data frame.

Note

This function was designed to avoid the use of stringr. This function is designed to name attributes when the read direction is specified as horizontal.

Author(s)

Tingwei Adeck

Examples

```
## Not run:
fpath <- system.file("extdata", "dat_1.dat", package = "normfluodbf", mustWork = TRUE)
dat_df <- read.table(file=fpath)
nocomma_dat <- clean_odddat_optimus(dat_df)
resampled_scaled <- resample_dat_scale(nocomma_dat, tnp=3, cycles=40)
n = c('A', 'B', 'C')
sample_col_names <- dat_col_names_horizontal(dat=fpath, resampled_scaled, n)
## End(Not run)
```

dat_col_names_optimus *Attribute(s) naming function.*

Description

This function is used to name attribute(s). Attribute(s) names, in this case, are equivalent to the well labels found on the microplate reader. An attribute for a sample loaded into row A - column 1 will be named A1. In short, the function takes a clean data frame and returns attribute names that match the FLUOstar plate layout often presented as an Excel file.

Usage

```
dat_col_names_optimus(  
  dat = NULL,  
  df,  
  rows_used = NULL,  
  cols_used = NULL,  
  user_specific_labels = NULL,  
  read_direction = NULL  
)
```

Arguments

dat	A string ("dat_1.dat") if the file is found within the present working directory (pwd) OR a path pointing directly to a ".dat" file.
df	A data frame that requires attribute labels.
rows_used	A character vector indicating the rows or tuples used on the microplate (usually a 96-well microplate). Initialized as NULL.
cols_used	A numeric vector indicating the plate columns or attributes used. Initialized as NULL.
user_specific_labels	A character vector where the user manually enters the used microplate wells based on the FLUOstar plate layout.
read_direction	A string input with two choices, "vertical" or "horizontal." The user indicates "vertical" if the user intends to have a final data frame with samples arranged as sample type triplets (A1, B1, C1, A1, B1, C1) OR "horizontal" if the user intends to have a final data frame with samples

Value

Returns a character or numeric vector of attribute(s) names for the normalized data frame.

Note

Users are advised to input rows used but won't be penalized for not doing so. If the user provides the rows used, then attribute names are generated for the user. The user must check to ensure that the names match the microplate layout. The user can leave the columns used as NULL if the user loaded samples from column 1 and did so in sequence. If the user fails to load in sequence from the first position, then the user must provide a numeric vector of columns used. For instance, where the user skips columns, the user will be prompted to interact with the program in order to ensure the final data frame has the correct attribute names. The user can bypass the rows used and columns used parameters if the user supplies a manually created character vector of the wells used in an experiment. The read direction parameter is used to determine the presentation of the samples in the final data frame.

Author(s)

Tingwei Adeck

See Also

[normfluodat\(\)](#), [dat_col_names_rigid\(\)](#)

Examples

```
## Not run:
fpath <- system.file("extdata", "dat_1.dat", package = "normfluodbf", mustWork = TRUE)
dat_df <- read.table(file=fpath)
nocomma_dat <- clean_odddat_optimus(dat_df)
resampled_scaled <- resample_dat_scale(nocomma_dat, tnp=3, cycles=40)
n = c('A', 'B', 'C')
sample_col_names <- dat_col_names_optimus(dat = fpath, resampled_scaled, n)
## End(Not run)
```

dat_col_names_prime *Attribute(s) naming function.*

Description

This function is used to name attribute(s). Attribute(s) names, in this case, are equivalent to the well labels found on the microplate reader. An attribute for a sample loaded into row A - column 1 will be named A1. In short, the function takes a clean data frame and returns attribute names that match the FLUOstar plate layout often presented as an Excel file.

Usage

```
dat_col_names_prime(
  dat = NULL,
  df,
  rows_used = NULL,
  cols_used = NULL,
```

```

    user_specific_labels = NULL
  )

```

Arguments

dat	A string ("dat_1.dat") if the file is found within the present working directory (pwd) OR a path pointing directly to a ".dat" file.
df	A data frame that requires attribute labels.
rows_used	A character vector indicating the rows or tuples used on the microplate (usually a 96-well microplate). Initialized as NULL.
cols_used	A numeric vector indicating the plate columns or attributes used. Initialized as NULL.
user_specific_labels	A character vector where the user manually enters the used microplate wells based on the FLUOstar plate layout.

Value

Returns a character vector of attribute(s) names for the normalized data frame.

Author(s)

Tingwei Adeck

Examples

```

## Not run:
fpath <- system.file("extdata", "dat_1.dat", package = "normfluodbf", mustWork = TRUE)
dat_df <- read.table(file=fpath)
nocomma_dat <- clean_odddat_optimus(dat_df)
resampled_scaled <- resample_dat_scale(nocomma_dat, tnp=3, cycles=40)
n = c('A', 'B', 'C')
sample_col_names <- dat_col_names_prime(dat = fpath, resampled_scaled, n)
## End(Not run)

```

dat_col_names_rigid *Attribute(s) naming function.*

Description

This function is used to name attribute(s). Attribute(s) names, in this case, are equivalent to the well labels found on the microplate reader. An attribute for a sample loaded into row A - column 1 will be named A1. In short, the function takes a clean data frame and returns attribute names that match the FLUOstar plate layout often presented as an Excel file.

Usage

```
dat_col_names_rigid(
  dat = NULL,
  df,
  rows_used = NULL,
  cols_used = NULL,
  user_specific_labels = NULL,
  read_direction = NULL
)
```

Arguments

<code>dat</code>	A string ("dat_1.dat") if the file is found within the present working directory (pwd) OR a path pointing directly to a ".dat" file.
<code>df</code>	A data frame that requires attribute labels.
<code>rows_used</code>	A character vector indicating the rows or tuples used on the microplate (usually a 96-well microplate). Initialized as NULL.
<code>cols_used</code>	A numeric vector indicating the plate columns or attributes used. Initialized as NULL.
<code>user_specific_labels</code>	A character vector where the user manually enters the used microplate wells based on the FLUOstar plate layout.
<code>read_direction</code>	A string input with two choices, "vertical" or "horizontal." The user indicates "vertical" if the user intends to have a final data frame with samples arranged as sample type triplets (A1, B1, C1, A1, B1, C1) OR "horizontal" if the user intends to have a final data frame with samples arranged as clusters per sample type (A1, A2, A3, B1, B2, B3).

Value

Returns a character vector of attribute(s) names for the normalized data frame.

Note

Users are advised to input rows used but won't be penalized for not doing so. If the user provides the rows used, then attribute names are generated for the user. The user must check to ensure that the names match the microplate layout. The user can leave the columns used as NULL if the user loaded samples from column 1 and did so in sequence. If the user fails to load in sequence from the first position, then the user must provide a numeric vector of columns used. For instance, where the user skips columns, the user will be prompted to interact with the program in order to ensure the final data frame has the correct attribute names. The user can bypass the rows used and columns used parameters if the user supplies a manually created character vector of the wells used in an experiment. The read direction parameter is used to determine the presentation of the samples in the final data frame.

This naming function only returns a character vector hence the rigid suffix.

Author(s)

Tingwei Adeck

See Also

[dat_col_names_optimus\(\)](#)

Examples

```
## Not run:
fpath <- system.file("extdata", "dat_1.dat", package = "normfluodbf", mustWork = TRUE)
dat_df <- read.table(file=fpath)
nocomma_dat <- clean_odddat_optimus(dat_df)
resampled_scaled <- resample_dat_scale(nocomma_dat, tnp=3, cycles=40)
n = c('A', 'B', 'C')
sample_col_names <- dat_col_names_rigid(dat = fpath, resampled_scaled, n)
## End(Not run)
```

defineparams

Define Plate Parameters

Description

Define Plate Parameters

Usage

```
define_params(plate)

## Default S3 method:
define_params(plate)

## S3 method for class ``96well_plate``
define_params(plate)

## S3 method for class ``384well_plate``
define_params(plate)

## S3 method for class ``1536well_plate_t1``
define_params(plate)

## S3 method for class ``1536well_plate_t2``
define_params(plate)

set_default_params(plate)
```

Arguments

plate plate

Value

default params
 default params
 default params
 default params
 default params
 plate

Examples

```
## Not run: define_params(plate)
```

definestatus	<i>Define Plate Status</i>
--------------	----------------------------

Description

Define Plate Status

Usage

```
define_status(plate)

## Default S3 method:
define_status(plate)

## S3 method for class ``96well_plate``
define_status(plate)

## S3 method for class ``384well_plate``
define_status(plate)

## S3 method for class ``1536well_plate_t1``
define_status(plate)

## S3 method for class ``1536well_plate_t2``
define_status(plate)

set_default_status(plate)

update_status_list(plate)

get_status_value(plate, index)
```

Arguments

plate	plate
index	index

Value

plate
 status
 status
 status
 status
 status
 status
 status
 plate
 plate
 plate

Examples

```
## Not run: define_steps(plate)
```

definesteps	<i>Define Plate Steps</i>
-------------	---------------------------

Description

Define Plate Steps

Usage

```
define_steps(plate)

## Default S3 method:
define_steps(plate)

## S3 method for class 'normfluodbf_plate'
define_steps(plate)

## S3 method for class '`96well_plate`'
define_steps(plate)

## S3 method for class '`384well_plate`'
define_steps(plate)
```

```
## S3 method for class '`1536well_plate_t1`'
define_steps(plate)

## S3 method for class '`1536well_plate_t2`'
define_steps(plate)

set_default_steps(plate, ...)

update_steps_list(plate, new_key, new_value, index)
```

Arguments

plate	plate
...	custom steps
new_key	new_key
new_value	new_value
index	index

Value

```
steps
steps
steps
steps
steps
steps
steps
plate
plate
```

Examples

```
## Not run: define_steps(plate)
## Not run: plate <- plate %>% update_steps_list('REMOVE_OUTLIER', 'remove_outlier', 3)
```

detectoutliers

Detect Outliers

Description

Detect Outliers

Usage

```
detect_outliers_time_cn(plate, data)

detect_outliers_cn(plate, data)
```

Arguments

plate	plate
data	data

Value

data frame
data frame
data frame

Examples

```
## Not run: detect_outliers_time_cn(plate, data)
```

dirutils

Directory Utils

Description

A function that facilitates a users' workflow by helping to check for DBFs in a directory.

A function that facilitates a users' workflow by helping to check for DATs in a directory.

Usage

```
list_dbfs(pathstring)  
  
list_dats(pathstring)  
  
is_file(pathstring)  
  
is_dir(pathstring = NULL)  
  
find_known_liposome_dat_file(fpath, fname)  
  
find_known_liposome_dbf_file(fpath, fname)
```

Arguments

pathstring	path string
fpath	fpath
fname	fname

Value

directory utils
dbfs
dbfs
dbfs
dbfs
dbfs
dbfs

See Also

Other dirutils: [normfluodbfcomms](#), [sampledata](#)

Examples

```
## Not run:  
fpath <- system.file("extdata", package = "normfluodbf", mustWork = TRUE)  
list_dbfs(fpath)  
list_dats(fpath)  
is_file(fpath)  
find_known_liposome_dat_file(fpath, 'dat_1.dat')  
find_known_liposome_dbf_file(fpath, 'liposomes_218')  
## End(Not run)
```

find_random_port

Random Port Normfluodbf Style

Description

Random Port Normfluodbf Style

Usage

```
find_random_port()
```

Details

Recursively find a random port that does not fall in the unsafe group Added some more unsafe ports for like PostgresDb (5432), MySQL (3306), StreamlitApp (8501), ngrok (4040), pinggy (4300), Flask (5000), Django (8000) and ReactApp (3000). Learnt a thing or two from Dean with recursion (Really Cool!!!).

Value

random port

formatplatedata	<i>Format Plate Data</i>
-----------------	--------------------------

Description

Format Plate Data

Usage

```
format_plate_data(plate)

## Default S3 method:
format_plate_data(plate)

## S3 method for class ``96well_plate``
format_plate_data(plate)

## S3 method for class ``384well_plate``
format_plate_data(plate)

## S3 method for class ``1536well_plate_t1``
format_plate_data(plate)

## S3 method for class ``1536well_plate_t2``
format_plate_data(plate)
```

Arguments

plate plate

Value

plate
plate
plate
plate
plate
plate
plate

Examples

```
## Not run: format_plate_data(plate)
```

getfilename	<i>Get File Name(s)</i>
-------------	-------------------------

Description

Get File Name(s)

Usage

```
get_dbf_file_name(dbf_file)
get_dat_file_name(dat_file)
get_dat_common_name(dat_file)
get_common_dat_names(dat_files)
```

Arguments

dbf_file	DBF file
dat_file	DAT file
dat_files	DAT files

Value

file
name
name
name
name

Examples

```
## Not run:
get_dbf_file_name(dbf_file = "liposomes_218.dbf")
get_dat_file_name(dat_file = "dat_1.dat")
get_common_dat_names(dat_files = list.files(fpath, pattern = "\\\\.dat$"))
## End(Not run)
```

get_wells_used	<i>Wells Used</i>
----------------	-------------------

Description

Wells Used

Usage

```
get_wells_used(pl_data)
```

Arguments

pl_data	data
---------	------

Value

wells used

See Also

Other plate_utils: [check_dirt\(\)](#), [plate_data_summary\(\)](#), [platename](#), [remove_leading_zero\(\)](#), [saveloadutils](#), [set_plate_version\(\)](#), [type\(\)](#)

Examples

```
## Not run: get_wells_used(data)
```

globalcache	<i>Globals Cache</i>
-------------	----------------------

Description

Globals Cache

isnormalized	<i>Is Normalized</i>
--------------	----------------------

Description

Is Normalized

Usage

```
is_normalized(data, type = c("min-max", "z-score", "hundred"))
```

Arguments

data	type
type	type

Value

boolean
boolean

Examples

```
## Not run: is_normalized(data,type)
```

launch	<i>Run the shiny App checking dependencies in R code ... WARNING In addition to the functions provided in this package, the normfluodbf package also provides an interactive tool that can be used to analyze liposome flux assay data more easily. The tool will be launched in a web browser.</i>
--------	---

Description

Run the shiny App checking dependencies in R code ... WARNING In addition to the functions provided in this package, the normfluodbf package also provides an interactive tool that can be used to analyze liposome flux assay data more easily. The tool will be launched in a web browser.

Usage

```
launch()
```

liposomes_214	<i>liposomes_214.</i>
---------------	-----------------------

Description

FLUOstar .dbf file in wide format and unable to use for data analysis.

Usage

liposomes_214

Format

An object of class data.frame with 11 rows and 52 columns.

liposomes_215	<i>liposomes_215.</i>
---------------	-----------------------

Description

FLUOstar .dbf file in wide format and unable to use for data analysis.

Usage

liposomes_215

Format

An object of class data.frame with 11 rows and 52 columns.

liposomes_216	<i>liposomes_216.</i>
---------------	-----------------------

Description

FLUOstar .dbf file in wide format and unable to use for data analysis.

Usage

liposomes_216

Format

An object of class data.frame with 8 rows and 52 columns.

liposomes_218	<i>liposomes_218.</i>
---------------	-----------------------

Description

FLUOstar .dbf file in wide format and unable to use for data analysis.

Usage

liposomes_218

Format

An object of class data.frame with 11 rows and 52 columns.

liposomes_221	<i>liposomes_221.</i>
---------------	-----------------------

Description

FLUOstar .dbf file in wide format and unable to use for data analysis.

Usage

liposomes_221

Format

An object of class data.frame with 38 rows and 52 columns.

liposomes_227	<i>liposomes_227.</i>
---------------	-----------------------

Description

FLUOstar .dbf file in wide format and unable to use for data analysis.

Usage

liposomes_227

Format

An object of class data.frame with 29 rows and 52 columns.

liposome_fluor_dbfs *Cleans and Normalizes DBF files obtained from experiments using the FLUOstar Omega microplate reader (from BMG LABTECH).*

Description

The simplest function utilization scenario entails an input of the path to a DBF file obtained from the FLUOstar microplate (usually a 96-well microplate) reader; In a single step, this function will create a data frame, clean the data frame, normalize the data frame, append a "Cycle_Number" attribute, perform an adjustment to the "time" attribute and return a data frame that is ready for analysis. Since the initial publication of this package, several changes have been made to improve the user experience and to give the user more options to fine-tune the output from the package to meet the users' aesthetic needs. Users who decide to move past the simplest utility scenario have been given more options to customize the output based on the users' needs. Notably, several normalization sub-parameters have been provided in the package which yields different outputs based on what the user is used to seeing. Just as the FLUOstar instrument is built to handle an array of assays, this function is designed to be multi-dimensional (meaning it can handle data with the same DBF extension from other assay types), on the condition that the data from assay types other than liposome flux assays follow the same data format this package was designed to handle. Of course, users of this package are advised to pre-analyze DBF files from other assay types to ensure they are compliant with this package (compliance in this scenario is simple meaning DBF files from other assays should be like DBF files from liposome flux assays).

Usage

```
norm_tidy_dbf(
  file = NULL,
  norm_scale = NULL,
  transformed = NULL,
  fun = NA,
  ...
)
```

```
normfluordbf(file = NULL, norm_scale = NULL, transformed = NULL, fun = NA, ...)
```

```
normfluodbf(file = NULL, norm_scale, transformed = NULL, fun = NA, ...)
```

Arguments

file	A string ("liposomes_xxx.dbf") if the file is found within the present working directory (pwd) OR a path pointing directly to a ".dbf" file.
norm_scale	This parameter takes sub-parameters: 'raw' , 'hundred' , 'one' , 'z-score' , or 'decimal' , which denotes the normalization type or scale; The parameter is initialized as NULL.
transformed	This parameter takes input 'log' , which denotes a logarithmic box-cox transformation; Initialized as NULL.

fun A parameter defined as NA is used for Boolean expressions or manipulation.

... An abstract placeholder or container parameter that can be used to capture extra variables if needed.

Value

A normalized data frame with an appended "Cycle_Number" attribute.

A normalized data frame with an appended "Cycle_Number" attribute.

A normalized data frame with an appended "Cycle_Number" attribute.

A normalized data frame with an appended "Cycle_Number" attribute.

Note

The default normalization sub-parameter outputs values in the 0-1 range. Unless a “norm_scale” level is specified by the user, the default output is in the 0-1 range. The “norm_scale” sub-parameter “decimal” is a machine-learning tool and should be avoided; it also provides no advantage for basic research analysis as its output operates on a sliding scale just like the raw data. Logarithmic transformation provides a minuscule advantage in data analysis and could/should be avoided. Backward compatibility is maintained in all updates, so there should be no issues with using the package the way the user was used to. The favorite "norm_scale" level is "z-score" since it divides the axis into negative and positive, thus facilitating interpretation.

The norm_scale must be provided if the user chooses to use this option.

Author(s)

Tingwei Adeck

See Also

[normfluordbf\(\)](#), [normfluodat\(\)](#)

Examples

```
## Not run:
fpath <- system.file("extdata", "liposomes_214.dbf", package = "normfluodbf", mustWork = TRUE)
normalized_dbf <- norm_tidy_dbf(file=fpath, norm_scale = 'raw')
normalized_dbf <- normfluordbf(file=fpath, norm_scale = 'raw')
## End(Not run)
## Not run: wells = normfluodbf(lipsum_214, norm_scale = 'hundred')
```

loadplatedata	<i>Load Plate Data</i>
---------------	------------------------

Description

Load Plate Data

Usage

```
load_plate_data(plate)

load_plate_data(plate) <- value
```

Arguments

plate	plate
value	data

Value

plate
plate
plate

Examples

```
## Not run: load_plate_data(plate,value = data)
```

loadplatemeta	<i>Load Plate Meta</i>
---------------	------------------------

Description

Load Plate Meta

Usage

```
load_plate_meta(plate)

load_plate_meta(plate) <- value
```

Arguments

plate	plate
value	metadata

Value

plate
 plate
 plate

Examples

```
## Not run: load_plate_meta(plate, meta)
```

modifyplatedata	<i>Modify Plate Data</i>
-----------------	--------------------------

Description

Modify Plate Data

Usage

```
modify_plate_data(plate)

## Default S3 method:
modify_plate_data(plate)

## S3 method for class ``96well_plate``
modify_plate_data(plate)

## S3 method for class ``384well_plate``
modify_plate_data(plate)

## S3 method for class ``1536well_plate_t1``
modify_plate_data(plate)

## S3 method for class ``1536well_plate_t2``
modify_plate_data(plate)
```

Arguments

plate plate

Value

plate
 plate
 plate
 plate

```
plate  
plate  
plate
```

Examples

```
## Not run: modify_plate_meta(plate)
```

move_file	<i>Move File</i>
-----------	------------------

Description

Move File

Usage

```
move_file(source_path, destination_path)
```

Arguments

```
source_path    src  
destination_path  
                dest
```

Value

kinetic file

Examples

```
## Not run:  
source_file <- "path/to/source/file.txt"  
destination_file <- "path/to/destination/file.txt"  
move_file(source_file, destination_file)  
move_file("~/Documents/Wip/R/PkgDev/pdf", "~/Wip/R/PkgDev/R/pdf")  
## End(Not run)
```

 multiplot

Multiplot

Description

Multiplot

Usage

```
multiplot(..., plotlist = NULL, file, cols = 1, layout = NULL)
```

Arguments

...	extra
plotlist	list
file	file
cols	cols
layout	layout

Value

grid plot

normalize

Normalize

Description

Normalize

Usage

```
normalize(plate)

## Default S3 method:
normalize(plate)

## S3 method for class ``96well_plate``
normalize(plate)

## S3 method for class ``384well_plate``
normalize(plate)

## S3 method for class ``1536well_plate_t1``
```

```
normalize(plate)

## S3 method for class '`1536well_plate_t2`'
normalize(plate)

normalize_dataframe(df)
```

Arguments

plate	plate
df	data frame

Value

```
plate
plate
plate
plate
plate
plate
plate
plate
plate
```

Examples

```
## Not run: normalize(plate)
normalize(plate)
## End(Not run)
```

normalizebywell	<i>Normalize by Well</i>
-----------------	--------------------------

Description

Normalize by Well

Usage

```
normalize_by_well(plate)

## Default S3 method:
normalize_by_well(plate)

## S3 method for class '`96well_plate`'
normalize_by_well(plate)
```

```
## S3 method for class ``384well_plate``  
normalize_by_well(plate)  
  
## S3 method for class ``1536well_plate_t1``  
normalize_by_well(plate)  
  
## S3 method for class ``1536well_plate_t2``  
normalize_by_well(plate)
```

Arguments

plate plate

Value

plate
plate
plate
plate
plate
plate
plate

Examples

```
## Not run: normalize_by_well(plate)
```

normalizingagents *Normalizing Agents*

Description

Normalizing Agents

Usage

```
min_max_norm(x)  
  
min_max_norm_df(df)  
  
min_max_norm_percent(x)  
  
min_max_norm_percent_df(df)  
  
norm_z(x)
```

```
norm_z_df(df)
decimal_scaling(x)
decimal_scaling_df(df)
log_transformation(x)
roundfluor(x)
```

Arguments

x	value(s)
df	data frame

Value

A normalized value when applied to a single value or a normalized attribute with values between the normalizing range.

normalized value (0-1)

normalized value (0-1)

normalized value (0-100)

normalized value (0-100)

normalized value ($Z = N(0,1)$)

normalized value ($Z = N(0,1)$)

normalized value

normalized value

log value

rounded value

See Also

Other normfluodbf_utils: [fluorthresholdcheck](#)

Examples

```
## Not run:
test_df <- as.data.frame(c(seq(40)))
colnames(test_df) <- "test"
test_df_norm <- lapply(test_df[1:ncol(test_df)], min_max_norm)
## End(Not run)
```

normfluodbfplots *Plot Plate - Favorite is Fluostar style*

Description

Plot Plate - Favorite is Fluostar style

Usage

```
## S3 method for class ``96well_plate``
plot(
  x,
  whichplot = 1,
  fluorstarplot = 1 %in% whichplot,
  superimpose = 2 %in% whichplot,
  plate_layout = 3 %in% whichplot,
  plot_side_by_side = 4 %in% whichplot,
  legend_labels = NULL,
  plot_name = NULL,
  ...
)

## S3 method for class ``384well_plate``
plot(
  x,
  whichplot = 1,
  fluorstarplot = 1 %in% whichplot,
  superimpose = 2 %in% whichplot,
  plate_layout = 3 %in% whichplot,
  plot_side_by_side = 4 %in% whichplot,
  legend_labels = NULL,
  plot_name = NULL,
  ...
)

## S3 method for class ``1536well_plate_t1``
plot(
  x,
  whichplot = 1,
  fluorstarplot = 1 %in% whichplot,
  superimpose = 2 %in% whichplot,
  plate_layout = 3 %in% whichplot,
  plot_side_by_side = 4 %in% whichplot,
  legend_labels = NULL,
  plot_name = NULL,
  ...
)
```

```
## S3 method for class '`1536well_plate_t2`'
plot(
  x,
  whichplot = 1,
  fluorstarplot = 1 %in% whichplot,
  superimpose = 2 %in% whichplot,
  plate_layout = 3 %in% whichplot,
  plot_side_by_side = 4 %in% whichplot,
  legend_labels = NULL,
  plot_name = NULL,
  ...
)
```

Arguments

x	plot requirement
whichplot	int
fluorstarplot	whichplot = 1
superimpose	whichplot = 2
plate_layout	whichplot = 3
plot_side_by_side	whichplot = 4
legend_labels	labels whichplot = 2,4
plot_name	plot name
...	additional parameters

Value

plot object
 print plot (return plate)
 print plot (return plate)
 print plot (return plate)
 print plot (return plate)

Examples

```
## Not run: plot(plate, whichplot = 1)
```

 normfluordat

Cleans and normalizes DAT files obtained from experiments using the FLUOstar Omega microplate reader (from BMG LABTECH).

Description

The simplest case scenario entails inputting the name or directory of a DAT file as a string, the number of rows denoted by the tnp (test, negative, positive) parameter, and the number of cycles (selected by the user when running the FLUOstar instrument). The program takes these three baseline parameters, performs cleaning and normalization of the DAT file, and then appends an attribute called “Cycle_Number” to the normalized data frame.

The simplest case scenario entails inputting the name or directory of a DAT file as a string, the number of rows denoted by the tnp (test, negative, positive) parameter, and the number of cycles (selected by the user when running the FLUOstar instrument). The program takes these three baseline parameters, performs cleaning and normalization of the DAT file, and then appends an attribute called “Cycle_Number” to the normalized data frame.

The simplest case scenario entails inputting the name or directory of a DAT file as a string, the number of rows denoted by the tnp (test, negative, positive) parameter, and the number of cycles (selected by the user when running the FLUOstar instrument). The program takes these three baseline parameters, performs cleaning and normalization of the DAT file, and then appends an attribute called “Cycle_Number” to the normalized data frame.

The simplest case scenario entails inputting the name or directory of a DAT file as a string, the number of rows denoted by the tnp (test, negative, positive) parameter, and the number of cycles (selected by the user when running the FLUOstar instrument). The program takes these three baseline parameters, performs cleaning and normalization of the DAT file, and then appends an attribute called “Cycle_Number” to the normalized data frame.

Usage

```
normfluordat(
  dat,
  tnp,
  cycles,
  rows_used = NULL,
  cols_used = NULL,
  user_specific_labels = NULL,
  read_direction = NULL,
  na_omit = NULL
)
```

```
normfluodat(
  dat,
  tnp = NULL,
  cycles = NULL,
  rows_used = NULL,
  cols_used = NULL,
```

```

    user_specific_labels = NULL,
    read_direction = NULL,
    norm_scale = NULL,
    interval = NULL,
    first_end = NULL,
    pause_duration = NULL,
    end_time = NULL,
    normfluodbf.verbose = TRUE
)

normfluodatlite(
  dat,
  tnp,
  cycles,
  rows_used = NULL,
  cols_used = NULL,
  user_specific_labels = NULL,
  read_direction = NULL,
  norm_scale = NULL
)

normfluodatfull(
  dat,
  tnp,
  cycles,
  rows_used = NULL,
  cols_used = NULL,
  user_specific_labels = NULL,
  read_direction = NULL,
  norm_scale = NULL,
  na_omit = NULL
)

```

Arguments

dat	A string ("dat_1.dat") if the file is found within the present working directory (pwd) OR a path pointing directly to a ".dat" file.
tnp	A numeric value indicating the number of rows used. TNP is used as an acronym for Test, Negative, Positive.
cycles	A numeric value indicating the number of cycles selected by the user when running the FLUOstar instrument.
rows_used	A character vector of the rows used; ru = c('A','B','C').
cols_used	A numeric vector of the columns used; cu = c(1,2,3).
user_specific_labels	A character vector manually prepared by the user to denote the wells used on the microplate reader; usl = c('A1','B1','C1').
read_direction	A string input with two choices, "vertical" or "horizontal." The user indicates "vertical" if the user intends to have a final data frame with samples arranged

	as sample type triplets (A1, B1, C1, A1, B1, C1) OR “horizontal” if the user intends to have a final data frame with samples arranged as clusters per sample type (A1, A2, A3, B1, B2, B3).
na_omit	Takes a string "yes" OR "no".
norm_scale	This parameter takes sub-parameters: 'raw' , 'hundred' , 'one' , 'z-score' , or 'decimal' , which denotes the normalization type or scale; Initialized as NULL.
interval	The time interval chosen for the assay often in seconds.
first_end	The end time of the initial run, often the pause for the introduction of a new substance. This can be the cycle number chosen for the initial stop.
pause_duration	The time between the first end (pause) and resumption of the assay.
end_time	The final end time of the assay.
normfluodbf.verbose	verbose option

Value

A normalized data frame with an appended "Cycle_Number" attribute. The “Cycle_Number” attribute is the X-variable.

A normalized data frame with an appended "Cycle_Number" attribute. The “Cycle_Number” attribute is the X-variable.

A normalized data frame with an appended "Cycle_Number" attribute. The “Cycle_Number” attribute is the X-variable.

A normalized data frame with an appended "Cycle_Number" attribute. The “Cycle_Number” attribute is the X-variable.

Note

This function is a single-step function leveraging several subordinate functions. It is assumed that the user has the 3 baseline parameters to get this function working. Users must double-check attribute names to ensure they end up with accurate results.

This function is a single-step function leveraging several subordinate functions. It is assumed that the user has the 3 baseline parameters to get this function working. Users must double-check attribute names to ensure they end up with accurate results.

This function is a single-step function leveraging several subordinate functions. It is assumed that the user has the 3 baseline parameters to get this function working. Users must double-check attribute names to ensure they end up with accurate results.

Author(s)

Tingwei Adeck

See Also

[normfluodat\(\)](#)

[normfluodatlite\(\)](#)

```
normfluodat()
```

```
normfluodat()
```

Examples

```
## Not run:
fpath <- system.file("extdata", "dat_1.dat", package = "normfluodbf", mustWork = TRUE)
normalized_fluo_dat <- normfluodat(dat=fpath, tnp = 3, cycles = 40)
## End(Not run)
## Not run:
fpath <- system.file("extdata", "dat_4.dat", package = "normfluodbf", mustWork = TRUE)
normalized_fluo_dat <- normfluodat(dat=fpath, tnp = 3, cycles = 40)
## End(Not run)
## Not run:
fpath <- system.file("extdata", "dat_1.dat", package = "normfluodbf", mustWork = TRUE)
normalized_fluo_dat <- normfluodatlite(dat=fpath, tnp = 3, cycles = 40)
## End(Not run)
## Not run:
fpath <- system.file("extdata", "dat_1.dat", package = "normfluodbf", mustWork = TRUE)
normalized_fluo_dat <- normfluodatfull(dat=fpath, tnp = 3, cycles = 40)
## End(Not run)
```

parenttype

Parent Type

Description

Parent Type

Usage

```
parent_plate_type(plate, type = NULL)

## S3 method for class 'normfluodbf_plate'
parent_plate_type(plate, type = NULL)

## Default S3 method:
parent_plate_type(plate, type = NULL)

## S3 method for class '`96well_plate`'
parent_plate_type(plate, type = NULL)

## S3 method for class '`384well_plate`'
parent_plate_type(plate, type = NULL)

## S3 method for class '`1536well_plate_t1`'
parent_plate_type(plate, type = NULL)

## S3 method for class '`1536well_plate_t2`'
parent_plate_type(plate, type = NULL)
```

Arguments

plate	plate
type	parent type

Value

plate
plate
plate
plate
plate

Examples

```
## Not run: parent_plate_type()
```

plate	<i>Plate</i>
-------	--------------

Description

Plate

Usage

```
empty_plate()
new_plate()
init_plate(plate = NULL, type = NULL, child_type = NULL)
setup_plate(plate, ...)
reset_plate(plate)
use_setup_plate()
use_initialized_plate()
```

Arguments

plate	plate
type	parent type
child_type	child type
...	dots

Value

plate
 plate
 plate
 plate
 plate
 plate
 plate
 plate
 plate

Examples

```
## Not run:
empty_plate()
new_plate()
init_plate()
setup_plate(plate)
reset_plate()
## End(Not run)
```

 platedata

Plate Data

Description

Plate Data

Usage

```
plate_data(file, tnp = NULL, cycles = NULL, rows_used = NULL, ...)
```

Arguments

file	file
tnp	tnp
cycles	cycles
rows_used	rows_used
...	dots

Value

plate data
 plate data

Examples

```
## Not run: plate_data(file, tnp, cycles, rows_used = c(A,B,C), norm_scale = 'raw')
```

 platemeta

Plate Meta

Description

Plate Meta

Usage

```
plate_meta(plate, num_wells)

## Default S3 method:
plate_meta(plate, num_wells = 96L)

## S3 method for class '`96well_plate`'
plate_meta(plate, num_wells = 96L)

## S3 method for class '`384well_plate`'
plate_meta(plate, num_wells = 384L)

## S3 method for class '`1536well_plate_t1`'
plate_meta(plate, num_wells = 1536L)

## S3 method for class '`1536well_plate_t2`'
plate_meta(plate, num_wells)
```

Arguments

plate	plate
num_wells	number of wells

Value

```
plate
plate
plate
plate
plate
plate
plate
```

Examples

```
## Not run: plate_meta(plate, num_wells = 96L)
```

platename	<i>Plate Name</i>
-----------	-------------------

Description

Plate Name

Usage

```
name(plate)  
  
name(plate) <- value
```

Arguments

plate	plate
value	value

Value

plate
plate

See Also

Other plate_utils: [check_dirt\(\)](#), [get_wells_used\(\)](#), [plate_data_summary\(\)](#), [remove_leading_zero\(\)](#), [saveloadutils](#), [set_plate_version\(\)](#), [type\(\)](#)

plate_data_summary	<i>Plate Data Summary</i>
--------------------	---------------------------

Description

Plate Data Summary

Usage

```
plate_data_summary(plate)
```

Arguments

plate	plate
-------	-------

Value

sprintf string

See Also

Other plate_utils: [check_dirt\(\)](#), [get_wells_used\(\)](#), [platename](#), [remove_leading_zero\(\)](#), [saveloadutils](#), [set_plate_version\(\)](#), [type\(\)](#)

plate_types_tbl	<i>Plate Types Tibble</i>
-----------------	---------------------------

Description

Plate Types Tibble
Plate Types List
Plate Types Vector
Plate Types Global

Usage

`plate_types_tbl()`

`plate_types`

`plate_types_vector()`

Format

An object of class list of length 5.

Details

The list equivalent of the tibble from `plate_types_tbl`.
The vector equivalent of the tibble from `plate_types_tbl`.

Value

A tibble
A list
A Vector

See Also

[plate_types\(\)](#)

printer	<i>Print</i>
---------	--------------

Description

Print

Usage

```
## S3 method for class ``96well_plate``  
print(x, ...)  
  
## S3 method for class ``384well_plate``  
print(x, ...)  
  
## S3 method for class ``1536well_plate_t1``  
print(x, ...)  
  
## S3 method for class ``1536well_plate_t2``  
print(x, ...)
```

Arguments

x	print requirement
...	placeholder

Value

plate
plate
plate
plate

Examples

```
## Not run: plate
```

quiet	<i>Quiet</i>
-------	--------------

Description

Quiet

Usage

```
quiet(
  expr,
  suppress_messages = FALSE,
  suppress_warnings = FALSE,
  suppress_output = FALSE,
  all = FALSE
)
```

Arguments

expr	expression
suppress_messages	logical
suppress_warnings	logical
suppress_output	logical
all	logical

Value

suppress comms

Examples

```
## Not run: quiet(expr)
```

removeoutliers	<i>Outliers</i>
----------------	-----------------

Description

Outliers

Usage

```
remove_outliers(plate)

## Default S3 method:
remove_outliers(plate)

## S3 method for class '`96well_plate`'
remove_outliers(plate)

## S3 method for class '`384well_plate`'
remove_outliers(plate)

## S3 method for class '`1536well_plate_t1`'
remove_outliers(plate)

## S3 method for class '`1536well_plate_t2`'
remove_outliers(plate)
```

Arguments

```
plate          plate
```

Value

```
plate
plate
plate
plate
plate
plate
plate
plate
```

Note

```
Works on a data frame not in well format.
Works on a data frame not in well format.
Works on a data frame not in well format.
Works on a data frame not in well format.
Works on a data frame not in well format.
```

Examples

```
## Not run: remove_outliers(plate)
```

remove_leading_zero *Format Well Names*

Description

Format Well Names

Usage

```
remove_leading_zero(names_vector)
```

Arguments

names_vector column names

Value

vector

See Also

Other plate_utils: [check_dirt\(\)](#), [get_wells_used\(\)](#), [plate_data_summary\(\)](#), [platename](#), [saveloadutils](#), [set_plate_version\(\)](#), [type\(\)](#)

Examples

```
## Not run: remove_leading_zero(names)
```

replace_word_in_file *Replace Word*

Description

Replace Word

Usage

```
replace_word_in_file(file_path, old_word, new_word)
```

Arguments

file_path path
old_word old func name
new_word new func name

Value

file

Note

Solves the inconvenient problem of renaming a function correctly and having to manually correct it.

Examples

```
## Not run: replace_word_in_file('R/plate_plot.R', 'plot_fluostar_style', 'plot_in_well')
```

resample_dat_scale	<i>A function to create an attribute or column for each sample loaded into the microplate wells.</i>
--------------------	--

Description

Creates a data frame where each sample loaded into the microplate wells has a separate attribute.

Creates a data frame where each sample loaded into the microplate wells has a separate attribute. NA values are retained for more control.

A function that takes tuples or rows consisting of several samples and perform a putative resampling to yield another data frame with a separate attribute for each sample.

A function that takes tuples or rows consisting of several samples and perform a putative resampling to yield another data frame with a separate attribute for each sample. NA values are retained.

A function that takes tuples or rows consisting of several samples and perform a putative resampling to yield another data frame with a separate attribute for each sample.

A function that takes tuples or rows consisting of several samples and perform a putative resampling to yield another data frame with a separate attribute for each sample.

Creates a data frame where each sample loaded into the microplate wells has a separate attribute.

Creates a data frame where each sample loaded into the microplate wells has a separate attribute. NA values are retained.

Creates a data frame where each sample loaded into the microplate wells has a separate attribute.

Creates a data frame where each sample loaded into the microplate wells has a separate attribute.

Usage

```
resample_dat_scale(df, tnp, cycles)
```

```
resample_dat_scale_naretainer(df, tnp, cycles)
```

```
resample_dat_scale_alt(df, tnp, cycles, na_omit = NULL)
```

```
resample_dat_scale_alt_na(df, tnp, cycles)
```

```

resample_dat_scale_alt_bf_na(df, tnp, cycles)

resample_dat_scale_alt_bfv(df, tnp, cycles)

resample_dat_scale_optimus(df, tnp, cycles)

resample_dat_scale_optimus_na(df, tnp, cycles)

resample_dat_scale_optimus_backend(df, tnp, cycles, na_omit = NULL)

resample_vect_scale(df, tnp, cycles, method = c("normal", "brute", "vector"))

```

Arguments

df	A clean data frame with attributes or tuples containing a mixture of samples.
tnp	A numeric value indicating the number of rows used. TNP is used as an acronym for Test, Negative, Positive.
cycles	A numeric value indicating the number of cycles selected by the user when running the FLUOstar instrument.
na_omit	Takes a string "yes" OR "no".
method	A string 'normal', 'brute' or 'vector' to specify the method of resampling.

Value

A new data frame where separated samples are assigned a separate attribute or column.

A new data frame where separated samples are assigned a separate attribute or column.

A new data frame where separated samples are assigned a separate attribute or column.

A new data frame where separated samples are assigned a separate attribute or column.

A new data frame where separated samples are assigned a separate attribute or column.

A new data frame where separated samples are assigned a separate attribute or column.

A new data frame where separated samples are assigned a separate attribute or column.

A new data frame where separated samples are assigned a separate attribute or column.

A new data frame where separated samples are assigned a separate attribute or column.

A new data frame where separated samples are assigned a separate attribute or column.

Note

This function builds on or scales-up @seealso [resample_dat\(\)](#), hence the suffix scale. This function is less optimized than @seealso [resample_dat_scale_optimus\(\)](#).

This function builds on or scales-up @seealso [resample_dat\(\)](#), hence the suffix scale. This function is less optimized than @seealso [resample_dat_scale_optimus\(\)](#).

This function builds on or scales-up @seealso [resample_dat\(\)](#), hence the suffix scale. This function is more optimized than @seealso [resample_dat_scale\(\)](#), hence the suffix scale_optimus.

This function builds on or scales-up @seealso [resample_dat\(\)](#), hence the suffix scale. This function is more optimized than @seealso [resample_dat_scale\(\)](#), hence the suffix scale_optimus.

This function builds on or scales-up @seealso [resample_dat\(\)](#), hence the suffix scale. This function is more optimized than @seealso [resample_dat_scale\(\)](#), hence the suffix scale_optimus.

This is the pseudo-vectorized approach and should be a more efficient function. This function will produce a vertical layout as defined in this package. This function inspired by the lapply approach pretty much applies the

Author(s)

Tingwei Adeck

See Also

[resample_dat\(\)](#)

[resample_dat\(\)](#)

[resample_dat_alt\(\)](#)

[resample_dat_alt\(\)](#)

[resample_dat_alt\(\)](#), [resample_dat_scale_alt\(\)](#)

[resample_dat_alt\(\)](#), [resample_dat_scale_alt\(\)](#)

[resample_dat\(\)](#)

[resample_dat\(\)](#)

[resample_dat\(\)](#)

[resample_dat_vect\(\)](#)

[resample_dat_vect\(\)](#). As a matter of fact, I took this approach to create compatibility with lapply and rapply but that failed.

Examples

```
## Not run:
fpath <- system.file("extdata", "dat_4.dat", package = "normfluodbf", mustWork = TRUE)
dat_df <- read.table(file=fpath)
nocomma_dat <- clean_odddat_optimus(dat_df)
resampled_scaled <- resample_dat_scale(nocomma_dat, tnp=3, cycles=40)
## End(Not run)
## Not run:
fpath <- system.file("extdata", "dat_4.dat", package = "normfluodbf", mustWork = TRUE)
dat_df <- read.table(file=fpath)
nocomma_dat <- clean_odddat_optimus(dat_df)
resampled_scaled <- resample_dat_scale_naretainer(nocomma_dat, tnp=3, cycles=40)
## End(Not run)
## Not run:
fpath <- system.file("extdata", "dat_1.dat", package = "normfluodbf", mustWork = TRUE)
dat_df <- read.table(file=fpath)
nocomma_dat <- clean_odddat_optimus(dat_df)
resampled_scaled <- resample_dat_scale_alt(nocomma_dat, tnp=3, cycles=40)
## End(Not run)
```

```

## Not run:
fpath <- system.file("extdata", "dat_1.dat", package = "normfluodbf", mustWork = TRUE)
dat_df <- read.table(file=fpath)
nocomma_dat <- clean_odddat_optimus(dat_df)
resampled_scaled <- resample_dat_scale_alt_na(nocomma_dat, tnp=3, cycles=40)
## End(Not run)
## Not run:
fpath <- system.file("extdata", "dat_4.dat", package = "normfluodbf", mustWork = TRUE)
dat_df <- read.table(file=fpath)
nocomma_dat <- clean_odddat_optimus(dat_df)
resampled_scaled <- resample_dat_scale_alt_bf_na(nocomma_dat, tnp=3, cycles=40)
## End(Not run)
## Not run:
fpath <- system.file("extdata", "dat_4.dat", package = "normfluodbf", mustWork = TRUE)
dat_df <- read.table(file=fpath)
nocomma_dat <- clean_odddat_optimus(dat_df)
resampled_scaled <- resample_dat_scale_alt_bfv(nocomma_dat, tnp=3, cycles=40)
## End(Not run)
## Not run:
fpath <- system.file("extdata", "dat_1.dat", package = "normfluodbf", mustWork = TRUE)
dat_df <- read.table(file=fpath)
nocomma_dat <- clean_odddat_optimus(dat_df)
resampled_scaled <- resample_dat_scale_optimus(nocomma_dat, tnp=3, cycles=40)
## End(Not run)
## Not run:
fpath <- system.file("extdata", "dat_1.dat", package = "normfluodbf", mustWork = TRUE)
dat_df <- read.table(file=fpath)
nocomma_dat <- clean_odddat_optimus(dat_df)
resampled_scaled <- resample_dat_scale_optimus_na(nocomma_dat, tnp=3, cycles=40)
## End(Not run)
## Not run:
fpath <- system.file("extdata", "dat_1.dat", package = "normfluodbf", mustWork = TRUE)
dat_df <- read.table(file=fpath)
nocomma_dat <- clean_odddat_optimus(dat_df)
resampled_scaled <- resample_dat_scale_optimus_backend(nocomma_dat, tnp=3, cycles=40)
## End(Not run)
## Not run:
fpath <- system.file("extdata", "dat_3.dat", package = "normfluodbf", mustWork = TRUE)
dat_df <- read.table(file=fpath)
nocomma_dat <- clean_odddat_optimus(dat_df)
alt_test_scale <- resample_vect_scale(nocomma_dat,3,40, method = 'brute')
alt_test_scale <- resample_vect_scale(nocomma_dat,3,40, method = 'normal')
alt_test_scale <- resample_vect_scale(nocomma_dat,3,40, method = 'vector')
alt_test_scale_norm <- lapply(alt_test_scale, min_max_norm)
## End(Not run)

```

resample_dat_vect

A function to create an attribute or column for each sample loaded into the microplate wells.

Description

Designed as a prototype function to take a single attribute or column consisting of several samples and perform a putative resampling to yield another data frame with a separate attribute for each sample.

Designed as a prototype function to take a single attribute or column consisting of several samples and perform a putative resampling to yield another data frame with a separate attribute for each sample.

: Designed as a prototype function to take a single tuple or row consisting of several samples and perform a putative resampling to yield another data frame with a separate attribute for each sample.

Usage

```
resample_dat_vect(df, tnp, cycles, output = NULL)
```

```
resample_dat(df, tnp, cycles)
```

```
resample_dat_alt(df, tnp, cycles)
```

Arguments

df	A clean data frame with attributes or tuples containing a mixture of samples.
tnp	A numeric value indicating the number of rows used. TNP is used as an acronym for Test, Negative, Positive.
cycles	A numeric value indicating the number of cycles selected by the user when running the FLUOstar instrument.
output	A choice between "df" and 'vector' outputs. Leave NULL for a data frame.

Value

A new data frame where separated samples are assigned a separate attribute or column.

A new data frame where separated samples are assigned a separate attribute or column.

A new data frame where separated samples are assigned a separate attribute or column.

Note

This is the vectorized approach and should be a more efficient function when compared to say

Author(s)

Tingwei Adeck

See Also

[resample_vect_scale\(\)](#)

[resample_dat\(\)](#) or @seealso [resample_dat_alt\(\)](#). This function will produce a vertical layout as defined in this package.

```
resample_dat_scale(), resample_dat_scale_optimus()  
resample_dat_scale_alt()
```

Examples

```
## Not run:  
fpath <- system.file("extdata", "dat_4.dat", package = "normfluodbf", mustWork = TRUE)  
dat_df <- read.table(file=fpath)  
nocomma_dat <- clean_odddat_optimus(dat_df)  
samples_delineated <- resample_dat_vect(nocomma_dat, tnp=3, cycles=40)  
## End(Not run)  
## Not run:  
fpath <- system.file("extdata", "dat_5.dat", package = "normfluodbf", mustWork = TRUE)  
dat_df <- read.table(file=fpath)  
nocomma_dat <- clean_odddat_optimus(dat_df)  
samples_delineated <- resample_dat(nocomma_dat, tnp=3, cycles=40)  
## End(Not run)  
## Not run:  
fpath <- system.file("extdata", "dat_5.dat", package = "normfluodbf", mustWork = TRUE)  
dat_df <- read.table(file=fpath)  
nocomma_dat <- clean_odddat_optimus(dat_df)  
samples_delineated <- resample_dat_alt(nocomma_dat, tnp=3, cycles=40)  
## End(Not run)
```

run_demo

Run the shiny App In addition to the functions provided in this package, the normfluodbf package also provides an interactive tool that can be used to analyze liposome flux assay data more easily. The tool will be launched in a web browser.

Description

Run the shiny App In addition to the functions provided in this package, the normfluodbf package also provides an interactive tool that can be used to analyze liposome flux assay data more easily. The tool will be launched in a web browser.

Usage

```
run_demo()
```

run_demo_bg	<i>Run Demo Background</i>
-------------	----------------------------

Description

Run Demo Background

Usage

```
run_demo_bg(  
  host = getOption("shiny.host", "127.0.0.1"),  
  appDir = system.file("shiny/demo", package = "normfluodbf")  
)
```

Arguments

host	localhost
appDir	dir

run_demo_in_background	<i>Run Demo in Background</i>
------------------------	-------------------------------

Description

Run Demo in Background

Usage

```
run_demo_in_background(  
  appDir = system.file("shiny/demo", package = "normfluodbf"),  
  job_name,  
  host,  
  port  
)
```

Arguments

appDir	dir
job_name	job name
host	host ip (localhost)
port	port

Value

NULL (run script)

run_demo_script *Run Demo Script*

Description

Run Demo Script

Usage

```
run_demo_script(  
  appDir = system.file("shiny/demo", package = "normfluodbf"),  
  port,  
  host  
)
```

Arguments

appDir	App Dir
port	Port
host	Host

Details

A quick script inspired by gptstudio to aid in running the cool normfluodbf demo.

Value

Script

sampledata *Get Development Data*

Description

Get Development Data

Usage

```
sample_data_dir()  
  
sample_data_file(gotofile = NULL)
```

Arguments

gotofile	file
----------	------

Value

directory data

See Also

Other dirutils: [dirutils](#), [normfluodbfcomms](#)

Examples

```
## Not run:
fpath <- system.file("extdata", package = "normfluodbf", mustWork = TRUE)
sample_data_dir()
sample_data_file(gotofile = NULL)
## End(Not run)
```

saveloadutils

Save and Load Plate

Description

Save and Load Plate

Usage

```
save_plate(plate, suffix = NULL, interactive = F)

save_rds_plate(plate, save_name, use_tempfile = F)

load_rds_plate(plate, interactive = F)

var_str(var)
```

Arguments

plate	plate
suffix	suffix
interactive	boolean
save_name	name
use_tempfile	boolean
var	variable

Value

plate
plate
plate
plate

See Also

Other plate_utils: [check_dirt\(\)](#), [get_wells_used\(\)](#), [plate_data_summary\(\)](#), [platename](#), [remove_leading_zero\(\)](#), [set_plate_version\(\)](#), [type\(\)](#)

setsteps

Set Plate Steps

Description

Set Plate Steps

Usage

```
steps(plate)
```

```
steps(plate) <- value
```

Arguments

plate plate

value value

Value

plate

plate

plate

See Also

Other steps: [stepsutils](#)

Examples

```
## Not run: steps(plate)
```

set_assiette_type *Set The Plate Types*

Description

Set The Plate Types

Usage

```
set_assiette_type(plate, type = NULL, child_type = NULL)
```

Arguments

plate	A parent plate
type	parent plate type
child_type	child plate type

Details

Non-recursive approach.

Value

plate

Examples

```
## Not run: set_assiette_type(parent_plate_type,96well_plate)
```

set_plate_type *Set The Child Plate Type*

Description

Set The Child Plate Type

Usage

```
set_plate_type(parent_plate, type)
```

Arguments

parent_plate	plate
type	child plate type

Details

This is a recursive method.

Value

plate

Examples

```
## Not run:  
x = set_plate_type(parent_plate, "96well_plate")  
print(class(x))  
## End(Not run)
```

set_plate_version *Plate Version*

Description

Plate Version

Usage

```
set_plate_version(plate, pkg)
```

Arguments

plate	plate
pkg	package

Value

plate

See Also

Other plate_utils: [check_dirt\(\)](#), [get_wells_used\(\)](#), [plate_data_summary\(\)](#), [platename](#), [remove_leading_zero\(\)](#), [saveloadutils](#), [type\(\)](#)

Examples

```
## Not run: set_plate_version(plate, pkg)
```

shiny_random_port	<i>Random Port gptstudio style</i>
-------------------	------------------------------------

Description

Random Port gptstudio style

Usage

```
shiny_random_port()
```

Value

port

status	<i>Status</i>
--------	---------------

Description

Status

Usage

```
status(plate)
status(plate) <- value
dirty(plate)
dirty(plate) <- value
is_plate_dirty(plate)
```

Arguments

plate	plate
value	value

Value

plate
plate
plate
plate
plate
logical

Examples

```
## Not run: status(plate, status)
```

```
stepspipeline
```

```
Steps Pipeline
```

Description

Steps Pipeline

Usage

```
.next_step(plate, n = 1)
next_step(plate, n = 1)
run_steps(plate, reset = FALSE, ...)
```

Arguments

plate	plate
n	n
reset	reset
...	dots

Value

```
plate
plate
plate
plate
```

Note

Recursive function to implement steps in the plate until all steps in the pipeline are complete
 Recursive function to implement steps in the plate until all steps in the pipeline are complete

Examples

```
## Not run: next_step(plate, n=1)
```

stepsutils

Steps Utils

Description

Steps Utils

Usage

```
step(plate, step)
step_name(plate, step)
.step_name(plate, step)
get_step_key_by_index(steps, index)
step_begin(...)
step_end(...)
has_step(plate, step)
check_step(plate, step)
steps_complete(plate)
```

Arguments

plate	plate
step	step
steps	steps
index	index
...	dots

Value

```
plate
step number
step name
step name
step name
boolean
boolean
boolean
```

Note

Step start time utilizing the cache

Step start time utilizing the cache

See Also

Other steps: [setsteps](#)

Examples

```
## Not run: step(plate, step)
```

test_boilerplate	<i>Test Boilerplate</i>
------------------	-------------------------

Description

Test Boilerplate

Open Testfile

Usage

```
test_boilerplate(file_name = NULL)
```

```
open_testfile(testfile)
```

Arguments

file_name file name

testfile test file

Value

test boilerplate

open test file

Note

Solves the inconvenient process of navigating to the tests folder every time

Examples

```
## Not run: test_boilerplate(file_name = "test_remove_shit.R")
```

```
## Not run: open_testfile('test_pipeline.R')
```

type	<i>Plate Type</i>
------	-------------------

Description

Plate Type

Usage

```
type(plate, all = FALSE)
```

Arguments

plate	plate
all	Boolean

Value

class attribute

See Also

Other plate_utils: [check_dirt\(\)](#), [get_wells_used\(\)](#), [plate_data_summary\(\)](#), [platename](#), [remove_leading_zero\(\)](#), [save_loadutils](#), [set_plate_version\(\)](#)

Examples

```
## Not run: type(plate)
```

uploadplatedata	<i>Upload Plate Data</i>
-----------------	--------------------------

Description

Upload Plate Data

Usage

```
upload_data(plate, file, ...)

## Default S3 method:
upload_data(plate, file, ...)

## S3 method for class '`96well_plate`'
upload_data(plate, file, ...)
```

```
## S3 method for class ``384well_plate``  
upload_data(plate, file, ...)  
  
## S3 method for class ``1536well_plate_t1``  
upload_data(plate, file, ...)  
  
## S3 method for class ``1536well_plate_t2``  
upload_data(plate, file, ...)
```

Arguments

plate	plate
file	file
...	dots

Value

plate
plate
plate
plate
plate
plate
plate

Examples

```
## Not run: upload_data(plate, file, ...)
```

viewerpane_background_normfluodbf
View App in Viewer Pane

Description

View App in Viewer Pane

Usage

```
viewerpane_background_normfluodbf(host, port)
```

Arguments

host	host
port	port

wait_for_bg_shinyapp *Validate URL*

Description

Validate URL

Usage

```
wait_for_bg_shinyapp(url)
```

Arguments

url url

xycoordinates *Plot Coordinates*

Description

Plot Coordinates

Usage

```
x_var_one(plate)
x_var_one(plate) <- value
x_var_two(plate)
x_var_two(plate) <- value
y_var(plate)
y_var(plate) <- value
x_var_one_label(plate)
x_var_one_label(plate) <- value
x_var_two_label(plate)
x_var_two_label(plate) <- value
```

Arguments

plate	plate
value	value

Value

plate
 plate
 plate
 plate
 plate
 plate
 plate
 plate
 plate
 plate
 plate

Examples

```
## Not run: x_var_one(plate,value)
```

%there% *The %there% operator*

Description

The %there% operator

Usage

```
dfile %there% dirpath
```

Arguments

dfile	file
dirpath	directory

Value

logical

Examples

```
## Not run:
fpath <- system.file("extdata", package = "normfluodbf", mustWork = TRUE)
"dat_1.dat" %there% fpath
## End(Not run)
```

Index

- * **analyze**
 - analyze, 4
- * **childtype**
 - childtype, 8
- * **datasets**
 - dat_1, 11
 - dat_2, 12
 - dat_3, 12
 - dat_4, 12
 - dat_5, 13
 - dat_6, 13
 - dat_7, 13
 - liposomes_214, 29
 - liposomes_215, 29
 - liposomes_216, 29
 - liposomes_218, 30
 - liposomes_221, 30
 - liposomes_227, 30
 - plate_types_tbl, 50
- * **defineparams**
 - defineparams, 19
- * **definestatus**
 - definestatus, 20
- * **definesteps**
 - definesteps, 21
- * **detectoutliers**
 - detectoutliers, 22
- * **dev_helpers**
 - check_broken_packages, 6
- * **dirutils**
 - dirutils, 23
 - sampladata, 62
- * **formatplatedata**
 - formatplatedata, 25
- * **getfilename**
 - getfilename, 26
- * **loadplatedata**
 - loadplatedata, 33
- * **loadplatemeta**
 - loadplatemeta, 33
- * **modifyplatedata**
 - modifyplatedata, 34
- * **normalizebywell**
 - normalizebywell, 37
- * **normalize**
 - normalize, 36
- * **normfluodbf_utils**
 - normalizingagents, 38
- * **normfluodbfplots**
 - normfluodbfplots, 40
- * **normfluodbf**
 - liposome_fluor_dbfs, 31
- * **operators**
 - %there%, 74
- * **parenttype**
 - parenttype, 45
- * **plate_utils**
 - check_dirt, 7
 - get_wells_used, 27
 - plate_data_summary, 49
 - platenam, 49
 - remove_leading_zero, 54
 - saveloadutils, 63
 - set_plate_version, 66
 - type, 71
- * **platedata**
 - platedata, 47
- * **platemeta**
 - platemeta, 48
- * **plate**
 - plate, 46
- * **printer**
 - printer, 51
- * **removeoutliers**
 - removeoutliers, 52
- * **status**
 - status, 67
- * **stepspipeline**

- stepspipeline, 68
- * **steps**
 - setsteps, 64
 - stepsutils, 69
- * **uploadplatedata**
 - uploadplatedata, 71
- * **utils**
 - check_broken_packages, 6
- * **xycoordinates**
 - xycoordinates, 73
- .next_step(stepspipeline), 68
- .step_name(stepsutils), 69
- %there%, 74

- add_package_namespace, 4
- analyze, 4
- analyze_ready(analyze), 4
- average_fluorescence_by_row_cycle, 5

- capitalize, 6
- check_broken_packages, 6
- check_dirt, 7, 27, 49, 50, 54, 64, 66, 71
- check_package_usage, 7
- check_step(stepsutils), 69
- child_plate_type(childtype), 8
- childtype, 8
- clean_commas, 8
- clean_even_dat(clean_odddat_optimus), 9
- clean_odddat_optimus, 9
- comma_cleaner, 10
- comment_out_lines, 11

- dat_1, 11
- dat_2, 12
- dat_3, 12
- dat_4, 12
- dat_5, 13
- dat_6, 13
- dat_7, 13
- dat_col_names_horizontal, 14
- dat_col_names_optimus, 15
- dat_col_names_optimus(), 19
- dat_col_names_prime, 16
- dat_col_names_rigid, 17
- dat_col_names_rigid(), 16
- decimal_scaling(normalizingagents), 38
- decimal_scaling_df(normalizingagents), 38
- define_params(defineparams), 19
- define_status(definestatus), 20
- define_steps(definesteps), 21
- defineparams, 19
- definestatus, 20
- definesteps, 21
- detect_outliers_cn(detectoutliers), 22
- detect_outliers_time_cn(detectoutliers), 22
- detectoutliers, 22
- dirty(status), 67
- dirty<- (status), 67
- dirutils, 23, 63

- empty_plate(plate), 46

- find_known_liposome_dat_file(dirutils), 23
- find_known_liposome_dbf_file(dirutils), 23
- find_random_port, 24
- fluorthresholdcheck, 39
- format_plate_data(formatplatedata), 25
- formatplatedata, 25

- get_common_dat_names(getfilename), 26
- get_dat_common_name(getfilename), 26
- get_dat_file_name(getfilename), 26
- get_dbf_file_name(getfilename), 26
- get_status_value(definestatus), 20
- get_step_key_by_index(stepsutils), 69
- get_wells_used, 7, 27, 49, 50, 54, 64, 66, 71
- getfilename, 26
- globalcache, 27

- has_step(stepsutils), 69

- init_plate(plate), 46
- is_dir(dirutils), 23
- is_file(dirutils), 23
- is_normalized(isnormalized), 28
- is_plate_dirty(status), 67
- isnormalized, 28

- launch, 28
- liposome_fluor_dbfs, 31
- liposomes_214, 29
- liposomes_215, 29
- liposomes_216, 29
- liposomes_218, 30
- liposomes_221, 30

- liposomes_227, 30
- list_dats (dirutils), 23
- list_dbfs (dirutils), 23
- load_plate_data (loadplatedata), 33
- load_plate_data<- (loadplatedata), 33
- load_plate_meta (loadplatemeta), 33
- load_plate_meta<- (loadplatemeta), 33
- load_rds_plate (save_loadutils), 63
- loadplatedata, 33
- loadplatemeta, 33
- log_transformation (normalizingagents), 38

- min_max_norm (normalizingagents), 38
- min_max_norm_df (normalizingagents), 38
- min_max_norm_percent (normalizingagents), 38
- min_max_norm_percent_df (normalizingagents), 38
- modify_plate_data (modifyplatedata), 34
- modifyplatedata, 34
- move_file, 35
- multiplot, 36

- name (platename), 49
- name<- (platename), 49
- new_plate (plate), 46
- next_step (stepsipeline), 68
- norm_tidy_dbf (liposome_fluor_dbfs), 31
- norm_z (normalizingagents), 38
- norm_z_df (normalizingagents), 38
- normalize, 36
- normalize_by_well (normalizebywell), 37
- normalize_dataframe (normalize), 36
- normalizebywell, 37
- normalizingagents, 38
- normfluodat (normfluodat), 42
- normfluodat(), 16, 32, 44, 45
- normfluodatfull (normfluodat), 42
- normfluodatlite (normfluodat), 42
- normfluodatlite(), 44
- normfluodbf (liposome_fluor_dbfs), 31
- normfluodbfcomms, 24, 63
- normfluodbfplots, 40
- normfluodat, 42
- normfluodbf (liposome_fluor_dbfs), 31
- normfluodbf(), 32

- open_testfile (test_boilerplate), 70

- parent_plate_type (parenttype), 45
- parenttype, 45
- plate, 46
- plate_data (platedata), 47
- plate_data_summary, 7, 27, 49, 49, 54, 64, 66, 71
- plate_meta (platemeta), 48
- plate_types (plate_types_tbl), 50
- plate_types(), 50
- plate_types_tbl, 50
- plate_types_vector (plate_types_tbl), 50
- platedata, 47
- platemeta, 48
- platename, 7, 27, 49, 50, 54, 64, 66, 71
- plot.1536well_plate_t1 (normfluodbfplots), 40
- plot.1536well_plate_t2 (normfluodbfplots), 40
- plot.384well_plate (normfluodbfplots), 40
- plot.96well_plate (normfluodbfplots), 40
- print.1536well_plate_t1 (printer), 51
- print.1536well_plate_t2 (printer), 51
- print.384well_plate (printer), 51
- print.96well_plate (printer), 51
- printer, 51

- quiet, 52

- remove_leading_zero, 7, 27, 49, 50, 54, 64, 66, 71
- remove_outliers (removeoutliers), 52
- removeoutliers, 52
- replace_word_in_file, 54
- resample_dat (resample_dat_vect), 58
- resample_dat(), 56, 57, 59
- resample_dat_alt (resample_dat_vect), 58
- resample_dat_alt(), 57, 59
- resample_dat_scale, 55
- resample_dat_scale(), 56, 57, 60
- resample_dat_scale_alt (resample_dat_scale), 55
- resample_dat_scale_alt(), 57, 60
- resample_dat_scale_alt_bf_na (resample_dat_scale), 55
- resample_dat_scale_alt_bfv (resample_dat_scale), 55
- resample_dat_scale_alt_na (resample_dat_scale), 55

resample_dat_scale_naretainer
 (resample_dat_scale), 55
 resample_dat_scale_optimus
 (resample_dat_scale), 55
 resample_dat_scale_optimus(), 56, 60
 resample_dat_scale_optimus_backend
 (resample_dat_scale), 55
 resample_dat_scale_optimus_na
 (resample_dat_scale), 55
 resample_dat_vect, 58
 resample_dat_vect(), 57
 resample_vect_scale
 (resample_dat_scale), 55
 resample_vect_scale(), 59
 reset_plate (plate), 46
 roundfluor (normalizingagents), 38
 run_demo, 60
 run_demo_bg, 61
 run_demo_in_background, 61
 run_demo_script, 62
 run_steps (stepspipeline), 68

 sample_data_dir (sampledata), 62
 sample_data_file (sampledata), 62
 sampledata, 24, 62
 save_plate (saveloadutils), 63
 save_rds_plate (saveloadutils), 63
 saveloadutils, 7, 27, 49, 50, 54, 63, 66, 71
 set_assiette_type, 65
 set_default_params (defineparams), 19
 set_default_status (definestatus), 20
 set_default_steps (definesteps), 21
 set_plate_type, 65
 set_plate_version, 7, 27, 49, 50, 54, 64, 66,
 71
 setsteps, 64, 70
 setup_plate (plate), 46
 shiny_random_port, 67
 status, 67
 status<- (status), 67
 step (stepsutils), 69
 step_begin (stepsutils), 69
 step_end (stepsutils), 69
 step_name (stepsutils), 69
 steps (setsteps), 64
 steps<- (setsteps), 64
 steps_complete (stepsutils), 69
 stepspipeline, 68
 stepsutils, 64, 69

 test_boilerplate, 70
 type, 7, 27, 49, 50, 54, 64, 66, 71

 update_status_list (definestatus), 20
 update_steps_list (definesteps), 21
 upload_data (uploadplatedata), 71
 uploadplatedata, 71
 use_initialized_plate (plate), 46
 use_setup_plate (plate), 46

 var_str (saveloadutils), 63
 viewerpane_background_normfluodbf, 72

 wait_for_bg_shinyapp, 73

 x_var_one (xycoordinates), 73
 x_var_one<- (xycoordinates), 73
 x_var_one_label (xycoordinates), 73
 x_var_one_label<- (xycoordinates), 73
 x_var_two (xycoordinates), 73
 x_var_two<- (xycoordinates), 73
 x_var_two_label (xycoordinates), 73
 x_var_two_label<- (xycoordinates), 73
 xycoordinates, 73

 y_var (xycoordinates), 73
 y_var<- (xycoordinates), 73