

Package ‘ouch’

May 9, 2026

Type Package

Title Ornstein-Uhlenbeck Models for Phylogenetic Comparative Hypotheses

Version 2.20

Date 2024-07-04

Maintainer Aaron A. King <kingaa@umich.edu>

Description Fit and compare Ornstein-Uhlenbeck models for evolution along a phylogenetic tree.

Depends R(>= 4.1)

Imports methods, stats, graphics, grDevices, utils, subplex

Suggests ape

URL <https://kingaa.github.io/ouch/>

License GPL-3

LazyLoad true

LazyData true

RoxygenNote 7.3.2

BugReports <https://github.com/kingaa/ouch/issues/>

Encoding UTF-8

Collate 'anolis.R' 'print.R' 'package.R' 'ouchtree.R' 'ape2ouch.R' 'bootstrap.R' 'update.R' 'simulate.R' 'plot.R' 'summary.R' 'logLik.R' 'coef.R' 'rmvnorm.R' 'glssoln.R' 'hansen.R' 'brown.R' 'as_data_frame.R' 'bimac.R' 'geospiza.R' 'paint.R'

NeedsCompilation yes

Author Aaron A. King [aut, cre] (ORCID: <https://orcid.org/0000-0001-6159-3207>),
Marguerite A. Butler [ctb]

Repository CRAN

Date/Publication 2024-07-04 16:20:02 UTC

Contents

ouch-package	2
anolis.ssd	3
as_data_frame	5
bimac	6
bootstrap	8
brown	9
coef	11
geospiza	12
hansen	13
logLik	16
ouchtree	17
paint	19
plot	20
simulate	22
summary	23
update	23
Index	25

ouch-package	<i>Ornstein-Uhlenbeck methods for comparative phylogenetic hypotheses</i>
--------------	---

Description

The **ouch** package provides facilities for phylogenetic comparative analysis based on Ornstein-Uhlenbeck models of trait evolution along a phylogeny. Multivariate data and complex adaptive hypotheses are supported.

Classes

The basic class, `ouchtree`, is provided to encode a phylogenetic tree. Plot and print methods are provided.

The class `browntree` derives from class `ouchtree` and encodes the results of fitting a Brownian Motion model to data.

The class `hansentree` derives from class `ouchtree` and encodes the results of fitting a Hansen model to data.

Detailed Documentation

- Phylogenies in **ouch** format: `ouchtree()`, `ape2ouch()`
- Brownian motion models: `brown()`
- Ornstein-Uhlenbeck models: `hansen()`, `paint()`
- Simulation of models: `simulate()`

- Display of data: [plot\(\)](#)
- Extraction of information from fitted models: [summary\(\)](#), [logLik\(\)](#), [coef\(\)](#)
- Example datasets: [anolis.ssd](#), [bimac](#)

Citing ouch

Execute `citation("ouch")` to view the correct citation for publications.

Author(s)

Aaron A. King

References

T.F. Hansen. 1997. Stabilizing selection and the comparative analysis of adaptation. *Evolution*, 51:1341–1351. doi:10.1111/j.15585646.1997.tb01457.x.

Butler, M.A. and A.A. King. 2004. Phylogenetic comparative analysis: a modeling approach for adaptive evolution. *American Naturalist* 164:683–695. doi:10.1086/426002.

Cressler, C. E., Butler, M. A., and King, A. A. 2015. Detecting adaptive evolution in phylogenetic comparative analysis using the Ornstein-Uhlenbeck model. *Systematic Biology*, 64:953–968. doi:10.1093/sysbio/syv043.

See Also

Useful links:

- <https://kingaa.github.io/ouch/>
- Report bugs at <https://github.com/kingaa/ouch/issues/>

Other phylogenetic comparative models: [brown\(\)](#), [hansen\(\)](#), [ouchtree](#), [paint\(\)](#)

Other methods for ouch trees: [as_data_frame](#), [bootstrap\(\)](#), [coef\(\)](#), [logLik](#), [paint\(\)](#), [plot\(\)](#), [print\(\)](#), [simulate\(\)](#), [summary\(\)](#), [update\(\)](#)

Other examples: [anolis.ssd](#), [bimac](#), [geospiza](#)

anolis.ssd

Greater Antillean anolis lizard sexual size dimorphism data

Description

The dataset consists of sexual size-dimorphism data for 38 species of anoles from Cuba, Hispaniola, Jamaica, and Puerto Rico (Butler, Schoener, and Losos 2000). Each of these species belongs to one of six microhabitat types, or "ecomorphs" (sensu Williams, 1972): trunk-ground, grass-bush, trunk, trunk-crown, twig, and crown-giant. The data were used to demonstrate an evolutionary association between habitat type and degree of sexual size dimorphism.

Format

A data frame with 38 observations on the following 6 variables.

- `node`: Labels for the nodes.
- `species`: Names of extant species.
- `log.SSD`: Log sexual size dimorphism of extant species.
- `ancestor`: Name of ancestor node.
- `time`: Time of node.
- `OU.1`: a factor with one level, `ns`.
- `OU.7`: a factor with levels corresponding to ecomorph (`tg`, `tc`, `gb`, `cg`, `tw`, `tr`, `anc`).

Details

Size dimorphism was calculated as the log-ratio of male snout-to-vent length to female snout-to-vent length (males are larger).

In this example, we tested three models of evolution: Brownian motion, Ornstein-Uhlenbeck with one global optimum, and Ornstein-Uhlenbeck with seven optima (one for each ecomorph type plus an additional one for an "unknown" type).

For the seven-optima model, we assigned each terminal branch to an optimum according to the ecomorph type of the extant species. Because we had no information to help guide hypotheses about internal branches, we assigned internal branches to the "unknown" selective regime. The phylogeny of these species is consistent with and adaptive radiation, with a burst of speciation events early in the evolutionary history of this clade (see phylogeny in Butler & King (2004) or example below).

Author(s)

Marguerite A. Butler, Aaron A. King

Source

Butler, M.A. and A.A. King. 2004. Phylogenetic comparative analysis: a modeling approach for adaptive evolution. *American Naturalist* 164:683–695. doi:10.1086/426002.

References

Butler, M. A., T. W. Schoener, and J. B. Losos. 2000. The relationship between sexual size dimorphism and habitat use in Greater Antillean Anolis lizards. *Evolution*, 54:259–272. doi:10.1111/j.00143820.2000.tb00026.x.

Williams, E. E. 1972. The origin of faunas. Evolution of lizard congeners in a complex island fauna: a trial analysis. *Evolutionary Biology*, 6:47–89. doi:10.1007/9781468490633_3.

See Also

Other examples: [bimac](#), [geospiza](#), [ouch-package](#)

Examples

```
## Analysis of sexual size dimorphism data
## Save time for CRAN
tree <- with(anolis.ssd,ouchtree(node,ancestor,time/max(time),species))
plot(tree,node.names=TRUE)

h1 <- brown(anolis.ssd['log.SSD'],tree)
h1
plot(h1)

h2 <- hansen(anolis.ssd['log.SSD'],tree,anolis.ssd['OU.1'],sqrt.alpha=1,sigma=1)
h2
plot(h2)

h3 <- hansen(anolis.ssd['log.SSD'],tree,anolis.ssd['OU.7'],sqrt.alpha=1,sigma=1)
h3
plot(h3)
```

as_data_frame

*Coerce an **ouch** object to a data frame*

Description

Coerce an **ouch** object to a data frame

Usage

```
## S3 method for class 'ouchtree'
as.data.frame(x, ...)

## S3 method for class 'browntree'
as.data.frame(x, ...)

## S3 method for class 'hansentree'
as.data.frame(x, ...)
```

Arguments

x any R object.
... additional arguments to be passed to or from methods.

See Also

Other methods for ouch trees: [bootstrap\(\)](#), [coef\(\)](#), [logLik](#), [ouch-package](#), [paint\(\)](#), [plot\(\)](#), [print\(\)](#), [simulate\(\)](#), [summary\(\)](#), [update\(\)](#)

bimac

Anolis bimaculatus lizard size data**Description**

This is the *Anolis bimaculatus* dataset used in Butler & King (2004). It is used to test a hypothesis of character displacement using an interspecific dataset of body sizes and current data on sympatry/allopatry.

Format

A data frame with 45 observations on the following 11 variables.

- node: Labels for the nodes.
- spcode: Two-letter code for each taxon.
- species: Species names for extant species.
- island: Name of the island on which the population is found.
- size: Body size (head length in mm) of extant species.
- ancestor: Ancestral node.
- time: Time of node.
- OU.1: a factor with levels ns
- OU.3: a factor with levels small, medium, large
- OU.4: a factor with levels small, medium, large, anc
- OU.LP: a factor with levels small, medium, large

Details

Explanations of the data follow:

- **Body size.** We use the phenotypic data and phylogeny of Losos (1990), which employed the head lengths (of males) as a proxy for body size. In this group of lizards, head length correlates very strongly with snout-to-vent length and the cube root of mass, which are standard measures of body size. The data are head lengths in mm; note that we use the log of this value in analyses.
- **Tree structure.** The phylogenetic tree is encoded via three variables: node, ancestor, and time. The node variable gives a name to each node. The ancestor variable names the ancestor of each node. The root node has no ancestor (i.e., ancestor=NA). The variable time specifies the temporal location of each node, the root node being at time 0.
- **Specifications of selective regimes.** (Columns OU.1, OU.3, OU.4, OU.LP). These columns are factors, the levels of which correspond to the “paintings” of the respective adaptive regime hypotheses onto the phylogeny (see `paint()`). Each selective regime is named (small, medium, large, etc.). Each column corresponds to a different painting of the selective regimes, and thus to a different hypothesis. In this example, there are 3 alternative models (see Butler & King 2004): OU.4 is 4-regime model, OU.3 is 3-regime model (all ancestors are medium), OU.LP is the linear parsimony model.

- **Other variables.** In addition to the above, there is a two-letter code for each taxon (scode) and the name of the island on which the taxon is found (island).

Author(s)

Marguerite A. Butler and Aaron A. King

Source

Butler, M.A. and A.A. King. 2004. Phylogenetic comparative analysis: a modeling approach for adaptive evolution. *American Naturalist* 164:683–695. doi:10.1086/426002.

References

Lazell, J. D. 1972. The anoles (Sauria: Iguanidae) of the Lesser Antilles. *Bull. Mus. Comp. Zool.*, 143:1–115.

Losos, J. B. 1990. A phylogenetic analysis of character displacement in Caribbean Anolis lizards. *Evolution*, 44:558–569. doi:10.1111/j.15585646.1990.tb05938.x.

See Also

Other examples: [anolis.ssd](#), [geospiza](#), [ouch-package](#)

Examples

```
## Analysis of Anolis bimaculatus data
## save time for CRAN
tree <- with(bimac, ouchtree(node, ancestor, time/max(time), scode))
plot(tree, node.names=TRUE)

h1 <- brown(log(bimac['size']), tree)
h1
plot(h1)

h2 <- hansen(log(bimac['size']), tree, bimac['OU.1'], sqrt.alpha=1, sigma=1)
h2
plot(h2)

h3 <- hansen(log(bimac['size']), tree, bimac['OU.3'], sqrt.alpha=1, sigma=1)
h3
plot(h3)

h4 <- hansen(log(bimac['size']), tree, bimac['OU.4'], sqrt.alpha=1, sigma=1)
h4
plot(h4)

h5 <- hansen(log(bimac['size']), tree, bimac['OU.LP'], sqrt.alpha=1, sigma=1, reltol=1e-5)
h5 <- update(h5, method='subplex', reltol=1e-11, parscale=c(0.1, 0.1), hessian=TRUE)
h5
plot(h5)
```

```
simdat <- simulate(h5,nsim=10)
h5sim <- update(h5,data=simdat[[1]])
summary(h5sim)
h1sim <- update(h1,data=simdat[[1]])
summary(h1sim)
```

bootstrap

Bootstrapping for uncertainty quantification

Description

Parametric bootstrapping for **ouch** models.

Usage

```
## S4 method for signature 'missing'
bootstrap(object, ...)

## S4 method for signature 'ANY'
bootstrap(object, ...)

## S4 method for signature 'hansentree'
bootstrap(object, nboot = 200, seed = NULL, ...)

## S4 method for signature 'browntree'
bootstrap(object, nboot = 200, seed = NULL, ...)
```

Arguments

object	A fitted model object.
...	Additional arguments are passed to update .
nboot	integer; number of bootstrap replicates.
seed	integer; setting seed to a non-NULL value allows one to fix the random seed (see simulate).

Details

`bootstrap` performs a parametric bootstrap for estimation of confidence intervals.

See Also

Other methods for ouch trees: [as_data_frame](#), [coef](#)(), [logLik](#), [ouch-package](#), [paint](#)(), [plot](#)(), [print](#)(), [simulate](#)(), [summary](#)(), [update](#)()

Examples

```

## Not run:
## Fit BM and a 5-regime OU model to the A. bimaculatus data
tree <- with(bimac,ouchtree(node,ancestor,time/max(time),species))

h1 <- brown(
  data=log(bimac['size']),
  tree=tree
)

h5 <- hansen(
  data=log(bimac['size']),
  tree=tree,
  regimes=bimac['OU.LP'],
  sqrt.alpha=1,
  sigma=1,
  reltol=1e-11,
  parscale=c(0.1,0.1),
  hessian=TRUE
)

## What are appropriate AIC.c cutoffs?
simdat <- simulate(h1,nsim=100,seed=92759587)
b1 <- sapply(simdat,function(x)summary(update(h1,data=x))$aic.c)
tic <- Sys.time()
b5 <- sapply(simdat,function(x)summary(update(h5,data=x))$aic.c)
toc <- Sys.time()
print(toc-tic)
cat("approximate 95% AIC.c cutoff",signif(quantile(b1-b5,0.95),digits=3),"\\n")

## Bootstrap confidence intervals
boots.h1 <- bootstrap(h1,nboot=200,seed=92759587)
cat("bootstrap 95% confidence intervals for h1:\\n")
print(t(sapply(boots.h1,quantile,probs=c(0.025,0.975))),digits=3)

boots.h5 <- bootstrap(h5,nboot=200,seed=92759587)
cat("bootstrap 95% confidence intervals for h5:\\n")
print(t(sapply(boots.h5,quantile,probs=c(0.025,0.975))),digits=3)

## End(Not run)

```

Description

The function `brown` creates a `browntree` object by fitting a Brownian-motion model to data.

Usage

```
brown(data, tree)
```

Arguments

data	Phenotypic data for extant species, i.e., at the terminal ends of the phylogenetic tree. This can either be a numeric vector or a list. If it is a numeric vector, there must be one entry for every node. If it is a list, it must consist entirely of numeric vectors, each of which has one entry per node. A data-frame is coerced to a list.
tree	A phylogenetic tree, specified as an ouchtree object.

Value

brown returns an object of class `browntree`.

Author(s)

Aaron A. King

References

Butler, M.A. and A.A. King. 2004. Phylogenetic comparative analysis: a modeling approach for adaptive evolution. *American Naturalist* 164:683–695. [doi:10.1086/426002](https://doi.org/10.1086/426002).

See Also

[bimac](#), [anolis.ssd](#), [hansen](#)

Other phylogenetic comparative models: [hansen\(\)](#), [ouch-package](#), [ouchtree](#), [paint\(\)](#)

Examples

```
## Analysis of Anolis bimaculatus data
## save time for CRAN
tree <- with(bimac, ouchtree(node, ancestor, time/max(time), socode))
plot(tree, node.names=TRUE)

h1 <- brown(log(bimac['size']), tree)
h1
plot(h1)

h2 <- hansen(log(bimac['size']), tree, bimac['OU.1'], sqrt.alpha=1, sigma=1)
h2
plot(h2)

h3 <- hansen(log(bimac['size']), tree, bimac['OU.3'], sqrt.alpha=1, sigma=1)
h3
plot(h3)

h4 <- hansen(log(bimac['size']), tree, bimac['OU.4'], sqrt.alpha=1, sigma=1)
h4
```

```

plot(h4)

h5 <- hansen(log(bimac['size']), tree, bimac['OU.LP'], sqrt.alpha=1, sigma=1, reltol=1e-5)
h5 <- update(h5, method='subplex', reltol=1e-11, parscale=c(0.1, 0.1), hessian=TRUE)
h5
plot(h5)

simdat <- simulate(h5, nsim=10)
hsim <- update(h5, data=simdat[[1]])
summary(hsim)
bsim <- update(h1, data=simdat[[1]])
summary(bsim)

```

coef

Model coefficients

Description

coef extracts the parameters from a fitted model object.

Usage

```

## S4 method for signature 'hansentree'
coef(object, ...)

## S4 method for signature 'browntree'
coef(object, ...)

```

Arguments

object	fitted model object.
...	additional arguments, ignored.

Value

coef applied to a hansentree object returns a named list containing the estimated α and σ^2 matrices (given as the alpha.matrix and sigma.sq.matrix elements, respectively) but also the MLE returned by the optimizer (as sqrt.alpha and sigma, respectively). **The latter elements should not be interpreted, but can be used to restart the algorithm, etc.**

coef applied to a browntree object extracts a list with three elements:

sigma	the coefficients of the sigma matrix.
theta	a list of the estimated optima, one per character.
sigma.sq.matrix	the sigma-squared matrix itself.

See Also

Other methods for ouch trees: [as_data_frame](#), [bootstrap\(\)](#), [logLik](#), [ouch-package](#), [paint\(\)](#), [plot\(\)](#), [print\(\)](#), [simulate\(\)](#), [summary\(\)](#), [update\(\)](#)

geospiza

Data on Darwin's finches

Description

Morphological measurements of Darwin's finches, together with a phylogeny.

Format

The object `geospiza` is a list containing:

- `phy`, a phylogenetic tree of class 'phylo' (see [read.tree](#))
- `dat`, a data frame containing data on various morphological measurements.

Author(s)

Aaron A. King, Emmanuel Paradis, Daniel Lawson

Source

Data obtained from the **geiger** package, version 2.0.7.1. It is attributed there to D. Schluter, with no other details given.

See Also

Other examples: [anolis.ssd](#), [bimac](#), [ouch-package](#)

Examples

```
### Darwin's finches.
## Save time for CRAN
### The data were taken from package 'geiger' due to the latter being orphaned.
if (requireNamespace("ape")) {

  data(geospiza)
  plot(geospiza$phy)
  print(geospiza$dat)

  ### make an ouchtree out of the phy-format tree
  ot <- ape2ouch(geospiza$phy)

  ### merge data with tree info
  otd <- as(ot,"data.frame")
  otd <- merge(otd,geospiza$dat,by.x="labels",by.y="row.names",all=TRUE)
  ### row-names are used by 'hansen'
```

```

rownames(otd) <- otd$nodes
print(otd)
### this data-frame now contains the data as well as the tree geometry

### now remake the ouch tree
ot <- with(otd, ouchtree(nodes=nodes,ancestors=ancestors,times=times,labels=labels))
plot(ot)

b1 <- brown(tree=ot,data=otd[c("tarsusL","beakD")])
summary(b1)

### evaluate an OU model with a single, global selective regime
otd$regimes <- as.factor("global")
h1 <- hansen(
  tree=ot,
  data=otd[c("tarsusL","beakD")],
  regimes=otd["regimes"],
  sqrt.alpha=c(1,0,1),
  sigma=c(1,0,1),
  maxit=10000
)
summary(h1)
plot(h1)
}

```

hansen

Ornstein-Uhlenbeck models of trait evolution

Description

The function `hansen` fits an Ornstein-Uhlenbeck model to data. The fitting is done using `optim` or `subplex`.

Usage

```

hansen(
  data,
  tree,
  regimes,
  sqrt.alpha,
  sigma,
  fit = TRUE,
  method = c("Nelder-Mead", "subplex", "BFGS", "L-BFGS-B"),
  hessian = FALSE,
  ...
)

```

Arguments

data	Phenotypic data for extant species, i.e., species at the terminal twigs of the phylogenetic tree. This can either be a single named numeric vector, a list of nchar named vectors, or a data frame containing nchar data variables. There must be an entry per variable for every node in the tree; use NA to represent missing data. If the data are supplied as one or more named vectors, the names attributes are taken to correspond to the node names specified when the ouchtree was constructed (see ouchtree). If the data are supplied as a data-frame, the rownames serve that purpose.
tree	A phylogenetic tree, specified as an ouchtree object.
regimes	A vector of codes, one for each node in the tree, specifying the selective regimes hypothesized to have been operative. Corresponding to each node, enter the code of the regime hypothesized for the branch segment terminating in that node. For the root node, because it has no branch segment terminating on it, the regime specification is irrelevant. If there are nchar quantitative characters, then one can specify a single set of regimes for all characters or a list of nchar regime specifications, one for each character.
sqrt.alpha, sigma	These are used to initialize the optimization algorithm. The selection strength matrix α and the random drift variance-covariance matrix σ^2 are parameterized by their matrix square roots. Specifically, these initial guesses are each packed into lower-triangular matrices (column by column). The product of this matrix with its transpose is the α or σ^2 matrix. See Details for more information.
fit	If fit=TRUE, then the likelihood will be maximized. If fit=FALSE, the likelihood will be evaluated at the specified values of sqrt.alpha and sigma; the optima theta will be returned as well.
method	The method to be used by the optimization algorithm. See subplex::subplex and stats::optim for information on the available options.
hessian	If hessian=TRUE, then the Hessian matrix will be computed by optim.
...	Additional arguments will be passed as control options to optim or subplex. See stats::optim() and subplex::subplex() for information on the available options.

Details

The Hansen model for the evolution of a multivariate trait X along a lineage can be written as a stochastic differential equation (Ito diffusion)

$$dX = \alpha(\theta(t) - X(t))dt + \sigma dB(t),$$

where t is time along the lineage, $\theta(t)$ is the optimum trait value, $B(t)$ is a standard Wiener process (Brownian motion), and α and σ are matrices quantifying, respectively, the strength of selection and random drift. Without loss of generality, one can assume σ is lower-triangular. This is because only the infinitesimal variance-covariance matrix $\sigma^2 = \sigma\sigma^T$ is identifiable, and for any admissible variance-covariance matrix, we can choose σ to be lower-triangular. Moreover, if we view the basic model as describing evolution on a fitness landscape, then α will be symmetric. If we further

restrict ourselves to the case of stabilizing selection, α will be positive definite as well. We make these assumptions and therefore can assume that the matrix α has a lower-triangular square root.

The hansen code uses unconstrained numerical optimization to maximize the likelihood. To do this, it parameterizes the α and σ^2 matrices in a special way: each matrix is parameterized by $nchar*(nchar+1)/2$ parameters, where nchar is the number of quantitative characters. Specifically, the parameters initialized by the `sqrt.alpha` argument of hansen are used to fill the nonzero entries of a lower-triangular matrix (in column-major order), which is then multiplied by its transpose to give the selection-strength matrix. The parameters specified in `sigma` fill the nonzero entries in the lower triangular σ matrix. When hansen is executed, the numerical optimizer maximizes the likelihood over these parameters.

Value

hansen returns an object of class `hansentree`.

Author(s)

Aaron A. King

References

T.F. Hansen. 1997. Stabilizing selection and the comparative analysis of adaptation. *Evolution*, 51:1341–1351. doi:[10.1111/j.15585646.1997.tb01457.x](https://doi.org/10.1111/j.15585646.1997.tb01457.x).

Butler, M.A. and A.A. King. 2004. Phylogenetic comparative analysis: a modeling approach for adaptive evolution. *American Naturalist* 164:683–695. doi:[10.1086/426002](https://doi.org/10.1086/426002).

Cressler, C. E., Butler, M. A., and King, A. A. 2015. Detecting adaptive evolution in phylogenetic comparative analysis using the Ornstein-Uhlenbeck model. *Systematic Biology*, 64:953–968. doi:[10.1093/sysbio/syv043](https://doi.org/10.1093/sysbio/syv043).

See Also

[stats::optim](#), [subplex::subplex](#), [bimac](#), [anolis.ssd](#)

Other phylogenetic comparative models: [brown\(\)](#), [ouch-package](#), [ouchtree](#), [paint\(\)](#)

Examples

```
## Analysis of sexual size dimorphism data
## Save time for CRAN
tree <- with(anolis.ssd, ouchtree(node, ancestor, time/max(time), species))
plot(tree, node.names=TRUE)

h1 <- brown(anolis.ssd['log.SSD'], tree)
h1
plot(h1)

h2 <- hansen(anolis.ssd['log.SSD'], tree, anolis.ssd['OU.1'], sqrt.alpha=1, sigma=1)
h2
plot(h2)
```

```

h3 <- hansen(anolis.ssd['log.SSD'],tree,anolis.ssd['OU.7'],sqrt.alpha=1,sigma=1)
h3
plot(h3)

### Darwin's finches.
## Save time for CRAN
### The data were taken from package 'geiger' due to the latter being orphaned.
if (requireNamespace("ape")) {

  data(geospiza)
  plot(geospiza$phy)
  print(geospiza$dat)

  ### make an ouchtree out of the phy-format tree
  ot <- ape2ouch(geospiza$phy)

  ### merge data with tree info
  otd <- as(ot,"data.frame")
  otd <- merge(otd,geospiza$dat,by.x="labels",by.y="row.names",all=TRUE)
  ### row-names are used by 'hansen'
  rownames(otd) <- otd$nodes
  print(otd)
  ### this data-frame now contains the data as well as the tree geometry

  ### now remake the ouch tree
  ot <- with(otd,ouchtree(nodes=nodes,ancestors=ancestors,times=times,labels=labels))
  plot(ot)

  b1 <- brown(tree=ot,data=otd[c("tarsusL","beakD")])
  summary(b1)

  ### evaluate an OU model with a single, global selective regime
  otd$regimes <- as.factor("global")
  h1 <- hansen(
    tree=ot,
    data=otd[c("tarsusL","beakD")],
    regimes=otd["regimes"],
    sqrt.alpha=c(1,0,1),
    sigma=c(1,0,1),
    maxit=10000
  )
  summary(h1)
  plot(h1)
}

```

Description

logLik extracts the log likelihood from a fitted model object.

Usage

```
## S4 method for signature 'hansentree'
logLik(object)

## S4 method for signature 'browntree'
logLik(object)
```

Arguments

object any object from which a log-likelihood value, or a contribution to a log-likelihood value, can be extracted.

Value

logLik returns a numeric value.

See Also

Other methods for ouch trees: [as_data_frame](#), [bootstrap\(\)](#), [coef\(\)](#), [ouch-package](#), [paint\(\)](#), [plot\(\)](#), [print\(\)](#), [simulate\(\)](#), [summary\(\)](#), [update\(\)](#)

ouchtree	<i>Phylogenetic tree object in ouch format</i>
----------	---

Description

ouchtree constructs a representation of a phylogenetic tree.

ape2ouch translates **ape**'s phylo representation of a phylogenetic tree into **ouch**'s ouchtree representation. Optionally, the user can adjust the branch lengths while preserving the topology.

Usage

```
ouchtree(nodes, ancestors, times, labels = as.character(nodes))

ape2ouch(tree, scale = TRUE, branch.lengths = tree$edge.length)
```

Arguments

nodes A character vector giving the name of each node. These are used internally and must be unique.

ancestors	Specification of the topology of the phylogenetic tree. This is in the form of a character vector specifying the name (as given in the nodes argument) of the immediate ancestor of each node. In particular, the <i>i</i> -th name is that of the ancestor of the <i>i</i> -th node. The root node is distinguished by having no ancestor (i.e., NA).
times	A vector of nonnegative numbers, one per node in the tree, specifying the time at which each node is located. Time should be increasing from the root node to the terminal twigs.
labels	Optional vector of node labels. These will be used in plots to label nodes. It is not necessary that these be unique.
tree	a tree of class <code>ape::phylo</code> .
scale	optional. If <code>scale=TRUE</code> , the tree's depth will be scaled to 1. If <code>scale</code> is a number, then the branch lengths will be scaled by this number.
branch.lengths	optional vector of branch lengths.

Details

`ouchtree()` creates an `ouchtree` object given information on the phylogeny's topology and node times. An `ouchtree` object also (optionally) holds names of taxa for display purposes.

Author(s)

Aaron A. King

A. A. King, D. Ackerly

See Also

Other phylogenetic comparative models: `brown()`, `hansen()`, `ouch-package`, `paint()`

Examples

```
tree <- with(
  bimac,
  ouchtree(nodes=node,ancestors=ancestor,times=time,labels=spcode)
)
tree

plot(tree)
plot(tree, node.names=TRUE) # display node names
```

paint	<i>Painting regimes on a phylogenetic tree</i>
-------	--

Description

Function to paint selective regimes on a phylogenetic tree.

Usage

```
paint(tree, subtree, branch, which = 1)
```

Arguments

tree	An object of class ouchtree .
subtree	An optional named vector specifying the root nodes of subtrees. Each branch that descends from this node will be painted with the specified regime.
branch	An optional named vector specifying the end nodes of branches. The unique branch that terminates at the named node will be painted with the specified regime.
which	integer; if tree is a hansentree , start not with a blank canvas but with the regime specifications tree contains for the character indicated by which.

Details

The names of subtree and branch must be the names of nodes of tree. The painting proceeds in a particular order: one can overpaint a branch. The subtrees indicated by the elements of subtree are painted first, in order. Then the branches indicated by branch are painted. If tree is of class [hansentree](#), then paint begins with the regimes specified in the regimes slot of tree. Otherwise, paint begins with a blank canvas, i.e., a tree painted with the single regime "nonspec". Note that, if tree is a multivariate hansentree, then there are multiple regime specifications contained in tree. In this case, the argument which lets you pick which one you wish to begin with; by default, the first is used.

Value

A vector of class 'factor' with names corresponding to the nodes in tree, specifying selective regimes.

Author(s)

Aaron A. King

See Also

Other methods for ouch trees: [as_data_frame](#), [bootstrap\(\)](#), [coef\(\)](#), [logLik](#), [ouch-package](#), [plot\(\)](#), [print\(\)](#), [simulate\(\)](#), [summary\(\)](#), [update\(\)](#)

Other phylogenetic comparative models: [brown\(\)](#), [hansen\(\)](#), [ouch-package](#), [ouchtree](#)

Examples

```

x <- with(
  bimac,
  ouchtree(nodes=node, times=time/max(time), ancestors=ancestor, labels=species)
)

r <- paint(x, subtree=c("1"="medium", "9"="large", "2"="small"),
  branch=c("38"="large", "2"="medium"))
plot(x, regimes=r, node.names=TRUE)

## compare to bimac['OU.LP']
h5 <- hansen(data=log(bimac['size']), tree=x, regimes=bimac['OU.LP'],
  sqrt.alpha=1, sigma=1, reltol=1e-5)
r <- paint(h5, branch=c("18"="large"), subtree=c("9"="small"))
plot(x, regimes=r, node.names=TRUE)

```

plot

ouch *plotting functions*

Description

Plot phylogenetic trees, with or without regime paintings.

Usage

```

## S4 method for signature 'ouchtree'
plot(
  x,
  ...,
  regimes = NULL,
  ladderize = TRUE,
  node.names = FALSE,
  legend = !is.null(regimes),
  labels,
  frame.plot = FALSE,
  palette = rainbow,
  margin = 0.1,
  text_opts = list(),
  legend_opts = list()
)

## S4 method for signature 'hansentree'
plot(x, ..., regimes, legend = TRUE)

```

Arguments

x	object to plot.
...	additional arguments, passed to plot .
regimes	factor or character; a vector of regime paintings.
ladderize	logical; should the tree be ladderized?
node.names	logical; should node names be displayed?
legend	logical; display a legend?
labels	character; taxon labels.
frame.plot	a logical indicating whether a box should be drawn around the plot.
palette	function or character; specifies the colors to be used for the several regimes on the tree. Specified as a function, when given an integer, n, the function should create a vector of n colors. See, for example rainbow . One can also specify the n colors as a vector of color codes. There must be at least as many colors as levels in the regimes.
margin	numeric; width of the right margin (as a fraction of the plot width). Adjust this if labels are clipped (see Examples below). One can also adjust the width of the left margin (for example to aid in the formatting of the figure legend). To do this, furnish <code>margin=c(L, R)</code> , where L and R are the widths of the right and left margins, respectively, as fractions of the plot width. Obviously, in this case, we must have $L+R < 1$.
text_opts	options for the labels; passed to text .
legend_opts	options for the the legend; passed to legend .

See Also

Other methods for ouch trees: [as_data_frame](#), [bootstrap\(\)](#), [coef\(\)](#), [logLik](#), [ouch-package](#), [paint\(\)](#), [print\(\)](#), [simulate\(\)](#), [summary\(\)](#), [update\(\)](#)

Examples

```
tree <- with(
  bimac,
  ouchtree(nodes=node,ancestors=ancestor,times=time,labels=spcode)
)

plot(tree)
plot(tree, node.names=TRUE) # display node names

## When taxon names are long, they are cut off when the
## default settings are used. For example:
tree2 <- with(
  bimac,
  ouchtree(nodes=node,ancestors=ancestor,times=time,
    labels=ifelse(is.na(species),NA,paste(species,island,sep=",")))
)
)
```

```
plot(tree2) # long species names are cut off
## This is fixed by increasing right margin and font size:
plot(tree2,margin=0.35,text_opts=list(cex=0.7))
```

simulate

Simulations of a phylogenetic trait model

Description

simulate generates random deviates from a fitted model.

Usage

```
## S4 method for signature 'hansentree'
simulate(object, nsim = 1, seed = NULL, ...)
```

```
## S4 method for signature 'browntree'
simulate(object, nsim = 1, seed = NULL, ...)
```

Arguments

object	fitted model object
nsim	integer; number of independent simulations.
seed	integer; if non-NULL, the RNG will be initialized with this seed for the simulations. The RNG will be reset to its pre-existing state when simulate returns.
...	additional arguments, ignored.

Value

simulate returns a list of data-frames, each comparable to the original data.

See Also

Other methods for ouch trees: [as_data_frame](#), [bootstrap\(\)](#), [coef\(\)](#), [logLik](#), [ouch-package](#), [paint\(\)](#), [plot\(\)](#), [print\(\)](#), [summary\(\)](#), [update\(\)](#)

summary	<i>Summary methods</i>
---------	------------------------

Description

Summary methods

Usage

```
## S4 method for signature 'hansentree'
summary(object, ...)

## S4 method for signature 'browntree'
summary(object, ...)
```

Arguments

object	fitted model object.
...	additional arguments, ignored.

Value

summary applied to a hansentree method displays the estimated α and σ^2 matrices as well as various quantities describing the goodness of model fit.

summary applied to a browntree object returns information about the fitted model, including parameter estimates and quantities describing the goodness of fit.

See Also

Other methods for ouch trees: [as_data_frame](#), [bootstrap\(\)](#), [coef\(\)](#), [logLik](#), [ouch-package](#), [paint\(\)](#), [plot\(\)](#), [print\(\)](#), [simulate\(\)](#), [update\(\)](#)

update	<i>Update and refit an ouch model</i>
--------	---------------------------------------

Description

update will update a model and re-fit. This allows one to change the data and/or parameters.

Usage

```
## S4 method for signature 'hansentree'
update(object, data, regimes, sqrt.alpha, sigma, ...)

## S4 method for signature 'browntree'
update(object, data, ...)
```

Arguments

<code>object</code>	fitted model object.
<code>data</code>	data that replace those used in the original fit.
<code>regimes</code>	A vector of codes, one for each node in the tree, specifying the selective regimes hypothesized to have been operative. Corresponding to each node, enter the code of the regime hypothesized for the branch segment terminating in that node. For the root node, because it has no branch segment terminating on it, the regime specification is irrelevant. If there are <code>nchar</code> quantitative characters, then one can specify a single set of regimes for all characters or a list of <code>nchar</code> regime specifications, one for each character.
<code>sqrt.alpha, sigma</code>	These are used to initialize the optimization algorithm. The selection strength matrix α and the random drift variance-covariance matrix σ^2 are parameterized by their matrix square roots. Specifically, these initial guesses are each packed into lower-triangular matrices (column by column). The product of this matrix with its transpose is the α or σ^2 matrix. See Details for more information.
<code>...</code>	Additional arguments replace the corresponding arguments in the original call.

Value

`update` returns a new fitted-model object of the same class as `object`.

See Also

Other methods for ouch trees: [as_data_frame](#), [bootstrap\(\)](#), [coef\(\)](#), [logLik](#), [ouch-package](#), [paint\(\)](#), [plot\(\)](#), [print\(\)](#), [simulate\(\)](#), [summary\(\)](#)

Index

- * **examples**
 - [anolis.ssd](#), [3](#)
 - [bimac](#), [6](#)
 - [geospiza](#), [12](#)
 - [ouch-package](#), [2](#)
 - * **methods for ouch trees**
 - [as_data_frame](#), [5](#)
 - [bootstrap](#), [8](#)
 - [coef](#), [11](#)
 - [logLik](#), [16](#)
 - [ouch-package](#), [2](#)
 - [paint](#), [19](#)
 - [plot](#), [20](#)
 - [simulate](#), [22](#)
 - [summary](#), [23](#)
 - [update](#), [23](#)
 - * **models**
 - [anolis.ssd](#), [3](#)
 - [bimac](#), [6](#)
 - [brown](#), [9](#)
 - [geospiza](#), [12](#)
 - [hansen](#), [13](#)
 - [ouch-package](#), [2](#)
 - [ouchtree](#), [17](#)
 - [paint](#), [19](#)
 - * **phylogenetic comparative models**
 - [brown](#), [9](#)
 - [hansen](#), [13](#)
 - [ouch-package](#), [2](#)
 - [ouchtree](#), [17](#)
 - [paint](#), [19](#)
- [anolis.ssd](#), [3](#), [3](#), [7](#), [10](#), [12](#), [15](#)
[ape2ouch \(ouchtree\)](#), [17](#)
[ape2ouch\(\)](#), [2](#)
[ape::phylo](#), [18](#)
[as.data.frame.browntree \(as_data_frame\)](#), [5](#)
[as.data.frame.hansentree \(as_data_frame\)](#), [5](#)
[as.data.frame.ouchtree \(as_data_frame\)](#), [5](#)
[as_data_frame](#), [3](#), [5](#), [8](#), [12](#), [17](#), [19](#), [21–24](#)
[bimac](#), [3](#), [4](#), [6](#), [10](#), [12](#), [15](#)
[bootstrap](#), [3](#), [5](#), [8](#), [12](#), [17](#), [19](#), [21–24](#)
[bootstrap, ANY-method \(bootstrap\)](#), [8](#)
[bootstrap, browntree-method \(bootstrap\)](#), [8](#)
[bootstrap, hansentree-method \(bootstrap\)](#), [8](#)
[bootstrap, missing-method \(bootstrap\)](#), [8](#)
[brown](#), [3](#), [9](#), [15](#), [18](#), [19](#)
[brown\(\)](#), [2](#)
[browntree-class \(brown\)](#), [9](#)
[coef](#), [3](#), [5](#), [8](#), [11](#), [17](#), [19](#), [21–24](#)
[coef\(\)](#), [3](#)
[coef, browntree-method \(coef\)](#), [11](#)
[coef, hansentree-method \(coef\)](#), [11](#)
[geospiza](#), [3](#), [4](#), [7](#), [12](#)
[hansen](#), [3](#), [10](#), [13](#), [18](#), [19](#)
[hansen\(\)](#), [2](#)
[hansentree](#), [19](#)
[hansentree-class \(hansen\)](#), [13](#)
[legend](#), [21](#)
[logLik](#), [3](#), [5](#), [8](#), [12](#), [16](#), [19](#), [21–24](#)
[logLik\(\)](#), [3](#)
[logLik, browntree-method \(logLik\)](#), [16](#)
[logLik, hansentree-method \(logLik\)](#), [16](#)
[ouch \(ouch-package\)](#), [2](#)
[ouch, package \(ouch-package\)](#), [2](#)
[ouch-package](#), [2](#)
[ouchtree](#), [3](#), [10](#), [14](#), [15](#), [17](#), [19](#)
[ouchtree\(\)](#), [2](#)
[ouchtree-class \(ouchtree\)](#), [17](#)

paint, [3](#), [5](#), [8](#), [10](#), [12](#), [15](#), [17](#), [18](#), [19](#), [21–24](#)
paint(), [2](#), [6](#)
plot, [3](#), [5](#), [8](#), [12](#), [17](#), [19](#), [20](#), [21–24](#)
plot(), [3](#)
plot, hansentree-method (plot), [20](#)
plot, ouchtree-method (plot), [20](#)
print, [3](#), [5](#), [8](#), [12](#), [17](#), [19](#), [21–24](#)

rainbow, [21](#)
read.tree, [12](#)

simulate, [3](#), [5](#), [8](#), [12](#), [17](#), [19](#), [21](#), [22](#), [23](#), [24](#)
simulate(), [2](#)
simulate, browntree-method (simulate), [22](#)
simulate, hansentree-method (simulate),
[22](#)
stats::optim, [14](#), [15](#)
stats::optim(), [14](#)
subplex::subplex, [14](#), [15](#)
subplex::subplex(), [14](#)
summary, [3](#), [5](#), [8](#), [12](#), [17](#), [19](#), [21](#), [22](#), [23](#), [24](#)
summary(), [3](#)
summary, browntree-method (summary), [23](#)
summary, hansentree-method (summary), [23](#)

text, [21](#)

update, [3](#), [5](#), [8](#), [12](#), [17](#), [19](#), [21–23](#), [23](#)
update, browntree-method (update), [23](#)
update, hansentree-method (update), [23](#)