

Package ‘quadkeyr’

May 9, 2026

Title Generate Raster Images from QuadKey-Identified Datasets

Version 0.1.0

Description A set of functions of increasing complexity allows users to
(1) convert QuadKey-identified datasets,
based on 'Microsoft's Bing Maps Tile System', into Simple Features data frames,
(2) transform Simple Features data frames into rasters, and
(3) process multiple 'Meta' ('Facebook') QuadKey-identified human mobility files
directly into raster files.
For more details, see D’Andrea et al. (2024) <[doi:10.21105/joss.06500](https://doi.org/10.21105/joss.06500)>.

License MIT + file LICENSE

URL <https://docs.ropensci.org/quadkeyr/>,
<https://github.com/ropensci/quadkeyr>

BugReports <https://github.com/ropensci/quadkeyr/issues>

Encoding UTF-8

RoxygenNote 7.3.2

Suggests bslib (>= 0.6.1), DT (>= 0.31), ggplot2 (>= 3.4.4), knitr,
leaflet (>= 2.2.1), magick (>= 2.8.5), rmarkdown, rnatualearth
(>= 1.0.0), shinytest2 (>= 0.3.2), testthat (>= 3.1.10), tidyr
(>= 1.3.0), viridis (>= 0.6.4), withr

VignetteBuilder knitr

Depends R (>= 4.1.0)

LazyData true

Imports dplyr (>= 1.1.2), lubridate (>= 1.9.2), purrr (>= 1.0.1),
readr (>= 2.1.4), rlang (>= 1.1.2), sf (>= 1.0.14), shiny (>= 1.7.4), stars (>= 0.6.2)

NeedsCompilation no

Author Florencia D’Andrea [aut, cre] (ORCID:
<<https://orcid.org/0000-0002-0041-097X>>),
Pilar Fernandez [aut] (ORCID: <<https://orcid.org/0000-0001-8645-2267>>),
Maria Paula Caldas [rev] (ORCID:
<<https://orcid.org/0000-0002-1938-6471>>, Maria Paula Caldas

reviewed the package (v. 0.0.0.9000) for rOpenSci, see <https://github.com/ropensci/software-review/issues/619>,
 Vincent van Hees [rev] (ORCID: <<https://orcid.org/0000-0003-0182-9008>>),
 Vincent van Hees reviewed the package (v. 0.0.0.9000) for rOpenSci,
 see <https://github.com/ropensci/software-review/issues/619>,
 Andrew Pulsipher [ctb] (ORCID: <<https://orcid.org/0000-0002-0773-3210>>),
 CDC's Center for Forecasting and Outbreak Analytics [fnd] (This project
 was made possible by cooperative agreement CDC-RFA-FT-23-0069
 (grant # NU38FT000009-01-00) from the CDC's Center for Forecasting
 and Outbreak Analytics. Its contents are solely the responsibility
 of the authors and do not necessarily represent the official views
 of the Centers for Disease Control and Prevention.),
 MIDAS-NIH COVID-19 urgent grant program [fnd],
 Paul G. Allen School for Global Health, Washington State University
 [cph]

Maintainer Florencia D'Andrea <florencia.dandrea@gmail.com>

Repository CRAN

Date/Publication 2025-03-24 15:00:02 UTC

Contents

add_regular_polygon_grid	3
apply_weekly_lag	4
create_qk_grid	5
create_stars_raster	6
format_fb_data	7
get_qk_coord	8
get_regular_polygon_grid	9
grid_to_polygon	10
ground_res	11
latlong_to_pixelXY	11
latlong_to_quadkey	12
mapscale	13
mapsize	14
missing_combinations	15
pixelXY_to_latlong	16
pixelXY_to_tileXY	17
polygon_to_raster	18
qkmap_app	19
quadkey_df_to_polygon	20
quadkey_to_latlong	21
quadkey_to_polygon	22
quadkey_to_tileXY	23
read_fb_mobility_files	24
regular_qk_grid	25
tileXY_to_pixelXY	26
tileXY_to_quadkey	27

`add_regular_polygon_grid`

Add the rows needed to complete a regular QuadKey polygon grid derived from the bounding box of the quadkey column of a data.frame.

Description

This function estimates the bounding box of the quadkeys given in the quadkey column and adds rows to complete the quadkeys and the geometry needed to create a regular grid. All other columns for the introduced QuadKeys will be filled with NAs.

For a detailed explanation on how to use this and other similar quadkeyr functions, read the the vignette: https://docs.ropensci.org/quadkeyr/articles/quadkey_identified_data_to_raster.html

Usage

```
add_regular_polygon_grid(data)
```

Arguments

`data` A data.frame with a quadkey column.

Value

A list with three elements:

- `data` A sf POLYGON data.frame with all the QuadKeys within the bounding box of the ones provided in the quadkey column of the input dataset, and the rest of the original variables. The columns `quadkey` and `geometry` are returned for all the grid, The values of the newly added QuadKeys will be NA for the rest of the variables.
- `num_rows` The number of columns of the regular grid.
- `num_cols` The number of rows of the regular grid.

Examples

```
# Read the file with the data
path <- paste0(
  system.file("extdata", package = "quadkeyr"),
  "/cityA_2020_04_15_0000.csv"
)
data <- read.csv(path)
data <- format_fb_data(data)

add_regular_polygon_grid(data = data)
```

apply_weekly_lag	<i>Apply a 7 day lag to the variable n_crisis</i>
------------------	---------------------------------------------------

Description

Applying a week lag to the data will create raster images showing the mobility a week before the date of interest. This function works only for QuadKeys reported without NAs for `n_crisis` and `percent_change` variables .

Usage

```
apply_weekly_lag(data)
```

Arguments

`data` A data.frame with the columns `quadkey`, `day`, `hour` and `n_crisis`.

Value

A data.frame with the extra columns `n_crisis_lag_7` and `percent_change_7`.

- `n_crisis_lag_7`, is the same variable defined as `n_crisis` in the Facebook mobility data.frame with a 7 day lag applied.
- `percent_change_7` is the difference between the `n_crisis` value between weeks expressed as percentage.

Examples

```
files <- read_fb_mobility_files(  
  path_to_csvs = paste0(system.file("extdata",  
    package = "quadkeyr"  
  ), "/"),  
  colnames = c(  
    "lat",  
    "lon",  
    "quadkey",  
    "date_time",  
    "n_crisis",  
    "percent_change"  
  ),  
  coltypes = list(  
    lat = "d",  
    lon = "d",  
    quadkey = "c",  
    date_time = "T",  
    n_crisis = "c",  
    percent_change = "c"  
  )  
)
```

```
apply_weekly_lag(data = files)
```

create_qk_grid	<i>Create grid of QuadKeys for a particular zoom or level of detail.</i>
----------------	--------------------------------------------------------------------------

Description

Generates a grid comprising all the QuadKeys within the area defined by the maximum and minimum coordinates of latitude and longitude along with a specified zoom level.

Usage

```
create_qk_grid(xmin, xmax, ymin, ymax, zoom)
```

Arguments

xmin	Minimum value in the x axis (longitude)
xmax	Maximum value in the y axis (latitude)
ymin	Minimum value in the x axis (longitude)
ymax	Maximum value in the Y axis (latitude)
zoom	Zoom or level of detail, from 1 (lowest detail) to 23 (highest detail).

Value

A list returning the QuadKeys as a data.frame (data), the number of rows (num_rows) and columns (num_cols) of the grid.

Examples

```
grid <- create_qk_grid(  
  xmin = -59,  
  xmax = -57,  
  ymin = -35,  
  ymax = -34,  
  zoom = 12  
)
```

create_stars_raster *Create a stars raster*

Description

The use of a template enables the creation of an accurate raster, even in the presence of NAs.

Usage

```
create_stars_raster(template, nx, ny, data, var)
```

Arguments

template	A sf POLYGON data.frame to use as template. Check stars::st_as_stars() documentation for more details.
nx	Integer; number of cells in x direction.
ny	Integer; number of cells in y direction.
data	A sf POLYGON data.frame with the variable we want to represent in the raster.
var	The column name of the variable to plot.

Value

A stars object.

See Also

[st_as_stars](#), [st_rasterize](#)

Examples

```
# Basic workflow
# Read the data
path <- paste0(
  system.file("extdata", package = "quadkeyr"),
  "/cityA_2020_04_15_0000.csv"
)
data <- read.csv(path)
data <- format_fb_data(data)

complete_polygon_grid <- add_regular_polygon_grid(data = data)

stars_object <- create_stars_raster(
  data = complete_polygon_grid$data,
  template = complete_polygon_grid$data,
  var = "percent_change",
  nx = complete_polygon_grid$num_cols,
  ny = complete_polygon_grid$num_rows
)
```

```
stars_object

# Other workflow
grid <- create_qk_grid(
  xmin = -59,
  xmax = -57,
  ymin = -35,
  ymax = -34,
  zoom = 12
)

grid_coords <- get_qk_coord(data = grid$data)

polygrid <- grid_to_polygon(grid_coords)

data("data_provided")
data_raster <- polygrid |>
  dplyr::inner_join(data_provided,
    by = c("quadkey")
  )

raster <- create_stars_raster(
  template = data_raster,
  nx = grid$num_cols,
  ny = grid$num_rows,
  data = data_raster,
  var = "variable"
)
```

format_fb_data

Format the Facebook mobility data

Description

This function removes unnecessary characters such as `\\N` and ensures that the format of the date and QuadKeys is correct.

Usage

```
format_fb_data(data, keep_format = NULL)
```

Arguments

data	A data.frame with a quadkey and date_time columns and other variables
keep_format	Vector of column names, besides date_time, day and quadkey, that you don't want to convert to a number.

Value

A data.frame without \N, quadkey without scientific notation and a new column day and hour

See Also

[read_fb_mobility_files](#)

Examples

```
data(result_read_fb_mobility_data)
format_fb_data(data = result_read_fb_mobility_data)
```

get_qk_coord

Get lat/long coordinates from the QuadKey

Description

Reads the QuadKey as a string and extracts the lat/long coordinates of the upper-left corner of the QuadKey.

Usage

```
get_qk_coord(data)
```

Arguments

data A dataframe with a quadkey column.

Value

A sf POINT data.frame containing the tiles XY coordinates (tileX, tileY), the QuadKeys (quadkey), and a geometry column.

See Also

[quadkey_to_tileXY](#)

[tileXY_to_pixelXY](#)

[pixelXY_to_latlong](#)

Examples

```
grid <- create_qk_grid(  
  xmin = -59,  
  xmax = -40,  
  ymin = -38,  
  ymax = -20,  
  zoom = 6  
)  
  
# quadkey column in grid$data converted to geographic coordinates  
grid_coords <- get_qk_coord(data = grid$data)  
  
plot(grid_coords)
```

get_regular_polygon_grid

Get regular QuadKey polygon grid derived from the bounding box of the quadkey column of a data.frame.

Description

This function estimates the bounding box of the QuadKeys given in the quadkey column and adds the rows needed to complete a regular grid.

For a detailed explanation on how to use this and other similar quadkeyr functions, read the the vignette: https://docs.ropensci.org/quadkeyr/articles/facebook_mobility_csvs_to_raster_files.html

Usage

```
get_regular_polygon_grid(data)
```

Arguments

data A data.frame with a quadkey column.

Value

A list with three elements:

- data An sf POLYGON data.frame with all the QuadKeys within the bounding box of the quadkey column of a data.frame. Only the columns quadkey, tileX, tileY and geometry are returned.
- num_rows The number of columns of the regular grid.
- num_cols The number of rows of the regular grid.

Examples

```
# Data File
path <- paste0(
  system.file("extdata", package = "quadkeyr"),
  "/cityA_2020_04_15_0000.csv"
)
data <- read.csv(path)
data <- format_fb_data(data)

get_regular_polygon_grid(data = data)
```

grid_to_polygon

Convert a grid of QuadKeys to square polygons

Description

The main argument of this function, the grid of geographic coordinates (lat/long WG84) represents the upper-left corner of the QuadKey. To transform these coordinates into square polygons, the function supplements the grid by adding a row and column of tiles. These points introduce QuadKeys located at the border of the area using the internal function `complete_grid_for_polygons()`. The function builds the polygons using all the points of the grid. Note that it's possible to associate each QuadKey with its square polygon.

Usage

```
grid_to_polygon(data)
```

Arguments

`data` A sf POINT data.frame with a quadkey and geometry column.

Value

A sf POLYGON data.frame with a quadkey column.

Examples

```
grid <- create_qk_grid(
  xmin = -59,
  xmax = -57,
  ymin = -35,
  ymax = -34,
  zoom = 11
)

grid_coords <- get_qk_coord(data = grid$data)

polygrid <- grid_to_polygon(grid_coords)
polygrid
```

ground_res	<i>Ground resolution at a specified latitude and zoom level</i>
------------	-----------------------------------------------------------------

Description

Determines the ground resolution (in meters per pixel) at a specified latitude and zoom level. For further information, refer to the Microsoft Bing Maps Tile System documentation.

Usage

```
ground_res(latitude, zoom)
```

Arguments

latitude	Latitude (in degrees) at which to measure the ground resolution.
zoom	Zoom or level of detail, from 1 (lowest detail) to 23 (highest detail).

Value

the ground resolution (meters / pixel)

References

<https://learn.microsoft.com/en-us/bingmaps/articles/bing-maps-tile-system>

Examples

```
ground_res(  
    latitude = 0,  
    zoom = 6  
)
```

latlong_to_pixelXY	<i>Convert lat/long coordinates to pixel XY coordinates</i>
--------------------	-------------------------------------------------------------

Description

Converts a point from latitude/longitude WGS-84 coordinates (in degrees) into pixel XY coordinates at a specified zoom level. For further information, refer to the Microsoft Bing Maps Tile System documentation.

Usage

```
latlong_to_pixelXY(lat, lon, zoom)
```

Arguments

lat	Latitude of the point, in degrees.
lon	Longitude of the point, in degrees.
zoom	Zoom or level of detail, from 1 (lowest detail) to 23 (highest detail).

Details

Converting latitude/longitude coordinates into a QuadKey and then back to latitude/longitude won't yield identical values, unless the initial latitude/longitude coordinates correspond to the upper-left Quadkey's pixel and tile XY coordinates at the same zoom level.

Understanding this distinction is crucial for the accurate use of these functions in coordinate conversions.

For a detailed explanation on how to use this and other similar quadkeyr functions, read the the vignette: https://docs.ropensci.org/quadkeyr/articles/quadkey_to_sf_conversion.html

Value

A list returning pixel X and pixel Y coordinates.

References

<https://learn.microsoft.com/en-us/bingmaps/articles/bing-maps-tile-system>

Examples

```
latlong_to_pixelXY(  
  lat = -35,  
  lon = -50,  
  zoom = 6  
)
```

latlong_to_quadkey *Convert latitude/longitude coordinates into QuadKeys*

Description

Converts a point from latitude/longitude WGS-84 coordinates (in degrees) into a Quadkey at a specified zoom level. For further information, refer to the Microsoft Bing Maps Tile System documentation.

Usage

```
latlong_to_quadkey(lat, lon, zoom)
```

Arguments

lat	Latitude of the point, in degrees.
lon	Longitude of the point, in degrees.
zoom	Zoom or level of detail, from 1 (lowest detail) to 23 (highest detail).

Details

Converting latitude/longitude coordinates into a QuadKey and then back to latitude/longitude won't yield identical values, unless the initial latitude/longitude coordinates correspond to the upper-left Quadkey's pixel and tile XY coordinates at the same zoom level.

Understanding this distinction is crucial for the accurate use of these functions in coordinate conversions.

For a detailed explanation on how to use this and other similar quadkeyr functions, read the the vignette: https://docs.ropensci.org/quadkeyr/articles/quadkey_to_sf_conversion.html

Value

A dataframe with latitude (lat), longitude (lon), zoom level (zoom) and the QuadKey as a string (quadkey).

References

<https://learn.microsoft.com/en-us/bingmaps/articles/bing-maps-tile-system>

Examples

```
latlong_to_quadkey(
  lat = 35.63051,
  lon = 139.69116,
  zoom = 20
)
latlong_to_quadkey(
  lat = c(-4, -25.33, -25.66),
  lon = c(-53, -60.33, -70.66),
  zoom = 4
)
```

mapscale

Map scale (1 : N)

Description

Determines the map scale at a specified latitude, zoom level, and screen resolution. For further information, refer to the Microsoft Bing Maps Tile System documentation.

Usage

```
mapscale(latitude, zoom, screen_dpi)
```

Arguments

latitude	Latitude (in degrees) at which to measure the map scale.
zoom	Zoom or level of detail, from 1 (lowest detail) to 23 (highest detail).
screen_dpi	Resolution of the screen, in dots per inch.

Value

The map scale, expressed as the denominator N of the ratio 1 : N.

References

<https://learn.microsoft.com/en-us/bingmaps/articles/bing-maps-tile-system>

Examples

```
mapscale(  
    latitude = 0,  
    zoom = 6,  
    screen_dpi = 96  
)
```

mapsize	<i>Map size in pixels</i>
---------	---------------------------

Description

Determines the map width and height (in pixels) at a specified zoom level. For further information, refer to the Microsoft Bing Maps Tile System documentation.

Usage

```
mapsize(zoom)
```

Arguments

zoom	Zoom or level of detail, from 1 (lowest detail) to 23 (highest detail).
------	-------------------------------------------------------------------------

Value

The map width and height in pixels.

References

<https://learn.microsoft.com/en-us/bingmaps/articles/bing-maps-tile-system>

Examples

```
mapsize(zoom = 6)
```

missing_combinations *Detect dates and hours missing in filenames*

Description

Facebook mobility data is reported daily at 3 different hours (0, 8, 16). This function reads the data extracted from the current files and detects if any file for a particular day or hour is missing.

Usage

```
missing_combinations(data, hour_col = "hour", date_col = "day")
```

Arguments

data	A data.frame with one column for the raster's date and another for the hour. If not explicitly specified in the function's arguments, the column names are day and hour.
hour_col	The name of the column with the hour information.
date_col	The name of the column with the date information.

Value

A data.frame with the missing days and hours, if any.

Examples

```
# Sample dataset
data <- data.frame(
  country = c("US", "MX", "MX"),
  day = c("2023-01-01", "2023-01-03", "2023-01-05"),
  hour = c(0, 8, 16)
)

missing_combinations(data)
```

pixelXY_to_latlong *Convert pixel XY coordinates into lat/long coordinates.*

Description

Converts a pixel from pixel XY coordinates at a specified zoom level into latitude/longitude WGS-84 coordinates (in degrees). For further information, refer to the Microsoft Bing Maps Tile System documentation.

Usage

```
pixelXY_to_latlong(pixelX, pixelY, zoom)
```

Arguments

pixelX	X coordinate of the point, in pixels.
pixelY	Y coordinates of the point, in pixels.
zoom	Zoom or level of detail, from 1 (lowest detail) to 23 (highest detail).

Details

Converting latitude/longitude coordinates into a QuadKey and then back to latitude/longitude won't yield identical values, unless the initial latitude/longitude coordinates correspond to the upper-left QuadKey's pixel and tile XY coordinates at the same zoom level.

Understanding this distinction is crucial for the accurate use of these functions in coordinate conversions.

For a detailed explanation on how to use this and other similar quadkeyr functions, read the the vignette: https://docs.ropensci.org/quadkeyr/articles/quadkey_to_sf_conversion.html

Value

A list with the longitude and latitude.

References

<https://learn.microsoft.com/en-us/bingmaps/articles/bing-maps-tile-system>

Examples

```
pixelXY_to_latlong(  
  pixelX = 768,  
  pixelY = 1280,  
  zoom = 3  
)
```

pixelXY_to_tileXY *Convert pixel XY coordinates into tile XY coordinates*

Description

Converts pixel XY coordinates into tile XY coordinates of the tile containing the specified pixel. For further information, refer to the Microsoft Bing Maps Tile System documentation.

Usage

```
pixelXY_to_tileXY(pixelX, pixelY)
```

Arguments

pixelX	Pixel X coordinate.
pixelY	Pixel Y coordinate.

Details

Converting latitude/longitude coordinates into a QuadKey and then back to latitude/longitude won't yield identical values, unless the initial latitude/longitude coordinates correspond to the upper-left Quadkey's pixel and tile XY coordinates at the same zoom level.

Understanding this distinction is crucial for the accurate use of these functions in coordinate conversions.

For a detailed explanation on how to use this and other similar quadkeyr functions, read the the vignette: https://docs.ropensci.org/quadkeyr/articles/quadkey_to_sf_conversion.html

Value

A list returning the tile X and tile Y coordinates.

References

<https://learn.microsoft.com/en-us/bingmaps/articles/bing-maps-tile-system>

Examples

```
pixelXY_to_tileXY(  
  pixelX = 5916,  
  pixelY = 9894  
)
```

`polygon_to_raster` *Create and save raster images for different dates and times*

Description

Creates one raster by each date and time reported and saves it as a `.tif`.

Usage

```
polygon_to_raster(  
  data,  
  nx,  
  ny,  
  template,  
  var = "percent_change",  
  filename,  
  path  
)
```

Arguments

<code>data</code>	A sf POLYGON data.frame with the variable we want to represent in the raster.
<code>nx</code>	Integer; number of cells in x direction.
<code>ny</code>	Integer; number of cells in y direction.
<code>template</code>	A sf POLYGON data.frame
<code>var</code>	The column name of the variable to plot.
<code>filename</code>	Select a name for the file. The date and time will be included automatically in the name.
<code>path</code>	Path where the files should be stored.

Value

as many `.tif` files as dates and times in the dataset

See Also

[st_as_stars](#), [st_rasterize](#)
[missing_combinations](#)

Examples

```
files <- read_fb_mobility_files(  
  path_to_csvs = paste0(system.file("extdata",  
    package = "quadkeyr"  
  ), "/"),  
  colnames = c(  
    "time", "x", "y", "value"  
  )  
)
```

```

      "lat", "lon",
      "quadkey", "date_time",
      "n_crisis", "percent_change"
    ),
    coltypes = list(
      lat = "d",
      lon = "d",
      quadkey = "c",
      date_time = "T",
      n_crisis = "c",
      percent_change = "c"
    )
  )
)

# Get a regular grid and create the polygons
regular_grid <- get_regular_polygon_grid(data = files)

# Keep only the QuadKeys reported
files_polygons <- files |>
  dplyr::inner_join(regular_grid$data,
    by = c("quadkey")
  )

# Generate the raster files
polygon_to_raster(
  data = files_polygons,
  nx = regular_grid$num_cols,
  ny = regular_grid$num_rows,
  template = files_polygons,
  var = "percent_change",
  filename = "cityA",
  path = paste0(
    system.file("extdata",
      package = "quadkeyr"
    ),
    "/"
  )
)
)

```

qkmap_app

Launch the Shiny App

Description

This function launches the Shiny app.

Usage

```
qkmap_app()
```

Value

This function does not return any value. It launches the Shiny app.

Examples

```
if(interactive()){  
  qkmap_app()  
}
```

quadkey_df_to_polygon *Convert data.frame with quadkey column to a sf POLYGON data.frame*

Description

Convert data.frame with quadkey column to a sf POLYGON data.frame

Usage

```
quadkey_df_to_polygon(data)
```

Arguments

data A data.frame with a quadkey column

Value

The same original data.frame with a sf POLYGON data.frame with a geometry column.

See Also

[quadkey_df_to_polygon](#)

Examples

```
# Quadkey as string  
quadkey_to_polygon(quadkey = "213")  
  
# QuadKeys as column in a data.frame  
# get data file  
path <- paste0(  
  system.file("extdata", package = "quadkeyr"),  
  "/cityA_2020_04_15_0000.csv"  
)  
data <- read.csv(path)  
data <- format_fb_data(data)  
  
quadkey_df_to_polygon(data = data)
```

quadkey_to_latlong *Convert a string of Quadkey numbers to lat/long coordinates*

Description

This function converts Quadkeys to latitude/longitude WGS-84 coordinates (in degrees). For further information, refer to the Microsoft Bing Maps Tile System documentation.

Usage

```
quadkey_to_latlong(quadkey_data)
```

Arguments

quadkey_data A single QuadKey as a string or a vector with unique QuadKeys.

Details

Converting latitude/longitude coordinates into a QuadKey and then back to latitude/longitude won't yield identical values, unless the initial latitude/longitude coordinates correspond to the upper-left Quadkey's pixel and tile XY coordinates at the same zoom level.

Understanding this distinction is crucial for the accurate use of these functions in coordinate conversions.

For a detailed explanation on how to use this and other similar quadkeyr functions, read the the vignette: https://docs.ropensci.org/quadkeyr/articles/quadkey_to_sf_conversion.html

Value

A sf POINT data.frame with a quadkey column. The latitude/longitude coordinates represent the upper-left corner of the QuadKey.

References

<https://learn.microsoft.com/en-us/bingmaps/articles/bing-maps-tile-system>

See Also

[quadkey_to_tileXY](#)

[tileXY_to_pixelXY](#)

[pixelXY_to_latlong](#)

Examples

```
quadkey_to_latlong(quadkey_data = "213")
quadkey_to_latlong(quadkey_data = c("213", "212", "210"))
```

quadkey_to_polygon	<i>Convert a QuadKey into a square polygon</i>
--------------------	------------------------------------------------

Description

This function creates a sf POLYGON data.frame from a QuadKey string.

Usage

```
quadkey_to_polygon(quadkey)
```

Arguments

quadkey The QuadKey as a string

Value

A sf POLYGON data.frame with a quadkey and geometry column.

See Also

[quadkey_df_to_polygon](#)

Examples

```
# Quadkey as string
quadkey_to_polygon(quadkey = "213")

# QuadKeys as column in a data.frame
# get data file
path <- paste0(
  system.file("extdata", package = "quadkeyr"),
  "/cityA_2020_04_15_0000.csv"
)
data <- read.csv(path)
data <- format_fb_data(data)

quadkey_df_to_polygon(data = data)
```

quadkey_to_tileXY	<i>Convert a QuadKey into tile XY coordinates.</i>
-------------------	----------------------------------------------------

Description

For further information, refer to the Microsoft Bing Maps Tile System documentation.

Usage

```
quadkey_to_tileXY(quadkey)
```

Arguments

quadkey A QuadKey as a single string.

Details

Converting latitude/longitude coordinates into a QuadKey and then back to latitude/longitude won't yield identical values, unless the initial latitude/longitude coordinates correspond to the upper-left QuadKey's pixel and tile XY coordinates at the same zoom level.

Understanding this distinction is crucial for the accurate use of these functions in coordinate conversions.

For a detailed explanation on how to use this and other similar quadkeyr functions, read the the vignette: https://docs.ropensci.org/quadkeyr/articles/quadkey_to_sf_conversion.html

Value

A list returning the tile X, tile Y coordinates and the zoom level.

References

<https://learn.microsoft.com/en-us/bingmaps/articles/bing-maps-tile-system>

Examples

```
quadkey_to_tileXY(quadkey = "213")
```

`read_fb_mobility_files`*Read all the .csv files in a folder and format the data.*

Description

This function reads all the .csv files in a particular folder. These files consistently contain identical columns, with variations only in location, day, and time. As a result, we can uniformly apply specific formatting to columns across these files.

Usage

```
read_fb_mobility_files(path_to_csvs, colnames, coltypes, keep_format = NULL)
```

Arguments

<code>path_to_csvs</code>	Path to the folder where the .csv files are stored
<code>colnames</code>	Columns to include in the results (as character). For more information go to readr::read_csv()
<code>coltypes</code>	Column specifications (as strings). See <code>vignette("readr", package = "readr")</code> for more details. documentation.
<code>keep_format</code>	Vector of column names, besides <code>date_time</code> , <code>day</code> and <code>quadkey</code> , that you don't want to convert to a number.

Value

A data.frame with the information of all the files read.

See Also

[format_fb_data](#)
[read_csv](#)

Examples

```
files <- read_fb_mobility_files(  
  path_to_csvs = paste0(system.file("extdata",  
    package = "quadkeyr"  
  ), "/"),  
  colnames = c( # The columns not listed here will be omitted  
    "lat",  
    "lon",  
    "quadkey",  
    "date_time",  
    "n_crisis",  
    "percent_change",  
    "day",
```

```
    "hour"
  ),
  coltypes = list(
    lat = "d",
    lon = "d",
    quadkey = "c",
    date_time = "T",
    n_crisis = "c",
    percent_change = "c",
    day = "D",
    hour = "i"
  )
)

head(files)
```

regular_qk_grid	<i>Convert a incomplete QuadKey sf POINT data.frame into a regular grid.</i>
-----------------	------------------------------------------------------------------------------

Description

This function completes sf POINT data.frame grid of QuadKeys using the bounding box of the data provided.

Usage

```
regular_qk_grid(data)
```

Arguments

data A sf POINT data.frame

Value

A list with three elements:

- data A sf POINT data.frame, with the rows needed to complete the grid.
- num_rows The number of columns of the regular grid.
- num_cols The number of rows of the regular grid.

See Also

[create_qk_grid](#)
[quadkey_to_latlong](#)

Examples

```
quadkey_vector <- c("213", "210", "211")  
  
qtll <- quadkey_to_latlong(quadkey = quadkey_vector)  
  
regular_qk_grid(qtll)
```

tileXY_to_pixelXY *Convert tile XY coordinates into pixel XY coordinates*

Description

Converts tile XY coordinates into pixel XY coordinates of the upper-left pixel of the specified tile. For further information, refer to the Microsoft Bing Maps Tile System documentation.

Usage

```
tileXY_to_pixelXY(tileX, tileY)
```

Arguments

tileX	Tile X coordinate.
tileY	Tile Y coordinate.

Details

Converting latitude/longitude coordinates into a QuadKey and then back to latitude/longitude won't yield identical values, unless the initial latitude/longitude coordinates correspond to the upper-left Quadkey's pixel and tile XY coordinates at the same zoom level.

Understanding this distinction is crucial for the accurate use of these functions in coordinate conversions.

For a detailed explanation on how to use this and other similar quadkeyr functions, read the the vignette: https://docs.ropensci.org/quadkeyr/articles/quadkey_to_sf_conversion.html

Value

A list returning the pixel X and pixel Y coordinates.

References

<https://learn.microsoft.com/en-us/bingmaps/articles/bing-maps-tile-system>

Examples

```
tileXY_to_pixelXY(  
  tileX = 3,  
  tileY = 5  
)
```

tileXY_to_quadkey	<i>Convert tile XY coordinates into a QuadKey.</i>
-------------------	----------------------------------------------------

Description

Converts tile XY coordinates into a QuadKey at a specified zoom level. For further information, refer to the Microsoft Bing Maps Tile System documentation.

Usage

```
tileXY_to_quadkey(tileX, tileY, zoom)
```

Arguments

tileX	Tile X coordinate.
tileY	Tile Y coordinate.
zoom	Zoom or level of detail, from 1 (lowest detail) to 23 (highest detail).

Details

Converting latitude/longitude coordinates into a QuadKey and then back to latitude/longitude won't yield identical values, unless the initial latitude/longitude coordinates correspond to the upper-left Quadkey's pixel and tile XY coordinates at the same zoom level.

Understanding this distinction is crucial for the accurate use of these functions in coordinate conversions.

For a detailed explanation on how to use this and other similar quadkeyr functions, read the the vignette: https://docs.ropensci.org/quadkeyr/articles/quadkey_to_sf_conversion.html

Value

The QuadKey as a string.

References

<https://learn.microsoft.com/en-us/bingmaps/articles/bing-maps-tile-system>

Examples

```
tileXY_to_quadkey(  
  tileX = 23,  
  tileY = 38,  
  zoom = 6  
)
```

Index

`add_regular_polygon_grid`, [3](#)
`apply_weekly_lag`, [4](#)

`create_qk_grid`, [5](#), [25](#)
`create_stars_raster`, [6](#)

`format_fb_data`, [7](#), [24](#)

`get_qk_coord`, [8](#)
`get_regular_polygon_grid`, [9](#)
`grid_to_polygon`, [10](#)
`ground_res`, [11](#)

`latlong_to_pixelXY`, [11](#)
`latlong_to_quadkey`, [12](#)

`mapscale`, [13](#)
`mapsize`, [14](#)
`missing_combinations`, [15](#), [18](#)

`pixelXY_to_latlong`, [8](#), [16](#), [21](#)
`pixelXY_to_tileXY`, [17](#)
`polygon_to_raster`, [18](#)

`qkmap_app`, [19](#)
`quadkey_df_to_polygon`, [20](#), [20](#), [22](#)
`quadkey_to_latlong`, [21](#), [25](#)
`quadkey_to_polygon`, [22](#)
`quadkey_to_tileXY`, [8](#), [21](#), [23](#)

`read_csv`, [24](#)
`read_fb_mobility_files`, [8](#), [24](#)
`readr::read_csv()`, [24](#)
`regular_qk_grid`, [25](#)

`st_as_stars`, [6](#), [18](#)
`st_rasterize`, [6](#), [18](#)
`stars::st_as_stars()`, [6](#)

`tileXY_to_pixelXY`, [8](#), [21](#), [26](#)
`tileXY_to_quadkey`, [27](#)