

Package ‘rrepast’

May 9, 2026

Type Package

Title Invoke 'Repast Symphony' Simulation Models

Version 0.8.0

Date 2020-02-18

Encoding UTF-8

Author Antonio Prestes Garcia [aut, cre],
Alfonso Rodriguez-Paton [aut, ths]

Maintainer Antonio Prestes Garcia <antonio.pgarcia@alumnos.upm.es>

URL <https://github.com/antonio-pgarcia/rrepast>

BugReports <https://github.com/antonio-pgarcia/RRepast/issues>

Description An R and Repast integration tool for running individual-based (IbM) simulation models developed using 'Repast Symphony' Agent-Based framework directly from R code supporting multicore execution. This package integrates 'Repast Symphony' models within R environment, making easier the tasks of running and analyzing model output data for automated parameter calibration and for carrying out uncertainty and sensitivity analysis using the power of R environment.

License MIT + file LICENSE

Imports lhs, sensitivity, ggplot2, digest, xlsx, doSNOW, rJava,
gridExtra, parallel, foreach

RoxygenNote 6.1.1

NeedsCompilation no

Repository CRAN

Date/Publication 2020-02-19 06:00:05 UTC

Contents

| | |
|----------------------|---|
| AddFactor | 5 |
| AddFactor0 | 5 |
| AddResults | 6 |

| | |
|---------------------------------------|----|
| AoE.Base | 6 |
| AoE.ColumnCoV | 7 |
| AoE.CoV | 7 |
| AoE.FullFactorial | 8 |
| AoE.GetMorrisOutput | 8 |
| AoE.LatinHypercube | 9 |
| AoE.MAE | 9 |
| AoE.Morris | 10 |
| AoE.NRMSD | 10 |
| AoE.RandomSampling | 11 |
| AoE.RMSD | 12 |
| AoE.Sobol | 12 |
| AoE.Stability | 13 |
| ApplyFactorRange | 13 |
| BuildParameterSet | 14 |
| Calibration.GetMemberKeys | 14 |
| Calibration.GetMemberList | 15 |
| check.integration | 15 |
| check.scenario | 16 |
| ClearResults | 16 |
| col.sum | 17 |
| config.check | 17 |
| config.copylib | 18 |
| config.scenario | 18 |
| createOutputDir | 19 |
| df2matrix | 19 |
| dffilterby | 20 |
| dfround | 20 |
| dfsumcol | 21 |
| Easy.Calibration | 21 |
| Easy.getChart | 22 |
| Easy.getPlot | 23 |
| Easy.Morris | 23 |
| Easy.Run | 24 |
| Easy.RunExperiment | 24 |
| Easy.Setup | 25 |
| Easy.ShowModelParameters | 25 |
| Easy.Sobol | 26 |
| Easy.Stability | 26 |
| Engine | 27 |
| Engine.endAt | 28 |
| Engine.Finish | 28 |
| Engine.getId | 28 |
| Engine.GetModelOutput | 29 |
| Engine.getParameter | 29 |
| Engine.getParameterAsDouble | 30 |
| Engine.getParameterAsNumber | 30 |
| Engine.getParameterAsString | 31 |

| | |
|--------------------------------------|----|
| Engine.getParameterNames | 31 |
| Engine.getParameterType | 32 |
| Engine.LoadModel | 32 |
| Engine.resetModelOutput | 33 |
| Engine.RunModel | 33 |
| Engine.SetAggregateDataSet | 33 |
| Engine.setParameter | 34 |
| enginestats.calls | 35 |
| enginestats.reset | 35 |
| getExperimentDataset | 35 |
| getExperimentOutput | 36 |
| getExperimentParamSet | 36 |
| GetFactorLevels | 37 |
| GetFactorsSize | 38 |
| getId | 38 |
| getKeyRandom | 38 |
| getLogDir | 39 |
| GetOutput | 39 |
| getOutputDir | 40 |
| getpkgcores | 40 |
| getpkgdefaultcores | 40 |
| GetResults | 41 |
| GetResultsParameters | 41 |
| GetSimulationParameters | 41 |
| GetSimulationParameterType | 42 |
| GoToPreviousDir | 42 |
| GoToWorkDir | 42 |
| hybrid.distance | 43 |
| hybrid.value | 43 |
| jarfile | 44 |
| jvm.enablejmx | 44 |
| jvm.getRuntime | 45 |
| jvm.get_parameters | 45 |
| jvm.init | 45 |
| jvm.memory | 46 |
| jvm.resetOut | 46 |
| jvm.runtimegc | 47 |
| jvm.setOut | 47 |
| jvm.set_parameters | 48 |
| lcontains | 48 |
| lget | 49 |
| Load | 49 |
| Logger.setLevelInfo | 50 |
| Logger.setLevelWarning | 50 |
| Model | 50 |
| ParallelClose | 51 |
| ParallelInit | 51 |
| parallelize | 52 |

| | |
|-----------------------------------|----|
| ParallelRunExperiment | 52 |
| ParallelRun | 53 |
| PB.close | 54 |
| PB.disable | 54 |
| PB.enable | 54 |
| PB.get | 55 |
| PB.init | 55 |
| PB.isEnabled | 55 |
| PB.pset | 56 |
| PB.rnum | 56 |
| PB.set | 56 |
| PB.update | 57 |
| pick.fittest | 57 |
| Plot.Calibration | 58 |
| Plot.Morris | 58 |
| Plot.Sobol | 59 |
| Plot.Stability | 59 |
| Results.GetCharts | 60 |
| Results.GetExperiment | 60 |
| Results.GetObject | 61 |
| Run | 61 |
| RunExperiment | 62 |
| SaveSimulationData | 63 |
| SequenceItem | 63 |
| setId | 64 |
| setKeyRandom | 64 |
| setOutputDir | 64 |
| setpkgcores | 65 |
| SetResults | 65 |
| SetResultsParameters | 65 |
| SetSimulationParameter | 66 |
| SetSimulationParameters | 66 |
| ShowClassPath | 67 |
| ShowCores | 67 |
| ShowModelPaths | 68 |
| UpdateDefaultParameters | 68 |
| WrapperRun | 69 |
| WrapperRunExperiment | 69 |

| | |
|-----------|---|
| AddFactor | <i>Adds a paramter to factor collection</i> |
|-----------|---|

Description

Builds up the factor collection.

Usage

```
AddFactor(factors = c(), lambda = "qunif", name, min, max,
           int = FALSE)
```

Arguments

| | |
|---------|---|
| factors | The current factor collection |
| lambda | The function to apply FUN(p,min,max) |
| name | The name of factor |
| min | The minimum of parameter p |
| max | The maximum of parameter p |
| int | Boolean for truncating the factor value |

Value

The collection of created factors

Examples

```
## Not run:
f<- AddFactor(name="Age",min=20,max=60)
f<- AddFactor(factors=f, name="Weight",min=50,max=120)
## End(Not run)
```

| | |
|------------|-------------------|
| AddFactor0 | <i>AddFactor0</i> |
|------------|-------------------|

Description

Creates or appends the factor collection

Usage

```
AddFactor0(factors = c(), ...)
```

Arguments

factors The current factor collection
 ... The variadic parameter list

Value

The factor collection

Examples

```
## Not run:
  f<- AddFactor0(name="Age",min=20,max=60)
  f<- AddFactor0(factors=f, name="Weight",min=50,max=120)
## End(Not run)
```

| | |
|------------|---|
| AddResults | <i>Concatenate results of multiple runs</i> |
|------------|---|

Description

This function stores the output of the last model execution and it is intended to be used internally.

Usage

```
AddResults(d)
```

Arguments

d A data frame containing one replication data

| | |
|----------|-----------------|
| AoE.Base | <i>AoE.Base</i> |
|----------|-----------------|

Description

The Design Of Experiments Base function

Usage

```
AoE.Base(m, factors = c(), fun = NULL)
```

Arguments

m The base design matrix
 factors A subset of model parameters
 fun The function which will be applied to m

Value

The design matrix

AoE.ColumnCoV

AoE.ColumnCoV

Description

This function Calculates the relative squared deviation (RSD or CoV) for an used provided column name key in the parameter dataset.

Usage

AoE.ColumnCoV(dataset, key)

Arguments

| | |
|---------|---------------------------------|
| dataset | A model output dataset |
| key | Column name from output dataset |

Value

A data frame with Coefficient of variations

AoE.CoV

AoE.CoV

Description

A simple function for calculate the Coefficient of Variation

Usage

AoE.CoV(d)

Arguments

| | |
|---|---------------------|
| d | The data collection |
|---|---------------------|

Value

The coefficient of variation for data

AoE.FullFactorial *AoE.FullFactorial design generator*

Description

Generate a Full Factorial sampling for evaluating the parameters of a model.

Usage

```
AoE.FullFactorial(n = 10, factors = c())
```

Arguments

| | |
|---------|--|
| n | The number of samples |
| factors | The model's parameters which will be evaluated |

Value

The Full Factorial design matrix for provided parameters

Examples

```
## Not run:  
f<- AddFactor(name="cyclePoint",min=40,max=90)  
f<- AddFactor(factors=f, name="conjugationCost",min=1,max=80)  
d<- AoE.FullFactorial(2,f)  
## End(Not run)
```

AoE.GetMorrisOutput *AoE.GetMorrisOutput*

Description

Returns a dataframe holding the Morris result set

Usage

```
AoE.GetMorrisOutput(obj)
```

Arguments

| | |
|-----|---|
| obj | A reference to a morris object instance |
|-----|---|

Value

The results of Morris method

AoE.LatinHypercube *AoE.LatinHypercube*

Description

Generate a LHS sample for model parameters

Usage

```
AoE.LatinHypercube(n = 10, factors = c(), convert = TRUE)
```

Arguments

| | |
|---------|--|
| n | The number of samples |
| factors | The model's parameters which will be evaluated |
| convert | Adjust experiment matrix to parameter scale |

Details

Generate the LHS sampling for evaluating the parameters of a model.

Value

The LHS design matrix for provided parameters

Examples

```
## Not run:  
f<- AddFactor(name="cyclePoint",min=40,max=90)  
f<- AddFactor(factors=f, name="conjugationCost",min=1,max=80)  
d<- AoE.LatinHypercube(2,f)  
## End(Not run)
```

AoE.MAE *AoE.MAE*

Description

Calculates the average-error magnitude (MAE)

Usage

```
AoE.MAE(xs, xe)
```

Arguments

| | |
|-----------------|---------------------------|
| <code>xs</code> | The simulated data set |
| <code>xe</code> | The experimental data set |

Value

The MAE value for provided datasets

| | |
|-------------------------|-------------------|
| <code>AoE.Morris</code> | <i>AoE.Morris</i> |
|-------------------------|-------------------|

Description

This is a wrapper for performing Morris's screening method on repast models. We rely on morris method from sensitivity package.

Usage

```
AoE.Morris(k = c(), p = 5, r = 4)
```

Arguments

| | |
|----------------|---|
| <code>k</code> | The factors for morris screening. |
| <code>p</code> | The number of levels for the model's factors. |
| <code>r</code> | Repetitions. The number of random sampling points of Morris Method. |

References

Gilles Pujol, Bertrand Iooss, Alexandre Janon with contributions from Sebastien Da Veiga, Jana Fruth, Laurent Gilquin, Joseph Guillaume, Loic Le Gratiet, Paul Lemaitre, Bernardo Ramos and Taieb Touati (2015). sensitivity: Sensitivity Analysis. R package version 1.11.1. <https://CRAN.R-project.org/package=sensitivity>

| | |
|------------------------|------------------|
| <code>AoE.NRMSD</code> | <i>AoE.NRMSD</i> |
|------------------------|------------------|

Description

A simple Normalized Root-Mean-Square Deviation calculation using max and min values. $NRMSD = RMSD(x) / (\max(x) - \min(x))$

Usage

```
AoE.NRMSD(xs, xe)
```

Arguments

| | |
|----|---------------------------|
| xs | The simulated data set |
| xe | The experimental data set |

Value

The NRRMSD value for provided datasets

AoE.RandomSampling *AoE.RandomSampling* experiment desing generator

Description

Generate a Simple Random Sampling experiment design matrix.

Usage

```
AoE.RandomSampling(n = 10, factors = c())
```

Arguments

| | |
|---------|--|
| n | The number of samples |
| factors | The model's parameters which will be evaluated |

Value

The random sampling design matrix

Examples

```
## Not run:  
f<- AddFactor(name="cyclePoint",min=40,max=90)  
f<- AddFactor(factors=f, name="conjugationCost",min=1,max=80)  
d<- AoE.RandomSampling(2,f)  
## End(Not run)
```

 AoE.RMSD

AoE.RMSD

Description

A simple Root-Mean-Square Deviation calculation.

Usage

```
AoE.RMSD(xs, xe)
```

Arguments

| | |
|----|---------------------------|
| xs | The simulated data set |
| xe | The experimental data set |

Value

The RMSD value for provided datasets

AoE.Sobol

AoE.Sobol

Description

This is a wrapper for performing Global Sensitivity Analysis using the Sobol Method provided by sensitivity package.

Usage

```
AoE.Sobol(n = 100, factors = c(), o = 2, nb = 100,
  fun.doe = AoE.LatinHypercube, fun.sobol = sobolmartinez)
```

Arguments

| | |
|-----------|---|
| n | The number of samples |
| factors | The model's parameters which will be evaluated |
| o | Maximum order in the ANOVA decomposition |
| nb | Number of bootstrap replicates |
| fun.doe | The sampling function to be used for sobol method |
| fun.sobol | The sobol implementation |

Details

This function is not intended to be used directly from user programs.

References

Gilles Pujol, Bertrand Iooss, Alexandre Janon with contributions from Sebastien Da Veiga, Jana Fruth, Laurent Gilquin, Joseph Guillaume, Loic Le Gratiet, Paul Lemaitre, Bernardo Ramos and Taieb Touati (2015). sensitivity: Sensitivity Analysis. R package version 1.11.1. <https://CRAN.R-project.org/package=sensitivity>

| | |
|---------------|----------------------|
| AoE.Stability | <i>AoE.Stability</i> |
|---------------|----------------------|

Description

This function verifies the stability of CoV for all columns given by parameter keys or all dataset columns if keys is empty.

Usage

```
AoE.Stability(dataset, keys = c())
```

Arguments

| | |
|---------|------------------------|
| dataset | A model output dataset |
| keys | A list of column names |

Value

A data frame with Coefficient of variations

| | |
|------------------|---------------------------------------|
| ApplyFactorRange | <i>Corrects the LHS design matrix</i> |
|------------------|---------------------------------------|

Description

Correct the LHS sampling matrix for a specific range applying the lambda function. The default value of 'lambda' is 'qunif'.

Usage

```
ApplyFactorRange(design, factors)
```

Arguments

| | |
|---------|---------------------------|
| design | The LHS design matrix |
| factors | The collection of factors |

Value

The corrected design matrix

| | |
|-------------------|--|
| BuildParameterSet | <i>Builds the simulation parameter set</i> |
|-------------------|--|

Description

Merges the design matrix with parameters which will be keep fixed along simulation runs.

Usage

```
BuildParameterSet(design, parameters)
```

Arguments

| | |
|------------|--|
| design | The experimental desing matrix for at least one factor |
| parameters | All parameters of the repast model. |

Value

A data frame holding all parameters required for running the model

Examples

```
## Not run:
modeldir<- "c:/usr/models/BactoSim(HaldaneEngine-1.0)"
e<- Model(modeldir=modeldir,dataset="ds::Output")
Load(e)

f<- AddFactor(name="cyclePoint",min=40,max=90)

p<- GetSimulationParameters(e)

d<- AoE.LatinHypercube(factors=f)

p1<- BuildParameterSet(d,p)
## End(Not run)
```

| | |
|---------------------------|----------------------------------|
| Calibration.GetMemberKeys | <i>Calibration.GetMemberKeys</i> |
|---------------------------|----------------------------------|

Description

Gets the list of keys (the factor names)

Usage

Calibration.GetMemberKeys(obj)

Arguments

obj An instance of the object returned by Easy methods

Value

The collection of keys

Calibration.GetMemberList

Calibration.GetMemberList

Description

Gets the member list value

Usage

Calibration.GetMemberList(obj, key, name)

Arguments

obj An instance of the object returned by Easy methods

key The key value

name The column name

Value

The member list

check.integration

check.integration

Description

Check if the integration jar library is correctly installed in the model lib directory

Usage

check.integration(modelpath)

Arguments

modelpath The path where model is installed

Value

TRUE if the integration code is correctelly deployed

check.scenario *check.scenario*

Description

Check if the scenario.xml is configured with the rrepast itegration code

Usage

check.scenario(modelpath)

Arguments

modelpath The path where model is installed

Value

TRUE if scenario is properly configured

ClearResults *Clear the results data.frame*

Description

This function is called automatically every time Run method is called.

Usage

ClearResults()

| | |
|---------|----------------|
| col.sum | <i>col.sum</i> |
|---------|----------------|

Description

Sum all columns but one (pset) of a data frame

Usage

```
col.sum(d, skip = c())
```

Arguments

| | |
|------|---|
| d | The data frame |
| skip | The columns which should not be included in the sum |

Value

The original data frame with a new column (sum) holding the sum

| | |
|--------------|---------------------|
| config.check | <i>config.check</i> |
|--------------|---------------------|

Description

Verify if the installed model is correctly configured.

Usage

```
config.check(modelpath)
```

Arguments

| | |
|-----------|-----------------------------------|
| modelpath | The path where model is installed |
|-----------|-----------------------------------|

Value

TRUE when all requisites are met

| | |
|----------------|-----------------------|
| config.copylib | <i>config.copylib</i> |
|----------------|-----------------------|

Description

Install or uninstall the integration jar file. This function manages the installation process of required jars to the model lib dir.

Usage

```
config.copylib(modelpath, uninstall = FALSE)
```

Arguments

| | |
|-----------|-----------------------------------|
| modelpath | The path where model is installed |
| uninstall | If TRUE uninstall integration jar |

Value

TRUE if install operation succeed

| | |
|-----------------|------------------------|
| config.scenario | <i>config.scenario</i> |
|-----------------|------------------------|

Description

Add the integration library to the model's configuration

Usage

```
config.scenario(modelpath, uninstall = FALSE)
```

Arguments

| | |
|-----------|--|
| modelpath | The path where model is installed |
| uninstall | If TRUE restore original scenario.xml file |

Value

A logical TRUE if the model's scenario file has been modified

| | |
|-----------------|--------------------------------|
| createOutputDir | <i>Create output directory</i> |
|-----------------|--------------------------------|

Description

A simple function to make a directory to save the model's data.

Usage

```
createOutputDir()
```

Details

Create the, if required, the directory to save the output data generate by the model. It is intended for internal use.

| | |
|-----------|------------------|
| df2matrix | <i>df2matrix</i> |
|-----------|------------------|

Description

This function converts data frames to matrix data type.

Usage

```
df2matrix(d, n = c())
```

Arguments

| | |
|---|---|
| d | The data frame |
| n | The column names to be converted. Null for all data frame columns |

Value

The data frame converted to a matrix

*dfilterby**dfilterby*

Description

Selects a subset of a data frame, filtering by column values.

Usage

```
dfilterby(d, key, values = c())
```

Arguments

| | |
|--------|--|
| d | The data frame holding data to be filtered |
| key | The column name for selection values |
| values | The collection of values used to filter the data set |

Value

The filtered data set

*dfround**dfround*

Description

Round all numeric columns of a data frame

Usage

```
dfround(d, p)
```

Arguments

| | |
|---|---|
| d | The data frame |
| p | The number of decimal digits to be kept |

Value

A data frame with rounded columns

| | |
|----------|-----------------|
| dfsumcol | <i>dfsumcol</i> |
|----------|-----------------|

Description

Sum data frame columns but tho

Usage

```
dfsumcol(d, lst = c(), invert = FALSE)
```

Arguments

| | |
|--------|---|
| d | The data frame |
| lst | Skip columns included. Sum columns NOT included |
| invert | Sum only the columns included in lst |

Value

The original data frame with a new column (sum) holding the sum

| | |
|------------------|-------------------------|
| Easy.Calibration | <i>Easy.Calibration</i> |
|------------------|-------------------------|

Description

Search for the best set of parameters trying to minimize the calibration function provided by the user. The function has to operational models, the first based on the experimental setup where all parameters are defined a priori and the second using optimization techniques. Currently the only supported optimization technique is the particle swarm optimization.

Usage

```
Easy.Calibration(m.dir, m.ds, m.time = 300, parameters, exp.n = 100,  
exp.r = 1, smax = 4, design = "lhs", FUN, default = NULL)
```

Arguments

| | |
|------------|---|
| m.dir | The installation directory of some repast model |
| m.ds | The name of any model aggregate dataset |
| m.time | The total simulated time |
| parameters | The input factors |
| exp.n | The experiment sample size |
| exp.r | The number of experiment replications |

| | |
|---------|---|
| smax | The number of solutions to be generated |
| design | The sampling scheme ["lhs" "mcs" "ffs"] |
| FUN | The objective or cost function. A function defined over the model output. |
| default | The alternative values for parameters which should be kept fixed |

Value

A list with holding experiment, object and charts

Examples

```
## Not run:
my.cost<- function(params, results) {
  criteria<- c()
  Rate<- AoE.RMSD(results$X.Simulated,results$X.Experimental)
  G<- AoE.RMSD(results$G.T.,52)
  total<- Rate + G
  criteria<- cbind(total,Rate,G)
  return(criteria)
}

Easy.Setup("/models/BactoSim")
v<- Easy.Calibration("/models/BactoSim","ds::Output",360,
  f,exp.n = 1000, exp.r=1, smax=4,
  design="mcs", my.cost)

## End(Not run)
```

Easy.getChart

Easy.getChart

Description

Returns the chart instance

Usage

```
Easy.getChart(obj, key)
```

Arguments

| | |
|-----|---|
| obj | A reference to the output of Easy.Stability |
| key | The param name |

Value

The plot instance

| | |
|--------------|---------------------|
| Easy.getPlot | <i>Easy.getPlot</i> |
|--------------|---------------------|

Description

Returns the chart instance

Usage

```
Easy.getPlot(obj, c, key)
```

Arguments

| | |
|-----|---|
| obj | A reference to the output of an "Easy" API method |
| c | The output name |
| key | The param name |

Value

The plot instance

| | |
|-------------|---|
| Easy.Morris | <i>Easy API for Morris's screening method</i> |
|-------------|---|

Description

This function wraps all calls to perform Morris method.

Usage

```
Easy.Morris(m.dir, m.ds, m.time = 300, parameters, mo.p, mo.r, exp.r,  
FUN, default = NULL)
```

Arguments

| | |
|------------|---|
| m.dir | The installation directory of some repast model |
| m.ds | The name of any model aggregate dataset |
| m.time | The total simulated time |
| parameters | The factors for morris screening. |
| mo.p | The number of levels for the model's factors. |
| mo.r | Repetitions. The number of random sampling points of Morris Method. |
| exp.r | The number of experiment replications |
| FUN | The objective or cost function. A function defined over the model output. |
| default | The alternative values for parameters which should be kept fixed |

Value

A list with holding experiment, object and charts

| | |
|----------|-------------------------------------|
| Easy.Run | <i>Easy API for running a model</i> |
|----------|-------------------------------------|

Description

This function provides a simple wrapper for performing a single or replicated model execution with a single set of parameters.

Usage

```
Easy.Run(m.dir, m.ds, m.time = 300, r = 1, default = NULL)
```

Arguments

| | |
|---------|---|
| m.dir | The installation directory of some repast model |
| m.ds | The name of any model aggregate dataset |
| m.time | The total simulated time |
| r | The number of replications |
| default | The alternative values for the default model parameters |

| | |
|--------------------|---|
| Easy.RunExperiment | <i>Easy API for Running Experiments</i> |
|--------------------|---|

Description

This function provides a simple wrapper for performing experimental setups using a design matrix

Usage

```
Easy.RunExperiment(m.dir, m.ds, m.time = 300, r = 1, design, FUN,
  default = NULL)
```

Arguments

| | |
|---------|---|
| m.dir | The installation directory of some repast model |
| m.ds | The name of any model aggregate dataset |
| m.time | The total simulated time |
| r | The number of replications |
| design | The design matrix holding parameter sampling |
| FUN | The objective or cost function. A function defined over the model output. |
| default | The alternative values for parameters which should be kept fixed |

Value

The experiment results

Easy.Setup

Easy.Setup

Description

This function configures the deployment directory where logs and output dataset will be generated. By default the deployment directory will be created under the model installation directory. The output generated by the Repast model will be redirected to the SystemOut.log file.

Usage

```
Easy.Setup(model, multicore = FALSE, deployment = c())
```

Arguments

| | |
|------------|---|
| model | The base directory where Repast model is installed. |
| multicore | Boolean flag indicating to use multiplecore. |
| deployment | The directory to save the output and logs. |

Details

If the deployment directory is empty the installation directory given by the parameter `model` is used instead as the base directory. The deployment directory is `/rrepast-deployment/`.

Easy.ShowModelParameters

Easy.ShowModelParameters

Description

Returns the list current model parameters

Usage

```
Easy.ShowModelParameters(v)
```

Arguments

| | |
|---|---|
| v | The installation directory of some repast model |
|---|---|

Value

The model parameters

Easy.Sobol

Easy API for Sobol's SA method

Description

This functions wraps all required calls to perform Sobol method for global sensitivity analysis.

Usage

```
Easy.Sobol(m.dir, m.ds, m.time = 300, parameters, exp.n = 500,
  bs.size = 200, exp.r = 1, FUN, default = NULL,
  fsobol = sobol2002, fsampl = AoE.LatinHypercube)
```

Arguments

| | |
|------------|---|
| m.dir | The installation directory of some repast model |
| m.ds | The name of any model aggregate dataset |
| m.time | The total simulated time |
| parameters | The input factors |
| exp.n | The experiment sample size |
| bs.size | The bootstrap sample size for sobol method |
| exp.r | The number of experiment replications |
| FUN | The objective or cost function. A function defined over the model output. |
| default | The alternative values for parameters which should be kept fixed |
| fsobol | The alternative function for calculating sobol indices |
| fsampl | The function for sampling data |

Value

A list with holding experimnt, object and charts

Easy.Stability

Easy API for output stability

Description

This functions run model several times in order to determine how many experiment replications are required for model's output being stable (i.e. the convergence of standard deviation)

Usage

```
Easy.Stability(m.dir, m.ds, m.time = 300, parameters, samples = 1,
  tries = 100, vars = c(), FUN, default = NULL)
```

Arguments

| | |
|------------|---|
| m.dir | The installation directory of some repast model |
| m.ds | The name of any model aggregate dataset |
| m.time | The total simulated time |
| parameters | The factors or model's parameter list |
| samples | The number of factor samples. |
| tries | The number of experiment replications |
| vars | The model's output variables for compute CoV |
| FUN | The objective or cost function. A function defined over the model output. |
| default | The alternative values for parameters which should be kept fixed |

Value

A list with holding experiment, object and charts

Engine

Engine

Description

Creates an instance of Engine

Usage

Engine()

Details

This function creates an instance of Repast model wrapper class. Before invoking the function Engine, make sure that environment was correctly initialized.

Value

An object instance of Engine class

| | |
|---------------------------|---------------------|
| <code>Engine.endAt</code> | <i>Engine.endAt</i> |
|---------------------------|---------------------|

Description

Configure the maximum simulated time for the current model run

Usage

`Engine.endAt(e, v)`

Arguments

| | |
|----------------|---------------------------------|
| <code>e</code> | An engine object instance |
| <code>v</code> | The number of Repast time ticks |

| | |
|----------------------------|----------------------|
| <code>Engine.Finish</code> | <i>Engine.Finish</i> |
|----------------------------|----------------------|

Description

Performs a cleanup on an engine instance. Finalize and destroy repast controller data.

Usage

`Engine.Finish(e)`

Arguments

| | |
|----------------|---------------------------|
| <code>e</code> | An engine object instance |
|----------------|---------------------------|

| | |
|---------------------------|-----------------------------|
| <code>Engine.getId</code> | <i>Returns the model id</i> |
|---------------------------|-----------------------------|

Description

This function provides a wrapper to the method `getId()` from repast context. The id is basically a String with the currently instantiated model name.

Usage

`Engine.getId(e)`

Arguments

| | |
|----------------|---------------------------|
| <code>e</code> | An engine object instance |
|----------------|---------------------------|

Engine.GetModelOutput *Engine.GetModelOutput*

Description

Gets the model output data as a CSV String array. Calls the engine method GetModelOutput to drain model output data.

Usage

```
Engine.GetModelOutput(e)
```

Arguments

e An engine object instance

Value

An array of strings containing the model's output

Examples

```
## Not run:  
d<- "c:/usr/models/your-model-directory"  
m<- Model(d)  
csv<- Engine.GetModelOutput(m)  
## End(Not run)
```

Engine.getParameter *Engine.getParameter*

Description

The function gets the value of model parameter k as java.lang.Object

Usage

```
Engine.getParameter(e, k)
```

Arguments

e An engine object instance
k The parameter name

Value

The parameter value

`Engine.getParameterAsDouble`
Engine.getParameterAsDouble

Description

Get the value of model parameter k as `java.lang.Double`

Usage

`Engine.getParameterAsDouble(e, k)`

Arguments

| | |
|---|---------------------------|
| e | An engine object instance |
| k | The parameter name |

Value

The parameter value as double

`Engine.getParameterAsNumber`
Engine.getParameterAsNumber

Description

Get the value of model parameter k as `java.lang.Number`

Usage

`Engine.getParameterAsNumber(e, k)`

Arguments

| | |
|---|---------------------------|
| e | An engine object instance |
| k | The parameter name |

Value

The parameter value as number

`Engine.getParameterAsString`
Engine.getParameterAsString

Description

Get the value of model parameter k as `java.lang.String`

Usage

`Engine.getParameterAsString(e, k)`

Arguments

| | |
|---|---------------------------|
| e | An engine object instance |
| k | The parameter name |

Value

The parameter value as string

`Engine.getParameterNames`
Engine.getParameterNames

Description

Get the parameter names

Usage

`Engine.getParameterNames(e)`

Arguments

| | |
|---|---------------------------|
| e | An engine object instance |
|---|---------------------------|

Details

Returns the names of all declared model's parameters in the `parameter.xml` file in the scenario directory.

Value

A collection of parameter names

Engine.getParameterType

Engine.getParameterType

Description

Returns the declared type of a Repast model parameter

Usage

Engine.getParameterType(e, k)

Arguments

| | |
|---|---------------------------|
| e | An engine object instance |
| k | The parameter name |

Value

The parameter type string

Engine.LoadModel

Engine.LoadModel

Description

Loads the model's scenario files

Usage

Engine.LoadModel(e, f)

Arguments

| | |
|---|-------------------------------------|
| e | An engine object instance |
| f | The full path of scenario directory |

Details

This function loads the scenario of a Repast Model and initialize de model.

Engine.resetModelOutput
Engine.resetModelOutput

Description

Resets the the model output holder

Usage

Engine.resetModelOutput(e)

Arguments

e An engine object instance

Engine.RunModel *Engine.RunModel*

Description

Performs the execution of Repast model

Usage

Engine.RunModel(e)

Arguments

e An engine object instance

Engine.SetAggregateDataSet
Engine.SetAggregateDataSet

Description

Sets the model's dataset

Usage

Engine.SetAggregateDataSet(e, k)

Arguments

| | |
|---|----------------------------------|
| e | An engine object instance |
| k | The repast model's data set name |

Details

Configure a dataset with the desired output values to be "drained" by the function `Engine.GetModelOutput`.

Examples

```
## Not run:  
d<- "C:/usr/models/your-model-directory"  
m<- Model(d)  
setAggregateDataSet(m, "dataset-name")  
## End(Not run)
```

`Engine.setParameter` *Engine.setParameter*

Description

Set the value of model parameter

Usage

```
Engine.setParameter(e, k, v)
```

Arguments

| | |
|---|---------------------------|
| e | An engine object instance |
| k | The parameter name |
| v | The parameter value |

enginestats.calls *enginestats.calls*

Description

Return the current calls to the 'Engine.RunModel' function

Usage

```
enginestats.calls(increment = FALSE)
```

Arguments

increment A flag telling to increment and update the counter

Value

The number of calls to 'Engine.RunModel'

enginestats.reset *enginestats.reset*

Description

Reset internal statistics

Usage

```
enginestats.reset()
```

getExperimentDataset *Helper function to get experiment dataset*

Description

The RunExperiment function returns a list holding the paramset, output and dataset collection. The paramset collection contains the parameters used for running the experimental setup. The output has the results from user provided calibration function. The dataset collection has the raw output of 'Repast' aggregated dataset.

Usage

```
getExperimentDataset(e)
```

Arguments

e The experiement object returned by [RunExperiment](#)

Value

The reference to dataset container.

getExperimentOutput *Helper function to get experiment output*

Description

The RunExperiment function returns a list holding the paramset, output and dataset collection. The paramset collection contains the parameters used for running the experimental setup. The output has the results from user provided calibration function. The dataset collection has the raw output of 'Repast' aggregated dataset.

Usage

getExperimentOutput(e)

Arguments

e The experiement object returned by [RunExperiment](#)

Value

The reference to output container.

getExperimentParamSet *Helper function to get experiment paramset*

Description

The RunExperiment function returns a list holding the paramset, output and dataset collection. The paramset collection contains the parameters used for running the experimental setup. The output has the results from user provided calibration function. The dataset collection has the raw output of 'Repast' aggregated dataset.

Usage

getExperimentParamSet(e)

Arguments

e The experiement object returned by [RunExperiment](#)

Value

The reference to output container.

Examples

```
## Not run:  
d<- "C:/usr/models/your-model-directory"  
m<- Model(d)  
...  
e<- RunExperiment(e,r=1,exp.design,my.cost)  
p<- getExperimentParamSet(e)  
## End(Not run)
```

GetFactorLevels

GetFactorLevels

Description

Returns the factor's levels

Usage

```
GetFactorLevels(factors, name)
```

Arguments

| | |
|---------|-------------------------------|
| factors | The current factor collection |
| name | The factor name |

Value

Levels

Examples

```
## Not run:  
f<- AddFactor0(name="Age", levels=c(25,30,40,65))  
f<- AddFactor0(factors=f, name="Weight", levels=c(60,70,80,90))  
  
GetFactorLevels(factors=f, "Age")  
## End(Not run)
```

| | |
|----------------|----------------------------------|
| GetFactorsSize | <i>Get the number of factors</i> |
|----------------|----------------------------------|

Description

Returns the total number of factors

Usage

```
GetFactorsSize(factors)
```

Arguments

factors A collection of factors created with AddFactor

Value

The number of parameters in factors collection

| | |
|-------|----------------------------|
| getId | <i>Gets the model name</i> |
|-------|----------------------------|

Description

Provides the name of the model currently instantiated.

Usage

```
getId()
```

| | |
|--------------|------------------------------------|
| getKeyRandom | <i>Gets Repast randomSeed name</i> |
|--------------|------------------------------------|

Description

Returns the Repast randomSeed parameter name.

Usage

```
getKeyRandom()
```

Value

A string value holding the randomSeed name.

| | |
|-----------|--------------------|
| getLogDir | <i>getLogDir()</i> |
|-----------|--------------------|

Description

Returns the value for log directory

Usage

```
getLogDir()
```

| | |
|-----------|------------------------|
| GetOutput | <i>Gets the output</i> |
|-----------|------------------------|

Description

Returns the results of a model a data.frame from the last RUN. Should be used only if model replication is equal to 1, otherwise GetResults must be used.

Usage

```
GetOutput(e)
```

Arguments

e An engine object instance

Value

Returns a data.frame with output data

Examples

```
## Not run:  
d<- "C:/usr/models/your-model-directory"  
m<- Model(d)  
...  
data<- GetOutput(m)  
## End(Not run)
```

getOutputDir *Gets output directory*

Description

Returns the value of module variable for storing the current output directory.

Usage

getOutputDir()

getpkgcores *getpkgcores*

Description

Returns the maximum number of cores to be used in parallel computations

Usage

getpkgcores()

Value

The number of cores

getpkgdefaultcores *getpkgdefaultcores*

Description

Provides the package default parallelism level which is 80% of total cores available

Usage

getpkgdefaultcores()

Value

Cores used by R/Repast

| | |
|------------|----------------------------------|
| GetResults | <i>Returns the model results</i> |
|------------|----------------------------------|

Description

Returns the model results

Usage

GetResults()

| | |
|----------------------|----------------------------|
| GetResultsParameters | <i>Gets the parameters</i> |
|----------------------|----------------------------|

Description

Returns the current set of paramters used for the last model run.

Usage

GetResultsParameters()

Value

A data.frame with parameters of the model.

| | |
|-------------------------|---------------------------------------|
| GetSimulationParameters | <i>Gets the simulation parameters</i> |
|-------------------------|---------------------------------------|

Description

Returns a dataframe with the current set of input parameters for the last model run.

Usage

GetSimulationParameters(e)

Arguments

e An engine object instance

Value

A data frame with simulation parameters

GetSimulationParameterType
GetSimulationParameterType

Description

Returns the declared parameter type.

Usage

```
GetSimulationParameterType(e, k)
```

Arguments

| | |
|---|--------------------------------|
| e | An instance of 'Engine' object |
| k | The parameter name |

Value

The parameter type as string

GoToPreviousDir *GoToPreviousDir*

Description

Returns to the saved work directory

Usage

```
GoToPreviousDir()
```

GoToWorkDir *GoToWorkDir*

Description

Changes the current work directory saving the previous one which is used in [GoToPreviousDir](#). This function is called by [Easy.Setup](#)

Usage

```
GoToWorkDir()
```

| | |
|-----------------|------------------------|
| hybrid.distance | <i>hybrid.distance</i> |
|-----------------|------------------------|

Description

Calculates the distance between some value a reference target value. It is an hybrid distance because when the value falls within a reference range the distance is 0, otherwise the distance between the value and the reference value is calculated using the user provided distance function.

Usage

```
hybrid.distance(value, reference, FUN = AoE.NRMSD)
```

Arguments

| | |
|-----------|--|
| value | The value which will be compared against the reference |
| reference | The reference value. It should be a list holding the value, the range of values. |
| FUN | The distance function. The default is the NRMSD |

Value

The distance metric

| | |
|--------------|---------------------|
| hybrid.value | <i>hybrid.value</i> |
|--------------|---------------------|

Description

A simple helper function for generating the input list for the function 'hybrid.distance'. This list must hold the value and a range centered over the value.

Usage

```
hybrid.value(value, distance)
```

Arguments

| | |
|----------|------------------------|
| value | The reference value |
| distance | The distance interval. |

Value

The list holding the value and the interval 'min — value — max'

jarfile *jarfile*

Description

The jarfile returns the full path to some jar file available inside rrpast package

Usage

```
jarfile(fjar)
```

Arguments

fjar The name of jar file

Value

The full path to jar file

jvm.enablejmx *jvm.enablejmx*

Description

Enable jmx for the current R/rJava session

Usage

```
jvm.enablejmx()
```

Details

Configures the JMX subsystem for the current session of R/rJava. This function must be called before any other function which initializes r/Java such as [Easy.Setup](#) or [Model](#) otherwise it will have no effect.

Examples

```
## Not run:  
  jvm.enablejmx()  
## End(Not run)
```

| | |
|----------------|-----------------------|
| jvm.getruntime | <i>jvm.getruntime</i> |
|----------------|-----------------------|

Description

A wrapper for System.getRuntime()

Usage

```
jvm.getRuntime()
```

Details

A simple wrapper for System.getRuntime() java method

| | |
|--------------------|---------------------------|
| jvm.get_parameters | <i>jvm.get_parameters</i> |
|--------------------|---------------------------|

Description

Returns the current java virtual machine parameters

Usage

```
jvm.get_parameters()
```

Value

A string with JVM parameters.

| | |
|----------|-------------------------------|
| jvm.init | <i>Init R/JVM environment</i> |
|----------|-------------------------------|

Description

Initialize rJava and repast environment with classpath. This function is called internally and it is not meant to be used directly.

Usage

```
jvm.init()
```

Details

The default parameters can be changed as needed calling the primitive `jvm.set_parameters` before instantiating the model engine.

References

[1] rJava: Low-Level R to Java Interface. Low-level interface to Java VM very much like `.C/Call` and friends. Allows creation of objects, calling methods and accessing fields.

Examples

```
## Not run:
  jvm.init()
## End(Not run)
```

| | |
|------------|-------------------|
| jvm.memory | <i>jvm.memory</i> |
|------------|-------------------|

Description

JVM memory state

Usage

```
jvm.memory()
```

Details

Provides information about the memory used by the JVM subsystem

| | |
|--------------|---------------------|
| jvm.resetOut | <i>jvm.resetOut</i> |
|--------------|---------------------|

Description

Reset the `System.out` filed value to console output

Usage

```
jvm.resetOut()
```

Examples

```
## Not run:
  jvm.resetOut()
## End(Not run)
```

| | |
|---------------|----------------------|
| jvm.runtimegc | <i>jvm.runtimegc</i> |
|---------------|----------------------|

Description

A wrapper for `Runtime.gc()`

Usage

```
jvm.runtimegc()
```

Details

Forces the execution of the JVM garbage collector

| | |
|------------|-------------------|
| jvm.setOut | <i>jvm.setOut</i> |
|------------|-------------------|

Description

Set the `System.out` filed to a file

Usage

```
jvm.setOut(f)
```

Arguments

| | |
|---|----------------------|
| f | The output file name |
|---|----------------------|

Examples

```
## Not run:  
jvm.setOut("/tmp/SysteOut.log")  
## End(Not run)
```

`jvm.set_parameters` *jvm.set_parameters*

Description

Configures the jvm parameters

Usage

`jvm.set_parameters(s)`

Arguments

`s` The paramter string to be passed to the underlying JVM

Details

Set the underlying parameters for java virtual machine. The default values are "-server -Xms1024m -Xmx1024m". These defaults can be changed to fit the model requirements.

Examples

```
## Not run:  
  jvm.set_parameters("-server -Xms512m -Xmx2048m")  
## End(Not run)
```

`lcontains` *lcontains*

Description

Cheks if a list contains a name

Usage

`lcontains(l, n)`

Arguments

`l` The list object
`n` The item name

Value

Boolean TRUE if name is found on list

| | |
|------|------------|
| lget | <i>get</i> |
|------|------------|

Description

Retrieve the value for a list item

Usage

```
lget(l, n)
```

Arguments

| | |
|---|-----------------|
| l | The list object |
| n | The item name |

Value

The item value

| | |
|------|----------------------------|
| Load | <i>The Scenario loader</i> |
|------|----------------------------|

Description

Loads the model's scenario. This function must be called before running the model.

Usage

```
Load(e)
```

Arguments

| | |
|---|---------------------------|
| e | An engine object instance |
|---|---------------------------|

Examples

```
## Not run:  
d<- "C:/usr/models/your-model-directory"  
m<- Model(d)  
Load(m)  
## End(Not run)
```

`Logger.setLevelInfo` *Set the log level to INFO*

Description

Configures the underlying logging system

Usage

`Logger.setLevelInfo()`

`Logger.setLevelWarning`
 Set the log level to WARNING

Description

Configures the underlying logging system

Usage

`Logger.setLevelWarning()`

`Model` *The easy API for model initialization*

Description

Instantiate a repast model from the model dir without loading the scenario file.

Usage

`Model(modeldir = "", maxtime = 300, dataset = "none", load = FALSE)`

Arguments

| | |
|-----------------------|---|
| <code>modeldir</code> | The installation directory of some repast model |
| <code>maxtime</code> | The total simulated time |
| <code>dataset</code> | The name of any model aggregate dataset |
| <code>load</code> | If true instantiate model and load scenario |

Details

This is the entry point for model execution. Typically any model execution will start with this function which encapsulates all low level calls for model initialization. In order to perform simulations with repast from R code only Model and a few more function calls are required: [Load](#), [Run](#). Finally the output of model is managed with functions [GetResults](#) and [SaveSimulationData](#).

Value

Returns the instance of repast model

References

[1] North, M.J., N.T. Collier, and J.R. Vos, "Experiences Creating Three Implementations of the Repast Agent Modeling Toolkit," ACM Transactions on Modeling and Computer Simulation, Vol. 16, Issue 1, pp. 1-25, ACM, New York, New York, USA (January 2006).

Examples

```
## Not run:  
  d<- "C:/usr/models/your-model-directory"  
  m<- Model(d)  
## End(Not run)
```

| | |
|---------------|----------------------|
| ParallelClose | <i>ParallelClose</i> |
|---------------|----------------------|

Description

Finalize the parallel execution environment for R/Repast

Usage

```
ParallelClose()
```

| | |
|--------------|---------------------|
| ParallelInit | <i>ParallelInit</i> |
|--------------|---------------------|

Description

Initialize the parallel execution environment for R/Repast

Usage

```
ParallelInit()
```

parallelize

parallelize

Description

Tells R/Repat to use multicore. Default is using just one core.

Usage

```
parallelize(v = NULL)
```

Arguments

| | |
|---|---|
| v | A Boolean value telling if use multiple cores. When null just returns the current setting |
|---|---|

Value

Boolean with current state

ParallelRunExperiment

ParallelRunExperiment

Description

Run the model multiple times for different parameters given by design matrix function parameter.

Usage

```
ParallelRunExperiment(modelldir, datasource, maxtime, r = 1, design, FUN,
  default = NULL)
```

Arguments

| | |
|------------|--|
| modelldir | The installation directory of some repast model |
| datasource | The name of any model aggregate dataset |
| maxtime | The total simulated time |
| r | The number of experiment replications |
| design | The desing matrix holding parameter sampling |
| FUN | THE calibration function. |
| default | The alternative values for parameters which should be kept fixed |

Details

The FUN function must return zero for perfect fit and values greater than zero otherwise.

Value

A list with output and dataset

Examples

```
## Not run:
my.cost<- function(params, results) { # your best fit calculation, being 0 the best metric. }
d<- "/usr/models/your-model-directory"
f<- AddFactor(name="cyclePoint",min=40,max=90)
f<- AddFactor(factors=f, name="conjugationCost",min=1,max=80)
d<- AoE.LatinHypercube(factors=f)
v<- ParallelRunExperiment()
## End(Not run)
```

ParallelRun

ParallelRun

Description

Run simulations in parallel. This function executes the time steps of an instantiated model. The number of replications of model runs can be specified by the function parameter. The seed parameter may be omitted and will be generated internally. If provided, the seed collection, must contain the same number of r parameter.

Usage

```
ParallelRun(modeldir, datasource, maxtime, r = 1, seed = c(),
  design = NULL, default = NULL)
```

Arguments

| | |
|------------|--|
| modeldir | The installation directory of some repast model |
| datasource | The name of any model aggregate dataset |
| maxtime | The total simulated time |
| r | The number of experiment replications |
| seed | The random seed collection |
| design | The desing matrix holding parameter sampling |
| default | The alternative values for parameters which should be kept fixed |

Value

The model output dataset

Examples

```
## Not run:  
md<- "/usr/models/your-model-directory"  
output<- ParallelRun(modeldir= md, maxtime = 360, dataset= ds, r=4)  
## End(Not run)
```

PB.close

PB.close

Description

Close the progress bar descriptor

Usage

PB.close()

PB.disable

PB.disable

Description

Disable the progress bar visualization

Usage

PB.disable()

PB.enable

PB.enable

Description

Enables the progress bar visualization

Usage

PB.enable()

| | |
|--------|---------------|
| PB.get | <i>PB.get</i> |
|--------|---------------|

Description

Gets the the progress bar descriptor

Usage

PB.get()

| | |
|---------|----------------|
| PB.init | <i>PB.init</i> |
|---------|----------------|

Description

Initialize progress bar for model execution.

Usage

PB.init(psets, replications)

Arguments

psets – The total number of paramter sets being simulated
replications – The number of replications per simulation round

| | |
|--------------|---------------------|
| PB.isEnabled | <i>PB.isEnabled</i> |
|--------------|---------------------|

Description

Returns the global value indicating if progress bar is enabled.

Usage

PB.isEnabled()

Value

Boolean TRUE if progress bar must be shown

PB.pset *PB.pset*

Description

Update pset value

Usage

PB.pset(v)

Arguments

v The current parameter set being simulated

PB.rnum *PB.rnum*

Description

Update run number value

Usage

PB.rnum(v)

Arguments

v The current run number

PB.set *PB.set*

Description

Ses the progress bar descriptor

Usage

PB.set(obj)

Arguments

obj – The progress bar descriptor

`PB.update`*PB.update*

Description

Update progress bar

Usage

```
PB.update(r = NULL)
```

Arguments

`r` The current replication number

`pick.fittest`*pick.fittest*

Description

Choose the best solutions minimizing the objective function

Usage

```
pick.fittest(out, goals = c(), n = 4)
```

Arguments

`out` The output data set holding the values of goals
`goals` The column names which must be used as goal
`n` The number of solutions

Value

The `n` rows holding the best results

| | |
|------------------|----------------------------|
| Plot.Calibration | <i>Plot of calibration</i> |
|------------------|----------------------------|

Description

Generate plot for parameter sets providing best fit

Usage

```
Plot.Calibration(obj, key, title = NULL)
```

Arguments

| | |
|-------|-----------------------------------|
| obj | An instance of calibration Object |
| key | The column name |
| title | Chart title, may be null |

Value

The resulting ggplot2 plot object

| | |
|-------------|------------------------------|
| Plot.Morris | <i>Plot of Morris output</i> |
|-------------|------------------------------|

Description

Generate plot for Morris's screening method

Usage

```
Plot.Morris(obj, type, title = NULL)
```

Arguments

| | |
|-------|---|
| obj | An instance of Morris Object AoE.Morris |
| type | The chart type ($\mu \cdot \sigma$ or $\mu \cdot \sigma^2$) |
| title | Chart title, may be null |

Value

The resulting ggplot2 plot object

| | |
|------------|-----------------------------|
| Plot.Sobol | <i>Plot of Sobol output</i> |
|------------|-----------------------------|

Description

Generate plot for Sobol's GSA

Usage

```
Plot.Sobol(obj, type, title = NULL)
```

Arguments

| | |
|-------|---|
| obj | An instance of Sobol Object AoE.Sobol |
| type | The chart type |
| title | Chart title, may be null |

Value

The resulting ggplot2 plot object

| | |
|----------------|---------------------------------|
| Plot.Stability | <i>Plot stability of output</i> |
|----------------|---------------------------------|

Description

Generate plot for visually access the stability of coefficient of variation as function of simulation sample size.

Usage

```
Plot.Stability(obj, title = NULL)
```

Arguments

| | |
|-------|---|
| obj | An instance of Morris Object AoE.Morris |
| title | Chart title, may be null |

Value

The resulting ggplot2 plot object

Results.GetCharts *Results.GetCharts*

Description

Simplify the access to the charts member

Usage

Results.GetCharts(obj)

Arguments

obj An instance of the object returned by Easy methods

Value

The charts element inside results

Results.GetExperiment *Results.GetExperiment*

Description

Simplify the access to the experiment member

Usage

Results.GetExperiment(obj)

Arguments

obj An instance of the object returned by Easy methods

Value

The experiment element inside results

| | |
|-------------------|--------------------------|
| Results.GetObject | <i>Results.GetObject</i> |
|-------------------|--------------------------|

Description

Simplify the access to the object member

Usage

Results.GetObject(obj)

Arguments

| | |
|-----|--|
| obj | An instance of the object returned by Easy methods |
|-----|--|

Value

The object element inside results

| | |
|-----|------------------------|
| Run | <i>Run simulations</i> |
|-----|------------------------|

Description

This function executes the time steps of an instantiated model. The number of replications of model runs can be specified by the function parameter. The seed parameter may be omitted and will be generated internally. If provided, the seed collection, must contain the same number of r parameter.

Usage

Run(e, r = 1, seed = c())

Arguments

| | |
|------|---------------------------------------|
| e | An engine object instance |
| r | The number of experiment replications |
| seed | The random seed collection |

Value

The model output dataset

Examples

```
## Not run:
d<- "C:/usr/models/your-model-directory"
m<- Model(d)
Load(m)
Run(m,r=2) # or Run(m,r=2,seed=c(1,2))
## End(Not run)
```

RunExperiment

Run an experimental setup

Description

Run the model multiple times for different parameters given by design matrix function parameter.

Usage

```
RunExperiment(e, r = 1, design, FUN)
```

Arguments

| | |
|--------|--|
| e | An engine object instance |
| r | The number of experiment replications |
| design | The desing matrix holding parameter sampling |
| FUN | THE calibration function. |

Details

The FUN function must return zero for perfect fit and values greater than zero otherwise.

Value

A list with output and dataset

Examples

```
## Not run:
my.cost<- function(params, results) { # your best fit calculation, being 0 the best metric. }
d<- "c:/usr/models/your-model-directory"
m<- Model(d,dataset="ds::Output")
Load(m)
f<- AddFactor(name="cyclePoint",min=40,max=90)
f<- AddFactor(factors=f, name="conjugationCost",min=1,max=80)
d<- LatinHypercube(factors=f)
p<- GetSimulationParameters(e)
exp.design<- BuildParameterSet(d,p)
v<- RunExperiment(e,r=1,exp.design,my.cost)
## End(Not run)
```

| | |
|--------------------|---------------------------------|
| SaveSimulationData | <i>Saving simulation output</i> |
|--------------------|---------------------------------|

Description

Saves the simulation results of last call to Run(e) function.

Usage

```
SaveSimulationData(as = "csv", experiment = NULL)
```

Arguments

| | |
|------------|---|
| as | The desired output type, must be csv or xls |
| experiment | The experiment output |

Details

The model must have been initialized or user must call setId explicitly.

Value

The id of saved data

| | |
|--------------|---------------------|
| SequenceItem | <i>SequenceItem</i> |
|--------------|---------------------|

Description

Generate a sequence from min to max using an increment based on the number of elements in v

Usage

```
SequenceItem(v, min, max)
```

Arguments

| | |
|-----|---------------------------------|
| v | A column of n x k design matrix |
| min | The lower boundary of range |
| max | The upper boundary of range |

Value

A sequence between min and max value

| | |
|-------|----------------------------|
| setId | <i>Sets the model name</i> |
|-------|----------------------------|

Description

Set the name of the model currently instantiated.

Usage

setId(s)

Arguments

| | |
|---|----------------|
| s | The model name |
|---|----------------|

| | |
|--------------|------------------------------------|
| setKeyRandom | <i>Sets Repast randomSeed name</i> |
|--------------|------------------------------------|

Description

Configures a non-default value for Repast randomSeed parameter name.

Usage

setKeyRandom(k)

Arguments

| | |
|---|--|
| k | The string with an alternative name for randomSeed |
|---|--|

| | |
|--------------|------------------------------|
| setOutputDir | <i>Sets output directory</i> |
|--------------|------------------------------|

Description

Configure the desired directory to save model output data.

Usage

setOutputDir(s)

Arguments

| | |
|---|------------------------------------|
| s | The full path for output directory |
|---|------------------------------------|

| | |
|-------------|--------------------|
| setpkgcores | <i>setpkgcores</i> |
|-------------|--------------------|

Description

Configures the maximum number of cores to be used in parallel computations

Usage

```
setpkgcores(v)
```

Arguments

| | |
|---|---------------------|
| v | The number of cores |
|---|---------------------|

| | |
|------------|----------------------------|
| SetResults | <i>Stores a data.frame</i> |
|------------|----------------------------|

Description

Stores a data.frame

Usage

```
SetResults(d)
```

Arguments

| | |
|---|--|
| d | A data frame containing one replication data |
|---|--|

| | |
|----------------------|----------------------------|
| SetResultsParameters | <i>Sets the parameters</i> |
|----------------------|----------------------------|

Description

Save the current set of parameters used for the last model run.

Usage

```
SetResultsParameters(d)
```

Arguments

| | |
|---|------------------------------------|
| d | A data.frame with parameter values |
|---|------------------------------------|

SetSimulationParameter

SetSimulationParameter

Description

Modify model's default parameter collection

Usage

SetSimulationParameter(e, key, value)

Arguments

| | |
|-------|---------------------------|
| e | An engine object instance |
| key | The parameter name |
| value | The parameter value |

SetSimulationParameters

Set parameters for running model

Description

Modify the repeat model parameters with values provided in parameter 'p' which is a data frame with just one row.

Usage

SetSimulationParameters(e, p)

Arguments

| | |
|---|---|
| e | An engine object instance |
| p | A data frame with simulation parameters |

| | |
|---------------|----------------------|
| ShowClassPath | <i>ShowClassPath</i> |
|---------------|----------------------|

Description

Shows the current classpath

Usage

```
ShowClassPath()
```

Value

the current setting of JVM classpath

Examples

```
## Not run:  
  ShowClassPath()  
## End(Not run)
```

| | |
|-----------|----------------------|
| ShowCores | <i>ShowUsedCores</i> |
|-----------|----------------------|

Description

Prints the number of cores used

Usage

```
ShowCores()
```

ShowModelPaths *ShowModelPaths*

Description

Prints the paths. Shows the directories currently used to load model scenario and lib. The output of this function is informational only and can be used to check whether model data is being loaded properly from correct locations.

Usage

```
ShowModelPaths()
```

Examples

```
## Not run:  
  ShowModelPaths()  
## End(Not run)
```

UpdateDefaultParameters
 UpdateDefaultParameters

Description

Modify the value of the default parameters which should be kept fixed

Usage

```
UpdateDefaultParameters(e, p)
```

Arguments

e An engine object instance
p The collection of model fixed parameters to change

Examples

```
## Not run:  
  d<- "C:/usr/models/your-model-directory"  
  m<- Model(d)  
  Load(m)  
  
  p<- c(name1=value1, name2=2)  
  UpdateDefaultParameters(m,p)  
## End(Not run)
```

| | |
|------------|-------------------|
| WrapperRun | <i>WrapperRun</i> |
|------------|-------------------|

Description

Wrapper for the Run and ParallelRun functions

Usage

```
WrapperRun(modelldir, datasource, maxtime, r = 1, seed = c(),
  design = NULL, default = NULL, multi = TRUE)
```

Arguments

| | |
|------------|---|
| modelldir | The installation directory of some repast model |
| datasource | The name of any model aggregate dataset |
| maxtime | The total simulated time |
| r | The number of experiment replications |
| seed | The random seed collection |
| design | The desing matrix holding parameter sampling |
| default | The alternative values for parameters which should be kept fixed |
| multi | allows forcing single core execution, default is using multi-core |

Value

The model output dataset

| | |
|----------------------|-----------------------------|
| WrapperRunExperiment | <i>WrapperRunExperiment</i> |
|----------------------|-----------------------------|

Description

Wrapper for the RunExperiment and ParallelRunExperiment functions

Usage

```
WrapperRunExperiment(modelldir, datasource, maxtime, r = 1, design, FUN,
  default = NULL)
```

Arguments

| | |
|------------|--|
| modeldir | The installation directory of some repast model |
| datasource | The name of any model aggregate dataset |
| maxtime | The total simulated time |
| r | The number of experiment replications |
| design | The desing matrix holding parameter sampling |
| FUN | The objective function. |
| default | The alternative values for parameters which should be kept fixed |

Value

The model output dataset

Index

AddFactor, 5
AddFactor0, 5
AddResults, 6
AoE.Base, 6
AoE.ColumnCoV, 7
AoE.CoV, 7
AoE.FullFactorial, 8
AoE.GetMorrisOutput, 8
AoE.LatinHypercube, 9
AoE.MAE, 9
AoE.Morris, 10, 58, 59
AoE.NRMSD, 10
AoE.RandomSampling, 11
AoE.RMSD, 12
AoE.Sobol, 12, 59
AoE.Stability, 13
ApplyFactorRange, 13

BuildParameterSet, 14

Calibration.GetMemberKeys, 14
Calibration.GetMemberList, 15
check.integration, 15
check.scenario, 16
ClearResults, 16
col.sum, 17
config.check, 17
config.copypilib, 18
config.scenario, 18
createOutputDir, 19

df2matrix, 19
dffilterby, 20
dfround, 20
dfsumcol, 21

Easy.Calibration, 21
Easy.getChart, 22
Easy.getPlot, 23
Easy.Morris, 23

Easy.Run, 24
Easy.RunExperiment, 24
Easy.Setup, 25, 42, 44
Easy.ShowModelParameters, 25
Easy.Sobol, 26
Easy.Stability, 26
Engine, 27
Engine.endAt, 28
Engine.Finish, 28
Engine.getId, 28
Engine.GetModelOutput, 29
Engine.getParameter, 29
Engine.getParameterAsDouble, 30
Engine.getParameterAsNumber, 30
Engine.getParameterAsString, 31
Engine.getParameterNames, 31
Engine.getParameterType, 32
Engine.LoadModel, 32
Engine.resetModelOutput, 33
Engine.RunModel, 33
Engine.SetAggregateDataSet, 33
Engine.setParameter, 34
enginestats.calls, 35
enginestats.reset, 35

getExperimentDataset, 35
getExperimentOutput, 36
getExperimentParamSet, 36
GetFactorLevels, 37
GetFactorsSize, 38
getId, 38
getKeyRandom, 38
getLogDir, 39
GetOutput, 39
getOutputDir, 40
getpkgcores, 40
getpkgdefaultcores, 40
GetResults, 41, 51
GetResultsParameters, 41
GetSimulationParameters, 41

GetSimulationParameterType, 42
GoToPreviousDir, 42, 42
GoToWorkDir, 42

hybrid.distance, 43
hybrid.value, 43

jarfile, 44
jvm.enablejmx, 44
jvm.get_parameters, 45
jvm.getruntime, 45
jvm.init, 45
jvm.memory, 46
jvm.resetOut, 46
jvm.runtimegc, 47
jvm.set_parameters, 46, 48
jvm.setOut, 47

lcontains, 48
lget, 49
Load, 49, 51
Logger.setLevelInfo, 50
Logger.setLevelWarning, 50

Model, 44, 50

ParallelClose, 51
ParallelInit, 51
parallelize, 52
ParallelRunExperiment, 52
ParallelRun, 53
PB.close, 54
PB.disable, 54
PB.enable, 54
PB.get, 55
PB.init, 55
PB.isEnabled, 55
PB.pset, 56
PB.rnum, 56
PB.set, 56
PB.update, 57
pick.fittest, 57
Plot.Calibration, 58
Plot.Morris, 58
Plot.Sobol, 59
Plot.Stability, 59

Results.GetCharts, 60
Results.GetExperiment, 60
Results.GetObject, 61
Run, 51, 61
RunExperiment, 36, 62

SaveSimulationData, 51, 63
SequenceItem, 63
setId, 64
setKeyRandom, 64
setOutputDir, 64
setpkgcores, 65
SetResults, 65
SetResultsParameters, 65
SetSimulationParameter, 66
SetSimulationParameters, 66
ShowClassPath, 67
ShowCores, 67
ShowModelPaths, 68

UpdateDefaultParameters, 68

WrapperRun, 69
WrapperRunExperiment, 69